

1. Finding Mean Using Python

```
▶ data = [10, 20, 30, 40, 50]

mean_val = sum(data) / len(data)

print("Data:", data)
print("Mean:", mean_val)
```

```
... Data: [10, 20, 30, 40, 50]
    Mean: 30.0
```

2. Finding Median Using Python

```
▶ data = [40, 10, 30, 50, 20]

data.sort()
n = len(data)

if n % 2 == 0:
    median_val = (data[n//2 - 1] + data[n//2]) / 2
else:
    median_val = data[n//2]

print("Sorted Data:", data)
print("Median:", median_val)
```

```
... Sorted Data: [10, 20, 30, 40, 50]
    Median: 30
```

3. Finding Mode Using Python

```
▶ from collections import Counter

data = [1, 2, 2, 3, 4, 2, 5]

count = Counter(data)
mode_val = count.most_common(1)[0][0]

print("Data:", data)
print("Mode:", mode_val)
```

```
... Data: [1, 2, 2, 3, 4, 2, 5]
    Mode: 2
```

4. Finding Range Using Python

```
▶ data = [15, 8, 22, 42, 10]

range_val = max(data) - min(data)

print("Data:", data)
print("Range:", range_val)
```

```
... Data: [15, 8, 22, 42, 10]
    Range: 34
```

5. Finding Variance Using Python (Population)

```
data = [2, 4, 4, 4, 5, 5, 7, 9]

mean_val = sum(data) / len(data)
variance_val = sum((x - mean_val) ** 2 for x in data) / len(data)

print("Mean:", mean_val)
print("Variance:", variance_val)
```

```
Mean: 5.0
Variance: 4.0
```

6. Finding Standard Deviation Pure Python

```
▶ data = [2, 4, 4, 4, 5, 5, 7, 9]

mean_val = sum(data) / len(data)
variance_val = sum((x - mean_val) ** 2 for x in data) / len(data)
std_dev = variance_val ** 0.5

print("Standard Deviation:", std_dev)
```

```
... Standard Deviation: 2.0
```

7. Using Built-in Module

```
▶ import statistics

data = [12, 15, 15, 18, 22, 25]

print("Mean:", statistics.mean(data))
print("Median:", statistics.median(data))
print("Mode:", statistics.mode(data))
print("Variance:", statistics.variance(data))
print("Standard Deviation:", statistics.stdev(data))
```

```
... Mean: 17.833333333333332
    Median: 16.5
    Mode: 15
    Variance: 23.766666666666666
    Standard Deviation: 4.875196836436168
```

8. Using NumPy Library

```
▶ import numpy as np

data = np.array([10, 20, 20, 30, 40])

print("Mean:", np.mean(data))
print("Median:", np.median(data))
print("Variance:", np.var(data, ddof=1))
print("Standard Deviation:", np.std(data, ddof=1))
print("Range:", np.ptp(data))
```

```
... Mean: 24.0
    Median: 20.0
    Variance: 130.0
    Standard Deviation: 11.40175425099138
    Range: 30
```

9. Using SciPy for Mode

```
▶ from scipy import stats

data = [5, 2, 5, 3, 5, 4]

mode_result = stats.mode(data, keepdims=True)

print("Mode:", mode_result.mode[0])
print("Count:", mode_result.count[0])
```

```
... Mode: 5
    Count: 3
```

10. Using Pandas for Complete Summary

```
▶ import pandas as pd

import pandas as pd

df = pd.DataFrame({
    "Values": [10, 20, 30, 40, 50, 50]
})

print("Mean:", df["Values"].mean())
print("Median:", df["Values"].median())
print("Mode:", df["Values"].mode().tolist())
print("Variance:", df["Values"].var())
print("Standard Deviation:", df["Values"].std())
print("Range:", df["Values"].max() - df["Values"].min())
```

```
... Mean: 33.333333333333336
    Median: 35.0
    Mode: [50]
    Variance: 266.6666666666667
    Standard Deviation: 16.32993161855452
    Range: 40
```