

CS5560 Knowledge Discovery and Management

Spark MapReduce Programing

PS2-B

6/12/2017

Class ID: *Megha Nagabhushan*

Name: *15*

Spark MapReduce Programming – Calculate everyone's common friends for Facebook

Facebook has a list of friends (note that friends are a bi-directional thing on Facebook. If I'm your friend, you're mine). They also have lots of disk space and they serve hundreds of millions of requests everyday. They've decided to pre-compute calculations when they can to reduce the processing time of requests. One common processing request is the "You and Joe have 230 friends in common" feature. When you visit someone's profile, you see a list of friends that you have in common. We're going to use MapReduce so that we can calculate everyone's common friends once a day and store those results. Later on it's just a quick lookup. We've got lots of disk, it's cheap.

- 1) Draw a MapReduce diagram similar to the word count diagram below.
- 2) Sketch a MapReduce algorithm for the common Facebook friends (referring to the word count code below).
- 3) Sketch Spark Scala implementation (referring to the word count code below).

Example

Assume the friends are stored as Person->[List of Friends], our friends list is then:


A -> B C D
B -> A C D E
C -> A B D E
D -> A B C E
E -> B C D

The result after reduction is:

(A B) -> (C D)
(A C) -> (B D)
(A D) -> (B C)
(B C) -> (A D E)
(B D) -> (A C E)
(B E) -> (C D)
(C D) -> (A B E)
(C E) -> (B D)
(D E) -> (B C)

Now when D visits B's profile, we can quickly look up (B D) and see that they have three friends in common, (A C E).

WORD COUNT EXAMPLE



Algorithm 2.1 Word count

The mapper emits an intermediate key-value pair for each word in a document.
The reducer sums up all counts for each word.

```

1: class MAPPER
2:   method MAP(docid a, doc d)
3:     for all term t ∈ doc d do
4:       EMIT(term t, count 1)
1: class REDUCER
2:   method REDUCE(term t, counts [c1, c2, ...])
3:     sum ← 0
4:     for all count c ∈ counts [c1, c2, ...] do
5:       sum ← sum + c
6:     EMIT(term t, count sum)
  
```

MapReduce Scala Code for WordCount

```
// This class performs the map operation, translating raw input into the key-value
// pairs we will feed into our reduce operation.
class TokenizerMapper extends Mapper[Object,Text,Text,IntWritable] {
  val one = new IntWritable(1)
  val word = new Text

  override
  def map(key:Object, value:Text, context:Mapper[Object,Text,Text,IntWritable]#Context) = {
    for (t <- value.toString().split("\\s")) {
      word.set(t)
      context.write(word, one)
    }
  }
}

// This class performs the reduce operation, iterating over the key-value pairs
// produced by our map operation to produce a result. In this case we just
// calculate a simple total for each word seen.
class IntSumReducer extends Reducer[Text,IntWritable,Text,IntWritable] {
  override
  def reduce(key:Text, values:java.lang.Iterable[IntWritable], context:Reducer[Text,IntWritable,Text,IntWritable]#Context) = {
    val sum = values.foldLeft(0) { (t,i) => t + i.get }
    context.write(key, new IntWritable(sum))
  }
}
```

Spark Scala Code for WordCount

```
val textFile = spark.textFile("hdfs://...")
val counts = textFile.flatMap(line => line.split(" "))
                      .map(word => (word, 1))
                      .reduceByKey(_ + _)
counts.saveAsTextFile("hdfs://...")
```

flatMap(func)

Similar to map, but each input item can be mapped to 0 or more output items (so func should return a Seq rather than a single item).

reduceByKey(func, [numTasks])

When called on a dataset of (K, V) pairs, returns a dataset of (K, V) pairs where the values for each key are aggregated using the given reduce function *func*, which must be of type (V,V) => V. Like in groupByKey, the number of reduce tasks is configurable through an optional second argument.


②

Mapping

Shuffling

Reducing

Final Result



Algorithm

Map function

map(key, value) {

~~reduce value~~

fullFriendList = (<friend-1> <friend-2> ... <friend-N>)

foreach friend in fullFriendList

friendPair = (friendName, friend)

emit(friendPair, fullFriendList)

Reduce function

reduce(friendPair, fullFriendList)

foreach friend in friendPair

If (friendPair contains(friendName))

mutualFriends.add(friendName);

emit(friend, mutualFriends)

Mutual Friends Code.

```
public class MutualFriend Mapper {
```

```
    public void map(LongWritable key, Text value,  
        OutputCollector <FriendPair, Text> output, Reporter  
        reporter) throws IOException {
```

```
        String fullFndList = value.toString().split("→")  
        MutualFriends.NAME = LIST_SPLIT;
```

```
        String fndName = fullFndList[0];
```

```
        String[] listOfFnds = fullFndList[1].split("→");
```

```
        for (String fnd : listOfFnds) {
```

```
            FriendPair fp = new FriendPair(new  
                Text(fndName), new Text(fnd));
```

```
            output.collect(fp, new Text(fullFndList[1]));
```

```
        }
```

```
    }
```

```
}
```



```
public class MutualFriends Reducer {
```

```
    public void reduce(FriendPair key, Iterator<Text>  
        values, OutputCollector<NullWritable, Text> output,  
        Reporter reporter) {
```

```
        HashSet<String> sec = new HashSet<String>();
```

```
        List<String> mutualFends = new ArrayList<String>();
```

```
        String fnds = values.next().toString();
```

```
        String[] names = fnds.split("→");
```

```
        for (String name: names) {
```

```
            sec.add(name);
```

```
        }
```

```
        if (values.hasNext()) {
```

```
            fnds = values.next().toString();
```

```
            names = fnds.split("→");
```

```
            for (String name: names) {
```

```
                if (sec.contains(name)) {
```

```
                    mutualFends.add(name);
```

```
                }
```

```
            }
```

```
        }
```



```
if (mutualFends.size() > 0) {
```

```
String val = key.toString() + " → " + " ";
```

```
boolean commaFlag = false;
```

```
for (String mutualFend : mutualFends) {
```

```
    if (commaFlag) {
```

```
        val += ", ";
```

```
    }
```

```
    val += mutualFend;
```

```
    commaFlag = true;
```

```
}
```

```
output.collect(NullKitable.get(), new Text(val))
```

```
}
```

```
}
```

```
}
```