

---

# Multi-layer Stack Ensembles for Time Series Forecasting

---

Nathanael Bosch<sup>1,\*</sup> Oleksandr Shchur<sup>2</sup> Nick Erickson<sup>2</sup> Michael Bohlke-Schneider<sup>2</sup>  
Caner Türkmen<sup>2</sup>

<sup>1</sup>Tübingen AI Center, University of Tübingen

<sup>2</sup>AWS

\*Work done during an internship at AWS

---

**Abstract** Ensembling is a powerful technique for improving the accuracy of machine learning models, with methods like stacking achieving strong results in tabular tasks. In time series forecasting, however, ensemble methods remain underutilized, with simple linear combinations still considered state-of-the-art. In this paper, we systematically explore ensembling strategies for time series forecasting. We evaluate 33 ensemble models—both existing and novel—across 50 real-world datasets. Our results show that stacking consistently improves accuracy, though no single stacker performs best across all tasks. To address this, we propose a multi-layer stacking framework for time series forecasting, an approach that combines the strengths of different stacker models. We demonstrate that this method consistently provides superior accuracy across diverse forecasting scenarios. Our findings highlight the potential of stacking-based methods to improve AutoML systems for time series forecasting.

---

## 1 Introduction

Time series forecasting plays a critical role in applications ranging from inventory management (Croston, 1972) to energy systems (Hong et al., 2016) and public health (Tsang et al., 2024). Driven by growing interest in the machine learning (ML) community, numerous forecasting models have been proposed in recent years. Yet no single model is universally dominant. Large-scale benchmarks show that while some models perform better on average, none consistently outperforms all others across diverse datasets and tasks (Aksu et al., 2024; Godahewa et al., 2021).

This variability in model performance motivates the use of automated machine learning (AutoML) for time series forecasting. By evaluating multiple models on a given dataset, an AutoML system can select the one that performs best for the specific forecasting task at hand. However, relying solely on model selection is often insufficient to achieve the lowest possible forecast error.

A growing body of work—both in academic research and prediction competitions—demonstrates that combining forecasts from multiple models can lead to substantial improvements in predictive performance (Bojer and Meldgaard, 2021; Makridakis et al., 2018, 2022). Yet, several key questions remain unanswered. While many forecast combination methods have been proposed over the years (X. Wang et al., 2023), there is limited understanding of which ensembling strategies are most effective in practice. In the related field of tabular AutoML, techniques such as multi-layer stacking repeatedly demonstrate state-of-the-art performance (Gijsbers et al., 2024). In contrast, time series forecasting has seen limited adoption of such techniques, with most practical systems relying on simple linear combinations of model outputs (Herzen et al., 2022; Shchur et al., 2023). Moreover, several studies suggest that in forecasting, simple arithmetic averages outperform more sophisticated ensembling techniques, which is often referred to as the "forecast combination puzzle" (Smith and Wallis, 2009; Stock and Watson, 2004).

To address this gap, we conduct a large-scale empirical study of forecast combination methods, aiming to identify strategies with the best predictive performance. Our main contributions are:

- **Empirical evaluation of ensembling methods.** We conduct a large-scale benchmark of 33 forecast combination methods across 50 real-world datasets on point and probabilistic forecasting tasks. Our results show that ensembling consistently improves the predictive accuracy, with learning-based ensembles significantly outperforming simple aggregation strategies.
- **Multi-layer stacking framework.** We propose a framework for building multi-layer stack ensembles for time series forecasting, designed to combine the strengths of different ensembling methods. This approach consistently outperforms any individual ensemble across both point and probabilistic forecasting tasks. Additional ablation studies reveal when and why multi-layer stacking is effective, demonstrating its adaptability and robustness across datasets.

## 2 Background

### 2.1 Probabilistic time series forecasting

Given a collection of  $N$  time series  $\mathcal{D} = \{y_{i,1:T}\}_{i=1}^N$ , with  $y_{i,t} \in \mathbb{R}$ , the goal of time series forecasting is to predict the future  $H$  values  $y_{i,T+1:T+H}$  for each time series  $i = 1, \dots, N$ . Specifically, in *probabilistic* time series forecasting, the aim is to model the conditional distribution  $p(y_{i,T+1:T+H} \mid y_{i,1:T})$  for all  $i$ . Often, it is sufficient to produce a quantile forecast rather than the full distribution. Given a predefined set of quantile levels  $\mathcal{Q} \subset (0, 1)$  with  $|\mathcal{Q}| = Q$ , the goal is to predict  $\hat{y}_{i,T+h}^q \in \mathbb{R}$  such that  $P(y_{i,T+h} < \hat{y}_{i,T+h}^q) = q$ , for all  $q, i, h$ . Alternatively, if uncertainty quantification is not needed, a conditional mean or median forecast may suffice. In this work, we primarily focus on quantile forecasts, but all methods also apply to point forecasts and we will also evaluate these in Sec. 6.

Time series forecasting *models*  $f_i : \mathbb{R}^T \rightarrow \mathbb{R}^{H \times Q}$  produce these quantile predictions, mapping  $f_i : y_{i,1:T} \mapsto \hat{y}_{i,T+h}^q$  for all  $i$ . Here, the collection of models  $\{f_i\}$  can be individually learned for each time series, an approach known as *local* time series modeling (Januschowski et al., 2020). Local time series models include *seasonal naive*, *exponential smoothing*, and *ARIMA*, which typically fit a small set of model parameters on each item individually, in order to capture simple patterns in the data such as trends and seasonality (R. Hyndman and Athanasopoulos, 2021).

On the other hand, a *global* time series model uses a single model for all time series, that is  $f_i = f$  for all  $i$ . The function  $f$  is learned over the entire training set  $\mathcal{D}$ . The aim in global time series modeling is to use a higher capacity function  $f$  (e.g., a neural network) to capture both simple temporal patterns and any dynamics common to all time series in a dataset. This approach includes many recent deep learning-based approaches, such as *DeepAR* (Salinas, Flunkert, et al., 2020), *TFT* (Lim et al., 2021), *PatchTST* (Nie et al., 2022), *DLinear* (Zeng et al., 2023), or *TiDE* (Das et al., 2023).

Finally, *pretrained* models also fit parameterized functions to data, but are trained on large corpora of real-world and/or synthetic time series from diverse domains. The model is then applied as a zero-shot forecaster, that is, without any additional training on the dataset  $\mathcal{D}$  associated with the given forecasting task. Recent examples of such pretrained models include *Chronos* (Ansari et al., 2024), *TimesFM* (Das et al., 2024), *Moirai* (Woo et al., 2024), and *TTM* (Ekambaram et al., 2024).

Time series models are trained via minimizing loss function  $\mathcal{L} : \mathbb{R}^{H \times Q} \times \mathbb{R}^H \rightarrow \mathbb{R}_{\geq 0}$  over the training set. Examples include quantile loss for probabilistic forecasting, or mean absolute error for point forecasting (R. Hyndman and Athanasopoulos, 2021).

### 2.2 Forecast combination

While many approaches to modeling exist, none of these dominate others in terms of accuracy or efficiency. The best forecasting approach is therefore often a combination of different models (X. Wang et al., 2023). Let  $f_{i,m}$  denote the forecast model for item  $i$ , obtained by using the modeling approach  $m \in 1, \dots, M$ . Forecasts from these models can be combined with a combination function  $g_i : (\mathbb{R}^{H \times Q})^M \rightarrow \mathbb{R}^{H \times Q}$  that operates on the outputs of a collection of base forecasting models




Figure 1: Architecture and training procedure of a single-layer stacker model.

$\{f_{i,m}\}$  to produce a single aggregated forecast. Composing the combination functions  $g_i$  with base forecasters  $\{f_{i,m}\}$ , we obtain forecast ensembles  $\bar{f}_i$

$$\bar{f}_i : \mathbb{R}^T \rightarrow \mathbb{R}^{H \times Q}, \quad y_{i,1:T} \mapsto g_i(f_{i,1}(y_{i,1:T}), f_{i,2}(y_{i,1:T}), \dots, f_{i,M}(y_{i,1:T})), \quad (1)$$

for all  $i$ . See also Fig. 1 for a visual description of the approach.

Similar to base models, combination methods can also be *global* with  $g_i = g$  for all  $i$ . This is possible regardless of whether the base models are local or global. For example, we could learn global combinations  $g$  of individually fitted local models  $\{f_{i,m}\}$ . Conversely, we could use a different combination method  $g_i$  for each time series, when combining global forecasting methods  $\{f_m\}$ . Combinations of global and local models as base models are also possible. In the following, we will rely on this generality to drop the item index  $i$  from our notation. For example, in the following  $\hat{y}_m$  may denote either the predictions for a single item  $\hat{y}_{i,m}$  or for all items  $\{y_{i,m}\}_{i=1}^N$ , depending on the context.

Likely the most popular forecast combination approach is **simple averaging** via the mean or median of individual forecasts, e.g.,  $g(\hat{y}_1, \dots, \hat{y}_M) = \frac{1}{M} \sum_{m=1}^M \hat{y}_m$ . Simple averaging has been shown to often outperform individual forecasting models (Perrone and Cooper, 1995; X. Wang et al., 2023). **Model selection** can also be cast in the same notation. That is,  $g(\hat{y}_1, \dots, \hat{y}_M) = \hat{y}_{m^*}$ , where  $m^*$  is the index of the model with the best validation score, i.e.  $m^* := \arg \min_{m=1, \dots, M} \mathcal{L}(\hat{y}_m, y_{\text{out}})$ , where  $y_{\text{out}}$  denotes the ground truth future values corresponding to the predictions  $\hat{y}_m$ .

In the AutoML literature, methods that combine outputs of individual models are referred to as *post-hoc ensembles* (Purucker and Beel, 2023) to differentiate them from other ensembling techniques like bagging and boosting. In forecasting literature, apart from *forecast combinations* (Clemen, 1989), these methods are called forecast ensembles (Adhikari and Agrawal, 2012) and model averaging (Montero-Manso et al., 2020). We use these terms interchangeably throughout the paper.

### 3 Stacking for time series forecasting

#### 3.1 Stacking

Simple averaging and model selection are strong baseline approaches. In this work, however, we explore a broader class of methods that can *learn* the combination functions  $g$  from data. In ML literature, such methods that learn to combine the outputs of other models are often called *stacking* methods (Zhou, 2012, Ch. 4). We now review some model families that fall into this category.

**Model averaging.** One generalization of simple averaging is weighted model averaging, with a stacker model of the form  $g(\hat{y}_1, \dots, \hat{y}_M) = \sum_{m=1}^M \omega_m \hat{y}_m$ , with weights  $\omega \in \mathbb{R}^M$ . The weights  $\omega$  can be chosen based on the **model performance**. For example, the weights can be computed as  $\omega_m \propto h(\mathcal{L}(\hat{y}_m, y_{\text{out}}))$ , where  $h$  are chosen as  $h_{\text{inv}}(L) = 1/L$ ,  $h_{\text{sqr}}(L) = 1/L^2$ , or  $h_{\text{exp}}(L) = \exp(1/L)$ , subject to  $\sum_{m=1}^M \omega_m = 1$  (Pawlikowski and Chorowska, 2020).

Alternatively, stacker weights  $\omega$  can be learned from data by minimizing the loss function,  $\omega = \arg \min_{\omega' \in \mathbb{R}^M} \mathcal{L}(g(\hat{y}_1, \dots, \hat{y}_M), y_{\text{out}})$ , often subject to  $\omega_m \geq 0$  and  $\sum_m \omega_m = 1$ . If the loss is differentiable, weights can be learned via a **numerical optimization** method such as gradient descent. Another popular approach is the greedy **ensemble selection** algorithm (Caruana et al., 2004), which adds models to the ensemble with replacement. Ensemble selection is used by default in several AutoML forecasting frameworks (Deng et al., 2022; Shchur et al., 2023; Zöller et al., 2024).

**General combinations via linear regression.** Instead of assigning a single weight per model, weights can vary with item  $i$ , time step  $h$ , quantile  $q$ , or any combination thereof. Reintroducing the item index  $i$ , we write:

$$[g_i(\hat{y}_{i,1}, \dots, \hat{y}_{i,M})]_{h,q} = \sum_{m=1}^M \omega_{i,h,q,m} \cdot [\hat{y}_{i,m}]_{h,q} \quad (2)$$

with weights  $\omega \in \mathbb{R}^{N \times H \times Q \times M}$ . These weights can be tied across horizon steps, e.g.,  $\omega_{i,h,q,m} = \omega_{i,q,m}$ , or even shared across items. This defines a broad family of linear combinations, as explored by Hasson et al. (2023) through different parameter-tying and regularization schemes. Our evaluation in Sec. 6 includes several of these linear variants.

**Nonlinear regression.** Finally,  $g$  can be a nonlinear function, often implemented using tree-based models such as gradient boosting—e.g., as in darts (Herzen et al., 2022), sktime (Löning et al., 2019), or Gastinger et al. (2021). As with linear models, these can vary in how they tie parameters across items, quantiles, or forecast horizons. Input normalization (e.g., scaling  $\hat{y}_m$ ) is often beneficial before applying nonlinear models. In Sec. 6, we evaluate several nonlinear tabular models.

### 3.2 Training stacker models with time series cross-validation

One important detail that we have not yet addressed is how to obtain the training data for the stacker models. It is conventional wisdom in ensemble training that in order to prevent overfitting, stacker models  $g$  should be trained on *out-of-fold* data—i.e., data that was held out during the training of the base models  $\{f_m\}$  (Zhou, 2012). Holding out data, in turn, requires special treatment in the case of time series (R. Hyndman and Athanasopoulos, 2021, Section 5.10). In line with this, we use a time series  $K$ -fold cross validation scheme which works as follows. For each fold  $k = 1, \dots, K$ , we first remove the last  $j := (K - k + 1)$  windows of size  $H$  from each time series, obtaining the training set  $y_{1:T-jH}$  used to train the base models  $\{f_m\}$ . Next, we make  $H$ -step-ahead predictions with all trained base models, obtaining  $M$  quantile forecasts  $\{\hat{y}_m^k\}$ , each covering the validation window  $y^k = y_{T-jH:T-(j-1)H}$ . After repeating this process  $K$  times, we collect the training set for the stacker model  $g$  consisting of the inputs (the out-of-fold predictions  $\hat{y}_m^k$  for each model  $m$  and fold  $k$ ), and the targets (the out-of-fold data  $y^k$  for each fold  $k$ ). See Fig. 1 for a visual depiction.

## 4 Multi-layer stacking for time series forecasting

### 4.1 Multi-layer stacking

As we will see in Sec. 6, the performance of different stacker models can vary greatly across datasets. To address this issue, we propose a *multi-layer stacking* approach that aggregates the outputs of multiple stackers with yet another stacker model (Fig. 2). This approach removes the need to decide on a single stacker model  $g$  in advance—we can instead learn the optimal combination of multiple stacker models  $\{g_c\}_{c=1}^C$ , similar to how we considered a set of base forecasting models  $\{f_m\}_{m=1}^M$ . Finally, we can combine the outputs of  $\{g_c\}_{c=1}^C$  using a new stacker model  $s: (\mathbb{R}^{H \times Q})^C \rightarrow \mathbb{R}^{H \times Q}$ . In the following, we refer to the base models  $\{f_m\}_{m=1}^M$  as the first layer of the multi-layer stack ensemble, the stacker models  $\{g_c\}_{c=1}^C$  as the second layer, and the aggregator model  $s$  as the third layer; or in short as L1, L2, and L3 models (cf. Fig. 2).




Figure 2: Architecture and training procedure of a multi-layer stacker model.

Concretely, to generate quantile predictions for an item, its past data  $y_{i,1:T}$  is used to produce forecasts  $\hat{y}_{i,1}, \dots, \hat{y}_{i,M}$  from each L1 model. These are then aggregated by a composition of L2 models and a single L3 model  $s$ . The resulting *multi-layer stack ensemble* defines the mapping:

$$y_{i,1:T} \mapsto s(g_1(\hat{y}_{i,1}, \dots, \hat{y}_{i,M}), \dots, g_C(\hat{y}_{i,1}, \dots, \hat{y}_{i,M})).$$

Note that all forecast combination and stacker models  $g$  discussed in the previous sections can also be used as the aggregator model  $s$ . For example, the aggregator  $s$  can perform model selection among the L2 stacker models, or it could combine the L2 models into a weighted ensemble.

#### 4.2 Training of multi-layer stacker models with two-level time series cross-validation

Similar to the individual stacker models  $g$ , we need to make sure that the L3 aggregator model  $s$  is trained on out-of-fold predictions of the L2 models to avoid overfitting. To achieve this, we adjust the procedure described in Sec. 3.2. Like before, we train the L1 base models using  $K$ -fold time series cross validation. Next, we only train the L2 stacker models  $\{g_c\}$  on the first  $K - 1$  validation windows. We then make predictions with the L2 models for the  $K$ th validation window, and use these predictions together with the ground truth values to fit the L3 aggregator model  $s$ . Finally, we re-train the L2 models using all  $K$  validation windows to ensure that these models have access to the most recent data. The entire process is shown in Fig. 2.

### 5 Related work

**Time series forecasting.** Time series modeling spans classical statistical methods (Box et al., 1970; R. Hyndman, Koehler, et al., 2008), deep learning models (Benidis et al., 2022; Challu et al., 2023; Nie et al., 2022; Salinas, Flunkert, et al., 2020), and more recently, pretrained models (Ansari et al., 2024; Das et al., 2024; Woo et al., 2024). Despite substantial progress, no single model consistently outperforms others across all datasets and problem settings (Aksu et al., 2024; Godahewa et al., 2021). This motivates AutoML systems that automatically train, tune, and combine models to achieve the best performance for a given task (Ali, 2020; Deng et al., 2022; Shchur et al., 2023; Zöller et al., 2024). Our stacking framework is compatible with arbitrary forecasting models, making it complementary to ongoing advances in model development.

**Forecast combinations.** The idea of combining forecasts dates back to Bates and Granger (1969) and has inspired many methods (X. Wang et al., 2023), often featured in winning solutions of prediction competitions (Bojer and Meldgaard, 2021; Makridakis et al., 2018, 2022). Early studies found that simple averages often outperform more complex methods—a phenomenon known as the "forecast combination puzzle" (Smith and Wallis, 2009; Stock and Watson, 2004). However, these results were based on small datasets, statistical models, and point forecasts (Gastinger et al., 2021). Later work showed that more sophisticated methods outperform simple averages when applied to modern ML models, larger datasets, and probabilistic forecasting (Hasson et al., 2023). Our results in Sec. 6 advance this discussion and show that stacking improves over simple aggregation strategies for both point and probabilistic forecasting.

**Stacking.** Stacking, or stacked generalization, was introduced by Wolpert (1992) and Breiman (1996), where a single stacker model combines predictions from base models to produce the final output (Van der Laan et al., 2007). Variants of stacking have been studied extensively, including for quantile regression (Fakoor et al., 2023). In AutoML systems, a common approach is ensemble selection (Caruana et al., 2004), popularized by Auto-Sklearn (Feurer et al., 2015). Multi-layer stack ensembles first appeared in competition-winning solutions (Itericz and Semenov, 2016; Koren, 2009), and gained broader adoption with AutoGluon-Tabular (Erickson et al., 2020), which introduced a robust bagging-based implementation. However, existing work on multi-layer stacking is limited to tabular tasks. Our paper extends this framework to point and probabilistic time series forecasting.

## 6 Experiments

The main goal of our experimental analysis is to determine which forecast combination methods result in the best prediction accuracy (Sec. 6.1). In subsequent experiments, we aim to get better understanding of these results. For this purpose, we investigate the effects of various design choices such as selection of L1 models or the amount of validation data (Sec. 6.2–6.5).

### 6.1 Which combination methods produce the most accurate forecasts?

In our main experiment, we perform a large-scale benchmark comparison of 33 forecast combination methods, including the single-layer (Sec. 3) and multi-layer stacking (Sec. 4).

**Datasets.** We use 50 univariate datasets from Ansari et al. (2024) and Woo et al. (2024), covering diverse domains and frequencies, totaling 90K time series with 110M observations (see Tab. 5). To ensure that enough data is available for training base and stacker models, we only keep time series with at least  $8 \times H$  observations (where  $H$  is the forecast horizon) in each dataset. As this filtering changes the data compared to the original publications, we re-evaluate all models ourselves.

**Models.** We consider 11 base forecasters (**L1 models**) covering all popular model categories: statistical models (*SeasonalNaive*, *AutoETS*, *Theta*), deep learning models (*DeepAR*, *PatchTST*, *TFT*, *TiDE*, *DLinear*), gradient-boosted trees (*DirectTabular*, *RecursiveTabular*), and one pretrained model (*Chronos-Bolt*). We use model implementations from AutoGluon-TimeSeries (Shchur et al., 2023), trained with default hyperparameters until convergence, without hyperparameter tuning for simplicity. These 11 L1 models are used as input to all the subsequent combination methods.

In addition, we train 31 combination methods (**L2 models**) from Sec. 3. These include 2 *simple averages*, *model selection*, 3 *performance-weighted averages*, 3 *greedy ensembles*, 18 *linear models*, and 4 *nonlinear models*. A detailed breakdown for each model category is available in Sec. B.

Finally, we consider 2 multi-layer stacking approaches (**L3 models**) from Sec. 4: *stacker model selection* that selects the best L2 model based on the performance on the last validation window, and *multi-layer stacking* that fits a greedy ensemble on top of the L2 models. To keep the training time reasonable, we limit the second level of the ensemble to 14 a priori chosen L2 models.

Table 1: Aggregated probabilistic forecasting performance of the representative combination methods based on SQL. Best result in **bold**, second best underlined. Individual results for all methods and datasets are available in Tab. 8

Method	(↑) Elo	(↑) Champion	(↓) Average rank	(↓) Average relative error	(↓) Median marginal training time
Median	1000	3	5.92	1.000	<b>1s</b>
Model selection	1049	<u>9</u>	5.43	1.001	<u>2s</u>
Performance-based average	1130	3	4.60	0.963	<u>2s</u>
Greedy ensemble selection	1191	4	3.92	0.952	11s
Linear model	<u>1220</u>	3	<u>3.62</u>	<u>0.947</u>	11s
Nonlinear model	1046	4	5.43	1.011	27s
Stacker model selection	1157	1	4.27	0.973	484s
Multi-layer stacking	<b>1306</b>	<b>20</b>	<b>2.81</b>	<b>0.945</b>	721s

Table 2: Aggregated probabilistic forecasting performance of the representative combination methods based on MASE. Best result in **bold**, second best underlined. Individual results for all methods and datasets are available in Tab. 9.

Method	(↑) Elo	(↑) Champion	(↓) Average rank	(↓) Average relative error	(↓) Median marginal training time
Median	1000	7	5.54	1.000	<b>1s</b>
Model selection	997	<u>8</u>	5.58	1.026	<b>1s</b>
Performance-based average	1059	2	4.98	0.989	<b>1s</b>
Greedy ensemble selection	1161	4	3.84	0.975	<u>2s</u>
Linear model	<u>1168</u>	3	<u>3.81</u>	0.975	5s
Nonlinear model	1004	5	5.48	1.033	6s
Stacker model selection	1158	3	3.87	<u>0.967</u>	295s
Multi-layer stacking	<b>1256</b>	<b>17</b>	<b>2.90</b>	<b>0.954</b>	443s

**Metrics.** For each dataset, we evaluate two tasks: point and probabilistic forecasting. Point accuracy is measured using *mean absolute scaled error* (MASE) on the median forecast, while probabilistic accuracy is assessed via *scaled quantile loss* (SQL) at quantile levels  $\mathcal{Q} = \{0.1, 0.2, \dots, 0.9\}$ . To aggregate results across datasets, we report the *Elo rating*, number of wins (*champion*), *average rank*, and *average relative error* (geometric mean of errors normalized against the baseline). We use "Simple average (median)" as the baseline for Elo and relative error. Further details are provided in Sec. C.

**Setup.** We reserve the last  $H$  observations of each time series as the test set. L1 models are trained using  $K=5$ -fold cross-validation, with the model from the last fold used for test prediction. Individual L2 models are trained on all 5 validation windows. For multi-layer stacking, the L3 model is fitted on the final window. After training, all models generate forecasts on the test set, and accuracy is evaluated using MASE or SQL, depending on the task.

**Results.** Complete results for 2 task types  $\times$  50 datasets  $\times$  44 models are reported in Tables 8–9 (appendix). To summarize these, we group forecast combination methods into 8 categories: simple average, model selection, performance-based average, greedy ensemble selection, linear model, nonlinear model, stacker model selection, and multi-layer stacking. We select the best-performing method (by average rank) from each category as its *representative method* and report aggregate metrics for these in Tables 1–2. Note that such aggregation does not give an unfair advantage to the multi-layer stacking approaches since there is only one method in each category. Moreover, multi-layer stacking has the best scores both in the full results (Tables 8–9) and in the aggregated results (Tables 1–2). Based on these results, we draw the following conclusions:

1. **Combination methods outperform individual forecasting models.** Combining multiple forecasts typically improves the accuracy compared to a single model, even if model selection is

performed. We see major accuracy gains, with up to 200 Elo points difference ( $\approx 75\%$  win rate) and up to 5% error reduction. This result reaffirms the previous findings on the importance of ensembling in forecasting (X. Wang et al., 2023).

2. **Stacking outperforms simple aggregation techniques.** Contrary to the “forecast combination puzzle,” which suggests that complex methods rarely outperform simple ones, our results clearly demonstrate that learned aggregation methods—like ensemble selection and linear models—yield substantially better accuracy than simple or performance-based averages.
3. **Multi-layer stacking outperforms individual combination methods.** Across both point and probabilistic tasks, multi-layer stacking achieves the highest accuracy. This result is consistent with our earlier observations: since no single L2 model performs best across all datasets, combining them in an L3 ensemble leads to improved overall accuracy. Notably, multi-layer stacking also outperforms model selection over L2 models, highlighting that combining multiple stackers is more effective than selecting the best one in isolation.

## 6.2 When and why does multi-layer stacking outperform other approaches?

**L3 model weights.** First, we investigate the weights assigned by the L3 ensemble selection algorithm to the underlying L2 models. We show the average weights in Fig. 3 and provide the per-dataset breakdown in Fig. 9–10 in the appendix. All constituent L2 stacker models receive non-zero weight, underscoring the value of maintaining a diverse portfolio. Notably, the nonlinear stacker LightGBM performs poorly on average when evaluated in isolation (Tab. 1), yet it is frequently selected by the L3 ensemble. This indicates that while LightGBM may underperform overall, it excels on specific datasets—which can be capitalized on by the adaptive multi-layer stacking framework.




Figure 3: Weights assigned by the L3 ensemble selection algorithm to the L2 models (average over 50 tasks).

**Normalized performance.** To understand where multi-layer stacking succeeds or fails, we compare each representative model’s score to the dataset-specific “champion” (Tab. 10). In 39 out of 50 datasets, most L2 models perform within 20% of the champion, and in these cases, multi-layer stacking typically ranks first or second in accuracy. In the remaining 11 datasets, where L2 model performance varies widely, multi-layer stacking tends to underperform. We hypothesize that allocating more validation data to train the L3 aggregator could mitigate this issue.

## 6.3 How much validation data do different combination methods require?

Previous experiments used 5 validation windows, requiring each base model to be trained 5 times. To reduce computational cost, we evaluated ensemble performance with fewer validation folds ( $K = 1$  to 5), using Median aggregation as a baseline since its performance is fold-independent.

Results show that even with just  $K = 2$ , multi-layer stacking outperforms all other methods, followed by the linear model. The nonlinear model benefits most from additional folds, while model selection performs best at  $K = 1$ , suggesting that older data is less indicative of the test set performance.




Figure 4: Influence of the number of validation windows on the model performance.



Table 3: Ablation: Aggregated probabilistic forecasting performance of representative combination methods when using only 6 base models. Best result in **bold**, second best underlined. Multi-layer stacking remains the top performer even with a reduced set of base models.

Method	(↑) Elo	(↑) Champion	(↓) Average rank	(↓) Average relative error	(↓) Median marginal training time
Median	1000	1	5.38	1.000	<b>1s</b>
Model selection	899	2	6.39	1.058	<b>1s</b>
Performance-based average	1095	7	4.46	0.994	<u>2s</u>
Greedy ensemble selection	1110	6	4.23	0.990	7s
Linear model	<u>1145</u>	2	<u>3.93</u>	<u>0.978</u>	8s
Nonlinear model	1047	<u>8</u>	4.93	1.002	21s
Stacker model selection	1128	2	4.07	0.982	418s
Multi-layer stacking	<b>1280</b>	22	<b>2.61</b>	<b>0.947</b>	578s

Table 4: Ablation: Aggregated probabilistic forecasting performance of multi-layer stacking with and without L2 model retraining. Scores are computed with respect to the methods in Tab. 1. Skipping retraining reduces fit time, but decreases forecast accuracy.

Method	(↑) Elo	(↑) Champion	(↓) Average rank	(↓) Average relative error	(↓) Median marginal training time
Multi-layer stacking (L2 retraining)	<b>1306</b>	<b>20</b>	<b>2.81</b>	<b>0.945</b>	720s
Multi-layer stacking (no L2 retraining)	1253	13	3.24	0.950	<b>483s</b>

#### 6.4 What is the effect of the L1 model choice?

Our experiments use a fixed set of 11 L1 forecasting models, but a robust ensembling method should perform well regardless of the base models used. To test this, we removed the 5 best-performing L1 models (*Chronos*, *PatchTST*, *TFT*, *DirectTabular*, *RecursiveTabular*) and retained only 6: *SeasonalNaive*, *AutoETS*, *Theta*, *DLinear*, *DeepAR*, and *TiDE*. The rest of the setup follows Sec. 6.1.

Aggregate results for 8 representative ensemble methods are shown in Tab. 3. The ranking remains unchanged: multi-layer stacking still performs best, showing robustness to L1 model choice. Model selection drops significantly due to the absence of *Chronos* (the strongest individual model), highlighting the importance of forecast combination when strong base models are unavailable.

#### 6.5 Is it necessary to retrain the L2 models?

Our training procedure for the multi-layer stack ensemble (Sec. 4.2) includes a final step where L2 models are retrained on all validation windows. To assess whether this step is necessary, we perform an ablation comparing performance with and without this retraining. As shown in Tab. 4, skipping retraining leads to 1.5x faster training at the cost of lower forecast accuracy. This highlights the importance of retraining L2 models on the full validation data to ensure optimal performance.

### 7 Discussion

**Limitations & future work.** While our study demonstrates the effectiveness of learned forecast combination methods, several limitations remain. Most stacker models require predictions from all base models, which results in slower inference compared to sparse methods like ensemble selection. Future work could explore pruning strategy to mitigate this issue (Tsoumakas et al., 2009). Similarly, multi-layer stacking incurs substantial training costs, as we currently train 14 L2 models. A more principled approach—such as offline portfolio optimization, akin to Salinas and Erickson (2024)—could reduce computational overhead while maintaining or even improving accuracy. In addition, this framework can be extended with meta-learning approaches such as FFORMA (Montero-Manso et al., 2020), which aim to select or weight models based on dataset-level

features. Finally, the search for better aggregation models to use at the L2 and L3 levels remains an open and important challenge.

**Summary.** Our large-scale empirical study shows that learned ensembling methods—particularly stacking—consistently outperform both individual forecasting models and simple aggregation techniques. These findings challenge the “forecast combination puzzle” and demonstrate that flexible, data-driven ensemble strategies can significantly improve predictive accuracy. Multi-layer stacking extends this idea by combining multiple stackers, yielding robust performance across a wide range of datasets. While this approach provides consistent improvements overall, our ablations show it is especially valuable when strong individual forecasting models are unavailable. As forecasting tools and AutoML systems continue to evolve, we see strong potential in integrating advanced ensemble methods that adapt to data characteristics, scale efficiently, and generalize well across diverse forecasting scenarios.

## 8 Broader Impact Statement

After careful reflection, the authors have determined that this work presents no notable negative impacts to society or the environment.

**Acknowledgements.** We would like to thank David Holzmüller for his help with adding multi-quantile support to the RealMLP codebase, which enabled us to use this model in our evaluation.

## References

- Adhikari, R. and R. Agrawal (2012). “Combining multiple time series models through a robust weighted mechanism”. In: *2012 1st International Conference on Recent Advances in Information Technology (RAIT)*. IEEE, pp. 455–460.
- Aksu, T. et al. (2024). “GIFT-Eval: A Benchmark For General Time Series Forecasting Model Evaluation”. In: *arxiv preprint arxiv:2410.10393*.
- Ali, M. (Apr. 2020). *PyCaret: An open source, low-code machine learning library in Python*. PyCaret version 1.0.0. URL: <https://www.pycaret.org>.
- Ansari, A. F. et al. (2024). “Chronos: Learning the language of time series”. In: *arXiv preprint arXiv:2403.07815*.
- Assimakopoulos, V. and K. Nikolopoulos (2000). “The theta model: a decomposition approach to forecasting”. In: *International journal of forecasting* 16.4, pp. 521–530.
- Bai, Y. et al. (2022). *Training a Helpful and Harmless Assistant with Reinforcement Learning from Human Feedback*. arXiv: 2204.05862 [cs.CL]. URL: <https://arxiv.org/abs/2204.05862>.
- Bates, J. M. and C. W. Granger (1969). “The combination of forecasts”. In: *Journal of the operational research society* 20.4, pp. 451–468.
- Benidis, K. et al. (2022). “Deep learning for time series forecasting: Tutorial and literature survey”. In: *ACM Computing Surveys* 55.6, pp. 1–36.
- Bojer, C. S. and J. P. Meldgaard (2021). “Kaggle forecasting competitions: An overlooked learning opportunity”. In: *International Journal of Forecasting* 37.2, pp. 587–603.
- Boubdir, M. et al. (2024). “Elo Uncovered: Robustness and Best Practices in Language Model Evaluation”. In: *The Thirty-eighth Annual Conference on Neural Information Processing Systems*. URL: <https://openreview.net/forum?id=Pc9LLjTL5f>.
- Box, G. E. et al. (1970). *Time series analysis: forecasting and control*. John Wiley & Sons.
- Breiman, L. (1996). “Stacked regressions”. In: *Machine learning* 24, pp. 49–64.
- Caruana, R. et al. (2004). “Ensemble selection from libraries of models”. In: *Proceedings of the twenty-first international conference on Machine learning*, p. 18.
- Challu, C. et al. (2023). “Nhits: Neural hierarchical interpolation for time series forecasting”. In: *Proceedings of the AAAI conference on artificial intelligence*. Vol. 37. 6, pp. 6989–6997.

- Chiang, W.-L. et al. (2024). *Chatbot Arena: An Open Platform for Evaluating LLMs by Human Preference*. arXiv: 2403.04132 [cs.AI]. URL: <https://arxiv.org/abs/2403.04132>.
- Clemen, R. T. (1989). "Combining forecasts: A review and annotated bibliography". In: *International journal of forecasting* 5.4, pp. 559–583.
- Croston, J. D. (Sept. 1972). "Forecasting and Stock Control for Intermittent Demands". In: *Journal of the Operational Research Society* 23.3, pp. 289–303. URL: <https://doi.org/10.1057/jors.1972.50>.
- Das, A. et al. (2023). "Long-term forecasting with TiDE: Time-series dense encoder". In: *arXiv preprint arXiv:2304.08424*.
- Das, A. et al. (2024). "A decoder-only foundation model for time-series forecasting". In: *Proceedings of the 41st International Conference on Machine Learning*. Ed. by R. Salakhutdinov et al. Vol. 235. Proceedings of Machine Learning Research. PMLR, pp. 10148–10167. URL: <https://proceedings.mlr.press/v235/das24c.html>.
- Deng, D. et al. (2022). "Efficient automated deep learning for time series forecasting". In: *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*. Springer, pp. 664–680.
- Ekambaram, V. et al. (2024). *Tiny Time Mixers (TTMs): Fast Pre-trained Models for Enhanced Zero/Few-Shot Forecasting of Multivariate Time Series*. arXiv: 2401.03955 [cs.LG]. URL: <https://arxiv.org/abs/2401.03955>.
- Elo, A. E. (1967). "The proposed uscf rating system, its development, theory, and applications". In: *Chess life* 22.8, pp. 242–247.
- Erickson, N. et al. (2020). "Autogluon-tabular: Robust and accurate automl for structured data". In: *arXiv preprint arXiv:2003.06505*.
- Fakoor, R. et al. (2023). "Flexible model aggregation for quantile regression". In: *Journal of Machine Learning Research* 24.162, pp. 1–45.
- Feurer, M. et al. (2015). "Efficient and robust automated machine learning". In: *Advances in neural information processing systems* 28.
- Fiorucci, J. A. et al. (2016). "Models for optimising the theta method and their relationship to state space models". In: *International journal of forecasting* 32.4, pp. 1151–1161.
- Garza, A. et al. (2022). *StatsForecast: Lightning fast forecasting with statistical and econometric models*. PyCon Salt Lake City, Utah, US 2022. URL: <https://github.com/Nixtla/statsforecast>.
- Gastinger, J. et al. (2021). "A study on ensemble learning for time series forecasting and the need for meta-learning". In: *2021 International Joint Conference on Neural Networks (IJCNN)*. IEEE, pp. 1–8.
- Gijsbers, P. et al. (2024). "Amlb: an automl benchmark". In: *Journal of Machine Learning Research* 25.101, pp. 1–65.
- Godahehwa, R. et al. (2021). "Monash Time Series Forecasting Archive". In: *Neural Information Processing Systems Track on Datasets and Benchmarks*.
- Hasson, H. et al. (2023). "Theoretical guarantees of learning ensembling strategies with applications to time series forecasting". In: *International Conference on Machine Learning*. PMLR, pp. 12616–12632.
- Herzen, J. et al. (2022). "Darts: User-Friendly Modern Machine Learning for Time Series". In: *Journal of Machine Learning Research* 23.124, pp. 1–6. URL: <http://jmlr.org/papers/v23/21-1177.html>.
- Holzmüller, D., L. Grinsztajn, and I. Steinwart (2024). "Better by default: Strong pre-tuned mlps and boosted trees on tabular data". In: *Advances in Neural Information Processing Systems* 37, pp. 26577–26658.
- Hong, T. et al. (2016). "Probabilistic energy forecasting: Global Energy Forecasting Competition 2014 and beyond". In: *International Journal of Forecasting* 32.3, pp. 896–913. URL: <https://www.sciencedirect.com/science/article/pii/S0169207016000133>.

- Hyndman, R., A. B. Koehler, et al. (2008). *Forecasting with exponential smoothing: the state space approach*. Springer Science & Business Media.
- Hyndman, R. J. and Y. Khandakar (2008). "Automatic time series forecasting: the forecast package for R". In: *Journal of statistical software* 27, pp. 1–22.
- Hyndman, R. and G. Athanasopoulos (2021). *Forecasting: Principles and Practice*. English. 3rd. Australia: OTexts.
- Itericz, G. and S. Semenov (2016). *1st place - winner solution. Otto Group Product Classification Challenge*. <https://www.kaggle.com/c/otto-group-product-classification-challenge/discussion/14335>. Accessed: 2025-03-21.
- Januschowski, T. et al. (2020). "Criteria for classifying forecasting methods". In: *International Journal of Forecasting* 36.1, pp. 167–177.
- Ke, G. et al. (2017). "Lightgbm: A highly efficient gradient boosting decision tree". In: *Advances in neural information processing systems* 30.
- Kingma, D. P. (2014). "Adam: A method for stochastic optimization". In: *arXiv preprint arXiv:1412.6980*.
- Koren, Y. (2009). "The bellkor solution to the netflix grand prize". In: *Netflix prize documentation* 81.2009, pp. 1–10.
- Lim, B. et al. (2021). "Temporal fusion transformers for interpretable multi-horizon time series forecasting". In: *International Journal of Forecasting* 37.4, pp. 1748–1764.
- Löning, M. et al. (2019). "sktime: A unified interface for machine learning with time series". In: *arXiv preprint arXiv:1909.07872*.
- Makridakis, S., E. Spiliotis, and V. Assimakopoulos (2018). "The M4 Competition: Results, findings, conclusion and way forward". In: *International Journal of forecasting* 34.4, pp. 802–808.
- Makridakis, S., E. Spiliotis, and V. Assimakopoulos (2022). "M5 accuracy competition: Results, findings, and conclusions". In: *International Journal of Forecasting* 38.4, pp. 1346–1364.
- Montero-Manso, P. et al. (2020). "FFORMA: Feature-based forecast model averaging". In: *International Journal of Forecasting* 36.1, pp. 86–92.
- Nie, Y. et al. (2022). "A time series is worth 64 words: Long-term forecasting with transformers". In: *arXiv preprint arXiv:2211.14730*.
- Pawlikowski, M. and A. Chorowska (2020). "Weighted ensemble of statistical models". In: *International Journal of Forecasting* 36.1, pp. 93–97.
- Perrone, M. P. and L. N. Cooper (1995). "When networks disagree: Ensemble methods for hybrid neural networks". In: *How we learn; How we remember: Toward an understanding of brain and neural systems: Selected papers of Leon N Cooper*. World Scientific, pp. 342–358.
- Purucker, L. O. and J. Beel (2023). "CMA-ES for post hoc ensembling in AutoML: a great success and salvageable failure". In: *International Conference on Automated Machine Learning*. PMLR, pp. 1–1.
- Salinas, D. and N. Erickson (2024). *TabRepo: A Large Scale Repository of Tabular Model Evaluations and its AutoML Applications*. arXiv: 2311.02971 [cs.LG]. URL: <https://arxiv.org/abs/2311.02971>.
- Salinas, D., V. Flunkert, et al. (2020). "DeepAR: Probabilistic forecasting with autoregressive recurrent networks". In: *International journal of forecasting* 36.3, pp. 1181–1191.
- Shchur, O. et al. (2023). "AutoGluon-TimeSeries: AutoML for probabilistic time series forecasting". In: *International Conference on Automated Machine Learning*. PMLR, pp. 9–1.
- Smith, J. and K. F. Wallis (2009). "A simple explanation of the forecast combination puzzle". In: *Oxford bulletin of economics and statistics* 71.3, pp. 331–355.
- Stock, J. H. and M. W. Watson (2004). "Combination forecasts of output growth in a seven-country data set". In: *Journal of forecasting* 23.6, pp. 405–430.

- Tsang, T. K. et al. (2024). “An adaptive weight ensemble approach to forecast influenza activity in an irregular seasonality context”. In: *Nature Communications* 15.1, p. 8625. URL: <https://doi.org/10.1038/s41467-024-52504-1>.
- Tsoumakas, G., I. Partalas, and I. Vlahavas (2009). “An ensemble pruning primer”. In: *Applications of supervised and unsupervised ensemble methods*, pp. 1–13.
- Van der Laan, M. J., E. C. Polley, and A. E. Hubbard (2007). “Super learner”. In: *Statistical applications in genetics and molecular biology* 6.1.
- Wang, X. et al. (2023). “Forecast combinations: An over 50-year review”. In: *International Journal of Forecasting* 39.4, pp. 1518–1547.
- Wolpert, D. H. (1992). “Stacked generalization”. In: *Neural networks* 5.2, pp. 241–259.
- Woo, G. et al. (2024). *Unified Training of Universal Time Series Forecasting Transformers*. arXiv: 2402.02592 [cs.LG]. URL: <https://arxiv.org/abs/2402.02592>.
- Zeng, A. et al. (2023). “Are transformers effective for time series forecasting?” In: *Proceedings of the AAAI conference on artificial intelligence*. Vol. 37. 9, pp. 11121–11128.
- Zhou, Z.-H. (2012). *Ensemble methods: foundations and algorithms*. CRC press.
- Zöller, M.-A., M. Lindauer, and M. F. Huber (2024). “Auto-sktime: Automated Time Series Forecasting”. In: *International Conference on Learning and Intelligent Optimization*. Springer, pp. 456–471.

## Submission Checklist

### 1. For all authors...

- (a) Do the main claims made in the abstract and introduction accurately reflect the paper’s contributions and scope? [Yes]
- (b) Did you describe the limitations of your work? [Yes] See Sec. 7.
- (c) Did you discuss any potential negative societal impacts of your work? [N/A] After careful consideration, we could not identify any notable negative societal impacts of our work.
- (d) Did you read the ethics review guidelines and ensure that your paper conforms to them? <https://2022.automl.cc/ethics-accessibility/> [Yes]

### 2. If you ran experiments...

- (a) Did you use the same evaluation protocol for all methods being compared (e.g., same benchmarks, data (sub)sets, available resources)? [Yes] All evaluated models and methods were implemented in the same software framework, ensuring uniform evaluation.
- (b) Did you specify all the necessary details of your evaluation (e.g., data splits, pre-processing, search spaces, hyperparameter tuning)? [Yes] All relevant details are provided in Sec. 6 and the appendix.
- (c) Did you repeat your experiments (e.g., across multiple random seeds or splits) to account for the impact of randomness in your methods or data? [No] Due to a large number of evaluated models and datasets (44 models  $\times$  50 datasets  $\times$  2 task types), we evaluated all models using a single random seed.
- (d) Did you report the uncertainty of your results (e.g., the variance across random seeds or splits)? [Yes] In addition to the aggregated scores reported in Tables 1–2, we visualize the distribution of the relative model errors in Sec. E.2.
- (e) Did you report the statistical significance of your results? [Yes] We include the critical differences diagrams in Sec. E.
- (f) Did you use tabular or surrogate benchmarks for in-depth evaluations? [No] No tabular or surrogate benchmarks are available for the tasks considered in this paper.
- (g) Did you compare performance over time and describe how you selected the maximum duration? [N/A] We provided a fixed training time budget to all methods, capping the runtime for individual L2 ensemble methods to 10 minutes.
- (h) Did you include the total amount of compute and the type of resources used (e.g., type of GPUs, internal cluster, or cloud provider)? [Yes] We include information about resources and training times in Sec. D.
- (i) Did you run ablation studies to assess the impact of different components of your approach? [Yes] We include numerous ablation studies in Sec. 6.

### 3. With respect to the code used to obtain your results...

- (a) Did you include the code, data, and instructions needed to reproduce the main experimental results, including all requirements (e.g., requirements.txt with explicit versions), random seeds, an instructive README with installation, and execution commands (either in the supplemental material or as a URL)? [Yes] Included in the supplementary materials.

- (b) Did you include a minimal example to replicate results on a small subset of the experiments or on toy data? [Yes]
  - (c) Did you ensure sufficient code quality and documentation so that someone else can execute and understand your code? [Yes]
  - (d) Did you include the raw results of running your experiments with the given code, data, and instructions? [Yes] Raw results are available in results/ in the supplementary materials.
  - (e) Did you include the code, additional data, and instructions needed to generate the figures and tables in your paper based on the raw results? [Yes] Aggregation logic for the results is included in the supplementary materials.
4. If you used existing assets (e.g., code, data, models)...
- (a) Did you cite the creators of used assets? [Yes]
  - (b) Did you discuss whether and how consent was obtained from people whose data you're using/curating if the license requires it? [N/A] We only used publicly available datasets with open source licenses that don't contain PII.
  - (c) Did you discuss whether the data you are using/curating contains personally identifiable information or offensive content? [N/A] The datasets used for evaluation contain no PII.
5. If you created/released new assets (e.g., code, data, models)...
- (a) Did you mention the license of the new assets (e.g., as part of your code submission)? [N/A] Our experiments were conducted on publicly available datasets and we have not introduced new datasets.
  - (b) Did you include the new assets either in the supplemental material or as a URL (to, e.g., GitHub or Hugging Face)? [N/A] Our experiments were conducted on publicly available datasets and we have not introduced new datasets.
6. If you used crowdsourcing or conducted research with human subjects...
- (a) Did you include the full text of instructions given to participants and screenshots, if applicable? [N/A] We did not use crowdsourcing.
  - (b) Did you describe any potential participant risks, with links to Institutional Review Board (IRB) approvals, if applicable? [N/A] We did not use crowdsourcing.
  - (c) Did you include the estimated hourly wage paid to participants and the total amount spent on participant compensation? [N/A] We did not use crowdsourcing.
7. If you included theoretical results...
- (a) Did you state the full set of assumptions of all theoretical results? [N/A] No theoretical results were included.
  - (b) Did you include complete proofs of all theoretical results? [N/A] No theoretical results were included.

## A Datasets

Table 5: Dataset statistics. Note that all datasets were filtered to only contain time series with at least  $8 \times H$  observations to ensure that enough training & validation data is available.

Dataset	Freq.	Seasonality	Horizon ( $H$ )	Num. Series	Num. Obs.	Min. Length	Max. Length
BDG-2 Bear	h	24	48	91	1,482,312	8,760	17,544
BDG-2 Bull	h	24	48	41	719,304	17,544	17,544
BDG-2 Fox	h	24	48	135	2,324,568	8,760	17,544
BDG-2 Hog	h	24	48	24	421,056	17,544	17,544
BDG-2 Panther	h	24	48	105	919,800	8,760	8,760
BDG-2 Rat	h	24	48	280	4,728,288	8,760	17,544
Beijing Air Quality	h	24	48	132	4,628,448	35,064	35,064
Beijing Subway	30min	48	96	552	867,744	1,572	1,572
Borealis	h	24	48	15	83,269	3,528	7,447
CDC Fluview ILINet	W	1	8	375	319,515	211	1,359
Favorita Store Sales	D	7	16	1,782	3,008,016	1,688	1,688
Favorita Transactions	D	7	16	54	91,152	1,688	1,688
GEF12	h	24	48	11	433,554	39,414	39,414
GEF17	h	24	48	8	140,352	17,544	17,544
HZMetro	15min	96	96	160	380,320	2,377	2,377
Hierarchical Sales	D	7	14	118	212,164	1,798	1,798
IDEAL	h	24	48	217	1,255,253	393	16,167
KDD Cup 2022	10min	144	96	134	4,727,519	35,279	35,280
Los-Loop	5min	288	96	207	7,094,304	34,272	34,272
M-Dense	h	24	48	30	525,600	17,520	17,520
PEMS03	5min	288	96	358	9,382,464	26,208	26,208
PEMS08	5min	288	96	510	9,106,560	17,856	17,856
Project Tycho	W	1	8	1,258	1,377,707	102	3,854
SHMetro	15min	96	96	576	5,073,984	8,809	8,809
SMART	h	24	48	5	95,709	8,398	26,304
SZ-Taxi	15min	96	96	156	464,256	2,976	2,976
Subseasonal Precipitation	D	7	14	862	9,760,426	11,323	11,323
Australian Electricity	30min	48	96	5	1,155,264	230,736	232,272
ERCOT	h	24	24	8	1,238,976	154,872	154,872
ETT (15 Min.)	15min	96	96	14	975,520	69,680	69,680
ETT (Hourly)	h	24	24	14	243,880	17,420	17,420
Electricity (Hourly)	h	24	48	321	8,443,584	26,304	26,304
Electricity (Weekly)	W	1	8	321	50,076	156	156
FRED-MD	M	12	12	107	77,896	728	728
KDD Cup 2018	h	24	48	270	2,942,364	9,504	10,920
M4 (Daily)	D	1	14	4,218	10,022,845	112	9,933
M4 (Hourly)	h	24	48	414	373,372	748	1,008
M4 (Monthly)	M	12	18	32,436	9,773,903	144	2,812
M4 (Quarterly)	Q	4	8	19,049	2,167,663	64	874
M4 (Weekly)	W	1	13	294	365,534	260	2,610
NN5 (Daily)	D	7	56	111	87,801	791	791
NN5 (Weekly)	W	1	8	111	12,543	113	113
Pedestrian Counts	h	24	168	64	3,130,594	1,777	96,424
Solar (10 Min.)	10min	144	96	137	7,200,720	52,560	52,560
Taxi (30 Min.)	30min	48	96	2,428	3,589,798	1,469	1,488
Taxi (Hourly)	h	24	48	2,428	1,794,292	734	744
Traffic (Weekly)	W	1	8	862	89,648	104	104
Uber TLC (Daily)	D	7	14	262	47,422	181	181
Uber TLC (Hourly)	h	24	48	262	1,138,128	4,344	4,344
Wind Farms (Daily)	D	7	14	335	119,407	149	366

## B Models

### B.1 Base models

We considered the following base models, using their implementations provided by AutoGluon-TimeSeries (Shchur et al., 2023):



- **SeasonalNaive**: Simple model that sets the forecast equal to the last observed value from the same season (R. Hyndman and Athanasopoulos, 2021).
- **AutoETS**: Automatically tuned exponential smoothing with trend and seasonality (Garza et al., 2022; R. Hyndman, Koehler, et al., 2008; R. J. Hyndman and Khandakar, 2008)
- **DynamicOptimizedTheta**: A generalization of the Theta method by Assimakopoulos and Nikolopoulos (2000), that automatically selects and revises some of the model hyperparameters (Fiorucci et al., 2016).
- **DeepAR**: Autoregressive forecasting model based on a recurrent neural network (Salinas, Flunkert, et al., 2020).
- **PatchTST**: Transformer-based forecaster that segments each time series into patches (Nie et al., 2022).
- **TemporalFusionTransformer**: Combines LSTM with a transformer layer to predict the quantiles of all future target values (Lim et al., 2021).
- **DirectTabular**: Predict the future time series values by transforming the task into a tabular prediction task and then applying the LightGBM quantile regressor (Ke et al., 2017).
- **RecursiveTabular**: Predict the future time series values one-by-one by transforming the task into a tabular prediction task and then applying the LightGBM regressor (Ke et al., 2017). In contrast to **DirectTabular**, the forecast is computed step-by-step by repeatedly applying the tabular method.
- **TiDEModel**: Time series dense encoder model (Das et al., 2023).
- **Chronos**: Pretrained time series forecasting model (Ansari et al., 2024). We use the `bol_t_base` configuration.

For simplicity, we do not investigate the effect of hyperparameter tuning on the models and keep all the hyperparameters to their default values. We do not expect this to affect our main conclusions, given the stability of our results with respect to the L1 model choice (Sec. 6.4).

For each dataset, we generate the base model predictions by fitting all models with 5 validation windows, refitting each model from scratch for each window. We set the maximum time limit of 30 minutes per window per model to avoid extremely long runtimes, though the vast majority of models complete training within 5 minutes per window. We save the base model predictions for all validation windows and the test window to disk. This enables us to train the stacker models without needing to re-fit the base models.

## B.2 Individual forecast combination methods

- **Simple averages**: We consider two simple averages, *mean* and *median*, which compute the mean or median of all base model predictions, respectively.
- **Model selection**: Model selection computes the index of the best-performing model according to the validation data during training, and then uses this individual model for forecasting.
- **Performance-weighted averages**: These models are weighted averages of the form  $g(\hat{y}_1, \dots, \hat{y}_M) = \sum_{m=1}^M \omega_m \hat{y}_m$ , where the weights  $\omega_m$  are computed directly from the (normalized) validation scores of the individual models, as  $\omega_m \propto h(L_m)$ , with  $L_m \propto \mathcal{L}(\hat{y}_m, y_{\text{out}})$  such that  $\sum_{m=1}^M L_m = 1$ , and  $\sum_{m=1}^M \omega_m = 1$ . We consider three options for the function  $h$ :
  - Inv.:  $h_{\text{inv}}(L) = 1/L$ ,
  - Sqr.:  $h_{\text{sqr}}(L) = 1/L^2$ ,

– Exp.:  $h_{\text{exp}}(L) = \exp(1/L)$

Refer to Pawlikowski and Chorowska (2020) for more details.

- **Greedy ensembles:** This is the *ensemble selection* method by (Caruana et al., 2004), which optimizes the validation loss by greedily adding models to an equally-weighted ensemble *with replacement*. As an equally-weighted ensemble with replacement is equivalent to a weighted average with fractional weights, the greedy ensemble can also be interpreted as a weighted average  $g(\hat{y}_1, \dots, \hat{y}_M) = \sum_{m=1}^M \omega_m \hat{y}_m$  which is optimized via coordinate-wise ascent: Starting with zero weights  $\omega^{(0)} = 0 \in \mathbb{R}^M$ , the algorithm iterates for  $j = 1, \dots, S$ , and selects at each step the model that would minimize the resulting loss, i.e.

$$m^{(j)} = \arg \min_{m=1, \dots, M} \mathcal{L} \left( g_{\hat{\omega}_m^{(j)}}(\hat{y}_1, \dots, \hat{y}_M), y_{\text{ensemble}} \right), \quad (3)$$

where  $\hat{\omega}_m^{(j)} := ((j-1)\omega^{(j-1)} + e_m)/j$  are the weights that the greedy ensemble would have if it were to select model  $m$ , with  $e_m \in \mathbb{R}^M$  being a canonical basis vector, i.e.  $[e_m]_k = \mathbb{1}_{k=m}$ . It then adds the model to the ensemble and sets  $\omega^{(j)} = \hat{\omega}_{m^{(j)}}^{(j)}$ . This approach is currently also used as the default in multiple AutoML forecasting frameworks (Deng et al., 2022; Shchur et al., 2023; Zöller et al., 2024). In our evaluation, we consider three versions of this model, with the number of iterations  $S$  set to 10, 100, and 1000, respectively.

- **Linear models:** For linear models, we consider a class of models  $g_i$  of the form

$$[g_i(\hat{y}_{i,1}, \dots, \hat{y}_{i,M})]_{h,q} = \sum_{m=1}^M \omega_{i,h,q,m} \cdot [\hat{y}_{i,m}]_{h,q} \quad (4)$$

with weights  $\omega \in \mathbb{R}^{N \times H \times Q \times M}$ . More concretely, we consider a number of variations of this model which satisfy different constraints or have different degrees of weight-tying:

- *Positivity and simplex constraints:* It is often desirable to enforce positivity and/or simplex constraints, that is,  $\omega_{i,h,q,m} > 0$  and  $\sum_m \omega_{i,h,q,m} = 1$ , respectively (X. Wang et al., 2023). In our model, we enforce constraints by parameterizing the weights through an unconstrained weight  $\tilde{\omega}_{i,h,q,m}$  and then passing it through an activation function. We consider two versions:
  - \* softmax: This version enforces both positivity and simplex constraints by passing the unconstrained weights through a softmax activation function:

$$\omega_{i,h,q,m} = \frac{\exp(\tilde{\omega}_{i,h,q,m})}{\sum_{m'} \exp(\tilde{\omega}_{i,h,q,m'})}. \quad (5)$$

- \* positive: This version enforces positivity, but not the simplex constraint, by passing the unconstrained weights through a quadratic function:

$$\omega_{i,h,q,m} = (\tilde{\omega}_{i,h,q,m})^2. \quad (6)$$

- *Weight-tying:* Instead of considering different weights for each model, item, time step, and quantile, we can lower the complexity by tying weights across some of these dimensions (Hasson et al., 2023). For example, tying weights across items would imply  $\omega_{i,h,q,m} = \omega_{i',h,q,m}$  for all items  $i, i'$ . This yields a number of different linear models, denoted by the dimension along which the weights are *not* tied:
  - \* m: One weight per model; weights are tied across items, prediction times, and quantiles. This case is equivalent to weighted average models.
  - \* mi: One weight per model and per item; weights are tied across prediction times and quantiles.

- \* mt: One weight per model and per prediction time; weights are tied across items and quantiles.
- \* mq: One weight per model and per quantile; weights are tied across items and prediction times.
- \* mit: One weight per model, item, and prediction time; weights are tied across quantiles.
- \* miq: One weight per model, item, and quantile; weights are tied across prediction times.
- \* mtq: One weight per model, prediction time, and quantile; weights are tied across items.
- \* mitq: One weight per model, item, prediction time, and quantile; no weight-tying.
- *Across-quantile weights*: Instead of treating all quantiles independently, we can also compute quantile predictions *across quantiles* and rely on the base model estimates of all quantiles, as proposed by Fakoor et al. (2023); In its most flexible form, this corresponds to a model of the form

$$[g_i(\hat{y}_{i,1}, \dots, \hat{y}_{i,M})]_{h,q} = \sum_{m=1}^M \sum_{q' \in \mathcal{Q}} \omega_{i,h,q,q',m} \cdot [\hat{y}_{i,m}]_{h,q'}, \quad (7)$$

with weights  $\omega \in \mathbb{R}^{N \times H \times Q \times Q \times M}$ . As before, we consider softmax and positive versions as well as different weight-tying options:

- \* mqq: One weight per model and across quantiles; weights are tied across items and prediction times.
- \* miqq: One weight per model, items, and across quantiles; weights are tied across prediction times.
- \* mtqq: One weight per model, prediction time, and across quantiles; weights are tied across items.

*Training.* We train linear stacker models by optimizing the resulting loss:

$$\omega = \arg \min_{\omega' \in \mathbb{R}^{N \times H \times Q \times M}} \sum_i \mathcal{L}(g_i(\hat{y}_{i,1}, \dots, \hat{y}_{i,M}), y_{i,T+1:T+H}), \quad (8)$$

where  $g_i$  is a linear model that uses the to-be-optimized weights  $\omega'$ . This can be approached with any numerical optimizer. In our implementation, we rely on the Adam optimizer (Kingma, 2014) and we use a custom learning rate schedule to reduce the learning rate whenever a plateau is hit and the loss starts oscillating. We also limit the training time to 10 minutes.

- **Nonlinear models:** To apply nonlinear models, we re-formulate the stacking problem as a tabular regression problem. Each item  $\times$  timestep combination corresponds to a row in the training data. The quantile forecasts of the L1 models are used as features, and the ground truth time series value is the training target. We can then train any tabular regression model on this data. In our experiments we consider two methods:
  - RealMLP is a deep-learning approach for tabular problems which improves on standard MLPs through a number of tricks and better, meta-learned default parameters (Holzmüller et al., 2024). We use the multi-quantile loss evaluated at levels  $\mathcal{Q}$  as the training objective.
  - LightGBM is a highly efficient implementation of gradient-boosted decision trees (Ke et al., 2017). We train a separate LightGBM regressor to predict each of the quantile levels  $\mathcal{Q}$ .

Additionally, we consider *scaled* versions of both methods in which we normalize the model predictions before feeding them into the tabular stacker model and then un-normalize the outputs again. This corresponds to a modified model  $g'$  of the form

$$g'_i(\hat{y}_{i,1}, \dots, \hat{y}_{i,M}) = \frac{g_i(\alpha \hat{y}_{i,1} + \beta, \dots, \alpha \hat{y}_{i,M} + \beta) - \beta}{\alpha}, \quad (9)$$

where  $\alpha, \beta$  are computed from the empirical mean and standard deviation of the predictions in order to standardize the inputs, and  $g$  is a tabular stacker model as introduced above.

From each category we select one “representative model” for our condensed experiment summary in the paper, as described in Tab. 6 and Tab. 7.

Table 6: Representative models per category for the quantile forecast experiment.

Model category	Model
Median	Median
Model Selection	Model selection
Performance-based average	Performance-based average (exp)
Greedy ensemble selection	Greedy (S=100)
Linear model	Linear(mq, softmax)
Nonlinear model	LightGBM (scaled)

Table 7: Representative models per category for the point forecast experiment.

Model category	Model
Median	Median
Model Selection	Model selection
Performance-based average	Performance-based average (exp)
Greedy ensemble selection	Greedy (S=100)
Linear model	Linear(m, softmax)
Nonlinear model	LightGBM (scaled)

### B.3 Multi-layer stacker models

For multilayer stacking, we use the following 14 stacker models as L2 models:

- Median
- Greedy (S=100)
- Linear (mi, softmax)
- Linear (mt, softmax)
- Linear (mq, softmax)
- Linear (mit, positive)
- Linear (mtq, positive)
- Linear (miq, positive)
- Linear (mqq, positive)
- Linear (miqq, positive)
- Linear (mtqq, positive)
- LightGBM
- LightGBM (scaled)
- RealMLP (scaled)

We have arbitrarily chosen these 14 L2 models since they provide a good coverage of different model families. To ensure a fair comparison, we have fixed this selection before running any experiments, and did not adjust the selection to optimize the benchmark performance.

We then consider multi-layer stackers resulting from two different L3 models:

- **Stacker model selection** uses *model selection* as its L3 model and thus relies on a single L2 model during test time.

- **Multi-layer stacking** uses *Greedy* ( $S=100$ ) as its L3 model to compute a weighted average of the L2 model predictions.

## C Evaluation metrics

### C.1 Loss functions

Loss functions are used both to train and evaluate time series models. In Sec. 2.1, we introduced them as functions that take in the (quantile) prediction of a particular item as well as the ground-truth values and return a positive scalar value, that is

$$\mathcal{L} : \mathbb{R}^{H \times Q} \times \mathbb{R}^H \rightarrow \mathbb{R}_{\geq 0}, \quad (10)$$

with lower values indicating a more accurate forecast. We consider the following two losses to evaluate quantile forecasts and point forecasts, respectively:

- **Scaled quantile loss (SQL):**

$$\text{SQL}(\hat{y}_i, y_i) := \frac{1}{H} \frac{1}{Q} \frac{1}{a_i} \sum_{h=1}^H \sum_{q \in Q} \rho_q(\hat{y}_{i,T+h}^q, y_{i,T+h}), \quad (11)$$

where  $\rho_q : \mathbb{R} \times \mathbb{R} \rightarrow \mathbb{R}$  is the *quantile loss at level  $q$* , defined as

$$\rho_q(\hat{y}_{i,h}^q, y_{i,h}) := 2 \cdot \begin{cases} q \cdot (y_{i,h} - \hat{y}_{i,h}^q), & \text{if } y_{i,h} < \hat{y}_{i,h}^q, \\ (1 - q) \cdot (\hat{y}_{i,h}^q - y_{i,h}), & \text{if } y_{i,h} \geq \hat{y}_{i,h}^q, \end{cases} \quad (12)$$

and where  $a_i$  is the *historic absolute seasonal error* of the time series, defined as

$$a_i = \frac{1}{T - m} \sum_{t=m+1}^T |y_{i,t} - y_{i,t-m}|, \quad (13)$$

with  $m$  the seasonality of the dataset provided in Tab. 5.

- **Mean absolute scaled error (MASE):**

$$\text{MASE}(\hat{y}_i, y_i) := \frac{1}{H} \frac{1}{a_i} \sum_{h=1}^H |\hat{y}_{i,T+h} - y_{i,T+h}|, \quad (14)$$

where  $a_i$  is the historic absolute seasonal error, as defined above. Note that MASE is equivalent to an SQL applied only to the 0.5 quantile.

To evaluate a particular time series model on a whole dataset, we average the loss across all individual items.

When evaluating point and probabilistic forecast performance, we used MASE or SQL as the training objective, respectively. This means, that all L2 and L3 models were trained once for point forecasting tasks using MASE as the training loss, and one more time for probabilistic forecasting tasks using the SQL loss.

### C.2 Result aggregation

To summarize the empirical evaluation, we aggregate the individual losses  $L_{m,d}$  of each model  $m$  and dataset  $d$  in a number of ways:

- **Elo:** The Elo rating system was originally introduced to calculate the relative skill levels of players in zero-sum games such as chess (Elo, 1967), but it has recently also been used to evaluate large language models (Bai et al., 2022; Boubdir et al., 2024). We compute our Elo scores as done in the recently proposed “Chatbot Arena” (Chiang et al., 2024), and calibrate the computation such that our chosen baseline has an Elo of 1000.
- **Average rank:** First, for each dataset in our evaluation, we rank the methods by their achieved error (resolving ties such that models receive the average rank of the tied models). Then, we compute the average rank of each model over all datasets with an arithmetic mean.
- **Champion:** This metric counts for how many datasets the method has achieved the lowest error among all methods included in the comparison. As we already computed a ranking for each dataset, this can be done by simply counting how often a method achieves rank 1. Since sometimes multiple methods are tied for the first place, the sum of the values in the “Champion” column does not always add up to the number of the datasets.
- **Average relative error:** To make the errors on different datasets more comparable, we first compute *relative* errors with respect to a chosen baseline method  $\bar{m}$  (namely the “simple average (median)” method), as

$$L_{m,d}^{\text{rel}} := \frac{L_{m,d}}{L_{\bar{m},d}}. \quad (15)$$

To limit the influence of outliers, we clip the individual relative errors to the range  $[10^{-3}, 5]$ . Then, we compute the *average relative error* of each model  $m$  across all datasets by aggregating the respective relative errors with a geometric mean:

$$\text{AverageRelativeError}_m = \text{GeometricMean}(L_{m,1}^{\text{rel}}, \dots, L_{m,D}^{\text{rel}}). \quad (16)$$

## D Computational resources

All models were trained on cloud-hosted machines with 16 vCPUs and 64GB RAM. The base models were trained with a time limit of 30 minutes per window per model to avoid extremely long runtimes, though the vast majority of models complete training within 5 minutes per window. The individual L2 stacker models were trained as described in Sec. B.2, either for a fixed, pre-specified number of steps, or until convergence within a time limit of 10 minutes. See also Tab. 11 and Tab. 12 for the median training times of the base and stacker models.

## E Additional figures and tables

- Tab. 8: Full probabilistic forecasting results. SQL error values for all datasets  $\times$  all methods (11 base models and 33 combination methods).
- Tab. 9: Full point forecasting results. MASE error values for all datasets  $\times$  all methods (11 base models and 33 combination methods).
- Fig. 5: Critical differences (CD) diagram for 8 representative combination methods (probabilistic forecasting / SQL).
- Fig. 6: Critical differences (CD) diagram for 8 representative combination methods (point forecasting / MASE).
- Fig. 7: Distribution of relative error scores for 8 representative combination methods (probabilistic forecasting / SQL).

- Fig. 8: Distribution of relative error scores for 8 representative combination methods (point forecasting / MASE).
- Tab. 11: Median training time per validation window for L1 models.
- Tab. 12: Median end-to-end training time for the ensemble models.
- Fig. 9: Weights assigned by the L3 ensemble selection algorithm to the constituent L2 stacker models (probabilistic forecasting / SQL).
- Fig. 10: Weights assigned by the L3 ensemble selection algorithm to the constituent L2 stacker models (point forecasting / MASE).
- Tab. 10: Normalized error for each representative combination method and dataset combination (probabilistic forecasting / SQL).

### E.1 Critical differences diagrams




Figure 5: Critical differences (CD) diagram for 8 representative combination methods. Based on probabilistic forecasting tasks (SQL metric).




Figure 6: Critical differences (CD) diagram for 8 representative combination methods. Based on point forecasting tasks (MASE metric).

## E.2 Distribution of relative errors




Figure 7: Distribution of the relative errors for each combination method (normalized by the performance of median aggregation). Based on probabilistic forecasting tasks (SQL metric).




Figure 8: Distribution of the relative errors for each combination method (normalized by the performance of median aggregation). Based on point forecasting tasks (MASE metric).



Table 8: Quantile forecast accuracy for base and stacker models, measured with scaled quantile loss (SQL). Lower values are better.

[illegible]

Point forecast accuracy for base and stacker models, measured with mean absolute scaled error (MASE). Lower values are better.

Dataset	Individual models										Performance-weighted										Greedy ensemble										Linear autothms										Low-positivity										Nonlinear models										Stacker Model Selection										Multi-layer Stacking																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																		
	Model Selection										Exp.										Inv.										Sqr.										S-100										S-1000										m											mi										m1										m2										m3										m4										m5										m6										m7										m8										m9										m10										m11										m12										m13										m14										m15										m16										m17										m18										m19										m20										m21										m22										m23										m24										m25										m26										m27										m28										m29										m30										m31										m32										m33										m34										m35										m36										m37										m38										m39										m40										m41										m42										m43										m44										m45										m46										m47										m48										m49										m50										m51										m52										m53										m54										m55										m56										m57										m58										m59										m60										m61										m62										m63										m64										m65										m66										m67										m68										m69										m70										m71										m72										m73										m74										m75										m76										m77										m78										m79										m80										m81										m82										m83										m84										m85										m86										m87										m88										m89										m90										m91										m92										m93										m94										m95										m96										m97										m98										m99										m100										m101										m102										m103										m104										m105										m106										m107										m108										m109										m110										m111										m112										m113										m114										m115										m116										m117										m118										m119										m120										m121										m122										m123										m124										m125										m126										m127										m128										m129										m130										m131										m132										m133										m134										m135										m136										m137										m138										m139										m140										m141										m142										m143										m144										m145										m146										m147										m148										m149										m150										m151										m152										m153										m154										m155										m156										m157										m158										m159										m160										m161										m162										m163										m164										m165										m166										m167										m168										m169										m170										m171										m172										m173										m174										m175										m176										m177										m178										m179										m180										m181										m182										m183										m184										m185										m186										m187										m188										m189										m190										m191										m192										m193										m194										m195										m196										m197										m198										m199										m200										m201										m202										m203										m204										m205										m206										m207										m208										m209										m210										m211										m212										m213										m214										m215										m216										m217										m218										m219										m220										m221										m222										m223										m224										m225										m226										m227										m228										m229										m230										m231										m232										m233										m234										m235										m236										m237										m238										m239										m240										m241										m242										m243										m244										m245										m246										m247										m248										m249										m250										m251										m252										m253										m254										m255										m256										m257										m258										m259										m260										m261										m262										m263										m264										m265										m266										m267										m268										m269										m270										m271										m272										m273										m274										m275										m276										m277										m278										m279										m280										m281										m282										m283										m284										m285										m286										m287										m288										m289										m290										m291										m292										m293										m294										m295										m296										m297										m298										m299										m300										m301										m302										m303										m304										m305										m306										m307										m308										m309										m310										m311										m312										m313										m314										m315										m316										m317										m318										m319										m320										m321										m322										m323										m324										m325										m326										m327										m328										m329										m330										m331										m332										m333										m334										m335										m336										m337										m338										m339										m340										m341										m342										m343										m344										m345										m346										m347										m348										m349										m350										m351										m352										m353										m354										m355										m356										m357										m358										m359										m360										m361										m362										m363										m364										m365										m366										m367										m368										m369										m370										m371										m372										m373										m374										m375										m376										m377										m378										m379										m380										m381										m382										m383										m384										m385										m386										m387										m388										m389										m390										m391										m392										m393										m394										m395										m396										m397										m398										m399										m400										m401										m402										m403										m404										m405										m406										m407										m408										m409										m410										m411										m412										m413										m414										m415										m416										m417										m418										m419										m420										m421										m422										m423										m424										m425										m426										m427										m428										m429										m430										m431										m432										m433										m434										m435										m436										m437										m438										m439										m440										m441										m442										m443										m444										m445										m446										m447										m448										m449										m450										m451										m452										m453										m454										m455										m456										m457										m458										m459										m460										m461										m462										m463										m464										m465										m466										m467										m468										m469										m470										m471										m472										m473										m474										m475										m476										m477										m478										m479										m480										m481										m482										m483										m484										m485										m486										m487										m488										m489										m490										m491										m492										m493										m494										m495										m496										m497										m498										m499										m500										m501										m502										m503										m504										m505										m506										m507										m508										m509										m510										m511										m512										m513										m514										m515										m516										m517										m518										m519										m520										m521										m522										m523										m524										m525										m526										m527										m528										m529										m530										m531										m532										m533										m534										m535										m536										m537										m538										m539										m540										m541										m542										m543										m544										m545										m546										m547										m548										m549										m550										m551										m552										m553										m554										m555										m556										m557										m558										m559										m560										m561										m562										m563										m564										m565										m566										m567										m568										m569										m570										m571										m572										m573										m574										m575										m576										m577										m578										m579										m580										m581										m582										m583										m584										m585										m586										m587										m588										m589										m590										m591										m592										m593										m594										m595										m596										m597										m598										m599										m600										m601										m602										m603										m604										m605										m606										m607										m608										m609										m610										m611										m612										m613										m614										m615										m616										m617										m618										m619										m620										m621										m622										m623										m624										m625										m626										m627										m628										m629										m630										m631										m632										m633										m634										m635										m636										m637										m638										m639										m640										m641										m642										m643										m644										m645										m646										m647										m648										m649										m650										m651										m652										m653										m654										m655										m656										m657										m658										m659										m660										m661										m662										m663										m664										m665										m666										m667										m668										m669										m670										m671										m672										m673										m674										m675										m676										m677										m678										m679										m680										m681										m682										m683										m684										m685										m686										m687										m688										m689										m690										m691										m692										m693										m694										m695										m696										m697										m698										m699										m700										m701										m702										m703										m704										m705										m706										m707										m708										m709										m710										m711										m712										m713										m714										m715										m716										m717										m718										m719										m720										m721										m722										m723										m724										m725										m726										m727										m728										m729										m730										m731										m732										m733										m734										m735										m736										m737										m738										m739										m740										m741										m742										m743										m744										m745										m746										m747										m748										m749										m750										m751										m752										m753										m754										m755										m756										m757										m758										m759										m760										m761										m762										m763										m764										m765										m766										m767										m768										m769										m770										m771										m772										m773										m774										m775										m776										m777										m778										m779										m780										m781										m782										m783										m784										m785										m786										m787										m788										m789										m790										m791										m792										m793										m794										m795										m796										m797										m798										m799										m800										m801										m802										m803										m804										m805										m806										m807										m808										m809										m810										m811										m812										m813										m814										m815										m816										m817										m818										m819										m820										m821										m822										m823										m824										m825										m826										m827										m828										m829										m830										m831										m832										m833										m834										m835										m836										m837										m838										m839										m840										m841										m842										m843										m844										m845										m846										m847										m848										m849										m850										m851										m852										m853										m854										m855										m856										m857										m858										m859										m860										m861										m862										m863										m864										m865										m866										m867										m868										m869										m870										m871										m872										m873										m874										m875										m876										m877										m878										m879										m880										m881										m882										m883										m884										m885										m886										m887										m888										m889										m890										m891										m892										m893										m894										m895										m896										m897										m898										m899										m900										m901										m902										m903										m904										m905										m906										m907										m908										m909										m910										m911										m912										m913										m914										m915										m916										m917										m918										m919										m920										m921										m922										m923										m924										m925										m926										m927										m928										m929										m930										m931										m932										m933										m934										m935										m936										m937										m938										m939										m940										m941										m942										m943										m944										m945							

Table 10: Normalized error of each representative combination method per dataset, relative to the best model for that dataset (probabilistic tasks / SQL metric). Two key observations: (1) When most stackers perform reasonably (normalized error < 1.2), multi-layer stacking typically ranks among the top performers. (2) It underperforms when most constituent stackers—especially nonlinear ones—produce poor forecasts.

Dataset	Median	Model selection	Performance-based average	Greedy ensemble selection	Linear model	Nonlinear model	Stacker model selection	Multi-layer stacking
ETTh	1.068	1.173	1.049	1.056	1.050	1.157	1.025	1.000
HZMETRO	1.096	1.139	1.115	1.095	1.086	1.029	1.032	1.000
LOS-LOOP	1.364	1.301	1.146	1.104	1.095	1.046	1.056	1.000
PEMS08	1.378	1.124	1.028	1.056	1.048	1.039	1.039	1.000
bdg-2-bear	1.089	1.107	1.064	1.087	1.123	1.070	1.045	1.000
bdg-2-rat	1.240	1.051	1.067	1.051	1.038	1.055	1.016	1.000
borealis	1.090	1.068	1.051	1.047	1.055	1.014	1.017	1.000
hog	1.199	1.224	1.146	1.160	1.120	1.040	1.040	1.000
ideal	1.041	1.021	1.007	1.001	1.001	1.006	1.010	1.000
m4-daily	1.007	1.042	1.029	1.029	1.005	1.479	1.007	1.000
m4-hourly	1.350	1.149	1.149	1.101	1.089	1.029	1.027	1.000
m4-monthly	1.043	1.436	1.097	1.436	1.078	2.118	1.024	1.000
m4-quarterly	1.033	1.066	1.029	1.017	1.019	1.001	1.012	1.000
m4-weekly	1.173	1.250	1.098	1.084	1.073	1.109	1.042	1.000
nn5	1.057	1.025	1.008	1.007	1.008	1.021	1.008	1.000
nn5-weekly	1.043	1.046	1.017	1.025	1.026	1.083	1.025	1.000
project-tycho	1.020	1.011	1.025	1.004	1.001	1.003	1.001	1.000
store-sales	1.022	1.000	1.013	1.001	1.007	1.012	1.007	1.000
transactions	1.124	1.103	1.063	1.049	1.048	1.047	1.015	1.000
uber-tlc-daily	1.027	1.024	1.002	1.001	1.009	1.026	1.027	1.000
SZ-TAXI	1.027	1.055	1.014	1.001	1.000	1.011	1.001	1.001
PEMS03	1.076	1.000	1.067	1.064	1.049	1.108	1.076	1.005
kdd-cup-2018	1.163	1.046	1.026	1.002	1.000	1.092	1.000	1.005
hierarchical-sales	1.011	1.009	1.013	1.003	1.000	1.037	1.000	1.005
taxi-30min	1.188	1.002	1.003	1.002	1.000	1.008	1.008	1.005
bull	1.008	1.031	1.000	1.017	1.005	1.048	1.017	1.008
uber-tlc-hourly	1.151	1.000	1.003	1.000	1.001	1.016	1.013	1.010
pedestrian-counts	1.026	1.060	1.060	1.052	1.039	1.000	1.028	1.011
ercot	1.121	1.124	1.052	1.000	1.069	1.030	1.000	1.016
traffic-weekly	1.043	1.084	1.020	1.000	1.004	1.064	1.045	1.025
taxi-1h	1.479	1.000	1.000	1.006	1.003	1.046	1.006	1.026
smart	1.030	1.054	1.000	1.032	1.032	1.121	1.032	1.027
ETTh	1.124	1.000	1.052	1.037	1.026	1.230	1.042	1.027
electricity-weekly	1.290	1.000	1.050	1.017	1.041	1.175	1.017	1.030
beijing-air-quality	1.343	1.042	1.048	1.089	1.061	1.093	1.000	1.030
wind-farms-daily	1.030	1.000	1.040	1.005	1.011	1.074	1.074	1.036
subseasonal-precip	1.151	1.127	1.126	1.078	1.058	1.000	1.053	1.037
electricity-hourly	1.245	1.000	1.043	1.040	1.046	1.090	1.040	1.037
cdc-fluview-ilinet	1.072	1.077	1.000	1.015	1.027	1.201	1.110	1.048
BEIJING-SUBWAY-30MIN	1.055	1.607	1.466	1.072	1.073	1.000	1.090	1.051
bdg-2-panther	1.173	1.000	1.129	1.069	1.082	1.157	1.144	1.064
fred-md	1.000	1.127	1.011	1.015	1.000	1.009	1.088	1.068
SHMETRO	1.000	1.018	1.017	1.022	1.015	1.094	1.094	1.075
kdd2022	1.034	1.382	1.226	1.341	1.120	1.000	1.140	1.140
gfc12-load	1.077	1.299	1.023	1.000	1.060	1.361	1.133	1.140
bdg-2-fox	1.555	1.000	1.335	1.152	1.150	1.111	1.152	1.150
M-DENSE	1.058	1.052	1.009	1.000	1.071	1.270	1.270	1.159
australian-electricity	1.076	1.000	1.141	1.264	1.218	1.484	1.277	1.321
gfc17-load	1.000	2.568	1.179	1.317	1.464	1.385	1.991	1.447
solar-10-minutes	1.000	1.583	1.576	1.096	1.163	2.945	2.945	2.158

Table 11: Median training time for L1 models per one validation window (in seconds) for probabilistic tasks.

Model	Duration (seconds)
AutoETS	14
Chronos	8
DLinear	26
DeepAR	149
DirectTabular	233
Theta	8
PatchTST	63
RecursiveTabular	51
SeasonalNaive	1
TFT	204
TiDE	176

Table 12: Median end-to-end training time for ensemble models (in seconds) for probabilistic tasks.

Model	Duration (seconds)
Simple Average (Mean)	1
Simple Average (Median)	1
Model Selection	1
Performance-based (Exp.)	2
Performance-based (Inv.)	2
Performance-based (Sqr.)	2
Greedy (S=10)	2
Greedy (S=100)	11
Greedy (S=1000)	70
Linear (m, softmax)	15
Linear (m, positive)	13
Linear (mi, softmax)	7
Linear (mi, positive)	34
Linear (miq, softmax)	12
Linear (miq, positive)	44
Linear (mit, softmax)	12
Linear (mit, positive)	44
Linear (mitq, softmax)	30
Linear (mitq, positive)	77
Linear (mq, softmax)	11
Linear (mq, positive)	15
Linear (mqq, softmax)	10
Linear (mqq, positive)	33
Linear (mt, softmax)	7
Linear (mt, positive)	31
Linear (mtq, softmax)	13
Linear (mtq, positive)	52
LightGBM	25
LightGBM (scaled)	26
RealMLP	200
RealMLP (scaled)	207
Stacker Model Selection	484
Multi-layer Stacking	721




Figure 9: Weights assigned by the L3 ensemble selection algorithm to the L2 stacker models over 50 probabilistic forecasting tasks.




Figure 10: Weights assigned by the L3 ensemble selection algorithm to the L2 stacker models over 50 point forecasting tasks.