



● Fixed Port	<ul style="list-style-type: none"> <li>➤ 16*10/100/1000Base-TX PoE port (Data/Power)</li> <li>➤ 2*1000M SFP</li> </ul>
● PoE Ports	<ul style="list-style-type: none"> <li>➤ 1-16 port supports PoE (optional first port outputs HiPoE_60W)</li> </ul>
● Function	<ul style="list-style-type: none"> <li>➤ N:(Standard normal)</li> <li>➤ V:(Port isolation)</li> <li>➤ S:(Super mode)</li> </ul>
● Network Protocol	<ul style="list-style-type: none"> <li>➤ IEEE 802.3</li> <li>➤ IEEE 802.3i 10BASE-T</li> <li>➤ IEEE 802.3u 100BASE-TX</li> <li>➤ IEEE 802.3ab1000BASE-T</li> <li>➤ IEEE 802.3x</li> <li>➤ IEEE 802.3z 1000BASE-X</li> <li>➤ IEEE 802.3af/at</li> </ul>
● PoE Standard	<ul style="list-style-type: none"> <li>➤ IEEE802.3af/at</li> </ul>
● Port Specification	<ul style="list-style-type: none"> <li>➤ 10/100/1000BaseT (X) Auto</li> </ul>
● Transmission Mode	<ul style="list-style-type: none"> <li>➤ Store and Forward(full wirespeed)</li> </ul>
● Bandwidth	<ul style="list-style-type: none"> <li>➤ 56Gbps</li> </ul>
● Packet Forwarding	<ul style="list-style-type: none"> <li>➤ 40.32Mpps</li> </ul>
● MAC Address	<ul style="list-style-type: none"> <li>➤ 8K</li> </ul>
● Buffer	<ul style="list-style-type: none"> <li>➤ 4.1M</li> </ul>
● Transmission Distance	<ul style="list-style-type: none"> <li>➤ 10BASE-T : Cat3,4,5 UTP(≤250 meter)</li> <li>➤ 100BASE-TX : Cat5 or later UTP(150 meter)</li> <li>➤ 1000BASE-TX : Cat6 or later UTP(150 meter)</li> <li>➤ 1000BASE-SX:62.5μm/50μm MMF(2m~550m)</li> <li>➤ 1000BASE-LX:62.5μm/50μm MM(2m~550m) or 10μm SMF(2m~5000m)</li> </ul>
● Power Pin	<ul style="list-style-type: none"> <li>➤ Default 1/2(+), 3/6(-); Optional order4/5(+), 7/8(-)</li> </ul>
● Single port power	<ul style="list-style-type: none"> <li>➤ Average 15.4W; MAX 30W</li> </ul>
● Total power/Input voltage	<ul style="list-style-type: none"> <li>➤ MAX 300W (AC100-240V 50/60HZ)</li> </ul>
● Watt	<ul style="list-style-type: none"> <li>➤ Standby Power Consumption: ≤20W;</li> </ul>
● LED Indicator	<ul style="list-style-type: none"> <li>➤ PWR:Power LED(optional over-power LED)</li> <li>➤ 1~16:(Link LED=10/100M Link、1000M=Gigabit Link)</li> <li>➤ 17 18:(SFP LED)</li> </ul>
● Power Input	<ul style="list-style-type: none"> <li>➤ Built-in power AC: 100 ~ 240V 50-60Hz 1A</li> </ul>
● Operating Temperature/Humidity	<ul style="list-style-type: none"> <li>➤ -10 ~ +55°C; 5% ~ 90% RH Non coagulation</li> </ul>
● Storage Temperature/Humidity	<ul style="list-style-type: none"> <li>➤ -40 ~ +75°C; 5% ~ 95% RH Non coagulation</li> </ul>
● Product size/Packing size (L*W*H)	<ul style="list-style-type: none"> <li>➤ 440mm*290mm*45mm</li> <li>➤ 515mm*375mm*95mm</li> </ul>
● N.W/G.W (kg)	<ul style="list-style-type: none"> <li>➤ 3.2kg/3.9kg</li> </ul>

● <b>Installation</b>	➤ Rack-mount(optional machine hanger spare parts)
● <b>Lightning protection level</b>	➤ 3KV 8/20us; ➤ IP30
● <b>Certificate</b>	➤ CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS;
● <b>Warranty</b>	➤ Whole device for 1 year (full wirespeed)