P/N: ITT-VT1423



Description:

The ITT-VT1423 Telephone Is Very Popular For Tunnels, Mining, Marine, Underground, Metro Stations, Railway Platform, Highway Side, Hotels, Parking Lots, Steel Plants, Chemical Plants, Power Plants And Related Heavy Duty Industrial Application, Etc.

Signal Voltage	PoE,12V DC 1A or 220VAC
Standby Work Current	> ≤0.2A
Frequency Response	> 250 ~ 3000 Hz
Ringer Volume	> ≤80dB(A)
Defend Grade	► IP65
Corrosion Grade	> WF1
Ambient Temperature	> -40 ~ +60°C
Atmospheric Pressure	> 80 ~ 110KPa
Relative Humidity	≥ ≤95%
Cable Gland	> 3-PG11
Installation	➤ Wall-mounted
Unit size	> 440*320*270 (mm)
	Net weight: 5 KG
	Gross weight: 6 KG

Features:

- Engineering plastics injection moulding shell, high mechanical strength and strong impact resistance.
- SIP/VoIP version.
- Support 2 lines SIP, SIP 2.0 (RFC3261).
- Audio Codes:G.711, G.722, G.729.
- IP Protocols:IPv4, TCP, UDP, TFTP, RTP, RTCP, DHCP, SIP.
- Echo cancellation code:G.167/G.168.
- Supports full duplex.
- WAN/LAN: support Bridge mode.
- Support DHCP get IP on WAN port.
- Support PPPoE for xDSL.
- Support DHCP get IP on WAN port.
- Heavy Duty handset with hearing Aid compatible receiver, Noise canceling microphone.
- Weather proof Protection class to IP65.
- Waterproof plastic Keypad.
- Wall mounted, Simple installation.
- Connection: RJ45 screw terminal pair cable.
- Sound level of ringing:over 80dB(A).
- The available colors as an option.
- Self-made telephone spare partavailable.
- CE, FCC, RoHS, ISO9001 compliant



