



Description:

The ITT-VT1421 Telephone Is Very Popular For Tunnels, Mining, Marine, Underground, Metro Stations, Railway Platform, Highway Side, Hotels, Parking Lots, Steel Plants, Chemical Plants, Power Plants And Related Heavy Duty Industrial Application, Etc.

• Signal Voltage	➤ PoE, 12V DC or 220VAC
• Standby Work Current	➤ ≤0.2A
• Frequency Response	➤ 250 ~ 3000 Hz
• Ringer Volume	➤ ≤80dB(A)
• Corrosion Grade	➤ WF1
• Ambient Temperature	➤ -40 ~ +70°C
• Atmospheric Pressure	➤ 80 ~ 110KPa
• Relative Humidity	➤ ≤95%
• Cable Gland	➤ 1-PG11
• Installation	➤ Wall-mounted
• Unit size	➤ 339*246*126 (mm) ➤ Net weight: 6 KG ➤ Gross weight: 7 KG

Features:

- Aluminum alloy die-casting shell, high mechanical strength and strong impact resistance.
- Heavy Duty handset with hearing Aid compatible receiver, Noise canceling microphone.
- Stainless Steel Illuminated Keypad, buttons can be programmed as speed dial button.
- Support 2 lines SIP, SIP 2.0 (RFC3261).
- Audio Codes: G.711, G.722, G.729.
- IP Protocols: IPv4, TCP, UDP, TFTP, RTP, RTCP, DHCP, SIP.
- Echo cancellation code: G.167/G.168.
- Supports full duplex.
- WAN/LAN: support Bridge mode.
- Support DHCP get IP on WAN port.
- Support PPPoE for xDSL.
- Support DHCP get IP on WAN port.
- Temperature: Operating: -30°C to +65°C Storing: -40°C to +75°C.
- Weather proof Protection class to IP67.
- Wall mounted, Simple installation.
- The available colors as an option.
- Self-made telephone spare part available.
- CE, FCC, RoHS, ISO9001 compliant

