
SWE 530: Software Design Process

Some Design Representations

Dr. H. Birkan YILMAZ

Department of Computer Engineering
Boğaziçi University

(birkan.yilmaz@bogazici.edu.tr)

Recap

- We examined some of the principal ways in which software design knowledge and expertise can be codified and transferred:
 - the reasons for transferring design knowledge,
 - the role of the concept of architectural style in providing a framework and a vocabulary for top-level design ideas,
 - the use of design methods to codify design practices and strategies;
 - the rationale for using design patterns and their ability to describe the core features of reusable design solutions.
-

Summary

- The problem of selecting forms
 - Black box notations
 - White box notations
 - Developing a diagram
-

Range of forms

- The roles and forms of representation range across:
 - form: including textual and diagrammatical forms of notation
 - viewpoint: constructional, behavioural, functional and data-modelling viewpoints
 - use: in terms of the form's role during the phases of design, the type of problem domain in which it might be appropriate, and the extent to which it is used

Selection of black box forms

Representation form	Viewpoints	Design characteristics
Data-Flow Diagram	Functional	Information flow, dependency of operations on other operations, relation with data stores
Entity–Relationship Diagram	Data modelling	Static relationships between design entities
State Transition Diagram	Behavioural	State-machine model of an entity
Statechart	Behavioural	System-wide state model, including parallelism (orthogonality), hierarchy and abstraction
Structure Diagram (Jackson)	Functional, data modelling, behavioural	Form of sequencing adopted (operations, data, actions)
UML: Class Diagram	Constructional	Interactions between classes and objects
UML: Use Case Diagram	Behavioural and functional	Interactions between a system and other ‘actors’
UML: Activity Diagram	Behavioural and functional	Synchronization and coordination of system activities

Selection of white box forms

Representation form	Viewpoints	Design characteristics
Structure Chart	Functional and constructional	Invocation hierarchy between subprograms, decomposition into subprogram units
Class and Object Diagrams	Constructional	<i>Uses</i> relationships between elements, interfaces and dependencies
Sequence Diagrams	Behavioural	Message-passing sequences, interaction protocols
Pseudocode	Functional	Algorithm form

Black box forms

- A black box notation is one that is concerned with the **external properties** of the elements of a design model. That is, it is used to describe **what** an element will do, rather than how to do it.
 - Data-Flow Diagram (DFD), Entity-Relationship Diagram (ERD), State Transition Diagram (STD), Statechart, Jackson Structure Diagram, UML forms.
-




Data-Flow Diagram

- Problem oriented view of the system
 - Each element modifies the information flowing into the element
 - Pre-dates the computer era!
 - Very effective to describe a **process**, stresses dependencies and prerequisites
-

Data-Flow Diagram COMPONENTS

- It has four elements:
 - the **circle** (or, as it is popularly termed, the bubble), which is used to denote an operation, and is labelled with a brief description of the operation;
 - the **box**, used to denote an external source or sink of information;
 - the **parallel bars**, to denote a data store or file;
 - the **arc**, used to denote the flow of information between the other three components.
-



Data-Flow Diagram



Activity

- Design a top-level DFD for an ATM machine
- Use a single “transaction” as an abstract operation
- What are the:
 - Operations (bubbles)
 - Sources and sinks of information (boxes)
 - Data stores (parallel bars)
 - Flow of information (arcs)?

DFD examples: ATM



Data-Flow Diagram

- Can be expanded in a hierarchical fashion
 - Is not concerned with the control logic
 - Changes at one level can cause inconsistencies with other levels...
 - Special drawing tools enable automatic consistency checking.
-


The DFD viewpoint

- Describes the architecture in terms of functions
 - Does not specify whether the operations are serially performed, or in parallel.
 - Some design methods use DFD to describe parallel operations, but the convention is to assume sequential order.
-


Using the DFD

- Widely used for initial modeling (analysis)
 - It models the problem, and the user can easily understand its logic
 - De Marco's distinction:
 1. logical DFD: what is being done to data
 2. physical DFD: who is doing it (physical entities)
-

Logical vs. Physical DFD




physical DFD



logical DFD



Entity-Relationship Diagram




Entity-Relationship Diagram

- Entities may be connected via multiple relationships
- Attributes may be composite
- Relationships may be one to one (1 to 1), one to many (1 to n), or many to many (m to n)
 - Books held in a library?
 - Authors having written books?

Activity

- Design the ERD of an air traffic control system.
 - The entities are: airport, runway, aircraft, landing stack
 - Relations are: “belongs to”, “lands on”, “takes off from”, “held in”, and “holds queue for”
 - Each entity has 1 or 2 attributes.
-

Entity-Relationship Diagram




ERD Viewpoint and Use

- ERD Viewpoint:
 - Provides a data-modelling viewpoint of a system
 - Use of the ERD:
 - Developing relational **database** modelling schemas
 - Plays a role in SSA/SD (Structured Systems Analysis and Structured Design)
-

Different ERD Forms


Crow's Foot ERD




Relationships (Cardinality and Modality)




Many - to - One




Many-to-Many



Many-to-Many



Crow's Foot Notation (more useful)







State Transition Diagram (STD)

- The form of STD used in SSA/SD has:
 - The **state** represents an externally observable mode of behaviour, and is represented by a **box**, with a text label
 - The **transition** is described by an **arrow**, and identifies a 'legal' change of state
 - The transition **condition**
 - The transition **action** describes the actions that arise as a result of the transition

State Transition Diagram



State Transition Diagram




Viewpoint and Use of STD

- Captures the **behaviour** of the system
- The transitions are not sequenced; they exist as conditionals
- Major role of STD is in modelling problem entities, and in real-time needs of the system
- There can be many states and many transitions
- Not easy to implement a hierarchy

Activity


- Design the STD for describing the behaviour of an **aircraft** in an air traffic control zone
 - Define
 - States
 - Events
 - Actions
-

State Transition Diagram







The Statechart



The Statechart




The Statechart




The viewpoint and use of Statechart

- Provides a behavioural description.
 - STD has more detailed descriptions, Statechart deals better with abstractions, defaults, history and scale.
 - Used in modelling reactive systems
 - Both STD and Statechart support data flow viewpoints.
-

Orthogonality




Orthogonality






Jackson Structure Diagram





Jackson Structure Diagram

- Describes sequential structure with 3 forms:
 - sequence
 - selection
 - iteration
- It can be used to describe:
 - the form of a data structure (data modelling v.p.)
 - sequencing of program actions (functional v.p.)
 - sequencing of states (behavioral v.p.)

Jackson Structure Diagram



Jackson Structure Diagram




You should **NOT** mix forms within a sequence!

Activity


- Describe the structure of a scientific textbook with Jackson Structure Diagram.
 - The book contains a preface, contents, chapters, references and an index.
 - Chapters may have exercises at the end
 - Chapters can start with an abstract or a quotation, and can contain multiple types of content
-

Jackson Structure Diagram




Jackson Structure Diagram

a simple text file



Jackson Structure Diagram

printing a bank statement



Selection of black box forms

Representation form	Viewpoints	Design characteristics
Data-Flow Diagram	Functional	Information flow, dependency of operations on other operations, relation with data stores
Entity–Relationship Diagram	Data modelling	Static relationships between design entities
State Transition Diagram	Behavioural	State-machine model of an entity
Statechart	Behavioural	System-wide state model, including parallelism (orthogonality), hierarchy and abstraction
Structure Diagram (Jackson)	Functional, data modelling, behavioural	Form of sequencing adopted (operations, data, actions)
UML: Class Diagram	Constructional	Interactions between classes and objects
UML: Use Case Diagram	Behavioural and functional	Interactions between a system and other ‘actors’
UML: Activity Diagram	Behavioural and functional	Synchronization and coordination of system activities

Summary

- A wide range of notations can be used to support and document the development of a design model
 - Examples illustrate the forms used for both white box and black box modelling across the set of viewpoints (functional, behavioural, data modelling and constructional)
 - The choice of any particular notation depends upon many factors, including the problem domain, architectural form of the eventual system, and design practices being used.
-

Questions?
