

## Autonomous Steering Agents

Generated by Doxygen 1.8.17



<b>1 Intent</b>	<b>1</b>
1.1 Dependencies	1
1.2 Resources	1
<b>2 Hierarchical Index</b>	<b>3</b>
2.1 Class Hierarchy	3
<b>3 Class Index</b>	<b>5</b>
3.1 Class List	5
<b>4 File Index</b>	<b>7</b>
4.1 File List	7
<b>5 Class Documentation</b>	<b>9</b>
5.1 agent Class Reference	9
5.1.1 Detailed Description	10
5.1.2 Constructor & Destructor Documentation	10
5.1.2.1 agent() [1/2]	10
5.1.2.2 agent() [2/2]	10
5.1.2.3 ~agent()	11
5.1.3 Member Function Documentation	11
5.1.3.1 setFeatures()	11
5.1.3.2 updatePosition()	12
5.1.4 Member Data Documentation	12
5.1.4.1 acceleration	13
5.1.4.2 arrive	13
5.1.4.3 desiredVelocity	13
5.1.4.4 fillColor	13
5.1.4.5 force	14
5.1.4.6 id	14
5.1.4.7 mass	14
5.1.4.8 maxForce	14
5.1.4.9 maxSpeed	15
5.1.4.10 name	15
5.1.4.11 position	15
5.1.4.12 r	15
5.1.4.13 steering	16
5.1.4.14 targetPoint	16
5.1.4.15 velocity	16
5.2 color Class Reference	16
5.2.1 Detailed Description	17
5.2.2 Constructor & Destructor Documentation	17
5.2.2.1 color() [1/2]	17
5.2.2.2 color() [2/2]	17

5.2.3 Member Function Documentation	18
5.2.3.1 createColors()	18
5.2.3.2 getColor()	18
5.2.4 Member Data Documentation	19
5.2.4.1 B	19
5.2.4.2 colors	19
5.2.4.3 G	19
5.2.4.4 R	20
5.3 evade Class Reference	20
5.3.1 Detailed Description	20
5.3.2 Constructor & Destructor Documentation	20
5.3.2.1 evade()	21
5.3.3 Member Function Documentation	21
5.3.3.1 loop()	21
5.4 flee Class Reference	21
5.4.1 Detailed Description	22
5.4.2 Constructor & Destructor Documentation	22
5.4.2.1 flee()	22
5.4.3 Member Function Documentation	22
5.4.3.1 loop()	23
5.5 flock Class Reference	23
5.5.1 Detailed Description	23
5.5.2 Constructor & Destructor Documentation	24
5.5.2.1 flock()	24
5.5.3 Member Function Documentation	24
5.5.3.1 loop()	24
5.6 flowField Class Reference	25
5.6.1 Detailed Description	25
5.6.2 Constructor & Destructor Documentation	25
5.6.2.1 flowField() [1/2]	25
5.6.2.2 flowField() [2/2]	25
5.6.3 Member Function Documentation	26
5.6.3.1 getField()	26
5.7 graphics Class Reference	26
5.7.1 Detailed Description	27
5.7.2 Member Function Documentation	28
5.7.2.1 drawAgent()	28
5.7.2.2 drawCircle()	28
5.7.2.3 drawLine()	29
5.7.2.4 drawPath()	29
5.7.2.5 drawPoint()	30
5.7.2.6 drawText()	30

5.7.2.7 drawWall()	31
5.7.2.8 forceInScreen()	31
5.7.2.9 getMousePosition()	32
5.7.2.10 handleKeypress()	32
5.7.2.11 handleResize()	32
5.7.2.12 initGraphics()	33
5.7.2.13 mouseButton()	33
5.7.2.14 mouseMove()	34
5.7.2.15 refreshScene()	34
5.7.2.16 timerEvent()	35
5.7.3 Member Data Documentation	35
5.7.3.1 target_x	35
5.7.3.2 target_y	35
5.8 mouseFollower Class Reference	36
5.8.1 Detailed Description	36
5.8.2 Constructor & Destructor Documentation	36
5.8.2.1 mouseFollower()	36
5.8.3 Member Function Documentation	36
5.8.3.1 loop()	37
5.9 obstacle Class Reference	37
5.9.1 Detailed Description	37
5.9.2 Constructor & Destructor Documentation	38
5.9.2.1 obstacle() [1/2]	38
5.9.2.2 obstacle() [2/2]	38
5.9.3 Member Data Documentation	38
5.9.3.1 p	39
5.9.3.2 r	39
5.10 obstacleAvoidance Class Reference	39
5.10.1 Detailed Description	40
5.10.2 Constructor & Destructor Documentation	40
5.10.2.1 obstacleAvoidance()	40
5.10.3 Member Function Documentation	40
5.10.3.1 createObstacle()	40
5.10.3.2 loop()	41
5.10.4 Member Data Documentation	41
5.10.4.1 obstacles	41
5.11 path Class Reference	42
5.11.1 Detailed Description	42
5.11.2 Constructor & Destructor Documentation	42
5.11.2.1 path() [1/2]	42
5.11.2.2 path() [2/2]	42
5.11.3 Member Function Documentation	43

5.11.3.1 addPoint()	43
5.11.4 Member Data Documentation	43
5.11.4.1 points	43
5.11.4.2 width	44
5.12 pathFollower Class Reference	44
5.12.1 Detailed Description	44
5.12.2 Constructor & Destructor Documentation	45
5.12.2.1 pathFollower()	45
5.12.3 Member Function Documentation	45
5.12.3.1 createPath()	45
5.12.3.2 loop()	46
5.12.4 Member Data Documentation	46
5.12.4.1 myPath	46
5.13 point Class Reference	46
5.13.1 Detailed Description	47
5.13.2 Constructor & Destructor Documentation	47
5.13.2.1 point() [1/2]	47
5.13.2.2 point() [2/2]	48
5.13.3 Member Function Documentation	48
5.13.3.1 div()	48
5.13.3.2 getNormalPoint()	49
5.13.3.3 mul()	49
5.13.3.4 operator+() [1/2]	49
5.13.3.5 operator+() [2/2]	50
5.13.3.6 operator-()	50
5.13.3.7 operator==()	51
5.13.3.8 print()	51
5.13.4 Member Data Documentation	52
5.13.4.1 x	52
5.13.4.2 y	52
5.14 prison Class Reference	52
5.14.1 Detailed Description	53
5.14.2 Constructor & Destructor Documentation	53
5.14.2.1 prison()	53
5.14.3 Member Function Documentation	53
5.14.3.1 loop()	54
5.15 pursuit Class Reference	54
5.15.1 Detailed Description	54
5.15.2 Constructor & Destructor Documentation	55
5.15.2.1 pursuit()	55
5.15.3 Member Function Documentation	55
5.15.3.1 loop()	55

5.16 pvector Class Reference	56
5.16.1 Detailed Description	57
5.16.2 Constructor & Destructor Documentation	57
5.16.2.1 pvector() [1/2]	57
5.16.2.2 pvector() [2/2]	57
5.16.3 Member Function Documentation	58
5.16.3.1 add()	58
5.16.3.2 angleBetween()	58
5.16.3.3 div()	59
5.16.3.4 dotProduct()	59
5.16.3.5 getAngle()	59
5.16.3.6 limit()	60
5.16.3.7 magnitude()	60
5.16.3.8 mul()	60
5.16.3.9 normalize()	61
5.16.3.10 operator+() [1/2]	61
5.16.3.11 operator+() [2/2]	62
5.16.3.12 operator+=()	62
5.16.3.13 operator-() [1/2]	63
5.16.3.14 operator-() [2/2]	63
5.16.3.15 operator==()	64
5.16.3.16 print()	64
5.16.4 Member Data Documentation	65
5.16.4.1 x	65
5.16.4.2 y	65
5.17 random Class Reference	65
5.17.1 Detailed Description	65
5.17.2 Member Function Documentation	65
5.17.2.1 createRandomArray()	65
5.18 scenario Class Reference	66
5.18.1 Detailed Description	67
5.18.2 Constructor & Destructor Documentation	67
5.18.2.1 scenario()	67
5.18.3 Member Function Documentation	67
5.18.3.1 createAgent()	67
5.18.3.2 initGL()	68
5.18.3.3 refresh()	68
5.18.4 Member Data Documentation	69
5.18.4.1 agents	69
5.18.4.2 behavior	69
5.18.4.3 callback	70
5.18.4.4 myColor	70

5.18.4.5 name . . . . .	70
5.18.4.6 view . . . . .	71
5.19 steeringBehavior Class Reference . . . . .	71
5.19.1 Detailed Description . . . . .	72
5.19.2 Member Function Documentation . . . . .	72
5.19.2.1 align() . . . . .	72
5.19.2.2 avoid() . . . . .	72
5.19.2.3 cohesion() . . . . .	73
5.19.2.4 evade() . . . . .	74
5.19.2.5 flee() . . . . .	75
5.19.2.6 inFlowField() . . . . .	75
5.19.2.7 pursuit() . . . . .	76
5.19.2.8 seek() . . . . .	77
5.19.2.9 separation() . . . . .	77
5.19.2.10 setAngle() . . . . .	78
5.19.2.11 stayInArea() . . . . .	78
5.19.2.12 stayInPath() . . . . .	79
5.19.2.13 wander() . . . . .	80
5.20 wander Class Reference . . . . .	80
5.20.1 Detailed Description . . . . .	81
5.20.2 Constructor & Destructor Documentation . . . . .	81
5.20.2.1 wander() . . . . .	81
5.20.3 Member Function Documentation . . . . .	81
5.20.3.1 loop() . . . . .	82
5.21 windy Class Reference . . . . .	82
5.21.1 Detailed Description . . . . .	83
5.21.2 Constructor & Destructor Documentation . . . . .	83
5.21.2.1 windy() . . . . .	83
5.21.3 Member Function Documentation . . . . .	83
5.21.3.1 loop() . . . . .	83
5.21.4 Member Data Documentation . . . . .	84
5.21.4.1 flow . . . . .	84
<b>6 File Documentation . . . . .</b>	<b>85</b>
6.1 include/agent.h File Reference . . . . .	85
6.2 include/color.h File Reference . . . . .	85
6.2.1 Detailed Description . . . . .	86
6.2.2 Enumeration Type Documentation . . . . .	86
6.2.2.1 num . . . . .	86
6.3 include/evade.h File Reference . . . . .	86
6.3.1 Detailed Description . . . . .	87
6.4 include/flee.h File Reference . . . . .	87



6.4.1 Detailed Description . . . . .	87
6.5 include/flock.h File Reference . . . . .	87
6.5.1 Detailed Description . . . . .	88
6.6 include/flowField.h File Reference . . . . .	88
6.6.1 Detailed Description . . . . .	88
6.6.2 Macro Definition Documentation . . . . .	88
6.6.2.1 FIELD_HEIGHT . . . . .	89
6.6.2.2 FIELD_WIDTH . . . . .	89
6.6.2.3 GRAVITY . . . . .	89
6.6.2.4 WIND_WEST . . . . .	89
6.7 include/graphics.h File Reference . . . . .	89
6.7.1 Detailed Description . . . . .	90
6.7.2 Macro Definition Documentation . . . . .	90
6.7.2.1 ESC . . . . .	90
6.7.2.2 HEIGHT . . . . .	90
6.7.2.3 PI . . . . .	90
6.7.2.4 WIDTH . . . . .	90
6.8 include/mouseFollower.h File Reference . . . . .	91
6.8.1 Detailed Description . . . . .	91
6.9 include/obstacle.h File Reference . . . . .	91
6.9.1 Detailed Description . . . . .	91
6.10 include/obstacleAvoidance.h File Reference . . . . .	92
6.10.1 Detailed Description . . . . .	92
6.11 include/path.h File Reference . . . . .	92
6.11.1 Detailed Description . . . . .	92
6.12 include/pathFollower.h File Reference . . . . .	93
6.12.1 Detailed Description . . . . .	93
6.13 include/point.h File Reference . . . . .	93
6.13.1 Detailed Description . . . . .	93
6.14 include/prison.h File Reference . . . . .	94
6.14.1 Detailed Description . . . . .	94
6.15 include/pursuit.h File Reference . . . . .	94
6.15.1 Detailed Description . . . . .	94
6.16 include/pvector.h File Reference . . . . .	95
6.16.1 Detailed Description . . . . .	95
6.16.2 Macro Definition Documentation . . . . .	95
6.16.2.1 PI . . . . .	95
6.17 include/random.h File Reference . . . . .	95
6.17.1 Detailed Description . . . . .	96
6.18 include/scenario.h File Reference . . . . .	96
6.18.1 Detailed Description . . . . .	96
6.18.2 Enumeration Type Documentation . . . . .	96

6.18.2.1 types . . . . .	96
6.19 include/steeringBehavior.h File Reference . . . . .	97
6.19.1 Detailed Description . . . . .	97
6.19.2 Macro Definition Documentation . . . . .	98
6.19.2.1 AVOID_OBSTACLE . . . . .	98
6.19.2.2 CIRCLE_DISTANCE . . . . .	98
6.19.2.3 CIRCLE_RADIUS . . . . .	98
6.19.2.4 EVADE . . . . .	98
6.19.2.5 FLEE . . . . .	98
6.19.2.6 FLOCK . . . . .	99
6.19.2.7 FOLLOW_MOUSE . . . . .	99
6.19.2.8 IN_FLOW_FIELD . . . . .	99
6.19.2.9 PURSUIT . . . . .	99
6.19.2.10 STAY_IN_FIELD . . . . .	99
6.19.2.11 STAY_IN_PATH . . . . .	99
6.19.2.12 WANDER . . . . .	100
6.20 include/wander.h File Reference . . . . .	100
6.20.1 Detailed Description . . . . .	100
6.21 include/windy.h File Reference . . . . .	100
6.21.1 Detailed Description . . . . .	101
6.22 main.cpp File Reference . . . . .	101
6.22.1 Detailed Description . . . . .	101
6.22.2 Function Documentation . . . . .	102
6.22.2.1 main() . . . . .	102
6.22.2.2 menu() . . . . .	102
6.22.3 Variable Documentation . . . . .	103
6.22.3.1 mode . . . . .	103
6.23 README.md File Reference . . . . .	103
6.24 src/agent.cpp File Reference . . . . .	103
6.24.1 Detailed Description . . . . .	103
6.25 src/color.cpp File Reference . . . . .	103
6.25.1 Detailed Description . . . . .	104
6.26 src/evade.cpp File Reference . . . . .	104
6.26.1 Detailed Description . . . . .	104
6.27 src/flee.cpp File Reference . . . . .	104
6.27.1 Detailed Description . . . . .	105
6.28 src/flock.cpp File Reference . . . . .	105
6.28.1 Detailed Description . . . . .	105
6.29 src/flowField.cpp File Reference . . . . .	105
6.29.1 Detailed Description . . . . .	105
6.30 src/graphics.cpp File Reference . . . . .	106
6.30.1 Detailed Description . . . . .	106

6.31 src/mouseFollower.cpp File Reference . . . . .	106
6.31.1 Detailed Description . . . . .	106
6.32 src/obstacle.cpp File Reference . . . . .	107
6.32.1 Detailed Description . . . . .	107
6.33 src/obstacleAvoidance.cpp File Reference . . . . .	107
6.33.1 Detailed Description . . . . .	107
6.34 src/path.cpp File Reference . . . . .	108
6.34.1 Detailed Description . . . . .	108
6.35 src/pathFollower.cpp File Reference . . . . .	108
6.35.1 Detailed Description . . . . .	108
6.36 src/point.cpp File Reference . . . . .	108
6.36.1 Detailed Description . . . . .	109
6.37 src/prison.cpp File Reference . . . . .	109
6.37.1 Detailed Description . . . . .	109
6.37.2 Macro Definition Documentation . . . . .	109
6.37.2.1 DISTANCE . . . . .	109
6.37.2.2 WALL . . . . .	110
6.38 src/pursuit.cpp File Reference . . . . .	110
6.38.1 Detailed Description . . . . .	110
6.39 src/pvector.cpp File Reference . . . . .	110
6.39.1 Detailed Description . . . . .	110
6.40 src/random.cpp File Reference . . . . .	111
6.40.1 Detailed Description . . . . .	111
6.41 src/scenario.cpp File Reference . . . . .	111
6.41.1 Detailed Description . . . . .	111
6.41.2 Macro Definition Documentation . . . . .	112
6.41.2.1 MAX_NUMBER_OF_AGENTS . . . . .	112
6.42 src/steeringBehavior.cpp File Reference . . . . .	112
6.42.1 Detailed Description . . . . .	112
6.43 src/wander.cpp File Reference . . . . .	112
6.43.1 Detailed Description . . . . .	113
6.44 src/windy.cpp File Reference . . . . .	113
6.44.1 Detailed Description . . . . .	113
6.45 test/test_suites.cpp File Reference . . . . .	113
6.45.1 Macro Definition Documentation . . . . .	114
6.45.1.1 BOOST_TEST_MODULE . . . . .	114
6.45.2 Function Documentation . . . . .	114
6.45.2.1 BOOST_AUTO_TEST_CASE() [1/12] . . . . .	114
6.45.2.2 BOOST_AUTO_TEST_CASE() [2/12] . . . . .	114
6.45.2.3 BOOST_AUTO_TEST_CASE() [3/12] . . . . .	115
6.45.2.4 BOOST_AUTO_TEST_CASE() [4/12] . . . . .	115
6.45.2.5 BOOST_AUTO_TEST_CASE() [5/12] . . . . .	115

6.45.2.6 BOOST_AUTO_TEST_CASE() [6/12] . . . . .	115
6.45.2.7 BOOST_AUTO_TEST_CASE() [7/12] . . . . .	116
6.45.2.8 BOOST_AUTO_TEST_CASE() [8/12] . . . . .	116
6.45.2.9 BOOST_AUTO_TEST_CASE() [9/12] . . . . .	116
6.45.2.10 BOOST_AUTO_TEST_CASE() [10/12] . . . . .	116
6.45.2.11 BOOST_AUTO_TEST_CASE() [11/12] . . . . .	117
6.45.2.12 BOOST_AUTO_TEST_CASE() [12/12] . . . . .	117

<b>Index</b>	<b>119</b>
--------------	------------

# Chapter 1

## Intent

- 1- implementing Craig Reynolds autonomous steering agents
- 2- implementing genetics algorithms
- 3- implementing neural network

### 1.1 Dependencies

```
$sudo apt-get install libglu1-mesa-dev freeglut3-dev mesa-common-dev
```

```
$sudo apt-get install libboost-all-dev
```

### 1.2 Resources

<https://natureofcode.com/book/chapter-6-autonomous-agents>

<https://gamedevelopment.tutsplus.com/series/understanding-steering-behaviors-gamedev-12>

<https://videotutorialsrock.com/index.php>

<https://www.opengl.org/resources/libraries/glut/spec3/node1.html>

<https://learnopengl.com/Getting-started/Coordinate-Systems>



## Chapter 2

# Hierarchical Index

### 2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

agent . . . . .	9
color . . . . .	16
flowField . . . . .	25
graphics . . . . .	26
obstacle . . . . .	37
path . . . . .	42
point . . . . .	46
pvector . . . . .	56
random . . . . .	65
scenario . . . . .	66
evade . . . . .	20
flee . . . . .	21
flock . . . . .	23
mouseFollower . . . . .	36
obstacleAvoidance . . . . .	39
pathFollower . . . . .	44
prison . . . . .	52
pursuit . . . . .	54
wander . . . . .	80
windy . . . . .	82
steeringBehavior . . . . .	71





## Chapter 3

# Class Index

### 3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

agent	9
color	16
evade	20
flee	21
flock	23
flowField	25
graphics	26
mouseFollower	36
obstacle	37
obstacleAvoidance	39
path	42
pathFollower	44
point	46
prison	52
pursuit	54
pvector	56
random	65
scenario	66
steeringBehavior	71
wander	80
windy	82



## Chapter 4

# File Index

### 4.1 File List

Here is a list of all files with brief descriptions:

<a href="#">main.cpp</a>	
Client code . . . . .	101
include/ <a href="#">agent.h</a>	
Agent class defines all agent specifications . . . . .	85
include/ <a href="#">color.h</a>	
Color class used for agent, path, wall etc. color . . . . .	85
include/ <a href="#">evade.h</a>	
Evade class inherited from scenario class . . . . .	86
include/ <a href="#">flee.h</a>	
Agents flee from mouse scenario . . . . .	87
include/ <a href="#">flock.h</a>	
Flocking agents scenario . . . . .	87
include/ <a href="#">flowField.h</a>	
FlowField class, screen can be filled with a force for each pixel . . . . .	88
include/ <a href="#">graphics.h</a>	
Graphics class, drives openGL . . . . .	89
include/ <a href="#">mouseFollower.h</a>	
Agents follow mouse scenario . . . . .	91
include/ <a href="#">obstacle.h</a>	
Circular obstacles for agent avoidance behaviors . . . . .	91
include/ <a href="#">obstacleAvoidance.h</a>	
Agents avoid from obstacles scenario . . . . .	92
include/ <a href="#">path.h</a>	
Path class used for path following steering behaviors . . . . .	92
include/ <a href="#">pathFollower.h</a>	
Path following scenario . . . . .	93
include/ <a href="#">point.h</a>	
Point class used for point operations . . . . .	93
include/ <a href="#">prison.h</a>	
Agents cant escape from field scenario . . . . .	94
include/ <a href="#">pursuit.h</a>	
One agent pursue other one scenario . . . . .	94
include/ <a href="#">pvector.h</a>	
Pvector class used for 2D vector operations . . . . .	95
include/ <a href="#">random.h</a>	
Utility class for random operations . . . . .	95

include/ <a href="#">scenario.h</a>	Base class for all scenarios . . . . .	96
include/ <a href="#">steeringBehavior.h</a>	Functions for autonomous steering behaviors . . . . .	97
include/ <a href="#">wander.h</a>	Random wandering agents scenario . . . . .	100
include/ <a href="#">windy.h</a>	Windy air scenario . . . . .	100
src/ <a href="#">agent.cpp</a>	Implementation of the agent class . . . . .	103
src/ <a href="#">color.cpp</a>	Color class implementation . . . . .	103
src/ <a href="#">evade.cpp</a>	Evade class implementation . . . . .	104
src/ <a href="#">flee.cpp</a>	Flee class implementation . . . . .	104
src/ <a href="#">flock.cpp</a>	Flock class implementation . . . . .	105
src/ <a href="#">flowField.cpp</a>	FlowField class implementation . . . . .	105
src/ <a href="#">graphics.cpp</a>	Graphics class implementation . . . . .	106
src/ <a href="#">mouseFollower.cpp</a>	MouseFollower class implementation . . . . .	106
src/ <a href="#">obstacle.cpp</a>	Obstacle class implementation . . . . .	107
src/ <a href="#">obstacleAvoidance.cpp</a>	ObstacleAvoidance class implementation . . . . .	107
src/ <a href="#">path.cpp</a>	Path class implementation . . . . .	108
src/ <a href="#">pathFollower.cpp</a>	PathFollower class implementation . . . . .	108
src/ <a href="#">point.cpp</a>	Point class implementation file . . . . .	108
src/ <a href="#">prison.cpp</a>	Prison class implementation . . . . .	109
src/ <a href="#">pursuit.cpp</a>	Prison class implementation . . . . .	110
src/ <a href="#">pvector.cpp</a>	Pvector class implementation . . . . .	110
src/ <a href="#">random.cpp</a>	Utility class for random operations . . . . .	111
src/ <a href="#">scenario.cpp</a>	Scenario base class implementation . . . . .	111
src/ <a href="#">steeringBehavior.cpp</a>	Implementation of autonomous steering behaviors . . . . .	112
src/ <a href="#">wander.cpp</a>	Wander class implementation . . . . .	112
src/ <a href="#">windy.cpp</a>	Windy class implementation . . . . .	113
test/ <a href="#">test_suites.cpp</a>	. . . . .	113

## Chapter 5

# Class Documentation

### 5.1 agent Class Reference

```
#include <agent.h>
```

Collaboration diagram for agent:

#### Public Member Functions

- `agent ()`  
*default constructor.*
- `agent (float x, float y)`  
*Constructor.*
- `~agent ()`  
*agent destructor*
- void `updatePosition` (bool `arrive`)  
*calculates next position in each update using force applied*
- void `setFeatures` (float `s`, float `f`, float `r`, float `m`)  
*used to initialize the agent*

#### Public Attributes

- string `name`  
*name of the agent*
- `color fillColor`  
*color of the agent*
- `point position`  
*x and y coordinates of the agent*
- `pvector velocity`  
*velocity of the agent*
- `point targetPoint`  
*target of the agent*
- float `maxSpeed`  
*maximum speed of the agent*

- float [maxForce](#)  
*maximum force of the agent*
- [pvector steering](#)  
*steering force to apply*
- [pvector force](#)  
*total force to apply*
- [pvector acceleration](#)  
*added to velocity in each update*
- [pvector desiredVelocity](#)  
*get using target point and used to get steering force*
- float [r](#)  
*agent slows down as target point gets smaller than radius*
- float [mass](#)  
*used to get acceleration from force*
- int [id](#)  
*used to distinguish specific agent*
- bool [arrive](#) = false  
*defines if agent will have arriving behavior*

### 5.1.1 Detailed Description

Definition at line 20 of file agent.h.

### 5.1.2 Constructor & Destructor Documentation

#### 5.1.2.1 [agent\(\)](#) [1/2]

```
agent::agent ( )
```

default constructor.

Creates new agent object.

See also

[agent\(float x, float y\)](#)

Definition at line 16 of file agent.cpp.

```
17 {
18
19 }
```

#### 5.1.2.2 [agent\(\)](#) [2/2]

```
agent::agent (
    float x,
    float y )
```

Constructor.

Creates new agent object.

## Parameters

x	position x of the agent
y	position y of the agent

## See also

[agent\(\)](#)

Definition at line 21 of file agent.cpp.

```

22 {
23     position      = point(x, y);
24     velocity      = pvector(0.6, 0.0);
25     acceleration  = pvector(0.0, 0.0);
26     steering      = pvector(0.0, 0.0);
27     desiredVelocity = pvector(0.0, 0.0);
28     force         = pvector(0.0, 0.0);
29     targetPoint   = point(0.0, 0.0);
30     fillColor     = color(1.0, 0.0, 0.0);
31 }

```

## 5.1.2.3 ~agent()

`agent::~agent ( )`

agent destructor

invokes when instance is killed

Definition at line 62 of file agent.cpp.

```

63 {
64
65 }

```

## 5.1.3 Member Function Documentation

## 5.1.3.1 setFeatures()

```

void agent::setFeatures (
    float s,
    float f,
    float r,
    float m )

```

used to initialize the agent

setting parameters

**Parameters**

<i>s</i>	maximum velocity
<i>f</i>	maximum force
<i>r</i>	radius for arriving behavior
<i>m</i>	mass

Definition at line 54 of file agent.cpp.

```

55 {
56     this->maxSpeed = s;
57     this->maxForce = f;
58     this->r = r;
59     this->mass = m;
60 }
```

**5.1.3.2 updatePosition()**

```

void agent::updatePosition (
    bool arrive )
```

calculates next position in each update using force applied

position update is invoked in periodically in a loop

**Parameters**

<i>arrive</i>	agent has arriving behavior or not
---------------	------------------------------------

**See also**

[agent\(\)](#)

Definition at line 33 of file agent.cpp.

```

34 {
35     force.limit(maxForce);
36     acceleration = force;
37     velocity += acceleration;
38
39     //arriving behavior implementation
40     if(arrive == true){
41         pvector diff = targetPoint - position;
42         if(diff.magnitude() > r)
43             velocity.limit(maxSpeed);
44         else
45             velocity.limit(maxSpeed * diff.magnitude() / r);
46     }
47     else
48         velocity.limit(maxSpeed);
49
50     position = position + velocity;
51     force = pvector(0,0);
52 }
```

Here is the call graph for this function:

**5.1.4 Member Data Documentation**



#### 5.1.4.1 acceleration

```
pvector agent::acceleration
```

added to velocity in each update

acceleration to apply

Definition at line 120 of file agent.h.

#### 5.1.4.2 arrive

```
bool agent::arrive = false
```

defines if agent will have arriving behavior

arriving behavior

Definition at line 150 of file agent.h.

#### 5.1.4.3 desiredVelocity

```
pvector agent::desiredVelocity
```

get using target point and used to get steering force

desired velocity to reach the target point

Definition at line 126 of file agent.h.

#### 5.1.4.4 fillColor

```
color agent::fillColor
```

color of the agent

color information passed to graphics

Definition at line 72 of file agent.h.

#### 5.1.4.5 force

`pvector agent::force`

total force to apply

force to apply to agent instance

Definition at line 114 of file agent.h.

#### 5.1.4.6 id

`int agent::id`

used to distinguish specific agent

identification number of the agent

Definition at line 144 of file agent.h.

#### 5.1.4.7 mass

`float agent::mass`

used to get acceleration from force

mass of the agent

Definition at line 138 of file agent.h.

#### 5.1.4.8 maxForce

`float agent::maxForce`

maximum force of the agent

if force of the agent is more than this value, limit function restricts force

Definition at line 102 of file agent.h.

#### 5.1.4.9 maxSpeed

```
float agent::maxSpeed
```

maximum speed of the agent

if velocity of the agent is more than this value, limit function restricts velocity

Definition at line 96 of file agent.h.

#### 5.1.4.10 name

```
string agent::name
```

name of the agent

used to distinguish specific agent

Definition at line 66 of file agent.h.

#### 5.1.4.11 position

```
point agent::position
```

x and y coordinates of the agent

position information

Definition at line 78 of file agent.h.

#### 5.1.4.12 r

```
float agent::r
```

agent slows down as target point gets smaller than radius

radius for arrivin behavior

Definition at line 132 of file agent.h.

#### 5.1.4.13 steering

`pvector` `agent::steering`

steering force to apply

steering force to change direction

Definition at line 108 of file agent.h.

#### 5.1.4.14 targetPoint

`point` `agent::targetPoint`

target of the agent

calculated target point of the agent

Definition at line 90 of file agent.h.

#### 5.1.4.15 velocity

`pvector` `agent::velocity`

velocity of the agent

velocity vector

Definition at line 84 of file agent.h.

The documentation for this class was generated from the following files:

- `include/agent.h`
- `src/agent.cpp`

## 5.2 color Class Reference

```
#include <color.h>
```

Collaboration diagram for color:

## Public Member Functions

- [color](#) ()  
*default constructor.*
- [color](#) (float r, float g, float b)  
*Constructor.*
- void [createColors](#) ()  
*fills colors vector with 8 main colors in color bar*
- [color](#) [getColor](#) (int i)  
*Constructor.*

## Public Attributes

- float [R](#)  
*red condiment*
- float [G](#)  
*green condiment*
- float [B](#)  
*blue condiment*
- vector< [color](#) > [colors](#)  
*stores main colors*

### 5.2.1 Detailed Description

Definition at line 20 of file color.h.

### 5.2.2 Constructor & Destructor Documentation

#### 5.2.2.1 [color\(\)](#) [1/2]

```
color::color ( )
```

default constructor.

Create a new color object.

See also

[color\(float r, float g, float b\)](#)

Definition at line 25 of file color.cpp.

```
26 {  
27  
28 }
```

#### 5.2.2.2 [color\(\)](#) [2/2]

```
color::color (  
    float r,  
    float g,  
    float b )
```

Constructor.

Create a new color object.

**Parameters**

<i>r</i>	red (0-255)
<i>g</i>	green (0-255)
<i>b</i>	blue (0-255)

**See also**

[path\(\)](#)

Definition at line 13 of file color.cpp.

```

14 {
15     R = r;
16     G = g;
17     B = b;
18 }
```

## 5.2.3 Member Function Documentation

### 5.2.3.1 createColors()

```
void color::createColors ( )
```

fills colors vector with 8 main colors in color bar

creates main colors for future use

Definition at line 30 of file color.cpp.

```

31 {
32     colors.push_back(color(0.0, 0.0, 0.0));
33     colors.push_back(color(0.0, 0.0, 1.0));
34     colors.push_back(color(0.0, 1.0, 0.0));
35     colors.push_back(color(0.0, 1.0, 1.0));
36     colors.push_back(color(1.0, 0.0, 0.0));
37     colors.push_back(color(1.0, 0.0, 1.0));
38     colors.push_back(color(1.0, 1.0, 0.0));
39     colors.push_back(color(1.0, 1.0, 1.0));
40 }
```

### 5.2.3.2 getColor()

```
color color::getColor (
    int i )
```

Constructor.

returns specified color from colors vector

**Parameters**

<i>i</i>	gets specified color
----------	----------------------

### Returns

requested pre-created color instance

Definition at line 20 of file color.cpp.

```
21 {  
22     return colors.at(i);  
23 }
```

Here is the caller graph for this function:

## 5.2.4 Member Data Documentation

### 5.2.4.1 B

```
float color::B
```

blue condiment

blue color ratio

Definition at line 69 of file color.h.

### 5.2.4.2 colors

```
vector<color> color::colors
```

stores main colors

vector of fundamental colors

Definition at line 75 of file color.h.

### 5.2.4.3 G

```
float color::G
```

green condiment

green color ratio

Definition at line 63 of file color.h.

#### 5.2.4.4 R

```
float color::R
```

red condiment

red color ratio

Definition at line 57 of file color.h.

The documentation for this class was generated from the following files:

- [include/color.h](#)
- [src/color.cpp](#)

## 5.3 evade Class Reference

```
#include <evade.h>
```

Inheritance diagram for evade:

Collaboration diagram for evade:

### Public Member Functions

- [evade](#) ()  
*default constructor.*

### Static Public Member Functions

- static void [loop](#) ()  
*loop function for evading scenario*

### Additional Inherited Members

#### 5.3.1 Detailed Description

Definition at line 15 of file evade.h.

#### 5.3.2 Constructor & Destructor Documentation



### 5.3.2.1 evade()

`evade::evade ( )`

default constructor.

Creates scenario

Definition at line 31 of file `evade.cpp`.

```
32 {
33     name = "evading";
34     createAgent(STATIC, nullptr, nullptr, nullptr);
35     callback = reinterpret_cast<void(*)()> ( (void *)(&loop) );
36 }
```

## 5.3.3 Member Function Documentation

### 5.3.3.1 loop()

`void evade::loop ( ) [static]`

loop function for evading scenario

evading loop function

#### Note

opengl callback forces that function to be static

Definition at line 15 of file `evade.cpp`.

```
16 {
17     for(auto it = agents.begin(); it < agents.end(); it++){
18         if((*it).name == "lion"){
19             (*it).targetPoint = view.getMousePosition();
20             (*it).force = behavior.seek(*it);
21             (*it).arrive = true;
22         }
23         else{//gazelle
24             (*it).force = behavior.evade(agents, *it, view);
25         }
26     }
27     refresh();
28 }
29 }
```

The documentation for this class was generated from the following files:

- `include/evade.h`
- `src/evade.cpp`

## 5.4 flee Class Reference

`#include <flee.h>`

Inheritance diagram for flee:

Collaboration diagram for flee:

## Public Member Functions

- [flee](#) ()

*default constructor.*

## Static Public Member Functions

- static void [loop](#) ()

*loop function for evading scenario*

## Additional Inherited Members

### 5.4.1 Detailed Description

Definition at line 14 of file flee.h.

### 5.4.2 Constructor & Destructor Documentation

#### 5.4.2.1 flee()

```
flee::flee ( )
```

default constructor.

Creates scenario

Definition at line 24 of file flee.cpp.

```
25 {  
26     int agentCount = 196;  
27     name = "fleeing troop";  
28     createAgent(TROOP, &agentCount, nullptr, nullptr);  
29     callback = reinterpret_cast <void(*)()> ( (void *)(&loop) );  
30 }
```

### 5.4.3 Member Function Documentation

### 5.4.3.1 loop()

```
void flee::loop ( ) [static]
```

loop function for evading scenario

fleeing loop function

#### Note

opengl callback forces that function to be static

Definition at line 15 of file flee.cpp.

```
16 {
17     for(auto it = agents.begin(); it < agents.end(); it++){
18         (*it).force = behavior.flee((*it), view, view.getMousePosition());
19     }
20
21     refresh();
22 }
```

The documentation for this class was generated from the following files:

- [include/flee.h](#)
- [src/flee.cpp](#)

## 5.5 flock Class Reference

```
#include <flock.h>
```

Inheritance diagram for flock:

Collaboration diagram for flock:

### Public Member Functions

- [flock \(\)](#)  
*default constructor.*

### Static Public Member Functions

- static void [loop \(\)](#)  
*loop function for evading scenario*

### Additional Inherited Members

#### 5.5.1 Detailed Description

Definition at line 15 of file flock.h.

## 5.5.2 Constructor & Destructor Documentation

### 5.5.2.1 flock()

```
flock::flock ( )
```

default constructor.

Creates scenario

Definition at line 36 of file flock.cpp.

```
37 {
38     int agentCount = 50;
39     float maxForce = 0.3;
40     float maxSpeed = 0.8;
41     name = "flocking agents";
42     createAgent(RANDOM, &agentCount, &maxForce, &maxSpeed);
43     callback = reinterpret_cast<void(*)()> ( (void *)(&loop) );
44 }
```

## 5.5.3 Member Function Documentation

### 5.5.3.1 loop()

```
void flock::loop ( ) [static]
```

loop function for evading scenario

flocking loop function

**Note**

opengl callback forces that function to be static

Definition at line 15 of file flock.cpp.

```
16 {
17     for(auto it = agents.begin(); it < agents.end(); it++){
18         view.forceInScreen((*it));
19
20         pvector sep = behavior.separation(agents, *it);
21         sep.mul(1.5);
22         pvector ali = behavior.align(agents, *it);
23         ali.mul(4);
24         pvector coh = behavior.cohesion(agents, *it);
25         coh.mul(0.1);
26
27         (*it).force = sep + ali + coh;
28         (*it).desiredVelocity = (*it).force + (*it).velocity;
29         (*it).targetPoint = (*it).position + (*it).desiredVelocity;
30         (*it).arrive = true;
31     }
32
33     refresh();
34 }
```

Here is the call graph for this function:

The documentation for this class was generated from the following files:

- [include/flock.h](#)
- [src/flock.cpp](#)

## 5.6 flowField Class Reference

```
#include <flowField.h>
```

Collaboration diagram for flowField:

### Public Member Functions

- [flowField](#) ()  
*default constructor.*
- [flowField](#) ([pvector](#) p)  
*constructor.*
- [pvector](#) [getField](#) (int x, int y)  
*get force for individual pixel*

### 5.6.1 Detailed Description

Definition at line 18 of file flowField.h.

### 5.6.2 Constructor & Destructor Documentation

#### 5.6.2.1 flowField() [1/2]

```
flowField::flowField ( )
```

default constructor.

Create a new [flowField](#) object.

See also

[flowField\(pvector p\)](#)

Definition at line 15 of file flowField.cpp.

```
16 {  
17  
18 }
```

#### 5.6.2.2 flowField() [2/2]

```
flowField::flowField (  
    pvector p )
```

constructor.

Create a new [flowField](#) object.

**Parameters**

$p$	force vector
-----	--------------

**See also**

[flowField\(\)](#)

Definition at line 10 of file flowField.cpp.

```
11 {
12     createFlowField(p);
13 }
```

**5.6.3 Member Function Documentation****5.6.3.1 getField()**

```
pvector flowField::getField (
    int x,
    int y )
```

get force for individual pixel

get force for a specific position

**Parameters**

$x$	x cprovidesoorinate
$y$	y coordinate

**Returns**

returns force at specified position

Definition at line 39 of file flowField.cpp.

```
40 {
41     return uniformField[x][y];
42 }
```

Here is the caller graph for this function:

The documentation for this class was generated from the following files:

- [include/flowField.h](#)
- [src/flowField.cpp](#)

**5.7 graphics Class Reference**

```
#include <graphics.h>
```

Collaboration diagram for graphics:

## Public Member Functions

- void `drawWall` (float border, `color` color)  
*draws wall*
- void `drawAgent` (`agent` &`agent`, `color` &`color`)  
*drawing agent*
- void `drawLine` (`point` p1, `point` p2, `color` cl)  
*drawing line*
- void `drawPath` (`path` &`path`, `color` color)  
*draws path that consists of points*
- void `drawPoint` (`point` p)  
*drawing point*
- void `drawCircle` (`point` p, float radius)  
*drawing circle*
- void `drawText` (string text, `point` p)  
*drawing text on screen*
- void `forceInScreen` (`agent` &`agent`)  
*changes agent position if it is out of screen*
- void `refreshScene` ()  
*position updates for all agents*
- `point` `getMousePosition` ()  
*gets mouse position*
- void `initGraphics` (int \*argv, char \*\*argc, void(\*callback)())  
*initialization of graphics*

## Static Public Member Functions

- static void `timerEvent` (int value)  
*periodic timer event function*
- static void `handleKeypress` (unsigned char key, int x, int y)  
*key press event of the openGL*
- static void `mouseButton` (int button, int state, int x, int y)  
*mouse press event of the openGL*
- static void `handleResize` (int w, int h)  
*event triggered after resizing*
- static void `mouseMove` (int x, int y)  
*event triggered after moving mouse*

## Static Public Attributes

- static int `target_x` = `-WIDTH`  
*mouse position x*
- static int `target_y` = `HEIGHT`  
*mouse position y*

### 5.7.1 Detailed Description

Definition at line 22 of file `graphics.h`.

## 5.7.2 Member Function Documentation

### 5.7.2.1 drawAgent()

```
void graphics::drawAgent (
    agent & agent,
    color & color )
```

drawing agent

draws agent and rotates it with its velocity

#### Parameters

<i>agent</i>	agent to draw
<i>color</i>	color of the agent

Definition at line 180 of file graphics.cpp.

```
181 {
182     glPushMatrix();
183     glTranslatef(agent.position.x, agent.position.y, 0.0f);
184     glRotatef(agent.velocity.getAngle(), 0.0f, 0.0f, 1.0f);
185     glBegin(GL_TRIANGLES);
186     glColor3f( color.R, color.G, color.B);
187     glVertex3f( 1.0f, 0.0f, 0.0f);
188     glVertex3f(-1.0f, 0.5f, 0.0f);
189     glVertex3f(-1.0f, -0.5f, 0.0f);
190     glEnd();
191     glPopMatrix();
192 }
```

Here is the call graph for this function:

### 5.7.2.2 drawCircle()

```
void graphics::drawCircle (
    point p,
    float radius )
```

drawing circle

draws circle using OpenGL

#### Parameters

<i>p</i>	center of the circle
<i>radius</i>	radius of the circle

Definition at line 139 of file graphics.cpp.

```
140 {
141     glBegin(GL_LINE_STRIP);
142     glLineWidth(2);
143     for (int i = 0; i <= 300; i++) {
```



```

144     float angle = 2 * PI * i / 300;
145     float x = cos(angle) * radius;
146     float y = sin(angle) * radius;
147     glVertex2d(p.x + x, p.y + y);
148 }
149 glEnd();
150 }

```

### 5.7.2.3 drawLine()

```

void graphics::drawLine (
    point p1,
    point p2,
    color cl )

```

drawing line

draws line with specified color

#### Parameters

<i>p1</i>	start point of the line
<i>p2</i>	end point of the line
<i>color</i>	color of the line

Definition at line 129 of file graphics.cpp.

```

130 {
131     glColor3f( cl.R, cl.G, cl.B);
132     glLineWidth(2);
133     glBegin(GL_LINES);
134     glVertex2f(p1.x, p1.y);
135     glVertex2f(p2.x, p2.y);
136     glEnd();
137 }

```

### 5.7.2.4 drawPath()

```

void graphics::drawPath (
    path & path,
    color color )

```

draws path that consists of points

draws path using lines

#### Parameters

<i>path</i>	path to draw
<i>color</i>	color of the path

Definition at line 115 of file graphics.cpp.

```

116 {

```

```

117     point p1, p2;
118     for(auto it = path.points.begin(); it < path.points.end()-1; it++){
119         p1 = point((*it).x, (*it).y - path.width/2) ;
120         p2 = point((*it+1).x, (*it+1).y - path.width/2);
121         drawLine(p1, p2, color.getColor(BLUE));
122
123         p1 = point((*it).x, (*it).y + path.width/2) ;
124         p2 = point((*it+1).x, (*it+1).y + path.width/2);
125         drawLine(p1, p2, color.getColor(BLUE));
126     }
127 }

```

Here is the call graph for this function:

#### 5.7.2.5 drawPoint()

```

void graphics::drawPoint (
    point p )

```

drawing point

draws point using OpenGL

##### Parameters

<i>p</i>	point to draw
----------	---------------

Definition at line 152 of file graphics.cpp.

```

153 {
154     glColor3f(1,1,1);
155     glPointSize(4.0);
156     glBegin(GL_POINTS);
157     glVertex2f(p.x, p.y);
158     glEnd();
159 }

```

Here is the caller graph for this function:

#### 5.7.2.6 drawText()

```

void graphics::drawText (
    string text,
    point p )

```

drawing text on screen

draws text using OpenGL

##### Parameters

<i>p</i>	position of the text
<i>text</i>	text to display

Definition at line 22 of file graphics.cpp.

```

23 {
24     glColor3f (0.0, 0.0, 1.0);
25     //glRasterPos2f(-34, 32.5);

```

```

26     glRasterPos2f(p.x, p.y);
27     for ( string::iterator it=text.begin(); it!=text.end(); ++it){
28         glutBitmapCharacter(GLUT_BITMAP_9_BY_15, *it);
29     }
30 }

```

Here is the caller graph for this function:

### 5.7.2.7 drawWall()

```

void graphics::drawWall (
    float border,
    color color )

```

draws wall

draws square that consists of 4 lines

#### Parameters

<i>border</i>	position of the wall
<i>color</i>	color of the wall

Definition at line 161 of file graphics.cpp.

```

162 {
163     point p1 {-border, border};
164     point p2 { border, border};
165     drawLine(p1, p2, color.getColor(BLUE));
166
167     p1 = point ( border, border);
168     p2 = point ( border, -border);
169     drawLine(p1, p2, color.getColor(BLUE));
170
171     p1 = point ( border, -border);
172     p2 = point ( -border, -border);
173     drawLine(p1, p2, color.getColor(BLUE));
174
175     p1 = point (-border, border);
176     p2 = point (-border, -border);
177     drawLine(p1, p2, color.getColor(BLUE));
178 }

```

Here is the call graph for this function:

### 5.7.2.8 forceInScreen()

```

void graphics::forceInScreen (
    agent & agent )

```

changes agent position if it is out of screen

makes the agent stay in screen

#### Parameters

<i>agent</i>	agent to be in screen
--------------	-----------------------

Definition at line 64 of file graphics.cpp.

```

65 {
66     if (agent.position.x > WIDTH)
67         agent.position.x -= 2 * WIDTH;
68     if (agent.position.x < -WIDTH)
69         agent.position.x += 2 * WIDTH;
70     if (agent.position.y > HEIGHT)
71         agent.position.y -= 2 * HEIGHT;
72     if (agent.position.y < -HEIGHT)
73         agent.position.y += 2 * HEIGHT;
74 }

```

### 5.7.2.9 getMousePosition()

```
point graphics::getMousePosition ( )
```

gets mouse position

used to get mouse position

Definition at line 59 of file graphics.cpp.

```

60 {
61     return point (graphics::target_x, graphics::target_y);
62 }

```

Here is the call graph for this function:

### 5.7.2.10 handleKeypress()

```

void graphics::handleKeypress (
    unsigned char key,
    int x,
    int y ) [static]

```

key press event of the openGL

openGL key press event

#### Parameters

<i>key</i>	key
<i>x</i>	unused but required for openGL
<i>y</i>	unused but required for openGL

Definition at line 108 of file graphics.cpp.

```

109 {
110     if (key == ESC) {
111         exit(0);
112     }
113 }

```

Here is the caller graph for this function:

### 5.7.2.11 handleResize()

```

void graphics::handleResize (
    int w,
    int h ) [static]

```

event triggered after resizing

OpenGL screen resize event

#### Parameters

<i>w</i>	width of the screen
<i>h</i>	height of the screen

Definition at line 84 of file graphics.cpp.

```

85 {
86     glViewport(0, 0, w, h); //Tell OpenGL how to convert from coordinates to pixel values
87     glMatrixMode(GL_PROJECTION); //Switch to setting the camera perspective
88     glLoadIdentity(); //Reset the camera
89     //Set the camera perspective
90     gluPerspective(45.0,           //The camera angle
91                   (double)w / (double)h, //The width-to-height ratio
92                   1.0,             //The near z clipping coordinate
93                   200.0);          //The far z clipping coordinate
94 }
```

Here is the caller graph for this function:

#### 5.7.2.12 initGraphics()

```

void graphics::initGraphics (
    int * argv,
    char ** argc,
    void(*)() callback )
```

initialization of graphics

used to init graphics

#### Parameters

<i>argv</i>	user parameters
<i>argc</i>	count of user parameters
<i>callback</i>	loop function for OpenGL periodic callback

Definition at line 42 of file graphics.cpp.

```

43 {
44     glutInit(argv, argc);
45     glutInitDisplayMode(GLUT_DOUBLE | GLUT_RGB | GLUT_DEPTH);
46     glutInitWindowSize(400, 400);
47     glutCreateWindow("Autonomous Steering Agents");
48     glClearColor(0.7f, 0.7f, 0.7f, 1.0f); //set background color
49     glEnable(GL_DEPTH_TEST);
50     glutDisplayFunc(*callback);
51     glutMouseFunc(graphics::mouseButton);
52     glutPassiveMotionFunc(graphics::mouseMove);
53     glutKeyboardFunc(graphics::handleKeypress);
54     glutReshapeFunc(graphics::handleResize);
55     glutTimerFunc(20, graphics::timerEvent, 0);
56     glutMainLoop();
57 }
```

Here is the call graph for this function:

#### 5.7.2.13 mouseButton()

```

void graphics::mouseButton (
```

```

    int button,
    int state,
    int x,
    int y ) [static]

```

mouse press event of the openGL

openGL key mouss press event

#### Parameters

<i>button</i>	mouse button
<i>x</i>	unused but required for openGL
<i>y</i>	unused but required for openGL

Definition at line 102 of file graphics.cpp.

```

103 {
104     if (button == GLUT_LEFT_BUTTON && state == GLUT_DOWN){
105     }
106 }

```

Here is the caller graph for this function:

#### 5.7.2.14 mouseMove()

```

void graphics::mouseMove (
    int x,
    int y ) [static]

```

event triggered after moving mouse

openGL mouse move event

#### Parameters

<i>x</i>	x position of the mouse
<i>y</i>	y position of the mouse

Definition at line 76 of file graphics.cpp.

```

77 {
78     //TODO: mouse position to glut
79     //TODO: magic numbers
80     graphics::target_x = x / 5.88 - 34;
81     graphics::target_y = 34 - y / 5.88;
82 }

```

Here is the caller graph for this function:

#### 5.7.2.15 refreshScene()

```

void graphics::refreshScene ( )

```

position updates for all agents

refresh screen for every existing object

Definition at line 33 of file graphics.cpp.

```
34 {
35     glutSwapBuffers();
36     glClear(GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT);
37     glMatrixMode(GL_MODELVIEW); //Switch to the drawing perspective
38     glLoadIdentity(); //Reset the drawing perspective
39     glTranslatef(0.0f, 0.0f, -85.0f); //Move to the center of the triangle
40 }
```

### 5.7.2.16 timerEvent()

```
void graphics::timerEvent (
    int value ) [static]
```

periodic timer event function

OpenGL timer event callback

#### Parameters

<i>value</i>	period as ms
--------------	--------------

Definition at line 96 of file graphics.cpp.

```
97 {
98     glutPostRedisplay(); //Tell GLUT that the display has changed
99     glutTimerFunc(value, timerEvent, 20);
100 }
```

Here is the caller graph for this function:

## 5.7.3 Member Data Documentation

### 5.7.3.1 target\_x

```
int graphics::target_x = -WIDTH [static]
```

mouse position x

holds mouse y position

Definition at line 153 of file graphics.h.

### 5.7.3.2 target\_y

```
int graphics::target_y = HEIGHT [static]
```

mouse position y

holds mouse x position

Definition at line 159 of file graphics.h.

The documentation for this class was generated from the following files:

- [include/graphics.h](#)
- [src/graphics.cpp](#)

## 5.8 mouseFollower Class Reference

```
#include <mouseFollower.h>
```

Inheritance diagram for mouseFollower:

Collaboration diagram for mouseFollower:

### Public Member Functions

- [mouseFollower](#) ()  
*default constructor.*

### Static Public Member Functions

- static void [loop](#) ()  
*loop function for evading scenario*

### Additional Inherited Members

#### 5.8.1 Detailed Description

Definition at line 14 of file mouseFollower.h.

#### 5.8.2 Constructor & Destructor Documentation

##### 5.8.2.1 mouseFollower()

```
mouseFollower::mouseFollower ( )
```

default constructor.

Creates scenario

Definition at line 25 of file mouseFollower.cpp.

```
26 {  
27     int agentCount = 30;  
28     float maxForce = 0.3;  
29     float maxSpeed = 0.6;  
30     name = "mouse following";  
31     createAgent(RANDOM, &agentCount, &maxForce, &maxSpeed);  
32     callback = reinterpret_cast <void(*)()> ( (void *)(&loop) );  
33 }
```

#### 5.8.3 Member Function Documentation



### 5.8.3.1 loop()

```
void mouseFollower::loop ( ) [static]
```

loop function for evading scenario

mouse following loop function

#### Note

opengl callback forces that function to be static

Definition at line 15 of file mouseFollower.cpp.

```
16 {
17     for(auto it = agents.begin(); it < agents.end(); it++){
18         (*it).targetPoint = view.getMousePosition();
19         (*it).force = behavior.seek(*it);
20         (*it).arrive = true;
21     }
22     refresh();
23 }
```

The documentation for this class was generated from the following files:

- include/mouseFollower.h
- src/mouseFollower.cpp

## 5.9 obstacle Class Reference

```
#include <obstacle.h>
```

Collaboration diagram for obstacle:

### Public Member Functions

- [obstacle \(\)](#)  
*default constructor.*
- [obstacle \(point p, float r\)](#)  
*constructor*

### Public Attributes

- [point p](#)  
*x and y coordinates*
- [float r](#)  
*the bigger radius the bigger the obstacle*

### 5.9.1 Detailed Description

Definition at line 12 of file obstacle.h.

## 5.9.2 Constructor & Destructor Documentation

### 5.9.2.1 obstacle() [1/2]

```
obstacle::obstacle ( )
```

default constructor.

create a new obstacle object.

See also

[obstacle\(point p, float r](#)

Definition at line 15 of file obstacle.cpp.

```
16 {  
17  
18 }
```

### 5.9.2.2 obstacle() [2/2]

```
obstacle::obstacle (  
    point p,  
    float r )
```

constructor

create a new obstacle object.

Parameters

<i>p</i>	center of the circular obstacle
<i>r</i>	radius of the obstacle

See also

[obstacle\(point p, float r\);](#)

Definition at line 20 of file obstacle.cpp.

```
21 {  
22     this->p = p;  
23     this->r = r;  
24 }
```

## 5.9.3 Member Data Documentation

### 5.9.3.1 p

`point obstacle::p`

x and y coordinates

center point of the obstacle

Definition at line 34 of file obstacle.h.

### 5.9.3.2 r

`float obstacle::r`

the bigger radius the bigger the obstacle

radius of the obstacle

Definition at line 40 of file obstacle.h.

The documentation for this class was generated from the following files:

- include/[obstacle.h](#)
- src/[obstacle.cpp](#)

## 5.10 obstacleAvoidance Class Reference

```
#include <obstacleAvoidance.h>
```

Inheritance diagram for obstacleAvoidance:

Collaboration diagram for obstacleAvoidance:

### Public Member Functions

- [obstacleAvoidance](#) ()  
*default constructor.*

### Static Public Member Functions

- static void [loop](#) ()  
*loop function for evading scenario*
- static void [createObstacle](#) (vector< [obstacle](#) > &[obstacles](#))  
*obstacle creation*

## Static Public Attributes

- static vector< [obstacle](#) > [obstacles](#)  
*list of obstacles*

## Additional Inherited Members

### 5.10.1 Detailed Description

Definition at line 15 of file obstacleAvoidance.h.

### 5.10.2 Constructor & Destructor Documentation

#### 5.10.2.1 obstacleAvoidance()

```
obstacleAvoidance::obstacleAvoidance ( )
```

default constructor.

Creates scenario

Definition at line 43 of file obstacleAvoidance.cpp.

```
44 {
45     name = "avoid obstacles";
46     createAgent(STATIC, nullptr, nullptr, nullptr);
47     createObstacle(obstacles);
48     callback = reinterpret_cast <void(*)()> ( (void *)(&loop) );
49 }
```

### 5.10.3 Member Function Documentation

#### 5.10.3.1 createObstacle()

```
void obstacleAvoidance::createObstacle (
    vector< obstacle > & obstacles ) [static]
```

obstacle creation

Parameters

<i>obstacles</i>	obstacle list to be created
------------------	-----------------------------

**Note**

opengl callback forces that function to be static

Definition at line 36 of file obstacleAvoidance.cpp.

```
37 {
38     obstacles.push_back(obstacle(point(0,0), 8));
39     obstacles.push_back(obstacle(point(-20,0), 3));
40     obstacles.push_back(obstacle(point(20,-10), 4));
41 }
```

Here is the call graph for this function:

**5.10.3.2 loop()**

```
void obstacleAvoidance::loop ( ) [static]
```

loop function for evading scenario

obstacle avoidance loop function

**Note**

opengl callback forces that function to be static

Definition at line 17 of file obstacleAvoidance.cpp.

```
18 {
19     for(auto it = agents.begin(); it < agents.end(); it++){
20         for(auto it = obstacles.begin(); it < obstacles.end(); it++){
21             point p = (*it).p;
22             view.drawCircle(p, (*it).r);
23         }
24     }
25     (*it).targetPoint = view.getMousePosition();
26     pvector seek = behavior.seek(*it);
27     seek.mul(0.5);
28
29     pvector avoid = behavior.avoid(obstacles, *it);
30     (*it).force = avoid + seek;
31     (*it).arrive = true;
32 }
33 refresh();
34 }
```

Here is the call graph for this function:

**5.10.4 Member Data Documentation****5.10.4.1 obstacles**

```
vector< obstacle > obstacleAvoidance::obstacles [static]
```

list of obstacles

**Note**

opengl callback forces that function to be static

Definition at line 34 of file obstacleAvoidance.h.

The documentation for this class was generated from the following files:

- include/[obstacleAvoidance.h](#)
- src/[obstacleAvoidance.cpp](#)

## 5.11 path Class Reference

```
#include <path.h>
```

Collaboration diagram for path:

### Public Member Functions

- [path](#) ()  
*Default constructor.*
- [path](#) (float [width](#))  
*Constructor.*
- void [addPoint](#) ([point](#) p)  
*adds a new point to the path*

### Public Attributes

- vector< [point](#) > [points](#)  
*points added to the path*
- int [width](#)  
*defines width of the path*

### 5.11.1 Detailed Description

Definition at line 15 of file path.h.

### 5.11.2 Constructor & Destructor Documentation

#### 5.11.2.1 [path\(\)](#) [1/2]

```
path::path ( )
```

Default constructor.

Create a new path object.

See also

[path\(float width\)](#)

Definition at line 16 of file path.cpp.

```
17 {  
18  
19 }
```

#### 5.11.2.2 [path\(\)](#) [2/2]

```
path::path (  
    float width )
```

Constructor.

Create a new path object.

## Parameters

<i>width</i>	The width of the path.
--------------	------------------------

## See also

[path\(\)](#)

Definition at line 21 of file path.cpp.

```
22 {  
23     this->width = width;  
24 }
```

### 5.11.3 Member Function Documentation

#### 5.11.3.1 addPoint()

```
void path::addPoint (  
    point p )
```

adds a new point to the path

Used when customizing path

## Parameters

<i>point</i>	new point to add to the path
--------------	------------------------------

Definition at line 11 of file path.cpp.

```
12 {  
13     points.push_back(p);  
14 }
```

Here is the caller graph for this function:

### 5.11.4 Member Data Documentation

#### 5.11.4.1 points

```
vector<point> path::points
```

points added to the path

path is created from these points

Definition at line 43 of file path.h.

#### 5.11.4.2 width

```
int path::width
```

defines width of the path

path width

Definition at line 49 of file path.h.

The documentation for this class was generated from the following files:

- include/[path.h](#)
- src/[path.cpp](#)

## 5.12 pathFollower Class Reference

```
#include <pathFollower.h>
```

Inheritance diagram for pathFollower:

Collaboration diagram for pathFollower:

### Public Member Functions

- [pathFollower](#) ()  
*default constructor.*

### Static Public Member Functions

- static void [loop](#) ()  
*loop function for evading scenario*
- static void [createPath](#) ([path](#) &p)  
*creates path*

### Static Public Attributes

- static [path](#) [myPath](#)  
*used to access path class behaviors*

### Additional Inherited Members

#### 5.12.1 Detailed Description

Definition at line 14 of file pathFollower.h.



## 5.12.2 Constructor & Destructor Documentation

### 5.12.2.1 pathFollower()

```
pathFollower::pathFollower ( )
```

default constructor.

Creates scenario

Definition at line 37 of file pathFollower.cpp.

```
38 {
39     int agentCount = 40;
40     float maxForce = 0.2;
41     float maxSpeed = 0.4;
42     myPath = path(8);
43     createPath(myPath);
44     name = "path following";
45     createAgent(RANDOM, &agentCount, &maxForce, &maxSpeed);
46     callback = reinterpret_cast <void(*)()> ( (void *)(&loop) );
47 }
```

## 5.12.3 Member Function Documentation

### 5.12.3.1 createPath()

```
void pathFollower::createPath (
    path & p ) [static]
```

creates path

path creating

Parameters

<i>path</i>	to create
-------------	-----------

Note

opengl callback forces that function to be static

Definition at line 29 of file pathFollower.cpp.

```
30 {
31     p.addPoint(point(-40, 5));
32     p.addPoint(point(-14, 15));
33     p.addPoint(point( 10, 7));
34     p.addPoint(point( 40, 12));
35 }
```

Here is the call graph for this function:

### 5.12.3.2 loop()

```
void pathFollower::loop ( ) [static]
```

loop function for evading scenario

path follower avoidance loop function

#### Note

opengl callback forces that function to be static

Definition at line 17 of file pathFollower.cpp.

```
18 {
19     for(auto it = agents.begin(); it < agents.end(); it++){
20         view.drawPath(myPath, myColor);
21         pvector seek = behavior.stayInPath(*it, myPath, view);
22         pvector sep = behavior.separation(agents, *it);
23         sep.mul(5);
24         (*it).force = sep + seek;
25     }
26     refresh();
27 }
```

Here is the call graph for this function:

## 5.12.4 Member Data Documentation

### 5.12.4.1 myPath

```
path pathFollower::myPath [static]
```

used to access path class behaviors

path instance

#### Note

opengl callback forces that function to be static

Definition at line 42 of file pathFollower.h.

The documentation for this class was generated from the following files:

- include/pathFollower.h
- src/pathFollower.cpp

## 5.13 point Class Reference

```
#include <point.h>
```

Collaboration diagram for point:

## Public Member Functions

- [point](#) ()  
*default constructor*
- [point](#) (float [x](#), float [y](#))  
*constructor*
- void [div](#) (float [d](#))  
*divide point*
- void [mul](#) (float [d](#))  
*multiply point*
- void [print](#) (const string &[s](#))  
*debug function*
- void [getNormalPoint](#) ([point](#) [predicted](#), [point](#) [start](#), [point](#) [end](#))  
*gets a points normal point on a vector*
- [point operator+](#) ([pvector](#) const &[obj](#))  
*used between vector and point*
- [point operator+](#) ([point](#) const &[obj](#))  
*used between point and point*
- [pvector operator-](#) ([point](#) const &[obj](#))  
*used between point and point*
- bool [operator==](#) ([point](#) const &[obj](#))  
*used between point and point*

## Public Attributes

- float [x](#)  
*x position of the point*
- float [y](#)  
*y position of the point*

### 5.13.1 Detailed Description

Definition at line 15 of file point.h.

### 5.13.2 Constructor & Destructor Documentation

#### 5.13.2.1 [point\(\)](#) [1/2]

```
point::point ( )
```

default constructor

create a new point instance

See also

[point\(float x, float y\)](#)

Definition at line 21 of file point.cpp.

```
21 {}
```

Here is the caller graph for this function:

### 5.13.2.2 point() [2/2]

```
point::point (
    float x,
    float y )
```

constructor

create a new point instance

#### Parameters

<i>x</i>	position x of the point
<i>y</i>	position y of the point

See also

[point\(\)](#)

Definition at line 15 of file point.cpp.

```
16 {
17     this->x = x;
18     this->y = y;
19 }
```

## 5.13.3 Member Function Documentation

### 5.13.3.1 div()

```
void point::div (
    float d )
```

divide point

helper function to divide point position

#### Parameters

<i>d</i>	scalar to divide position of the point
----------	--

Definition at line 38 of file point.cpp.

```
39 {
40     x = x / d;
41     y = y / d;
42 }
```

Here is the caller graph for this function:

### 5.13.3.2 getNormalPoint()

```
void point::getNormalPoint (
    point predicted,
    point start,
    point end )
```

gets a points normal point on a vector

provides normal point on a vector of a point

#### Parameters

<i>predicted</i>	point that caller require normal on the vector
<i>start</i>	start point of the vector
<i>end</i>	end point of the vector

Definition at line 67 of file point.cpp.

```
68 {
69     pvector a = predicted - start;
70     pvector b = end - start;
71     b.normalize();
72     float a_dot_b = a.dotProduct(b);
73     b.mul(a_dot_b);
74     point normalPoint = start + b;
75     this->x = normalPoint.x;
76     this->y = normalPoint.y;
77 }
```

Here is the call graph for this function: Here is the caller graph for this function:

### 5.13.3.3 mul()

```
void point::mul (
    float d )
```

multiply point

helper function to multiply point position

#### Parameters

<i>d</i>	scalar to multiply position of the point
----------	--

Definition at line 44 of file point.cpp.

```
45 {
46     x = x * d;
47     y = y * d;
48 }
```

Here is the caller graph for this function:

### 5.13.3.4 operator+() [1/2]

```
point point::operator+ (
    point const & obj )
```

used between point and point

overloaded + operator

#### Parameters

<i>obj</i>	point to add
------------	--------------

#### Returns

subtracted result

Definition at line 51 of file point.cpp.

```
52 {  
53     point res;  
54     res.x = x + obj.x;  
55     res.y = y + obj.y;  
56     return res;  
57 }
```

### 5.13.3.5 operator+() [2/2]

```
point point::operator+ (  
    pvector const & obj )
```

used between vector and point

overloaded + operator

#### Parameters

<i>obj</i>	vector to add
------------	---------------

#### Returns

subtracted result

Definition at line 23 of file point.cpp.

```
24 {  
25     point res;  
26     res.x = x + obj.x;  
27     res.y = y + obj.y;  
28     return res;  
29 }
```

### 5.13.3.6 operator-()

```
pvector point::operator- (  
    point const & obj )
```

used between point and point

overloaded - operator

**Parameters**

<i>obj</i>	point to subtract
------------	-------------------

**Returns**

subtracted result

Definition at line 59 of file point.cpp.

```
60 {  
61     pvector res;  
62     res.x = x - obj.x;  
63     res.y = y - obj.y;  
64     return res;  
65 }
```

**5.13.3.7 operator==()**

```
bool point::operator== (  
    point const & obj )
```

used between point and point

overloaded == operator

**Parameters**

<i>obj</i>	point to compare
------------	------------------

**Returns**

true or false

Definition at line 31 of file point.cpp.

```
32 {  
33     if(x == obj.x && y == obj.y)  
34         return true;  
35     return false;  
36 }
```

**5.13.3.8 print()**

```
void point::print (  
    const string & s )
```

debug function

prints position of the point

#### Parameters

s	explanation string of the log
---	-------------------------------

Definition at line 79 of file point.cpp.

```
80 {  
81     cout << " " << s << " " << x << " " << y << endl;  
82 }
```

### 5.13.4 Member Data Documentation

#### 5.13.4.1 x

```
float point::x
```

x position of the point

x coordinate

Definition at line 99 of file point.h.

#### 5.13.4.2 y

```
float point::y
```

y position of the point

y coordinate

Definition at line 105 of file point.h.

The documentation for this class was generated from the following files:

- [include/point.h](#)
- [src/point.cpp](#)

## 5.14 prison Class Reference

```
#include <prison.h>
```

Inheritance diagram for prison:

Collaboration diagram for prison:



## Public Member Functions

- `prison ()`

*default constructor.*

## Static Public Member Functions

- `static void loop ()`

*loop function for evading scenario*

## Additional Inherited Members

### 5.14.1 Detailed Description

Definition at line 15 of file prison.h.

### 5.14.2 Constructor & Destructor Documentation

#### 5.14.2.1 prison()

```
prison::prison ( )
```

default constructor.

Creates scenario

Definition at line 28 of file prison.cpp.

```
29 {  
30     int agentCount = 30;  
31     float maxForce = 0.6;  
32     float maxSpeed = 0.6;  
33  
34     name = "stay in prison";  
35     createAgent(RANDOM, &agentCount, &maxForce, &maxSpeed);  
36     callback = reinterpret_cast<void(*)()> ( (void *)(&loop) );  
37 }
```

### 5.14.3 Member Function Documentation

### 5.14.3.1 loop()

```
void prison::loop ( ) [static]
```

loop function for evading scenario

prison loop function

#### Note

opengl callback forces that function to be static

Definition at line 18 of file prison.cpp.

```
19 {  
20     for(auto it = agents.begin(); it < agents.end(); it++){  
21         view.drawWall(WALL, myColor);  
22         (*it).force = behavior.stayInArea(*it, WALL - DISTANCE);  
23         (*it).force += behavior.separation(agents, *it);  
24     }  
25     refresh();  
26 }
```

The documentation for this class was generated from the following files:

- [include/prison.h](#)
- [src/prison.cpp](#)

## 5.15 pursuit Class Reference

```
#include <pursuit.h>
```

Inheritance diagram for pursuit:

Collaboration diagram for pursuit:

### Public Member Functions

- [pursuit \(\)](#)  
*default constructor.*

### Static Public Member Functions

- static void [loop \(\)](#)  
*loop function for evading scenario*

### Additional Inherited Members

#### 5.15.1 Detailed Description

Definition at line 14 of file pursuit.h.

## 5.15.2 Constructor & Destructor Documentation

### 5.15.2.1 pursuit()

```
pursuit::pursuit ( )
```

default constructor.

Creates scenario

Definition at line 31 of file pursuit.cpp.

```
32 {  
33     name = "pursuit";  
34     createAgent(STATIC, nullptr, nullptr, nullptr);  
35     callback = reinterpret_cast <void(*)()> ( (void *)(&loop) );  
36 }
```

## 5.15.3 Member Function Documentation

### 5.15.3.1 loop()

```
void pursuit::loop ( ) [static]
```

loop function for evading scenario

pursuing loop function

#### Note

opengl callback forces that function to be static

Definition at line 15 of file pursuit.cpp.

```
16 {  
17     for(auto it = agents.begin(); it < agents.end(); it++){  
18         if((*it).name == "gazelle"){  
19             (*it).targetPoint = view.getMousePosition();  
20             (*it).force = behavior.seek(*it);  
21         }  
22         else{//lion  
23             (*it).force = behavior.pursuit(agents, *it, view);  
24         }  
25         (*it).arrive = true;  
26     }  
27     refresh();  
28 }  
29 }
```

The documentation for this class was generated from the following files:

- include/pursuit.h
- src/pursuit.cpp

## 5.16 pvector Class Reference

```
#include <pvector.h>
```

Collaboration diagram for pvector:

### Public Member Functions

- [pvector](#) ()  
*default constructor*
- [pvector](#) (float x, float y)  
*constructor*
- float [magnitude](#) ()  
*calculates magnitude of the vector*
- [pvector](#) & [normalize](#) ()  
*normalize vector*
- void [div](#) (float i)  
*divides vector by given scalar value*
- void [mul](#) (float i)  
*multiplies vector by given scalar value*
- void [add](#) ([pvector](#) p)  
*addition of vectors*
- void [limit](#) (float limit)  
*limits vector with the given parameter*
- float [getAngle](#) ()  
*get angle using its x and y magnitudes*
- float [dotProduct](#) ([pvector](#) v)  
*dot product of two vectors*
- float [angleBetween](#) ([pvector](#) v)  
*angle is calculated using dot product*
- void [print](#) (const string &s)  
*debug function*
- [pvector](#) [operator+=](#) ([pvector](#) const &obj)  
*used between vectors*
- [pvector](#) [operator+](#) ([pvector](#) const &obj)  
*used between vectors*
- [pvector](#) [operator-](#) ([pvector](#) const &obj)  
*used between vectors*
- [pvector](#) [operator-](#) ([point](#) const &obj)  
*used between vector and point*
- [pvector](#) [operator+](#) ([point](#) const &obj)  
*used between vector and point*
- bool [operator==](#) ([pvector](#) const &obj)  
*used between vectors*

### Public Attributes

- float x  
*used between vector and point*
- float y  
*used between vector and point*

### 5.16.1 Detailed Description

Definition at line 17 of file pvector.h.

### 5.16.2 Constructor & Destructor Documentation

#### 5.16.2.1 pvector() [1/2]

```
pvector::pvector ( )
```

default constructor

create a new pvector instance

See also

[pvector\(float x, float y\)](#)

Definition at line 35 of file pvector.cpp.

```
36 {  
37  
38 }
```

#### 5.16.2.2 pvector() [2/2]

```
pvector::pvector (  
    float x,  
    float y )
```

constructor

create a new pvector instance

Parameters

<i>x</i>	x magnitude of the vector
<i>y</i>	y magnitude of the vector

See also

[pvector\(\)](#)

Definition at line 40 of file pvector.cpp.

```
41 {  
42     this->x = x;  
43     this->y = y;  
44 }
```

### 5.16.3 Member Function Documentation

#### 5.16.3.1 add()

```
void pvector::add (
    pvector p )
```

addition of vectors

vector addition

##### Parameters

<i>p</i>	vector to add
----------	---------------

Definition at line 58 of file pvector.cpp.

```
59 {
60     x = x + p.x;
61     y = y + p.y;
62 }
```

#### 5.16.3.2 angleBetween()

```
float pvector::angleBetween (
    pvector v )
```

angle is calculated using dot product

angle calculation between two vectors

##### Parameters

<i>v</i>	vector to calculate angle
----------	---------------------------

##### Returns

angle value between two vectors

Definition at line 23 of file pvector.cpp.

```
24 {
25     float angle = this->dotProduct(v) / (this->magnitude() * v.magnitude());
26     angle = acos(angle) * 180 / PI;
27     return angle;
28 }
```

Here is the call graph for this function: Here is the caller graph for this function:

### 5.16.3.3 div()

```
void pvector::div (
    float i )
```

divides vector by given scalar value

vector division

#### Parameters

<i>i</i>	scalar value to divide
----------	------------------------

Definition at line 46 of file pvector.cpp.

```
47 {
48     x = x / i;
49     y = y / i;
50 }
```

Here is the caller graph for this function:

### 5.16.3.4 dotProduct()

```
float pvector::dotProduct (
    pvector v )
```

dot product of two vectors

dot product calculation

#### Parameters

<i>v</i>	vector to calculate dot product
----------	---------------------------------

#### Returns

returns scalar dot product value

Definition at line 30 of file pvector.cpp.

```
31 {
32     return ((x * v.x) + (y * v.y));
33 }
```

Here is the caller graph for this function:

### 5.16.3.5 getAngle()

```
float pvector::getAngle ( )
```

get angle using its x and y magnitudes

calculates vector angle

**Returns**

angle of the vector

Definition at line 16 of file pvector.cpp.

```
17 {
18     float angle;
19     angle = atan2 (this->y, this->x) * 180 / PI;
20     return angle;
21 }
```

Here is the caller graph for this function:

**5.16.3.6 limit()**

```
void pvector::limit (
    float limit )
```

limits vector with the given parameter

vector limitation

**Parameters**

<i>limit</i>	upper limit to restrict vector
--------------	--------------------------------

Definition at line 83 of file pvector.cpp.

```
84 {
85     this->normalize();
86     this->mul(limit);
87 }
```

Here is the call graph for this function: Here is the caller graph for this function:

**5.16.3.7 magnitude()**

```
float pvector::magnitude ( )
```

calculates magnitude of the vector

uses pisagor theorem for magnitude calculation

**Returns**

magnitude of the vector

Definition at line 64 of file pvector.cpp.

```
65 {
66     return sqrt((this->x * this->x) + (this->y * this->y));
67 }
```

Here is the caller graph for this function:

**5.16.3.8 mul()**

```
void pvector::mul (
    float i )
```

multiplies vector by given scalar value

vector multiplication



## Parameters

<i>i</i>	scalar value to multiply
----------	--------------------------

Definition at line 52 of file pvector.cpp.

```
53 {
54     x = x * i;
55     y = y * i;
56 }
```

Here is the caller graph for this function:

## 5.16.3.9 normalize()

```
pvector & pvector::normalize ( )
```

normalize vector

divides vector by magnitude

## Returns

normalized vector

Definition at line 69 of file pvector.cpp.

```
70 {
71     float magnitude = this->magnitude();
72     if(magnitude != 0){
73         this->x = this->x / magnitude;
74         this->y = this->y / magnitude;
75     }
76     else{
77         this->x = 0;
78         this->y = 0;
79     }
80     return *this;
81 }
```

Here is the caller graph for this function:

## 5.16.3.10 operator+() [1/2]

```
pvector pvector::operator+ (
    point const & obj )
```

used between vector and point

overloaded + operator

## Parameters

<i>obj</i>	point to add
------------	--------------

## Returns

sum

Definition at line 111 of file pvector.cpp.

```
112 {  
113     pvector res;  
114     res.x = x + obj.x;  
115     res.y = y + obj.y;  
116     return res;  
117 }
```

#### 5.16.3.11 operator+() [2/2]

```
pvector pvector::operator+ (  
    pvector const & obj )
```

used between vectors

overloaded + operator

##### Parameters

<i>obj</i>	vector to add
------------	---------------

##### Returns

sum of vectors

Definition at line 89 of file pvector.cpp.

```
90 {  
91     pvector res;  
92     res.x = x + obj.x;  
93     res.y = y + obj.y;  
94     return res;  
95 }
```

#### 5.16.3.12 operator+=()

```
pvector pvector::operator+= (  
    pvector const & obj )
```

used between vectors

overloaded += operator

##### Parameters

<i>obj</i>	vector to add
------------	---------------

##### Returns

sum of vectors

Definition at line 97 of file pvector.cpp.

```
98 {  
99     x = x + obj.x;  
100    y = y + obj.y;  
101    return *this;  
102 }
```

### 5.16.3.13 operator-() [1/2]

```
pvector pvector::operator- (  
    point const & obj )
```

used between vector and point

overloaded - operator

#### Parameters

<i>obj</i>	point to subtract
------------	-------------------

#### Returns

difference

Definition at line 119 of file pvector.cpp.

```
120 {  
121     pvector res;  
122     res.x = x - obj.x;  
123     res.y = y - obj.y;  
124     return res;  
125 }
```

### 5.16.3.14 operator-() [2/2]

```
pvector pvector::operator- (  
    pvector const & obj )
```

used between vectors

overloaded - operator

#### Parameters

<i>obj</i>	vector to subtract
------------	--------------------

#### Returns

difference of vectors

Definition at line 132 of file pvector.cpp.

```

133 {
134     pvector res;
135     res.x = x - obj.x;
136     res.y = y - obj.y;
137     return res;
138 }

```

#### 5.16.3.15 operator==()

```

bool pvector::operator== (
    pvector const & obj )

```

used between vectors

overloaded == operator

##### Parameters

<i>obj</i>	vector to check if equal
------------	--------------------------

##### Returns

true or false

Definition at line 104 of file pvector.cpp.

```

105 {
106     if (x == obj.x && y == obj.y)
107         return true;
108     return false;
109 }

```

#### 5.16.3.16 print()

```

void pvector::print (
    const string & s )

```

debug function

prints position of the vector

##### Parameters

<i>s</i>	explanation string of the log
----------	-------------------------------

Definition at line 127 of file pvector.cpp.

```

128 {
129     cout << s << " " << x << " " << y << endl;
130 }

```

## 5.16.4 Member Data Documentation

### 5.16.4.1 x

```
float pvector::x
```

used between vector and point

x magnitude of the vector

Definition at line 159 of file pvector.h.

### 5.16.4.2 y

```
float pvector::y
```

used between vector and point

y magnitude of the vector

Definition at line 165 of file pvector.h.

The documentation for this class was generated from the following files:

- [include/pvector.h](#)
- [src/pvector.cpp](#)

## 5.17 random Class Reference

```
#include <random.h>
```

Collaboration diagram for random:

### Static Public Member Functions

- static void [createRandomArray](#) (int \*arr, int size)  
*generates random array usin swap between its elements*

### 5.17.1 Detailed Description

Definition at line 9 of file random.h.

## 5.17.2 Member Function Documentation

### 5.17.2.1 createRandomArray()

```
void random::createRandomArray (
    int * arr,
    int size ) [static]
```

generates random array usin swap between its elements

random array generation

**Parameters**

<i>arr</i>	int array that will include random values
<i>size</i>	size of the array

Definition at line 14 of file random.cpp.

```

14                                     {
15     srand(time(NULL));
16     for (int i=0; i<size; i++)
17         arr[i] = i+1;
18
19     for (int i=0; i < size; i++){
20         int r = rand() % size;
21         swap(arr[i], arr[r]);
22     }
23 }
```

The documentation for this class was generated from the following files:

- include/[random.h](#)
- src/[random.cpp](#)

## 5.18 scenario Class Reference

```
#include <scenario.h>
```

Inheritance diagram for scenario:

Collaboration diagram for scenario:

### Public Member Functions

- [scenario](#) ()  
*default constructor.*
- void [createAgent](#) (int type, int \*count, float \*force, float \*speed)  
*agent creation*
- void [initGL](#) (int \*argv, char \*\*argc)  
*initializing of openGL*

### Static Public Member Functions

- static void [refresh](#) ()  
*refresh behavior for all items*

### Public Attributes

- void(\* [callback](#) )()  
*openGL screen refresh callback function*

## Static Public Attributes

- static vector< [agent](#) > [agents](#)  
*all the agents*
- static [graphics](#) [view](#)  
*graphics instance*
- static [steeringBehavior](#) [behavior](#)  
*behavior instance*
- static [color](#) [myColor](#)  
*color instance*
- static string [name](#)  
*name of the scenario*

### 5.18.1 Detailed Description

Definition at line 19 of file scenario.h.

### 5.18.2 Constructor & Destructor Documentation

#### 5.18.2.1 scenario()

```
scenario::scenario ( )
```

default constructor.

Creates scenario

Definition at line 28 of file scenario.cpp.

```
29 {  
30     srand(time(NULL));  
31     myColor.createColors();  
32     view = graphics();  
33 }
```

### 5.18.3 Member Function Documentation

#### 5.18.3.1 createAgent()

```
void scenario::createAgent (  
    int type,  
    int * count,  
    float * force,  
    float * speed )
```

agent creation

creates agents

**Parameters**

<i>type</i>	type of creation method
<i>count</i>	number of agents to be created
<i>force</i>	max force of agents to be created
<i>speed</i>	max speed of agents to be created

Definition at line 106 of file scenario.cpp.

```

107 {
108     if(type == TROOP){
109         createTroop(*count);
110     }
111     else if(type == RANDOM){
112         createRandomAgents(*count, *force, *speed);
113     }
114     else if(type == STATIC){
115         createStaticAgents();
116     }
117     else{
118         //error message
119     }
120 }
```

**5.18.3.2 initGL()**

```

void scenario::initGL (
    int * argv,
    char ** argc )
```

initializing of openGL

graphics initialization

**Parameters**

<i>argv</i>	list of user arguments
<i>argc</i>	number of user arguments

Definition at line 22 of file scenario.cpp.

```

23 {
24     view.initGraphics(argc, argv, callback);
25 }
```

Here is the caller graph for this function:

**5.18.3.3 refresh()**

```

void scenario::refresh ( ) [static]
```

refresh behavior for all items

applying force, upodating position etc for all items



**Note**

opengl callback forces that function to be static

Definition at line 35 of file scenario.cpp.

```

36 {
37     for(auto it = agents.begin(); it < agents.end(); it++){
38         (*it).updatePosition((*it).arrive);
39         view.drawAgent(*it, (*it).fillColor);
40     }
41
42     view.drawText(name, point(-34, 32.25)); //TODO: magic numbers, define left corner
43     view.refreshScene();
44 }
```

Here is the call graph for this function:

## 5.18.4 Member Data Documentation

### 5.18.4.1 agents

```
vector< agent > scenario::agents [static]
```

all the agents

existing agents stored in that variable

**Note**

opengl callback forces that function to be static

Definition at line 57 of file scenario.h.

### 5.18.4.2 behavior

```
steeringBehavior scenario::behavior [static]
```

behavior instance

used to apply steering behaviors

**Note**

opengl callback forces that function to be static

Definition at line 71 of file scenario.h.

#### 5.18.4.3 callback

```
void(* scenario::callback) ()
```

OpenGL screen refresh callback function

used as main loop in derived classes

Definition at line 91 of file scenario.h.

#### 5.18.4.4 myColor

```
color scenario::myColor [static]
```

color instance

used to apply color behaviors

##### Note

opengl callback forces that function to be static

Definition at line 78 of file scenario.h.

#### 5.18.4.5 name

```
string scenario::name [static]
```

name of the scenario

used to display scenario on screen

##### Note

opengl callback forces that function to be static

Definition at line 85 of file scenario.h.

## 5.18.4.6 view

```
graphics scenario::view [static]
```

graphics instance

used to apply graphics operations

## Note

opengl callback forces that function to be static

Definition at line 64 of file scenario.h.

The documentation for this class was generated from the following files:

- include/scenario.h
- src/scenario.cpp

## 5.19 steeringBehavior Class Reference

```
#include <steeringBehavior.h>
```

Collaboration diagram for steeringBehavior:

## Public Member Functions

- [pvector stayInArea](#) ([agent &agent](#), int turnPoint)  
*returns force to apply if it is near the specified border*
- [pvector inFlowField](#) ([agent &agent](#), [flowField &flow](#))  
*applies flow field at agents position*
- [pvector stayInPath](#) ([agent &agent](#), [path &path](#), [graphics view](#))  
*agent follows given path*
- [pvector seek](#) ([agent &agent](#))  
*agent goes to specified point*
- [pvector separation](#) (vector< [agent](#) > agents, [agent &agent](#))  
*agent stays away from other agents, with specified distance*
- [pvector cohesion](#) (vector< [agent](#) > boids, [agent &agent](#))  
*agent goes at the center of other agents positions*
- [pvector align](#) (vector< [agent](#) > boids, [agent &agent](#))  
*agent velocity aligned with other agents, with specified distance*
- [pvector wander](#) ([agent &agent](#))  
*agent that will wander*
- [pvector pursuit](#) (vector< [agent](#) > boids, [agent &pursuer](#), [graphics view](#))  
*agent pursuits other agent in all agents*
- [pvector evade](#) (vector< [agent](#) > boids, [agent &evader](#), [graphics view](#))  
*agent escapes other agent in all agents*
- [pvector flee](#) ([agent &agent](#), [graphics &view](#), [point p](#))  
*agent flees from mouse*
- [pvector avoid](#) (vector< [obstacle](#) > obstacles, [agent &agent](#))  
*agent escapes other agent in all agents*
- void [setAngle](#) ([pvector &p](#), float angle)  
*applies angle on vector*

### 5.19.1 Detailed Description

Definition at line 35 of file steeringBehavior.h.

### 5.19.2 Member Function Documentation

#### 5.19.2.1 align()

```
pvector steeringBehavior::align (
    vector< agent > boids,
    agent & agent )
```

agent velocity aligned with other agents, with specified distance

align behavior

##### Parameters

<i>agent</i>	agent to be aligned
<i>boids</i>	list of all the agents

##### Returns

force to be applied

Definition at line 117 of file steeringBehavior.cpp.

```
118 {
119     float neighborDist = 30; //TODO: magic number
120     pvector sum {0,0};
121     int count = 0;
122     for(auto it = boids.begin(); it < boids.end(); it++){
123         float d = (agent.position - (*it).position).magnitude();
124         if( (d > 0) && (d < neighborDist) ){
125             sum += (*it).velocity;
126             count++;
127         }
128     }
129     if(count > 0){
130         sum.div(count);
131         sum.normalize().mul(agent.maxSpeed);
132         agent.steering = sum - agent.velocity;
133         return agent.steering;
134     }
135     return pvector(0,0);
136 }
```

Here is the call graph for this function:

#### 5.19.2.2 avoid()

```
pvector steeringBehavior::avoid (
    vector< obstacle > obstacles,
    agent & agent )
```

agent escapes other agent in all agents

avoidin behavior

## Parameters

<i>agent</i>	agent that will avoid from obstacles
<i>obstacles</i>	list of all existing objects

## Returns

force to be applied

Definition at line 181 of file steeringBehavior.cpp.

```

182 {
183     float dynamic_length = agent.velocity.magnitude() / agent.maxSpeed;
184     pvector vel = agent.velocity;
185     vel.normalize().mul(dynamic_length);
186     pvector ahead = vel + agent.position;
187     vel.mul(6);
188     pvector ahead2 = vel + agent.position;
189     //view.drawPoint(point(ahead.x, ahead.y));
190     //view.drawPoint(point(ahead2.x, ahead2.y));
191
192     for(auto it = obstacles.begin(); it < obstacles.end(); it++){
193         float dist = (ahead - (*it).p).magnitude();
194         float dist2 = (ahead2 - (*it).p).magnitude();
195         if(dist < (*it).r + 2 || dist2 < (*it).r + 2){
196             pvector avoidance = ahead - (*it).p;
197             avoidance.normalize().mul(20);
198             /*a = point(avoidance.x, avoidance.y);
199             view.drawLine(agent.position, agent.position + a, color(0,1,0));*/
200             return avoidance;
201         }
202     }
203     return pvector(0,0);
204 }
```

Here is the call graph for this function:

## 5.19.2.3 cohesion()

```

pvector steeringBehavior::cohesion (
    vector< agent > boids,
    agent & agent )
```

agent goes at the center of other agents positions

cohesion behavior

## Parameters

<i>agent</i>	agent to go to center of other agents, with specified distance
<i>boids</i>	list of all the agents

## Returns

force to be applied

Definition at line 138 of file steeringBehavior.cpp.

```

139 {
140     float neighborDist = 20; //TODO: magic number
141     point sum {0,0};
142     int count = 0;
```

```

143     for(auto it = boids.begin(); it < boids.end(); it++){
144         float d = (agent.position - (*it).position).magnitude();
145         if( (d > 0) && (d < neighborDist) ){
146             sum = sum + (*it).position;
147             count++;
148         }
149     }
150     if(count > 0){
151         sum.div(count);
152         agent.targetPoint = sum;
153         return seek(agent);
154     }
155     return pvector(0,0);
156 }

```

Here is the call graph for this function:

#### 5.19.2.4 evade()

```

pvector steeringBehavior::evade (
    vector< agent > boids,
    agent & evader,
    graphics view )

```

agent escapes other agent in all agents

evading behavior

##### Parameters

<i>evader</i>	agent that will escape
<i>view</i>	used for debugging
<i>boids</i>	list of all the agents

##### Returns

force to be applied

Definition at line 45 of file steeringBehavior.cpp.

```

46 {
47     agent target;
48     for(auto it = boids.begin(); it < boids.end(); it++){
49         if((*it).name == "lion"){
50             target = *it;
51         }
52     }
53
54     point p = point(evader.position.x + 2, evader.position.y - 2);
55     view.drawText(evader.name, p);
56     p = point(target.position.x + 2, target.position.y - 2);
57     view.drawText(target.name, p);
58
59     pvector targetVel = target.velocity;
60     targetVel.mul(5); //TODO: magic number
61
62     point futurePos = target.position + targetVel;
63     view.drawPoint(futurePos);
64
65     pvector dist = evader.position - futurePos;
66     dist.normalize().mul( 1 / dist.magnitude() );
67
68     evader.targetPoint = evader.position + dist;
69     return flee(evader, view, futurePos);
70 }

```

Here is the call graph for this function:

### 5.19.2.5 flee()

```
pvector steeringBehavior::flee (
    agent & agent,
    graphics & view,
    point p )
```

agent flees from mouse

fleeing behavior

#### Parameters

<i>agent</i>	agent that will flee
<i>view</i>	used for debugging
<i>p</i>	point that agent flees

#### Returns

force to be applied

Definition at line 28 of file steeringBehavior.cpp.

```
29 {
30     pvector dist = agent.targetPoint - p;
31     view.drawPoint(agent.targetPoint);
32
33     if(dist.magnitude() < 15){ //TODO: magic number
34         agent.arrive = false;
35         agent.desiredVelocity = agent.position - p;
36     }
37     else{
38         agent.arrive = true;
39         agent.desiredVelocity = agent.targetPoint - agent.position;
40     }
41     agent.steering = agent.desiredVelocity - agent.velocity;
42     return agent.steering;
43 }
```

Here is the call graph for this function:

### 5.19.2.6 inFlowField()

```
pvector steeringBehavior::inFlowField (
    agent & agent,
    flowField & flow )
```

applies flow field at agents position

flow field behavior

#### Parameters

<i>agent</i>	unit to apply flow field
<i>flow</i>	flow field

**Returns**

force to be applied

Definition at line 236 of file steeringBehavior.cpp.

```
237 {
238     //pos_x, pos_y must be non negative integer
239     int pos_x = abs((int)agent.position.x) % WIDTH;
240     int pos_y = abs((int)agent.position.y) % HEIGHT;
241     //TODO: modification required for non uniform fields
242     return flow.getField(pos_x, pos_y);
243 }
```

Here is the call graph for this function:

**5.19.2.7 pursuit()**

```
pvector steeringBehavior::pursuit (
    vector< agent > boids,
    agent & pursuer,
    graphics view )
```

agent pursuits other agent in all agents

pursuing behavior

**Parameters**

<i>pursuer</i>	agent that will follow specified agent
<i>view</i>	used for debugging
<i>boids</i>	list of all the agents

**Returns**

force to be applied

Definition at line 72 of file steeringBehavior.cpp.

```
73 {
74     agent target;
75     for(auto it = boids.begin(); it < boids.end(); it++){
76         if((*it).name == "gazelle"){
77             target = *it;
78         }
79     }
80
81     point p = point(target.position.x + 2, target.position.y - 2);
82     view.drawText(target.name, p);
83     p = point(pursuer.position.x + 2, pursuer.position.y - 2);
84     view.drawText(pursuer.name, p);
85
86     float dist = (target.position - pursuer.position).magnitude();
87     float t = dist / target.maxSpeed;
88
89     pvector targetVel = target.velocity;
90     targetVel.mul(t);
91     point futurePos = target.position + targetVel;
92     pursuer.targetPoint = futurePos;
93     return seek(pursuer);
94 }
```

Here is the call graph for this function:



## 5.19.2.8 seek()

```
pvector steeringBehavior::seek (
    agent & agent )
```

agent goes to specified point

seek behavior

## Parameters

<i>agent</i>	agent that will go to specific target point
--------------	---

## Returns

force to be applied

Definition at line 206 of file steeringBehavior.cpp.

```
207 {
208     agent.desiredVelocity = agent.targetPoint - agent.position;
209     agent.steering = agent.desiredVelocity - agent.velocity;
210     return agent.steering;
211 }
```

## 5.19.2.9 separation()

```
pvector steeringBehavior::separation (
    vector< agent > agents,
    agent & agent )
```

agent stays away from other agents, with specified distance

separation behavior

## Parameters

<i>agent</i>	agent to be stayed away
<i>agents</i>	list of all the agents

## Returns

force to be applied

Definition at line 158 of file steeringBehavior.cpp.

```
159 {
160     float desiredSeparation = 5; //TODO: magic number
161     pvector sum = pvector(0,0);
162     int count = 0;
163     for(auto it = agents.begin(); it < agents.end(); it++){
164         float d = (agent.position - (*it).position).magnitude();
165         if( (d > 0) && (d < desiredSeparation) ){
166             pvector diff = agent.position - (*it).position;
167             diff.normalize().div(d);
168             sum = sum + diff;
```

```

169         count++;
170     }
171 }
172 if(count > 0){
173     sum.div(count);
174     sum.normalize().mul(agent.maxSpeed);
175     agent.steering = sum - agent.velocity;
176     return agent.steering;
177 }
178 return pvector(0,0);
179 }

```

Here is the call graph for this function:

#### 5.19.2.10 setAngle()

```

void steeringBehavior::setAngle (
    pvector & p,
    float angle )

```

applies angle on vector

rotates vector with angle

##### Parameters

<i>angle</i>	angle that will be set
<i>p</i>	vector that angle will be applied

Definition at line 22 of file steeringBehavior.cpp.

```

23 {
24     p.x = cos ( angle * PI / 180.0 );
25     p.y = sin ( angle * PI / 180.0 );
26 }

```

#### 5.19.2.11 stayInArea()

```

pvector steeringBehavior::stayInArea (
    agent & agent,
    int turnPoint )

```

returns force to apply if it is near the specified border

reflection behavior

##### Parameters

<i>agent</i>	unit to check
<i>turnpoint</i>	defines border to apply force

##### Returns

force to be applied

Definition at line 245 of file steeringBehavior.cpp.

```

246 {
247     if(agent.position.x >= turnPoint){
248         agent.desiredVelocity = pvector( -agent.maxSpeed, agent.velocity.y );
249         agent.steering = agent.desiredVelocity - agent.velocity;
250         return agent.steering;
251     }
252     else if(agent.position.x <= -turnPoint){
253         agent.desiredVelocity = pvector( agent.maxSpeed, agent.velocity.y );
254         agent.steering = agent.desiredVelocity - agent.velocity;
255         return agent.steering;
256     }
257     else if(agent.position.y >= turnPoint){
258         agent.desiredVelocity = pvector( agent.velocity.x, -agent.maxSpeed );
259         agent.steering = agent.desiredVelocity - agent.velocity;
260         return agent.steering;
261     }
262     else if(agent.position.y <= -turnPoint){
263         agent.desiredVelocity = pvector( agent.velocity.x, agent.maxSpeed );
264         agent.steering = agent.desiredVelocity - agent.velocity;
265         return agent.steering;
266     }
267     return pvector(0,0);
268 }
```

### 5.19.2.12 stayInPath()

```

pvector steeringBehavior::stayInPath (
    agent & agent,
    path & path,
    graphics view )
```

agent follows given path

multi segment path following behavior

#### Parameters

<i>agent</i>	agent to follow the pathk
<i>path</i>	path to follow
<i>view</i>	used for debugging

#### Returns

force to be applied

Definition at line 213 of file steeringBehavior.cpp.

```

214 {
215     float worldRecord = 1000000; //TODO: magic number
216     point normalPoint, predictedPos, start, end;
217     pvector distance;
218     for(auto it = path.points.begin(); it < path.points.end()-1; it++){
219         start = point ((*it).x, (*it).y);
220         end = point ((*it+1).x, (*it+1).y);
221         predictedPos = agent.position + agent.velocity;
222         normalPoint.getNormalPoint(predictedPos, start, end);
223         if (normalPoint.x < start.x || normalPoint.x > end.x){
224             normalPoint = end;
225         }
226         distance = predictedPos - normalPoint;
227         if (distance.magnitude() < worldRecord){
228             worldRecord = distance.magnitude();
229             agent.targetPoint = end;
230         }
231         view.drawPoint(agent.targetPoint);
232     }
```

```

233     return seek(agent);
234 }

```

Here is the call graph for this function:

### 5.19.2.13 wander()

```

pvector steeringBehavior::wander (
    agent & agent )

```

agent that will wander

wandering behavior

#### Parameters

<i>agent</i>	agent to be stayed away
--------------	-------------------------

#### Returns

force to be applied

Definition at line 96 of file steeringBehavior.cpp.

```

97 {
98     pvector circleCenter = agent.velocity;
99     circleCenter.normalize().mul(CIRCLE_DISTANCE + CIRCLE_RADIUS);
100
101     int wanderAngle = (rand() % 360);
102     pvector displacement {0, 1};
103     setAngle(displacement, wanderAngle);
104     displacement.mul(CIRCLE_RADIUS);
105
106     agent.desiredVelocity = displacement + circleCenter;
107     agent.steering = agent.desiredVelocity - agent.velocity;
108
109     //move it to the center when it is out of screen
110     if(agent.position.x > WIDTH || agent.position.x < -WIDTH ||
111        agent.position.y > HEIGHT || agent.position.y < -HEIGHT)
112         agent.position = point(0,0);
113
114     return agent.steering;
115 }

```

Here is the call graph for this function:

The documentation for this class was generated from the following files:

- include/steeringBehavior.h
- src/steeringBehavior.cpp

## 5.20 wander Class Reference

```
#include <wander.h>
```

Inheritance diagram for wander:

Collaboration diagram for wander:

## Public Member Functions

- `wander ()`  
*default constructor.*

## Static Public Member Functions

- static void `loop ()`  
*loop function for evading scenario*

## Additional Inherited Members

### 5.20.1 Detailed Description

Definition at line 14 of file wander.h.

### 5.20.2 Constructor & Destructor Documentation

#### 5.20.2.1 wander()

```
wander::wander ( )
```

default constructor.

Creates scenario

Definition at line 24 of file wander.cpp.

```
25 {  
26     int agentCount = 30;  
27     float maxForce = 0.3;  
28     float maxSpeed = 0.6;  
29  
30     name = "wandering objects";  
31     createAgent(RANDOM, &agentCount, &maxForce, &maxSpeed);  
32     callback = reinterpret_cast<void(*)()> ( (void *)(&loop) );  
33 }
```

### 5.20.3 Member Function Documentation

### 5.20.3.1 loop()

```
void wander::loop ( ) [static]
```

loop function for evading scenario

wandering loop function

#### Note

opengl callback forces that function to be static

Definition at line 15 of file wander.cpp.

```
16 {  
17     for(auto it = agents.begin(); it < agents.end(); it++){  
18         (*it).force = behavior.wander(*it);  
19     }  
20  
21     refresh();  
22 }
```

The documentation for this class was generated from the following files:

- include/wander.h
- src/wander.cpp

## 5.21 windy Class Reference

```
#include <windy.h>
```

Inheritance diagram for windy:

Collaboration diagram for windy:

### Public Member Functions

- windy ()  
*default constructor.*

### Static Public Member Functions

- static void loop ()  
*loop function for evading scenario*

### Static Public Attributes

- static flowField flow  
*flow field instance*

## Additional Inherited Members

### 5.21.1 Detailed Description

Definition at line 15 of file windy.h.

### 5.21.2 Constructor & Destructor Documentation

#### 5.21.2.1 windy()

```
windy::windy ( )
```

default constructor.

Creates scenario

Definition at line 29 of file windy.cpp.

```
30 {
31     int agentCount = 30;
32     float maxForce = 0.3;
33     float maxSpeed = 0.6;
34
35     name = "flow field";
36     createAgent(RANDOM, &agentCount, &maxForce, &maxSpeed);
37     callback = reinterpret_cast<void(*)()> ( (void *)(&loop) );
38 }
```

### 5.21.3 Member Function Documentation

#### 5.21.3.1 loop()

```
void windy::loop ( ) [static]
```

loop function for evading scenario

windy loop function

#### Note

opengl callback forces that function to be static

Definition at line 17 of file windy.cpp.

```
18 {
19     for(auto it = agents.begin(); it < agents.end(); it++){
20         flow = flowField(pvector(GRAVITY));
21         (*it).force = behavior.inFlowField(*it, flow);
22
23         flow = flowField(pvector(WIND_WEST));
24         (*it).force += behavior.inFlowField(*it, flow);
25     }
26     refresh();
27 }
```

## 5.21.4 Member Data Documentation

### 5.21.4.1 flow

```
flowField windy::flow [static]
```

flow field instance

#### Note

opengl callback forces that function to be static

Definition at line 34 of file windy.h.

The documentation for this class was generated from the following files:

- include/[windy.h](#)
- src/[windy.cpp](#)



## Chapter 6

# File Documentation

### 6.1 include/agent.h File Reference

agent class defines all agent specifications

```
#include "point.h"
#include "color.h"
#include "flowField.h"
#include <vector>
#include <string>
Include dependency graph for agent.h:
```

### 6.2 include/color.h File Reference

color class used for agent, path, wall etc. color

```
#include <vector>
Include dependency graph for color.h: This graph shows which files directly or indirectly include this file:
```

#### Classes

- class `color`

#### Enumerations

- enum `num` {  
    `BLACK` =0, `BLUE`, `GREEN`, `CYAN`,  
    `RED`, `MAGENDA`, `YELLOW`, `WHITE` }  
    *used to get color from colors vector*

## 6.2.1 Detailed Description

color class used for agent, path, wall etc. color

### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

### Date

13.05.2021

## 6.2.2 Enumeration Type Documentation

### 6.2.2.1 num

enum [num](#)

used to get color from colors vector

color names for fundamental colors

#### Enumerator

BLACK	
BLUE	
GREEN	
CYAN	
RED	
MAGENDA	
YELLOW	
WHITE	

Definition at line 18 of file color.h.

```
18 { BLACK=0, BLUE, GREEN, CYAN, RED, MAGENDA, YELLOW, WHITE };
```

## 6.3 include/evade.h File Reference

evade class inherited from scenario class

```
#include "scenario.h"  
#include <vector>
```

Include dependency graph for evade.h: This graph shows which files directly or indirectly include this file:

### Classes

- class [evade](#)

### 6.3.1 Detailed Description

evade class inherited from scenario class

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

15.05.2021

## 6.4 include/flee.h File Reference

agents flee from mouse scenario

```
#include "scenario.h"
#include <vector>
```

Include dependency graph for flee.h: This graph shows which files directly or indirectly include this file:

### Classes

- class [flee](#)

### 6.4.1 Detailed Description

agents flee from mouse scenario

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

15.05.2021

## 6.5 include/flock.h File Reference

flocking agents scenario

```
#include "scenario.h"
#include <vector>
```

Include dependency graph for flock.h: This graph shows which files directly or indirectly include this file:

### Classes

- class [flock](#)

### 6.5.1 Detailed Description

flocking agents scenario

Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

Date

15.05.2021

## 6.6 include/flowField.h File Reference

[flowField](#) class, screen can be filled with a force for each pixel

```
#include "pvector.h"
```

Include dependency graph for flowField.h: This graph shows which files directly or indirectly include this file:

### Classes

- class [flowField](#)

### Macros

- #define [FIELD\\_WIDTH](#) 34
- #define [FIELD\\_HEIGHT](#) 34
- #define [WIND\\_WEST](#) 0.1, 0.0
- #define [GRAVITY](#) 0.0, -0.1

### 6.6.1 Detailed Description

[flowField](#) class, screen can be filled with a force for each pixel

Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

Date

13.05.2021

### 6.6.2 Macro Definition Documentation

### 6.6.2.1 FIELD\_HEIGHT

```
#define FIELD_HEIGHT 34
```

Definition at line 13 of file flowField.h.

### 6.6.2.2 FIELD\_WIDTH

```
#define FIELD_WIDTH 34
```

Definition at line 12 of file flowField.h.

### 6.6.2.3 GRAVITY

```
#define GRAVITY 0.0, -0.1
```

Definition at line 16 of file flowField.h.

### 6.6.2.4 WIND\_WEST

```
#define WIND_WEST 0.1, 0.0
```

Definition at line 15 of file flowField.h.

## 6.7 include/graphics.h File Reference

graphics class, drives OpenGL

```
#include "agent.h"  
#include "path.h"
```

Include dependency graph for graphics.h: This graph shows which files directly or indirectly include this file:

### Classes

- class [graphics](#)

### Macros

- #define [WIDTH](#) 34
- #define [HEIGHT](#) 34
- #define [ESC](#) 27
- #define [PI](#) 3.14159265

### 6.7.1 Detailed Description

graphics class, drives openGL

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

15.05.2021

### 6.7.2 Macro Definition Documentation

#### 6.7.2.1 ESC

```
#define ESC 27
```

Definition at line 16 of file graphics.h.

#### 6.7.2.2 HEIGHT

```
#define HEIGHT 34
```

Definition at line 14 of file graphics.h.

#### 6.7.2.3 PI

```
#define PI 3.14159265
```

Definition at line 17 of file graphics.h.

#### 6.7.2.4 WIDTH

```
#define WIDTH 34
```

Definition at line 13 of file graphics.h.

## 6.8 include/mouseFollower.h File Reference

agents follow mouse scenario

```
#include "scenario.h"  
#include <vector>
```

Include dependency graph for mouseFollower.h: This graph shows which files directly or indirectly include this file:

### Classes

- class [mouseFollower](#)

#### 6.8.1 Detailed Description

agents follow mouse scenario

##### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

##### Date

15.05.2021

## 6.9 include/obstacle.h File Reference

circular obstacles for agent avoidance behaviors

```
#include "point.h"
```

Include dependency graph for obstacle.h: This graph shows which files directly or indirectly include this file:

### Classes

- class [obstacle](#)

#### 6.9.1 Detailed Description

circular obstacles for agent avoidance behaviors

##### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

##### Date

12.05.2021

## 6.10 include/obstacleAvoidance.h File Reference

agents avoid from obstacles scenario

```
#include "scenario.h"
#include "obstacle.h"
#include <vector>
```

Include dependency graph for obstacleAvoidance.h: This graph shows which files directly or indirectly include this file:

### Classes

- class [obstacleAvoidance](#)

### 6.10.1 Detailed Description

agents avoid from obstacles scenario

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

15.05.2021

## 6.11 include/path.h File Reference

path class used for path following steering behaviors.

```
#include "point.h"
#include <vector>
```

Include dependency graph for path.h: This graph shows which files directly or indirectly include this file:

### Classes

- class [path](#)

### 6.11.1 Detailed Description

path class used for path following steering behaviors.

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

12.05.2021



## 6.12 include/pathFollower.h File Reference

path following scenario

```
#include "scenario.h"  
#include <vector>
```

Include dependency graph for pathFollower.h: This graph shows which files directly or indirectly include this file:

### Classes

- class [pathFollower](#)

#### 6.12.1 Detailed Description

path following scenario

##### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

##### Date

15.05.2021

## 6.13 include/point.h File Reference

point class used for point operations

```
#include "pvector.h"  
#include <string>
```

Include dependency graph for point.h: This graph shows which files directly or indirectly include this file:

### Classes

- class [point](#)

#### 6.13.1 Detailed Description

point class used for point operations

##### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

##### Date

15.05.2021

## 6.14 include/prison.h File Reference

agents cant escape from field scenario

```
#include "scenario.h"  
#include <vector>
```

Include dependency graph for prison.h: This graph shows which files directly or indirectly include this file:

### Classes

- class [prison](#)

### 6.14.1 Detailed Description

agents cant escape from field scenario

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

15.05.2021

## 6.15 include/pursuit.h File Reference

one agent pursue other one scenario

```
#include "scenario.h"  
#include <vector>
```

Include dependency graph for pursuit.h: This graph shows which files directly or indirectly include this file:

### Classes

- class [pursuit](#)

### 6.15.1 Detailed Description

one agent pursue other one scenario

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

15.05.2021

## 6.16 include/pvector.h File Reference

pvector class used for 2D vector operations

```
#include <string>
```

Include dependency graph for pvector.h: This graph shows which files directly or indirectly include this file:

### Classes

- class [pvector](#)

### Macros

- #define [PI](#) 3.14159265

#### 6.16.1 Detailed Description

pvector class used for 2D vector operations

##### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

##### Date

15.05.2021

#### 6.16.2 Macro Definition Documentation

##### 6.16.2.1 PI

```
#define PI 3.14159265
```

Definition at line 11 of file pvector.h.

## 6.17 include/random.h File Reference

utility class for random operations

This graph shows which files directly or indirectly include this file:

## Classes

- class [random](#)

### 6.17.1 Detailed Description

utility class for random operations

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

15.05.2021

## 6.18 include/scenario.h File Reference

base class for all scenarios

```
#include "agent.h"
#include "graphics.h"
#include "steeringBehavior.h"
#include <vector>
```

Include dependency graph for scenario.h: This graph shows which files directly or indirectly include this file:

## Classes

- class [scenario](#)

## Enumerations

- enum [types](#) { [RANDOM](#) =0, [STATIC](#), [TROOP](#) }

### 6.18.1 Detailed Description

base class for all scenarios

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

15.05.2021

### 6.18.2 Enumeration Type Documentation

#### 6.18.2.1 types

enum [types](#)

### Enumerator

RANDOM	
STATIC	
TROOP	

Definition at line 17 of file scenario.h.

```
17 { RANDOM=0, STATIC, TROOP };
```

## 6.19 include/steeringBehavior.h File Reference

functions for autonomous steering behaviors

```
#include "flowField.h"
#include <vector>
#include "graphics.h"
#include "obstacle.h"
```

Include dependency graph for steeringBehavior.h: This graph shows which files directly or indirectly include this file:

### Classes

- class [steeringBehavior](#)

### Macros

- #define [CIRCLE\\_DISTANCE](#) 0.1
- #define [CIRCLE\\_RADIUS](#) 0.4
- #define [FOLLOW\\_MOUSE](#) 1
- #define [STAY\\_IN\\_FIELD](#) 2
- #define [IN\\_FLOW\\_FIELD](#) 3
- #define [AVOID\\_OBSTACLE](#) 4
- #define [STAY\\_IN\\_PATH](#) 5
- #define [FLOCK](#) 6
- #define [WANDER](#) 7
- #define [FLEE](#) 8
- #define [PURSUIT](#) 9
- #define [EVADE](#) 10

### 6.19.1 Detailed Description

functions for autonomous steering behaviors

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

15.05.2021

## 6.19.2 Macro Definition Documentation

### 6.19.2.1 AVOID\_OBSTACLE

```
#define AVOID_OBSTACLE 4
```

Definition at line 21 of file steeringBehavior.h.

### 6.19.2.2 CIRCLE\_DISTANCE

```
#define CIRCLE_DISTANCE 0.1
```

Definition at line 15 of file steeringBehavior.h.

### 6.19.2.3 CIRCLE\_RADIUS

```
#define CIRCLE_RADIUS 0.4
```

Definition at line 16 of file steeringBehavior.h.

### 6.19.2.4 EVADE

```
#define EVADE 10
```

Definition at line 27 of file steeringBehavior.h.

### 6.19.2.5 FLEE

```
#define FLEE 8
```

Definition at line 25 of file steeringBehavior.h.

### 6.19.2.6 FLOCK

```
#define FLOCK 6
```

Definition at line 23 of file steeringBehavior.h.

### 6.19.2.7 FOLLOW\_MOUSE

```
#define FOLLOW_MOUSE 1
```

Definition at line 18 of file steeringBehavior.h.

### 6.19.2.8 IN\_FLOW\_FIELD

```
#define IN_FLOW_FIELD 3
```

Definition at line 20 of file steeringBehavior.h.

### 6.19.2.9 PURSUIT

```
#define PURSUIT 9
```

Definition at line 26 of file steeringBehavior.h.

### 6.19.2.10 STAY\_IN\_FIELD

```
#define STAY_IN_FIELD 2
```

Definition at line 19 of file steeringBehavior.h.

### 6.19.2.11 STAY\_IN\_PATH

```
#define STAY_IN_PATH 5
```

Definition at line 22 of file steeringBehavior.h.

### 6.19.2.12 WANDER

```
#define WANDER 7
```

Definition at line 24 of file steeringBehavior.h.

## 6.20 include/wander.h File Reference

random wandering agents scenario

```
#include "scenario.h"  
#include <vector>
```

Include dependency graph for wander.h: This graph shows which files directly or indirectly include this file:

### Classes

- class [wander](#)

### 6.20.1 Detailed Description

random wandering agents scenario

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

15.05.2021

## 6.21 include/windy.h File Reference

windy air scenario

```
#include "scenario.h"  
#include "flowField.h"  
#include <vector>
```

Include dependency graph for windy.h: This graph shows which files directly or indirectly include this file:

### Classes

- class [windy](#)



### 6.21.1 Detailed Description

windy air scenario

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

15.05.2021

## 6.22 main.cpp File Reference

client code

```
#include <iostream>
#include "mouseFollower.h"
#include "prison.h"
#include "windy.h"
#include "wander.h"
#include "pursuit.h"
#include "flee.h"
#include "scenario.h"
#include "evade.h"
#include "flock.h"
#include "pathFollower.h"
#include "obstacleAvoidance.h"
Include dependency graph for main.cpp:
```

### Functions

- void [menu](#) ()  
*displays menu*
- int [main](#) (int argc, char \*\*argv)  
*main routine*

### Variables

- int [mode](#)  
*specifies user selected scenario*

### 6.22.1 Detailed Description

client code

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

15.05.2021

## 6.22.2 Function Documentation

### 6.22.2.1 main()

```
int main (
    int argc,
    char ** argv )
```

main routine

Definition at line 48 of file main.cpp.

```
48     {
49         menu();
50
51         scenario* sc;
52
53         if(mode == FOLLOW_MOUSE) {
54             *sc = mouseFollower();
55         }
56         else if(mode == STAY_IN_FIELD) {
57             *sc = prison();
58         }
59         else if(mode == IN_FLOW_FIELD) {
60             *sc = windy();
61         }
62         else if(mode == WANDER) {
63             *sc = wander();
64         }
65         else if(mode == PURSUIT) {
66             *sc = pursuit();
67         }
68         else if(mode == FLEE) {
69             *sc = flee();
70         }
71         else if(mode == EVADE) {
72             *sc = evade();
73         }
74         else if(mode == FLOCK) {
75             *sc = flock();
76         }
77         else if(mode == STAY_IN_PATH) {
78             *sc = pathFollower();
79         }
80         else if(mode == AVOID_OBSTACLE) {
81             *sc = obstacleAvoidance();
82         }
83
84         sc->initGL(&argc, argv);
85
86         return 0;
87     }
```

Here is the call graph for this function:

### 6.22.2.2 menu()

```
void menu ( )
```

displays menu

Definition at line 31 of file main.cpp.

```
31     {
32         cout << "Follow Mouse      : 1" << endl;
33         cout << "Stay in Field      : 2" << endl;
34         cout << "In Flow Field     : 3" << endl;
35         cout << "OBSTACLE AVOIDANCE : 4" << endl;
36         cout << "Stay in Path      : 5" << endl;
37         cout << "FLOCK            : 6" << endl;
38         cout << "WANDER           : 7" << endl;
39         cout << "FLEE            : 8" << endl;
40         cout << "PURSUIT          : 9" << endl;
41         cout << "EVADE           : 10" << endl;
42         cin >> mode;
43     }
```

Here is the caller graph for this function:

### 6.22.3 Variable Documentation

#### 6.22.3.1 mode

```
int mode
```

specifies user selected scenario

Definition at line 26 of file main.cpp.

## 6.23 README.md File Reference

## 6.24 src/agent.cpp File Reference

implementation of the agent class

```
#include "agent.h"  
#include "pvector.h"  
#include "graphics.h"  
#include "random.h"  
#include <iostream>  
Include dependency graph for agent.cpp:
```

### 6.24.1 Detailed Description

implementation of the agent class

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

14.05.2021

## 6.25 src/color.cpp File Reference

color class implementation

```
#include "color.h"  
#include <vector>  
Include dependency graph for color.cpp:
```

### 6.25.1 Detailed Description

color class implementation

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

13.05.2021

## 6.26 src/evade.cpp File Reference

evade class implementation

```
#include "scenario.h"
#include "evade.h"
#include <iostream>
#include <GL/glut.h>
Include dependency graph for evade.cpp:
```

### 6.26.1 Detailed Description

evade class implementation

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

15.05.2021

## 6.27 src/flee.cpp File Reference

flee class implementation

```
#include "scenario.h"
#include "flee.h"
#include <iostream>
#include <GL/glut.h>
Include dependency graph for flee.cpp:
```

### 6.27.1 Detailed Description

flee class implementation

Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

Date

15.05.2021

## 6.28 src/flock.cpp File Reference

flock class implementation

```
#include "scenario.h"
#include "flock.h"
#include <iostream>
#include <GL/glut.h>
Include dependency graph for flock.cpp:
```

### 6.28.1 Detailed Description

flock class implementation

Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

Date

15.05.2021

## 6.29 src/flowField.cpp File Reference

[flowField](#) class implementation

```
#include "flowField.h"
Include dependency graph for flowField.cpp:
```

### 6.29.1 Detailed Description

[flowField](#) class implementation

Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

Date

13.05.2021

## 6.30 src/graphics.cpp File Reference

graphics class implementation

```
#include "graphics.h"
#include <GL/glut.h>
#include <iostream>
#include "math.h"
Include dependency graph for graphics.cpp:
```

### 6.30.1 Detailed Description

graphics class implementation

Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

Date

15.05.2021

## 6.31 src/mouseFollower.cpp File Reference

[mouseFollower](#) class implementation

```
#include "scenario.h"
#include "mouseFollower.h"
#include <iostream>
#include <GL/glut.h>
Include dependency graph for mouseFollower.cpp:
```

### 6.31.1 Detailed Description

[mouseFollower](#) class implementation

Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

Date

15.05.2021

## 6.32 src/obstacle.cpp File Reference

obstacle class implementation

```
#include "obstacle.h"
#include "graphics.h"
#include "point.h"
#include <vector>
Include dependency graph for obstacle.cpp:
```

### 6.32.1 Detailed Description

obstacle class implementation

Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

Date

12.05.2021

## 6.33 src/obstacleAvoidance.cpp File Reference

[obstacleAvoidance](#) class implementation

```
#include "scenario.h"
#include "obstacleAvoidance.h"
#include <iostream>
#include <GL/glut.h>
Include dependency graph for obstacleAvoidance.cpp:
```

### 6.33.1 Detailed Description

[obstacleAvoidance](#) class implementation

Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

Date

15.05.2021

## 6.34 src/path.cpp File Reference

path class implementation

```
#include "path.h"
#include "graphics.h"
Include dependency graph for path.cpp:
```

### 6.34.1 Detailed Description

path class implementation

Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

Date

12.05.2021

## 6.35 src/pathFollower.cpp File Reference

[pathFollower](#) class implementation

```
#include "scenario.h"
#include "pathFollower.h"
#include <iostream>
#include <GL/glut.h>
Include dependency graph for pathFollower.cpp:
```

### 6.35.1 Detailed Description

[pathFollower](#) class implementation

Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

Date

15.05.2021

## 6.36 src/point.cpp File Reference

point class implementation file

```
#include "point.h"
#include "pvector.h"
#include <string>
#include <iostream>
Include dependency graph for point.cpp:
```



### 6.36.1 Detailed Description

point class implementation file

Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

Date

15.05.2021

## 6.37 src/prison.cpp File Reference

prison class implementation

```
#include "scenario.h"
#include "prison.h"
#include <iostream>
#include <GL/glut.h>
Include dependency graph for prison.cpp:
```

### Macros

- #define [WALL](#) 30
- #define [DISTANCE](#) 2

### 6.37.1 Detailed Description

prison class implementation

Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

Date

15.05.2021

### 6.37.2 Macro Definition Documentation

#### 6.37.2.1 DISTANCE

```
#define DISTANCE 2
```

Definition at line 14 of file prison.cpp.

### 6.37.2.2 WALL

```
#define WALL 30
```

Definition at line 13 of file prison.cpp.

## 6.38 src/pursuit.cpp File Reference

prison class implementation

```
#include "scenario.h"  
#include "pursuit.h"  
#include <iostream>  
#include <GL/glut.h>
```

Include dependency graph for pursuit.cpp:

### 6.38.1 Detailed Description

prison class implementation

Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

Date

15.05.2021

## 6.39 src/pvector.cpp File Reference

pvector class implementation

```
#include "pvector.h"  
#include "math.h"  
#include "point.h"  
#include <iostream>  
#include <string>
```

Include dependency graph for pvector.cpp:

### 6.39.1 Detailed Description

pvector class implementation

Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

Date

15.05.2021

## 6.40 src/random.cpp File Reference

utility class for random operations

```
#include "random.h"
#include <stdlib.h>
#include <iostream>
Include dependency graph for random.cpp:
```

### 6.40.1 Detailed Description

utility class for random operations

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

15.05.2021

## 6.41 src/scenario.cpp File Reference

scenario base class implementation

```
#include "scenario.h"
#include "random.h"
#include <iostream>
Include dependency graph for scenario.cpp:
```

### Macros

- #define [MAX\\_NUMBER\\_OF\\_AGENTS](#) 50

### 6.41.1 Detailed Description

scenario base class implementation

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

15.05.2021

## 6.41.2 Macro Definition Documentation

### 6.41.2.1 MAX\_NUMBER\_OF\_AGENTS

```
#define MAX_NUMBER_OF_AGENTS 50
```

Definition at line 12 of file scenario.cpp.

## 6.42 src/steeringBehavior.cpp File Reference

implementation of autonomous steering behaviors

```
#include "steeringBehavior.h"
#include "pvector.h"
#include "agent.h"
#include "path.h"
#include "point.h"
#include <vector>
#include "graphics.h"
#include "math.h"
#include "obstacle.h"
#include <iostream>
#include <GL/glut.h>
```

Include dependency graph for steeringBehavior.cpp:

### 6.42.1 Detailed Description

implementation of autonomous steering behaviors

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

15.05.2021

## 6.43 src/wander.cpp File Reference

wander class implementation

```
#include "scenario.h"
#include "wander.h"
#include <iostream>
#include <GL/glut.h>
```

Include dependency graph for wander.cpp:

### 6.43.1 Detailed Description

wander class implementation

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

15.05.2021

## 6.44 src/windy.cpp File Reference

windy class implementation

```
#include "scenario.h"
#include "windy.h"
#include <iostream>
#include <GL/glut.h>
Include dependency graph for windy.cpp:
```

### 6.44.1 Detailed Description

windy class implementation

#### Author

Mehmet Rıza Öz - [mehmetrizaoz@gmail.com](mailto:mehmetrizaoz@gmail.com)

#### Date

15.05.2021

## 6.45 test/test\_suites.cpp File Reference

```
#include <boost/test/included/unit_test.hpp>
#include "../include/pvector.h"
#include "../include/point.h"
#include <iostream>
Include dependency graph for test_suites.cpp:
```

### Macros

- `#define BOOST_TEST_MODULE test_suites`

## Functions

- [BOOST\\_AUTO\\_TEST\\_CASE](#) (s1t1)
- [BOOST\\_AUTO\\_TEST\\_CASE](#) (s1t2)
- [BOOST\\_AUTO\\_TEST\\_CASE](#) (s1t3)
- [BOOST\\_AUTO\\_TEST\\_CASE](#) (s1t4)
- [BOOST\\_AUTO\\_TEST\\_CASE](#) (s1t5)
- [BOOST\\_AUTO\\_TEST\\_CASE](#) (s1t6)
- [BOOST\\_AUTO\\_TEST\\_CASE](#) (s1t7)
- [BOOST\\_AUTO\\_TEST\\_CASE](#) (s1t8)
- [BOOST\\_AUTO\\_TEST\\_CASE](#) (s1t9)
- [BOOST\\_AUTO\\_TEST\\_CASE](#) (s2t1)
- [BOOST\\_AUTO\\_TEST\\_CASE](#) (s2t2)
- [BOOST\\_AUTO\\_TEST\\_CASE](#) (s2t3)

### 6.45.1 Macro Definition Documentation

#### 6.45.1.1 BOOST\_TEST\_MODULE

```
#define BOOST_TEST_MODULE test_suites
```

Definition at line 1 of file test\_suites.cpp.

### 6.45.2 Function Documentation

#### 6.45.2.1 BOOST\_AUTO\_TEST\_CASE() [1/12]

```
BOOST_AUTO_TEST_CASE (
    s1t1 )
```

Definition at line 12 of file test\_suites.cpp.

```
13 {
14     pvector p1 = pvector(0, 4);
15     pvector p2 = pvector(3, 0);
16     pvector p3 = p1 + p2;
17     BOOST_CHECK(p3.magnitude() == 5);
18 }
```

Here is the call graph for this function:

#### 6.45.2.2 BOOST\_AUTO\_TEST\_CASE() [2/12]

```
BOOST_AUTO_TEST_CASE (
    s1t2 )
```

Definition at line 20 of file test\_suites.cpp.

```
21 {
22     pvector p1 = pvector(1, 1);
23     p1.mul(3);
24     pvector p2 = pvector(3, 3);
25     BOOST_CHECK(p1 == p2);
26 }
```

Here is the call graph for this function:

### 6.45.2.3 BOOST\_AUTO\_TEST\_CASE() [3/12]

```
BOOST_AUTO_TEST_CASE (
    slt3 )
```

Definition at line 28 of file test\_suites.cpp.

```
29 {
30     pvector p1 = pvector(5, 5);
31     p1.div(5);
32     pvector p2 = pvector(1, 1);
33     BOOST_CHECK(p1 == p2);
34 }
```

Here is the call graph for this function:

### 6.45.2.4 BOOST\_AUTO\_TEST\_CASE() [4/12]

```
BOOST_AUTO_TEST_CASE (
    slt4 )
```

Definition at line 36 of file test\_suites.cpp.

```
37 {
38     pvector p1 = pvector(1, 4);
39     pvector p2 = pvector(3, 2);
40     float dotProduct = p1.dotProduct(p2);
41     BOOST_CHECK(dotProduct == 11);
42 }
```

Here is the call graph for this function:

### 6.45.2.5 BOOST\_AUTO\_TEST\_CASE() [5/12]

```
BOOST_AUTO_TEST_CASE (
    slt5 )
```

Definition at line 44 of file test\_suites.cpp.

```
45 {
46     pvector p1 = pvector(10, 10);
47     pvector p2 = pvector(0, 10);
48     float angle = p1.angleBetween(p2);
49     BOOST_CHECK(angle == 45);
50 }
```

Here is the call graph for this function:

### 6.45.2.6 BOOST\_AUTO\_TEST\_CASE() [6/12]

```
BOOST_AUTO_TEST_CASE (
    slt6 )
```

Definition at line 52 of file test\_suites.cpp.

```
53 {
54     pvector p1 = pvector(3, 4);
55     float angle = p1.getAngle();
56     BOOST_CHECK(angle < 53.2 && angle > 52.8);
57 }
```

Here is the call graph for this function:

**6.45.2.7 BOOST\_AUTO\_TEST\_CASE()** [7/12]

```
BOOST_AUTO_TEST_CASE (
    slt7 )
```

Definition at line 59 of file test\_suites.cpp.

```
60 {
61     pvector p1 = pvector(2, 2);
62     p1.normalize();
63     float range = 0.01;
64     BOOST_CHECK_CLOSE_FRACTION(0.707, p1.x, range);
65     BOOST_CHECK_CLOSE_FRACTION(0.707, p1.y, range);
66 }
```

Here is the call graph for this function:

**6.45.2.8 BOOST\_AUTO\_TEST\_CASE()** [8/12]

```
BOOST_AUTO_TEST_CASE (
    slt8 )
```

Definition at line 68 of file test\_suites.cpp.

```
69 {
70     pvector p1 = pvector(2, 2);
71     p1.limit(3);
72     float range = 0.01;
73     BOOST_CHECK_CLOSE_FRACTION(2.12, p1.x, range);
74     BOOST_CHECK_CLOSE_FRACTION(2.12, p1.y, range);
75 }
```

Here is the call graph for this function:

**6.45.2.9 BOOST\_AUTO\_TEST\_CASE()** [9/12]

```
BOOST_AUTO_TEST_CASE (
    slt9 )
```

Definition at line 77 of file test\_suites.cpp.

```
78 {
79     pvector p1 = pvector(1, 1);
80     p1 += pvector(1, 1);
81     BOOST_CHECK(p1 == pvector(2, 2));
82     p1 = pvector(1, 1) + pvector(3, 3);
83     BOOST_CHECK(p1 == pvector(4, 4));
84     p1 = pvector(4, 1) - pvector(3, 3);
85     BOOST_CHECK(p1 == pvector(1, -2));
86     p1 = pvector(4, 1) - point(3, 3);
87     BOOST_CHECK(p1 == pvector(1, -2));
88     p1 = pvector(4, 1) + point(3, 3);
89     BOOST_CHECK(p1 == pvector(7, 4));
90 }
```

Here is the call graph for this function:

**6.45.2.10 BOOST\_AUTO\_TEST\_CASE()** [10/12]

```
BOOST_AUTO_TEST_CASE (
    s2t1 )
```

Definition at line 96 of file test\_suites.cpp.

```
97 {
98     point p1 = point(1, 1);
99     p1.mul(3);
100     point p2 = point(3, 3);
101     BOOST_CHECK(p1 == p2);
102 }
```

Here is the call graph for this function:



**6.45.2.11 BOOST\_AUTO\_TEST\_CASE()** [11/12]

```
BOOST_AUTO_TEST_CASE (
    s2t2 )
```

Definition at line 104 of file test\_suites.cpp.

```
105 {
106     point p1 = point(4, 4);
107     p1.div(4);
108     point p2 = point(1, 1);
109     BOOST_CHECK(p1 == p2);
110 }
```

Here is the call graph for this function:

**6.45.2.12 BOOST\_AUTO\_TEST\_CASE()** [12/12]

```
BOOST_AUTO_TEST_CASE (
    s2t3 )
```

Definition at line 112 of file test\_suites.cpp.

```
113 {
114     point p1 = point(1,1) + point(3,3);
115     BOOST_CHECK(p1 == point(4,4));
116     p1 = point(1,1) + pvector(3,3);
117     BOOST_CHECK(p1 == point(4,4));
118     pvector p2 = point(1,1) - point(3,3);
119     BOOST_CHECK(p2 == pvector(-2,-2));
120 }
```

Here is the call graph for this function:



# Index

- ~agent
  - agent, [11](#)
- acceleration
  - agent, [12](#)
- add
  - pvector, [58](#)
- addPoint
  - path, [43](#)
- agent, [9](#)
  - ~agent, [11](#)
  - acceleration, [12](#)
  - agent, [10](#)
  - arrive, [13](#)
  - desiredVelocity, [13](#)
  - fillColor, [13](#)
  - force, [13](#)
  - id, [14](#)
  - mass, [14](#)
  - maxForce, [14](#)
  - maxSpeed, [14](#)
  - name, [15](#)
  - position, [15](#)
  - r, [15](#)
  - setFeatures, [11](#)
  - steering, [15](#)
  - targetPoint, [16](#)
  - updatePosition, [12](#)
  - velocity, [16](#)
- agents
  - scenario, [69](#)
- align
  - steeringBehavior, [72](#)
- angleBetween
  - pvector, [58](#)
- arrive
  - agent, [13](#)
- avoid
  - steeringBehavior, [72](#)
- AVOID\_OBSTACLE
  - steeringBehavior.h, [98](#)
- B
  - color, [19](#)
- behavior
  - scenario, [69](#)
- BLACK
  - color.h, [86](#)
- BLUE
  - color.h, [86](#)
- BOOST\_AUTO\_TEST\_CASE
  - test\_suites.cpp, [114–117](#)
- BOOST\_TEST\_MODULE
  - test\_suites.cpp, [114](#)
- callback
  - scenario, [69](#)
- CIRCLE\_DISTANCE
  - steeringBehavior.h, [98](#)
- CIRCLE\_RADIUS
  - steeringBehavior.h, [98](#)
- cohesion
  - steeringBehavior, [73](#)
- color, [16](#)
  - B, [19](#)
  - color, [17](#)
  - colors, [19](#)
  - createColors, [18](#)
  - G, [19](#)
  - getColor, [18](#)
  - R, [19](#)
- color.h
  - BLACK, [86](#)
  - BLUE, [86](#)
  - CYAN, [86](#)
  - GREEN, [86](#)
  - MAGENDA, [86](#)
  - num, [86](#)
  - RED, [86](#)
  - WHITE, [86](#)
  - YELLOW, [86](#)
- colors
  - color, [19](#)
- createAgent
  - scenario, [67](#)
- createColors
  - color, [18](#)
- createObstacle
  - obstacleAvoidance, [40](#)
- createPath
  - pathFollower, [45](#)
- createRandomArray
  - random, [65](#)
- CYAN
  - color.h, [86](#)
- desiredVelocity
  - agent, [13](#)
- DISTANCE
  - prison.cpp, [109](#)

- div
  - point, 48
  - pvector, 58
- dotProduct
  - pvector, 59
- drawAgent
  - graphics, 28
- drawCircle
  - graphics, 28
- drawLine
  - graphics, 29
- drawPath
  - graphics, 29
- drawPoint
  - graphics, 30
- drawText
  - graphics, 30
- drawWall
  - graphics, 31
- ESC
  - graphics.h, 90
- EVADE
  - steeringBehavior.h, 98
- evade, 20
  - evade, 20
  - loop, 21
  - steeringBehavior, 74
- FIELD\_HEIGHT
  - flowField.h, 88
- FIELD\_WIDTH
  - flowField.h, 89
- fillColor
  - agent, 13
- FLEE
  - steeringBehavior.h, 98
- flee, 21
  - flee, 22
  - loop, 22
  - steeringBehavior, 74
- FLOCK
  - steeringBehavior.h, 98
- flock, 23
  - flock, 24
  - loop, 24
- flow
  - windy, 84
- flowField, 25
  - flowField, 25
  - getField, 26
- flowField.h
  - FIELD\_HEIGHT, 88
  - FIELD\_WIDTH, 89
  - GRAVITY, 89
  - WIND\_WEST, 89
- FOLLOW\_MOUSE
  - steeringBehavior.h, 99
- force
  - agent, 13
- forceInScreen
  - graphics, 31
- G
  - color, 19
- getAngle
  - pvector, 59
- getColor
  - color, 18
- getField
  - flowField, 26
- getMousePosition
  - graphics, 32
- getNormalPoint
  - point, 48
- graphics, 26
  - drawAgent, 28
  - drawCircle, 28
  - drawLine, 29
  - drawPath, 29
  - drawPoint, 30
  - drawText, 30
  - drawWall, 31
  - forceInScreen, 31
  - getMousePosition, 32
  - handleKeypress, 32
  - handleResize, 32
  - initGraphics, 33
  - mouseButton, 33
  - mouseMove, 34
  - refreshScene, 34
  - target\_x, 35
  - target\_y, 35
  - timerEvent, 35
- graphics.h
  - ESC, 90
  - HEIGHT, 90
  - PI, 90
  - WIDTH, 90
- GRAVITY
  - flowField.h, 89
- GREEN
  - color.h, 86
- handleKeypress
  - graphics, 32
- handleResize
  - graphics, 32
- HEIGHT
  - graphics.h, 90
- id
  - agent, 14
- IN\_FLOW\_FIELD
  - steeringBehavior.h, 99
- include/agent.h, 85
- include/color.h, 85
- include/evade.h, 86

- include/flee.h, 87
- include/flock.h, 87
- include/flowField.h, 88
- include/graphics.h, 89
- include/mouseFollower.h, 91
- include/obstacle.h, 91
- include/obstacleAvoidance.h, 92
- include/path.h, 92
- include/pathFollower.h, 93
- include/point.h, 93
- include/prison.h, 94
- include/pursuit.h, 94
- include/pvector.h, 95
- include/random.h, 95
- include/scenario.h, 96
- include/steeringBehavior.h, 97
- include/wander.h, 100
- include/windy.h, 100
- inFlowField
  - steeringBehavior, 75
- initGL
  - scenario, 68
- initGraphics
  - graphics, 33
- limit
  - pvector, 60
- loop
  - evade, 21
  - flee, 22
  - flock, 24
  - mouseFollower, 36
  - obstacleAvoidance, 41
  - pathFollower, 45
  - prison, 53
  - pursuit, 55
  - wander, 81
  - windy, 83
- MAGENDA
  - color.h, 86
- magnitude
  - pvector, 60
- main
  - main.cpp, 102
- main.cpp, 101
  - main, 102
  - menu, 102
  - mode, 103
- mass
  - agent, 14
- MAX\_NUMBER\_OF\_AGENTS
  - scenario.cpp, 112
- maxForce
  - agent, 14
- maxSpeed
  - agent, 14
- menu
  - main.cpp, 102
- mode
  - main.cpp, 103
- mouseButton
  - graphics, 33
- mouseFollower, 36
  - loop, 36
  - mouseFollower, 36
- mouseMove
  - graphics, 34
- mul
  - point, 49
  - pvector, 60
- myColor
  - scenario, 70
- myPath
  - pathFollower, 46
- name
  - agent, 15
  - scenario, 70
- normalize
  - pvector, 61
- num
  - color.h, 86
- obstacle, 37
  - obstacle, 38
  - p, 38
  - r, 39
- obstacleAvoidance, 39
  - createObstacle, 40
  - loop, 41
  - obstacleAvoidance, 40
  - obstacles, 41
- obstacles
  - obstacleAvoidance, 41
- operator+
  - point, 49, 50
  - pvector, 61, 62
- operator+=
  - pvector, 62
- operator-
  - point, 50
  - pvector, 63
- operator==
  - point, 51
  - pvector, 64
- p
  - obstacle, 38
- path, 42
  - addPoint, 43
  - path, 42
  - points, 43
  - width, 43
- pathFollower, 44
  - createPath, 45
  - loop, 45
  - myPath, 46

- pathFollower, 45
- PI
  - graphics.h, 90
  - pvector.h, 95
- point, 46
  - div, 48
  - getNormalPoint, 48
  - mul, 49
  - operator+, 49, 50
  - operator-, 50
  - operator==, 51
  - point, 47
  - print, 51
  - x, 52
  - y, 52
- points
  - path, 43
- position
  - agent, 15
- print
  - point, 51
  - pvector, 64
- prison, 52
  - loop, 53
  - prison, 53
- prison.cpp
  - DISTANCE, 109
  - WALL, 109
- PURSUIT
  - steeringBehavior.h, 99
- pursuit, 54
  - loop, 55
  - pursuit, 55
  - steeringBehavior, 76
- pvector, 56
  - add, 58
  - angleBetween, 58
  - div, 58
  - dotProduct, 59
  - getAngle, 59
  - limit, 60
  - magnitude, 60
  - mul, 60
  - normalize, 61
  - operator+, 61, 62
  - operator+=, 62
  - operator-, 63
  - operator==, 64
  - print, 64
  - pvector, 57
  - x, 65
  - y, 65
- pvector.h
  - PI, 95
- R
  - color, 19
- r
  - agent, 15
  - obstacle, 39
- RANDOM
  - scenario.h, 97
- random, 65
  - createRandomArray, 65
- README.md, 103
- RED
  - color.h, 86
- refresh
  - scenario, 68
- refreshScene
  - graphics, 34
- scenario, 66
  - agents, 69
  - behavior, 69
  - callback, 69
  - createAgent, 67
  - initGL, 68
  - myColor, 70
  - name, 70
  - refresh, 68
  - scenario, 67
  - view, 70
- scenario.cpp
  - MAX\_NUMBER\_OF\_AGENTS, 112
- scenario.h
  - RANDOM, 97
  - STATIC, 97
  - TROOP, 97
  - types, 96
- seek
  - steeringBehavior, 76
- separation
  - steeringBehavior, 77
- setAngle
  - steeringBehavior, 78
- setFeatures
  - agent, 11
- src/agent.cpp, 103
- src/color.cpp, 103
- src/evade.cpp, 104
- src/flee.cpp, 104
- src/flock.cpp, 105
- src/flowField.cpp, 105
- src/graphics.cpp, 106
- src/mouseFollower.cpp, 106
- src/obstacle.cpp, 107
- src/obstacleAvoidance.cpp, 107
- src/path.cpp, 108
- src/pathFollower.cpp, 108
- src/point.cpp, 108
- src/prison.cpp, 109
- src/pursuit.cpp, 110
- src/pvector.cpp, 110
- src/random.cpp, 111
- src/scenario.cpp, 111
- src/steeringBehavior.cpp, 112
- src/wander.cpp, 112

- src/windy.cpp, [113](#)
- STATIC
  - scenario.h, [97](#)
- STAY\_IN\_FIELD
  - steeringBehavior.h, [99](#)
- STAY\_IN\_PATH
  - steeringBehavior.h, [99](#)
- stayInArea
  - steeringBehavior, [78](#)
- stayInPath
  - steeringBehavior, [79](#)
- steering
  - agent, [15](#)
- steeringBehavior, [71](#)
  - align, [72](#)
  - avoid, [72](#)
  - cohesion, [73](#)
  - evade, [74](#)
  - flee, [74](#)
  - inFlowField, [75](#)
  - pursuit, [76](#)
  - seek, [76](#)
  - separation, [77](#)
  - setAngle, [78](#)
  - stayInArea, [78](#)
  - stayInPath, [79](#)
  - wander, [80](#)
- steeringBehavior.h
  - AVOID\_OBSTACLE, [98](#)
  - CIRCLE\_DISTANCE, [98](#)
  - CIRCLE\_RADIUS, [98](#)
  - EVADE, [98](#)
  - FLEE, [98](#)
  - FLOCK, [98](#)
  - FOLLOW\_MOUSE, [99](#)
  - IN\_FLOW\_FIELD, [99](#)
  - PURSUIT, [99](#)
  - STAY\_IN\_FIELD, [99](#)
  - STAY\_IN\_PATH, [99](#)
  - WANDER, [99](#)
- target\_x
  - graphics, [35](#)
- target\_y
  - graphics, [35](#)
- targetPoint
  - agent, [16](#)
- test/test\_suites.cpp, [113](#)
- test\_suites.cpp
  - BOOST\_AUTO\_TEST\_CASE, [114–117](#)
  - BOOST\_TEST\_MODULE, [114](#)
- timerEvent
  - graphics, [35](#)
- TROOP
  - scenario.h, [97](#)
- types
  - scenario.h, [96](#)
- updatePosition
  - agent, [12](#)
- velocity
  - agent, [16](#)
- view
  - scenario, [70](#)
- WALL
  - prison.cpp, [109](#)
- WANDER
  - steeringBehavior.h, [99](#)
- wander, [80](#)
  - loop, [81](#)
  - steeringBehavior, [80](#)
  - wander, [81](#)
- WHITE
  - color.h, [86](#)
- WIDTH
  - graphics.h, [90](#)
- width
  - path, [43](#)
- WIND\_WEST
  - flowField.h, [89](#)
- windy, [82](#)
  - flow, [84](#)
  - loop, [83](#)
  - windy, [83](#)
- x
  - point, [52](#)
  - pvector, [65](#)
- y
  - point, [52](#)
  - pvector, [65](#)
- YELLOW
  - color.h, [86](#)