Heroku cheatsheet

Proudly sponsored by

COVID-19 projects looking for volunteers 🖐



Volunteer yourself or create a new one.

ethical ad by CodeFund

Heroku is a web hosting platform supporting many languages, and this guide is a reference to Heroku's commandline interface.

create - Create an app

```
heroku create sushi
git push heroku master
```

access - Collaboration

```
Manage collaborators
heroku access
                                     # List
heroku access:add me@xy.com
heroku access:remove me@xy.com
Transfer to another owner
heroku apps:transfer new@owner.com
```

logs - Show logs

```
heroku logs
heroku logs -t # --tail (stream)
heroku logs -s app # --source (only on app logs)
```

releases

```
heroku releases
heroku releases:info v25
heroku rollback
```

Start a database heroku addons:add heroku-postgresql Enable backups heroku addons:add pgbackups:auto-month See: Heroku PostgreSQL (devcenter.heroku.com)

config - Environment var configuration

```
Listing

heroku config  # List
heroku config -s  # List in shell format

Getting

heroku config:get KEY

Setting

heroku config:set KEY=val
heroku config:set KEY1=val KEY2=val ...

heroku config:unset KEY1
```

apps - Applications

```
heroku apps # list
heroku apps:create [NAME]
heroku apps:destroy --app APP
heroku apps:info
heroku apps:open # open in browser
heroku apps:rename NEWNAME
```

maintenance

heroku maintenance:on
heroku maintenance:off

Processes

ps - Managing processes

```
heroku ps  # list
heroku ps:scale web=1  # spawn more dynos
```

restart

heroku restart

run - Running tasks

```
heroku run bash
heroku run console  # Rails console
heroku run rake assets:precompile
```

Domains

domains - Custom domains

Add both!

heroku domains:add example.com heroku domains:add www.example.com

Removing

heroku domains:clear

heroku domains:remove example.com

See: Custom domains (devcenter.heroku.com)

Wildcard domains

heroku addons:add wildcard domains

*.yourdomain.com => heroku.com

Other tricks

htpasswd (for PHP apps)

Create an .htaccess file in the webroot:

AuthUserFile /app/www/.htpasswd

AuthType Basic

AuthName "Restricted Access"

Require valid-user

Create a .htpasswd file:

\$ htpasswd -c .htpasswd [username]

See: gist.github.com

References

https://addons.heroku.com/

https://devcenter.heroku.com/