


# Density-Based Stream Network Extraction from Digital Elevation Models Mehran Ghandehari, Barbara P. Buttenfield



Meridian Lab, Department of Geography, University of Colorado-Boulder

# Introduction


Digital Elevation Models (DEMs) are widely used for stream network extraction. DEM-based methods track the simulated flow of water to calculate flow direction and flow accumulation (Tarboton et al, 1991).

Stream network delineation depends on several factors:


- a) DEM Resolution (1m vs. 30m vs. 90m)
- b) Flow Direction algorithm (D8 vs. D-infinity)


c) Flow Accumulation Threshold

The most common way to determine a cutoff threshold is by trial and error, which can be time consuming, inconsistent from one location to another, and possibly erroneous (if an inappropriate threshold value is selected).




# Datasets





# HUC12 Stream Network NIO Flowlines UNIO Flowlines



#### Results The Piceance-Yellow River subbasin (Colorado) **Stream Network** Extracted Extracted NHD Flowlines **Density Partitions** (KM / Square KM) 2.3580 **Threshold CLC (%)** CLC Threshold Elevation Slope CLC Threshold Elevation Slope CLC Threshold Elevation Slope 0.9488 Max 0.4737 0.1772

# Conclusion

- Choosing one threshold for extracting streams from DEM leads to inaccurate results
- Using density partitions for extracting streams from DEM improves the results
- There is a correlation between threshold and CLC and also between threshold and density
- Some of the small CLC values are related to DEM-based method problems (e.g., flat areas, water bodies), which more investigation is required
- Most of the errors in the extracted streams are related to the first order streams (head waters)

## Future Work

- Investigating the influence of DEM resolution on the results
- Evaluating the performance of different flow direction methods
- Incorporating landscape characteristics (e.g., slope, roughness, climate, soil, vegetation) into threshold analysis
- Testing the practicality of and the possibilities for the implementation of an automated USA-wide method
- Proposing a method for identifying stream channel heads as the main problem of stream extraction from DEM

### References

Buttenfield, B.P., Stanislawski, L.V. and Brewer, C.A., 2010, Multiscale Representations of Water: Tailoring Generalization Sequences to Specific Physiographic Regimes. GIScience 2010 Short Paper Proceedings, Zurich, Switzerland, September.

Stanislawski, L.V., Buttenfield, B.P. and Samaranayake, V.A., 2010, Automated Metric Assessment of Hydrographic Feature Generalization Through Bootstrapping, Proceedings, 13th International Cartographic Association Symposium on Multiple Representations and Map Generalization, Zurich Switzerland, September.

Tarboton, D.G., Bras, R.L., and Rodriguez-Iturbe, I., 1991, On the extraction of channel networks from digital elevation data. Hydrologic Processes, v. 5(1), p. 81-100.

# Acknowledgments

We would like to acknowledge Lawrence V Stanislawski, researcher of Center of Excellence for Geospatial Information Science at U.S. Geological Survey, for providing us with the data.



10th Annual Hydrologic Sciences Research Symposium Water

Missouri

Texas

0.5362

2202.57 26.73%

Colorado