

🔑 master ▾

[coursera /](#)

Go to file

...

[05-卷积神经网络-Convolutional Neural Network](#)
[s](#)
[/ exm-02.md](#)

ericjij no message

Latest commit ffa9b5e on Nov 23, 2017 [🕒 History](#)

👤 1 contributor

105 lines (58 sloc) | 3.84 KB

Raw

Blame



Deep convolutional models

1

Which of the following do you typically see as you move to deeper layers in a ConvNet?

nH and nW increases, while nC decreases

nH and nW decreases, while nC also decreases

nH and nW increases, while nC also increases

☒ nH and nW decrease, while nC increases

2

Which of the following do you typically see in a ConvNet? (Check all that apply.)

Multiple CONV layers followed by a POOL layer

Multiple POOL layers followed by a CONV layer

FC layers in the last few layers

FC layers in the first few layers

3

In order to be able to build very deep networks, we usually only use pooling layers to downsize the height/width of the activation volumes while convolutions are used with "valid" padding. Otherwise, we would downsize the input of the model too quickly.

True

False

4

Training a deeper network (for example, adding additional layers to the network) allows the network to fit more complex functions and thus almost always results in lower training error. For this question, assume we're referring to "plain" networks.

True

False

5

The following equation captures the computation in a ResNet block. What goes into the two blanks above?

$$a[l+2]=g(W[l+2]g(W[l+1]a[l]+b[l+1])+b[l+2]+\text{_____})+\text{_____}$$

$a[l]$ and 0, respectively

0 and $z[l+1]$, respectively

$z[l]$ and $a[l]$, respectively

0 and $a[l]$, respectively

6

Which ones of the following statements on Residual Networks are true? (Check all that apply.)

Using a skip-connection helps the gradient to backpropagate and thus helps you to train deeper networks

A ResNet with L layers would have on the order of L^2 skip connections in total.

The skip-connections compute a complex non-linear function of the input to pass to a deeper layer in the network.

The skip-connection makes it easy for the network to learn an identity mapping between the input and the output within the ResNet block.

7

Suppose you have an input volume of dimension $64 \times 64 \times 16$. How many parameters would a single 1×1 convolutional filter have (including the bias)?

2

4097

1

17

8

Suppose you have an input volume of dimension $n_H \times n_W \times n_C$. Which of the following statements you agree with? (Assume that "1x1 convolutional layer" below always uses a stride of 1 and no padding.)

You can use a 1x1 convolutional layer to reduce n_C but not n_H , n_W .

You can use a 1x1 convolutional layer to reduce n_H , n_W , and n_C .

You can use a pooling layer to reduce n_H , n_W , but not n_C .

You can use a pooling layer to reduce nH, nW, and nC.

9

Which ones of the following statements on Inception Networks are true?
(Check all that apply.)

A single inception block allows the network to use a combination of 1x1, 3x3, 5x5 convolutions and pooling.

Making an inception network deeper (by stacking more inception blocks together) should not hurt training set performance.

Inception blocks usually use 1x1 convolutions to reduce the input data volume's size before applying 3x3 and 5x5 convolutions.

Inception networks incorporates a variety of network architectures (similar to dropout, which randomly chooses a network architecture on each step) and thus has a similar regularizing effect as dropout.

10

Which of the following are common reasons for using open-source implementations of ConvNets (both the model and/or weights)? Check all that apply.

A model trained for one computer vision task can usually be used to perform data augmentation even for a different computer vision task.

It is a convenient way to get working an implementation of a complex ConvNet architecture.

The same techniques for winning computer vision competitions, such as using multiple crops at test time, are widely used in practical deployments (or production system deployments) of ConvNets.

Parameters trained for one computer vision task are often useful as pretraining for other computer vision tasks.