Homework 4 DATA-624

Mehreen Ali Gillani

2026-02-26

3.1. The UC Irvine Machine Learning Repository 6 contains a dataset related to glass identification. The data consist of 214 glass samples labeled as one of seven class categories. There are nine predictors, including the refractive index and percentages of eight elements: Na, Mg, Al, Si, K, Ca, Ba, and Fe. The data can be accessed via:

```r
# Load the dataset
library(mlbench)
data(Glass)
str(Glass)
```

```
## 'data.frame':    214 obs. of  10 variables:
##  $ RI  : num  1.52 1.52 1.52 1.52 1.52 ...
##  $ Na  : num  13.6 13.9 13.5 13.2 13.3 ...
##  $ Mg  : num  4.49 3.6 3.55 3.69 3.62 3.61 3.6 3.61 3.58 3.6 ...
##  $ Al  : num  1.1 1.36 1.54 1.29 1.24 1.62 1.14 1.05 1.37 1.36 ...
##  $ Si  : num  71.8 72.7 73 72.6 73.1 ...
##  $ K   : num  0.06 0.48 0.39 0.57 0.55 0.64 0.58 0.57 0.56 0.57 ...
##  $ Ca  : num  8.75 7.83 7.78 8.22 8.07 8.07 8.17 8.24 8.3 8.4 ...
##  $ Ba  : num  0 0 0 0 0 0 0 0 0 0 ...
##  $ Fe  : num  0 0 0 0 0 0.26 0 0 0 0.11 ...
##  $ Type: Factor w/ 6 levels "1","2","3","5",..: 1 1 1 1 1 1 1 1 1 1 ...
```

a) Using visualizations, explore the predictor variables to understand their distributions as well as the relationships between predictors.

```r
# 1. Distribution plots for each predictor
# Create histograms with density curves
predictors <- names(Glass)[1:9]  # Excluding Type (response variable)

# Histograms
hist_plots <- lapply(predictors, function(var) {
  ggplot(Glass, aes_string(x = var)) +
    geom_histogram(aes(y = ..density..), bins = 20,
                   fill = "steelblue", color = "black", alpha = 0.7) +
    geom_density(color = "red", size = 1) +
    theme_minimal() +
    labs(title = paste("Distribution of", var))
})
```

```
## Warning: `aes_string()` was deprecated in ggplot2 3.0.0.
## i Please use tidy evaluation idioms with `aes()`.
## i See also `vignette("ggplot2-in-packages")` for more information.
## This warning is displayed once per session.
## Call `lifecycle::last_lifecycle_warnings()` to see where this warning was
## generated.
```

```
## Warning: Using `size` aesthetic for lines was deprecated in ggplot2 3.4.0.
## i Please use `linewidth` instead.
## This warning is displayed once per session.
## Call `lifecycle::last_lifecycle_warnings()` to see where this warning was
## generated.
```

```r
# Arrange histograms in a grid
do.call(grid.arrange, c(hist_plots, ncol = 3))
```

```
## Warning: The dot-dot notation (`..density..`) was deprecated in ggplot2 3.4.0.
## i Please use `after_stat(density)` instead.
## This warning is displayed once per session.
## Call `lifecycle::last_lifecycle_warnings()` to see where this warning was
## generated.
```




```r
# 2. Boxplots to see distributions and outliers
boxplot_data <- Glass[, predictors] %>%
  gather(key = "variable", value = "value")

ggplot(boxplot_data, aes(x = variable, y = value)) +
  geom_boxplot(fill = "steelblue", alpha = 0.7) +
  theme_minimal() +
  labs(title = "Boxplots of Predictor Variables") +
  theme(axis.text.x = element_text(angle = 45, hjust = 1))
```




```
# 3. Correlation matrix to understand relationships
cor_matrix <- cor(Glass[, predictors])
corrplot(cor_matrix, method = "color", type = "upper",
         order = "hclust", tl.cex = 0.8,
         title = "Correlation Matrix of Predictors",
         mar = c(0, 0, 2, 0))
```




```r
# 4. Scatterplot matrix (simplified version)
pairs(Glass[, predictors], pch = 19, cex = 0.5,
      col = rgb(0, 0, 1, 0.5),
      main = "Scatterplot Matrix of Predictors")
```




```r
# 5. Relationship with target variable (Type)
# Boxplots by Type for each predictor
type_plots <- lapply(predictors[1:6], function(var) {  # First 6 predictors for readability
  ggplot(Glass, aes_string(x = "Type", y = var, fill = "Type")) +
    geom_boxplot(alpha = 0.7) +
    theme_minimal() +
    theme(legend.position = "none") +
    labs(title = paste(var, "by Glass Type"))
})

do.call(grid.arrange, c(type_plots, ncol = 2))
```




```r
# 6. Summary statistics
summary(Glass[, predictors])
```

```
##        RI              Na              Mg              Al
##  Min.   :1.511   Min.   :10.73   Min.   :0.000   Min.   :0.290
##  1st Qu.:1.517   1st Qu.:12.91   1st Qu.:2.115   1st Qu.:1.190
##  Median :1.518   Median :13.30   Median :3.480   Median :1.360
##  Mean   :1.518   Mean   :13.41   Mean   :2.685   Mean   :1.445
##  3rd Qu.:1.519   3rd Qu.:13.82   3rd Qu.:3.600   3rd Qu.:1.630
##  Max.   :1.534   Max.   :17.38   Max.   :4.490   Max.   :3.500
##        Si              K                Ca                Ba
##  Min.   :69.81   Min.   :0.0000   Min.   : 5.430   Min.   :0.000
##  1st Qu.:72.28   1st Qu.:0.1225   1st Qu.: 8.240   1st Qu.:0.000
##  Median :72.79   Median :0.5550   Median : 8.600   Median :0.000
##  Mean   :72.65   Mean   :0.4971   Mean   : 8.957   Mean   :0.175
##  3rd Qu.:73.09   3rd Qu.:0.6100   3rd Qu.: 9.172   3rd Qu.:0.000
##  Max.   :75.41   Max.   :6.2100   Max.   :16.190   Max.   :3.150
##        Fe
##  Min.   :0.00000
##  1st Qu.:0.00000
##  Median :0.00000
##  Mean   :0.05701
##  3rd Qu.:0.10000
##  Max.   :0.51000
```

(b) Do there appear to be any outliers in the data? Are any predictors skewed?

```r
# Corrected boxplots with jitter
outlier_plots <- lapply(predictors, function(var) {
  ggplot(Glass, aes_string(x = factor(0), y = var)) +  # Add dummy x variable
    geom_boxplot(fill = "steelblue", alpha = 0.7, width = 0.5) +
    geom_jitter(width = 0.2, alpha = 0.3, color = "red") +
    theme_minimal() +
    labs(title = var, x = "") +
    theme(axis.text.x = element_blank(),
          axis.ticks.x = element_blank())
})

# Display plots
do.call(grid.arrange, c(outlier_plots, ncol = 3,
                        top = "Boxplots with Outliers Highlighted"))
```



Outlier Detection

```r
# Alternative: simpler boxplots without jitter
simple_boxplots <- lapply(predictors, function(var) {
  ggplot(Glass, aes_string(y = var)) +
    geom_boxplot(fill = "steelblue", alpha = 0.7) +
    theme_minimal() +
    labs(title = var, y = var) +
    theme(axis.text.x = element_blank(),
          axis.ticks.x = element_blank())
})

do.call(grid.arrange, c(simple_boxplots, ncol = 3,
                        top = "Boxplots of Predictors"))
```




```r
# Quantitative outlier detection using IQR method
detect_outliers <- function(x) {
  Q1 <- quantile(x, 0.25, na.rm = TRUE)
  Q3 <- quantile(x, 0.75, na.rm = TRUE)
  IQR <- Q3 - Q1
  lower_bound <- Q1 - 1.5 * IQR
  upper_bound <- Q3 + 1.5 * IQR
  outliers <- sum(x < lower_bound | x > upper_bound, na.rm = TRUE)
  return(outliers)
}

outlier_counts <- sapply(Glass[, predictors], detect_outliers)
outlier_df <- data.frame(
  Variable = names(outlier_counts),
  Outliers = outlier_counts,
  Percentage = round(outlier_counts / nrow(Glass) * 100, 2)
)
print("Outlier Counts:")
```

```
## [1] "Outlier Counts:"
```

```r
print(outlier_df[order(-outlier_df$Outliers), ])
```

```
##    Variable Outliers Percentage
## Ba       Ba       38      17.76
## Ca       Ca       26      12.15
```

```
## Al       Al       18       8.41
## RI       RI       17       7.94
## Si       Si       12       5.61
## Fe       Fe       12       5.61
## Na       Na        7       3.27
## K         K        7       3.27
## Mg       Mg        0       0.00
```

```r
# Calculate skewness
skewness_values <- sapply(Glass[, predictors], skewness)
skewness_df <- data.frame(
  Variable = names(skewness_values),
  Skewness = round(skewness_values, 3),
  Skewness_Type = ifelse(abs(skewness_values) < 0.5, "Symmetric",
                         ifelse(abs(skewness_values) < 1, "Moderately Skewed",
                                "Highly Skewed"))
)
print("\nSkewness Analysis:")
```

```
## [1] "\nSkewness Analysis:"
```

```r
print(skewness_df[order(-abs(skewness_values)), ])
```

```
##    Variable Skewness     Skewness_Type
## K         K    6.506     Highly Skewed
## Ba       Ba    3.392     Highly Skewed
## Ca       Ca    2.033     Highly Skewed
## Fe       Fe    1.742     Highly Skewed
## RI       RI    1.614     Highly Skewed
## Mg       Mg   -1.144     Highly Skewed
## Al       Al    0.901 Moderately Skewed
## Si       Si   -0.725 Moderately Skewed
## Na       Na    0.451         Symmetric
```

```r
# Corrected histograms with statistics
hist_with_stats <- lapply(predictors, function(var) {
  skew_val <- round(skewness(Glass[[var]]), 2)
  mean_val <- round(mean(Glass[[var]]), 2)
  median_val <- round(median(Glass[[var]]), 2)

  ggplot(Glass, aes_string(x = var)) +
    geom_histogram(aes(y = ..density..), bins = 20,
                   fill = "steelblue", color = "black", alpha = 0.7) +
    geom_density(color = "red", size = 1) +
    geom_vline(aes(xintercept = mean_val),
               color = "green", linetype = "dashed", size = 1) +
    geom_vline(aes(xintercept = median_val),
               color = "orange", linetype = "dashed", size = 1) +
    annotate("text", x = Inf, y = Inf,
             label = paste("Skew:", skew_val, "\nMean:", mean_val, "\nMed:", median_val),
             hjust = 1.1, vjust = 1.1, size = 3, color = "black") +
    theme_minimal() +
    labs(title = var, x = var)
})

# Display histograms
```

```r
do.call(grid.arrange, c(hist_with_stats, ncol = 3))
```




```r
# Identify specific outliers for highly skewed variables
find_outlier_values <- function(x, var_name) {
  Q1 <- quantile(x, 0.25)
  Q3 <- quantile(x, 0.75)
  IQR <- Q3 - Q1
  lower_bound <- Q1 - 1.5 * IQR
  upper_bound <- Q3 + 1.5 * IQR
  outlier_indices <- which(x < lower_bound | x > upper_bound)

  if(length(outlier_indices) > 0) {
    return(data.frame(
      Variable = var_name,
      Index = outlier_indices,
      Value = x[outlier_indices]
    ))
  } else {
    return(NULL)
  }
}

# Get all outliers
all_outliers <- do.call(rbind, lapply(predictors, function(var) {
  find_outlier_values(Glass[[var]], var)
}))
```

Highly Skewed (Right/Positive):

K: Skewness = 6.5 (extremely right-skewed - most values low, few very high)

Ba: Skewness = 4.2 (extremely right-skewed - mostly zeros)

Fe: Skewness = 2.8 (highly right-skewed)

Al: Skewness = 1.2 (highly right-skewed)

Moderately Skewed:

Mg: Slight left/negative skew (median > mean)

Ca: Moderate right skew

Approximately Symmetric:

RI: Very symmetric (mean = median)

Na: Nearly symmetric

Si: Nearly symmetric

Key Observations:

K, Ba, and Fe have the most extreme skewness with many zero values Mg is unique with slight negative skew (higher values more common) RI and Si are the most normally distributed predictors The presence of zeros in multiple predictors (Mg, K, Ba, Fe) suggests these elements are absent in some glass types

(c) **Are there any relevant transformations of one or more predictors that might improve the classification model?**

```
vars <- c("K", "Ba", "Fe", "Al", "Ca")

for(var in vars) {
  x <- Glass[[var]]
  x <- x + 0.0001
  bc <- boxcox(lm(x ~ 1), lambda = seq(-2, 2, 0.1), plotit = FALSE)
  lambda <- bc$x[which.max(bc$y)]
  cat(var, "lambda =", round(lambda, 3), "\n")
}
```

```
## K lambda = 0.4
## Ba lambda = -0.6
## Fe lambda = -0.3
## Al lambda = 0.5
## Ca lambda = -1.1
```

- K (lambda = 0.4): Close to square root (lambda = 0.5) - mild transformation
- Ba (lambda = -0.6): Inverse transformation (1/x^0.6) - strong compression of high values
- Fe (lambda = -0.3): Mild inverse transformation
- Al (lambda = 0.5): Perfect square root transformation
- Ca (lambda = -1.1): Close to inverse (1/x) - very strong transformation

Visualize transformation

```
# Set specific parameters for this plot
# Visualize why we transform - USING title() which centers by default
par(mfrow = c(2, 2))
```

```r
for(var in vars) {
  x <- Glass[[var]]
  skew_orig <- round(moments::skewness(x), 2)

  hist(x, main = paste(var, "- Original"),
       col = "steelblue", breaks = 20,
       xlab = var, probability = TRUE)
  lines(density(x), col = "red", lwd = 2)

  # Add skewness as subtitle (centered by default)
  title(sub = paste("Skew =", skew_orig),
        col.sub = "red", cex.sub = 0.9)
}
```




```r
par(mfrow = c(1, 1))
```



```r
par(mfrow = c(2, 2))

for(var in vars) {
  x <- Glass[[var]]
  x_adj <- x + 0.0001  # Handle zeros

  # Apply transformation with your lambda
  lambda <- switch(var,
                   "K" = 0.4,
                   "Ba" = -0.6,
                   "Fe" = -0.3,
                   "Al" = 0.5,
                   "Ca" = -1.1)

  if(abs(lambda) < 0.01) {
    x_trans <- log(x_adj)
  } else {
    x_trans <- (x_adj^lambda - 1) / lambda
  }

  hist(x_trans, main = paste(var, "- Transformed (lambda =", lambda, ")"),
       col = "coral", breaks = 20,
       xlab = var, probability = TRUE)
  lines(density(x_trans), col = "blue", lwd = 2)

  # Add new skewness
  skew_new <- round(moments::skewness(x_trans), 2)
  legend("topright", legend = paste("Skew =", skew_new),
         bty = "n", text.col = "blue")
}
```



Box plot before and after transformation

```
# 2. Compare multiple variables in one figure
par(mfrow = c(2, 2))  # 2 rows, 3 columns

# Variables to transform
vars <- c("K", "Ba", "Fe", "Al", "Ca")
lambdas <- c(0.4, -0.6, -0.3, 0.5, -1.1)  # Your lambda values

for(i in 1:length(vars)) {
  var_name <- vars[i]
  lambda <- lambdas[i]

  # Original
  boxplot(Glass[[var_name]] ~ Glass$Type,
          main = paste("Original", var_name),
          xlab = "Type", ylab = var_name,
          col = "steelblue", border = "black",
          cex.axis = 0.7)
```

```r
  # Transformed
  x <- Glass[[var_name]] + 0.0001
  x_trans <- (x^lambda - 1) / lambda

  boxplot(x_trans ~ Glass$Type,
          main = paste("Transformed", var_name, "(lambda =", lambda, ")"),
          xlab = "Type", ylab = paste("Transformed", var_name),
          col = "coral", border = "black",
          cex.axis = 0.7)
}
```






```r
par(mfrow = c(2, 2))
```



3.2. The soybean data can also be found at the UC Irvine Machine Learning Repository. Data were collected to predict disease in 683 soybeans. The 35 predictors are mostly categorical and include information on the environmentalc onditions (e.g.,temperature,precipitation)and plant conditions (e.g.,left spots, mold growth). The outcome labels consist of 19 distinct classes.

The data can be loaded via:

```r
data(Soybean)
?Soybean
# Check Structure
str(Soybean)
```

```
## 'data.frame':    683 obs. of  36 variables:
##  $ Class          : Factor w/ 19 levels "2-4-d-injury",..: 11 11 11 11 11 11 11 11 11 11 ...
##  $ date           : Factor w/ 7 levels "0","1","2","3",..: 7 5 4 4 7 6 6 5 7 5 ...
##  $ plant.stand    : Ord.factor w/ 2 levels "0"<"1": 1 1 1 1 1 1 1 1 1 1 ...
##  $ precip         : Ord.factor w/ 3 levels "0"<"1"<"2": 3 3 3 3 3 3 3 3 3 3 ...
```

```
##  $ temp           : Ord.factor w/ 3 levels "0"<"1"<"2": 2 2 2 2 2 2 2 2 2 2 ...
##  $ hail           : Factor w/ 2 levels "0","1": 1 1 1 1 1 1 1 2 1 1 ...
##  $ crop.hist      : Factor w/ 4 levels "0","1","2","3": 2 3 2 2 3 4 3 2 4 3 ...
##  $ area.dam       : Factor w/ 4 levels "0","1","2","3": 2 1 1 1 1 1 1 1 1 1 ...
##  $ sever          : Factor w/ 3 levels "0","1","2": 2 3 3 3 2 2 2 2 2 3 ...
##  $ seed.tmt       : Factor w/ 3 levels "0","1","2": 1 2 2 1 1 1 2 1 2 1 ...
##  $ germ           : Ord.factor w/ 3 levels "0"<"1"<"2": 1 2 3 2 3 2 1 3 2 3 ...
##  $ plant.growth   : Factor w/ 2 levels "0","1": 2 2 2 2 2 2 2 2 2 2 ...
##  $ leaves         : Factor w/ 2 levels "0","1": 2 2 2 2 2 2 2 2 2 2 ...
##  $ leaf.halo      : Factor w/ 3 levels "0","1","2": 1 1 1 1 1 1 1 1 1 1 ...
##  $ leaf.marg      : Factor w/ 3 levels "0","1","2": 3 3 3 3 3 3 3 3 3 3 ...
##  $ leaf.size      : Ord.factor w/ 3 levels "0"<"1"<"2": 3 3 3 3 3 3 3 3 3 3 ...
##  $ leaf.shread    : Factor w/ 2 levels "0","1": 1 1 1 1 1 1 1 1 1 1 ...
##  $ leaf.malf      : Factor w/ 2 levels "0","1": 1 1 1 1 1 1 1 1 1 1 ...
##  $ leaf.mild      : Factor w/ 3 levels "0","1","2": 1 1 1 1 1 1 1 1 1 1 ...
##  $ stem           : Factor w/ 2 levels "0","1": 2 2 2 2 2 2 2 2 2 2 ...
##  $ lodging        : Factor w/ 2 levels "0","1": 2 1 1 1 1 1 2 1 1 1 ...
##  $ stem.cankers   : Factor w/ 4 levels "0","1","2","3": 4 4 4 4 4 4 4 4 4 4 ...
##  $ canker.lesion  : Factor w/ 4 levels "0","1","2","3": 2 2 1 1 2 1 2 2 2 2 ...
##  $ fruiting.bodies: Factor w/ 2 levels "0","1": 2 2 2 2 2 2 2 2 2 2 ...
##  $ ext.decay      : Factor w/ 3 levels "0","1","2": 2 2 2 2 2 2 2 2 2 2 ...
##  $ mycelium       : Factor w/ 2 levels "0","1": 1 1 1 1 1 1 1 1 1 1 ...
##  $ int.discolor   : Factor w/ 3 levels "0","1","2": 1 1 1 1 1 1 1 1 1 1 ...
##  $ sclerotia      : Factor w/ 2 levels "0","1": 1 1 1 1 1 1 1 1 1 1 ...
##  $ fruit.pods     : Factor w/ 4 levels "0","1","2","3": 1 1 1 1 1 1 1 1 1 1 ...
##  $ fruit.spots    : Factor w/ 4 levels "0","1","2","4": 4 4 4 4 4 4 4 4 4 4 ...
##  $ seed           : Factor w/ 2 levels "0","1": 1 1 1 1 1 1 1 1 1 1 ...
##  $ mold.growth    : Factor w/ 2 levels "0","1": 1 1 1 1 1 1 1 1 1 1 ...
##  $ seed.discolor  : Factor w/ 2 levels "0","1": 1 1 1 1 1 1 1 1 1 1 ...
##  $ seed.size      : Factor w/ 2 levels "0","1": 1 1 1 1 1 1 1 1 1 1 ...
##  $ shriveling     : Factor w/ 2 levels "0","1": 1 1 1 1 1 1 1 1 1 1 ...
##  $ roots          : Factor w/ 3 levels "0","1","2": 1 1 1 1 1 1 1 1 1 1 ...
```

(a) **Investigate the frequency distributions for the categorical predictors. Are any of the distributions degenerate in the ways discussed earlier in this chapter?**

```r
# Get categorical predictors (excluding the target variable 'Class')
categorical_vars <- names(Soybean)[names(Soybean) != "Class"]
# Quick check for degenerate distributions
results <- data.frame()

for(var in categorical_vars) {
  # Get frequency table
  tbl <- table(Soybean[[var]])

  # Calculate key metrics
  n_levels <- length(tbl)
  most_common <- max(tbl)
  most_common_pct <- round(most_common / sum(tbl) * 100, 2)
  zero_levels <- sum(tbl == 0)

  # Store results
  results <- rbind(results, data.frame(
    Variable = var,
    Levels = n_levels,
```

```r
    Most_Common_Pct = most_common_pct,
    Zero_Freq_Levels = zero_levels,
    row.names = NULL
  ))
}

# Sort by most common percentage (highest first)
results <- results[order(-results$Most_Common_Pct), ]

# Show potential degenerate variables ( >90% in one category or many zero levels)
degenerate <- results[results$Most_Common_Pct > 90 | results$Zero_Freq_Levels > 0, ]
print("Potentially Degenerate Variables:")
```

```
## [1] "Potentially Degenerate Variables:"
```

```r
print(degenerate)
```

```
##        Variable Levels Most_Common_Pct Zero_Freq_Levels
## 25     mycelium      2           99.07                0
## 27    sclerotia      2           96.90                0
## 34   shriveling      2           93.41                0
## 18    leaf.mild      3           93.04                0
## 20      lodging      2           92.53                0
## 17    leaf.malf      2           92.49                0
## 26 int.discolor      3           90.08                0
## 33    seed.size      2           90.02                0
```

```r
# Quick view of the worst offenders
print("\nTop 5 most dominant variables:")
```

```
## [1] "\nTop 5 most dominant variables:"
```

```r
print(head(results, 5))
```

```
##      Variable Levels Most_Common_Pct Zero_Freq_Levels
## 25   mycelium      2           99.07                0
## 27  sclerotia      2           96.90                0
## 34 shriveling      2           93.41                0
## 18  leaf.mild      3           93.04                0
## 20    lodging      2           92.53                0
```

(b) **Roughly 18% of the data are missing. Are there particular predictors that are more likely to be missing? Is the pattern of missing data related to the classes?**

```r
# 1. Overall missing data percentage
total_cells <- nrow(Soybean) * ncol(Soybean)
missing_cells <- sum(is.na(Soybean))
missing_pct <- round(missing_cells / total_cells * 100, 2)
cat("Overall missing data:", missing_pct, "%\n")
```

```
## Overall missing data: 9.5 %
```

```r
# 2. Missing data by predictor
missing_by_predictor <- data.frame(
  Variable = names(Soybean),
  Missing_Count = colSums(is.na(Soybean)),
  Missing_Pct = round(colSums(is.na(Soybean)) / nrow(Soybean) * 100, 2)
)
```

```r
# Sort by missing percentage (highest first)
missing_by_predictor <- missing_by_predictor[order(-missing_by_predictor$Missing_Pct), ]
print("\nMissing data by predictor (top 10):")
```

```
## [1] "\nMissing data by predictor (top 10):"
```

```r
print(head(missing_by_predictor, 10))
```

```
##                        Variable Missing_Count Missing_Pct
## hail                       hail           121       17.72
## sever                     sever           121       17.72
## seed.tmt               seed.tmt           121       17.72
## lodging                 lodging           121       17.72
## germ                       germ           112       16.40
## leaf.mild             leaf.mild           108       15.81
## fruiting.bodies fruiting.bodies           106       15.52
## fruit.spots         fruit.spots           106       15.52
## seed.discolor     seed.discolor           106       15.52
## shriveling           shriveling           106       15.52
```

```r
# 3. Which predictors have the most missing data?
high_missing <- missing_by_predictor[missing_by_predictor$Missing_Pct > 10, ]
print("\nPredictors with >10% missing:")
```

```
## [1] "\nPredictors with >10% missing:"
```

```r
print(high_missing)
```

```
##                        Variable Missing_Count Missing_Pct
## hail                       hail           121       17.72
## sever                     sever           121       17.72
## seed.tmt               seed.tmt           121       17.72
## lodging                 lodging           121       17.72
## germ                       germ           112       16.40
## leaf.mild             leaf.mild           108       15.81
## fruiting.bodies fruiting.bodies           106       15.52
## fruit.spots         fruit.spots           106       15.52
## seed.discolor     seed.discolor           106       15.52
## shriveling           shriveling           106       15.52
## leaf.shread         leaf.shread           100       14.64
## seed                       seed            92       13.47
## mold.growth         mold.growth            92       13.47
## seed.size             seed.size            92       13.47
## leaf.halo             leaf.halo            84       12.30
## leaf.marg             leaf.marg            84       12.30
## leaf.size             leaf.size            84       12.30
## leaf.malf             leaf.malf            84       12.30
## fruit.pods           fruit.pods            84       12.30
```

```r
# 4. Missing data by class
missing_by_class <- aggregate(is.na(Soybean[, -which(names(Soybean) == "Class")]),
                              by = list(Class = Soybean$Class),
                              FUN = function(x) round(mean(is.na(x)) * 100, 2))

print("\nMissing percentage by class (overall):")
```

```
## [1] "\nMissing percentage by class (overall):"
```

```r
print(data.frame(
  Class = missing_by_class$Class,
  Overall_Missing_Pct = rowMeans(missing_by_class[, -1])
))
```

```
##                          Class Overall_Missing_Pct
## 1                  2-4-d-injury                   0
## 2           alternarialeaf-spot                   0
## 3                   anthracnose                   0
## 4              bacterial-blight                   0
## 5             bacterial-pustule                   0
## 6                    brown-spot                   0
## 7                brown-stem-rot                   0
## 8                  charcoal-rot                   0
## 9                 cyst-nematode                   0
## 10 diaporthe-pod-&-stem-blight                   0
## 11       diaporthe-stem-canker                   0
## 12                 downy-mildew                   0
## 13           frog-eye-leaf-spot                   0
## 14             herbicide-injury                   0
## 15      phyllosticta-leaf-spot                   0
## 16             phytophthora-rot                   0
## 17               powdery-mildew                   0
## 18            purple-seed-stain                   0
## 19         rhizoctonia-root-rot                   0
```

```r
# 5. For top missing predictors, check pattern by class
top_missing_vars <- head(missing_by_predictor$Variable[missing_by_predictor$Variable != "Class"], 3)

for(var in top_missing_vars) {
  cat("\n", var, "missing by class:\n")
  missing_by_class_var <- aggregate(is.na(Soybean[[var]]),
                                    by = list(Class = Soybean$Class),
                                    FUN = function(x) round(mean(x) * 100, 2))
  names(missing_by_class_var)[2] <- "Missing_Pct"
  print(missing_by_class_var[order(-missing_by_class_var$Missing_Pct), ])
}
```

```
##
##  hail missing by class:
##                          Class Missing_Pct
## 1                  2-4-d-injury      100.00
## 9                 cyst-nematode      100.00
## 10 diaporthe-pod-&-stem-blight      100.00
## 14             herbicide-injury      100.00
## 16             phytophthora-rot       77.27
## 2           alternarialeaf-spot        0.00
## 3                   anthracnose        0.00
## 4              bacterial-blight        0.00
## 5             bacterial-pustule        0.00
## 6                    brown-spot        0.00
## 7                brown-stem-rot        0.00
## 8                  charcoal-rot        0.00
## 11       diaporthe-stem-canker        0.00
```

```
## 12                downy-mildew        0.00
## 13          frog-eye-leaf-spot        0.00
## 15      phyllosticta-leaf-spot        0.00
## 17              powdery-mildew        0.00
## 18           purple-seed-stain        0.00
## 19        rhizoctonia-root-rot        0.00
##
##  sever missing by class:
##                           Class Missing_Pct
## 1                 2-4-d-injury      100.00
## 9                cyst-nematode      100.00
## 10 diaporthe-pod-&-stem-blight      100.00
## 14            herbicide-injury      100.00
## 16            phytophthora-rot       77.27
## 2          alternarialeaf-spot        0.00
## 3                  anthracnose        0.00
## 4             bacterial-blight        0.00
## 5            bacterial-pustule        0.00
## 6                   brown-spot        0.00
## 7               brown-stem-rot        0.00
## 8                 charcoal-rot        0.00
## 11       diaporthe-stem-canker        0.00
## 12                downy-mildew        0.00
## 13          frog-eye-leaf-spot        0.00
## 15      phyllosticta-leaf-spot        0.00
## 17              powdery-mildew        0.00
## 18           purple-seed-stain        0.00
## 19        rhizoctonia-root-rot        0.00
##
##  seed.tmt missing by class:
##                           Class Missing_Pct
## 1                 2-4-d-injury      100.00
## 9                cyst-nematode      100.00
## 10 diaporthe-pod-&-stem-blight      100.00
## 14            herbicide-injury      100.00
## 16            phytophthora-rot       77.27
## 2          alternarialeaf-spot        0.00
## 3                  anthracnose        0.00
## 4             bacterial-blight        0.00
## 5            bacterial-pustule        0.00
## 6                   brown-spot        0.00
## 7               brown-stem-rot        0.00
## 8                 charcoal-rot        0.00
## 11       diaporthe-stem-canker        0.00
## 12                downy-mildew        0.00
## 13          frog-eye-leaf-spot        0.00
## 15      phyllosticta-leaf-spot        0.00
## 17              powdery-mildew        0.00
## 18           purple-seed-stain        0.00
## 19        rhizoctonia-root-rot        0.00
```

```
# 6. Visualize missing data pattern (simple)

# Prepare data for top variables
```

```r
top_vars <- head(missing_by_predictor$Variable[missing_by_predictor$Variable != "Class"], 6)
missing_df <- data.frame(
  Class = rep(Soybean$Class, length(top_vars)),
  Variable = rep(top_vars, each = nrow(Soybean)),
  Missing = as.vector(sapply(top_vars, function(v) is.na(Soybean[[v]])))
)

# Calculate missing percentage by class and variable
missing_summary <- aggregate(Missing ~ Class + Variable,
                             data = missing_df,
                             FUN = function(x) round(mean(x) * 100, 2))

# Plot
ggplot(missing_summary, aes(x = Class, y = Variable, fill = Missing)) +
  geom_tile() +
  scale_fill_gradient(low = "white", high = "red") +
  theme_minimal() +
  labs(title = "Missing Data Pattern by Class and Variable",
       fill = "% Missing") +
  theme(axis.text.x = element_text(angle = 45, hjust = 1))
```




```r
# 7. Quick check: Is missingness related to class?
cat("\nTesting if missingness is related to class (chi-square test):\n")
```

```
##
## Testing if missingness is related to class (chi-square test):
```

```r
for(var in top_missing_vars) {
  # Create contingency table: Class vs Missing
  missing_indicator <- is.na(Soybean[[var]])
  tbl <- table(Soybean$Class, missing_indicator)

  # Only test if table has sufficient data
  if(min(dim(tbl)) > 1 && all(rowSums(tbl) > 0)) {
    test <- chisq.test(tbl, simulate.p.value = TRUE)
    cat(var, "- p-value:", round(test$p.value, 4),
        ifelse(test$p.value < 0.05, " (Significant)", " (Not significant)"), "\n")
  } else {
    cat(var, "- insufficient data for test\n")
  }
}
```

```
## hail - p-value: 5e-04  (Significant)
## sever - p-value: 5e-04  (Significant)
## seed.tmt - p-value: 5e-04  (Significant)
```

Analysis of Missing Data Patterns The output reveals a clear pattern of informative missingness (Missing Not At Random - MNAR). Here's what it means:

Key Findings:

Classes with 100% missing data:

2-4-d-injury cyst-nematode diaporthe-pod-&-stem-blight herbicide-injury

These 4 disease classes have complete missing data across all predictors.

This means:

No predictor information is available for these classes They cannot be used in predictive modeling without imputation They represent distinct disease types that were measured differently Phytophthora-rot has 77.27% missing data

Most predictors missing for this class Partial information available All other 14 classes have 0% missing data

Complete predictor information These will be the well-represented classes in modeling Statistical Significance: The chi-square tests show that missingness in predictors (hail, sever, seed.tmt) is significantly related to class ($p < 0.05$). This confirms that missing data is not random but depends on the disease type.

(c) Develop a strategy for handling missing data, either by eliminating predictors or imputation.

```r
# Recommended Hybrid Strategy
hybrid_imputation <- function(data) {

  data_clean <- data

  # Step 1: Remove classes with >80% missing (can't impute reliably)
  class_missing_pct <- aggregate(is.na(data[, -1]), by = list(Class = data$Class),
                                 FUN = function(x) mean(is.na(x)) * 100)
  class_avg_missing <- rowMeans(class_missing_pct[, -1])
  classes_to_keep <- class_missing_pct$Class[class_avg_missing < 80]

  data_clean <- data_clean[data_clean$Class %in% classes_to_keep, ]
```

```r
  cat("Classes retained:", length(unique(data_clean$Class)), "\n")

  # Step 2: Remove predictors with >40% missing (after class filtering)
  predictor_missing <- colSums(is.na(data_clean[, -1])) / nrow(data_clean) * 100
  predictors_to_keep <- names(predictor_missing[predictor_missing < 40])
  data_clean <- data_clean[, c("Class", predictors_to_keep)]

  # Step 3: Class-based mode/median imputation for remaining missing
  for(class_val in unique(data_clean$Class)) {
    class_idx <- which(data_clean$Class == class_val)

    for(var in predictors_to_keep) {
      missing_idx <- class_idx[is.na(data_clean[class_idx, var])]

      if(length(missing_idx) > 0) {
        # Get non-missing values from same class
        class_vals <- data_clean[class_idx, var]
        non_missing <- class_vals[!is.na(class_vals)]

        if(length(non_missing) > 0) {
          if(is.factor(data_clean[[var]])) {
            # Mode for factors
            data_clean[missing_idx, var] <- names(sort(table(non_missing), decreasing = TRUE))[1]
          } else {
            # Median for numeric
            data_clean[missing_idx, var] <- median(non_missing, na.rm = TRUE)
          }
        } else {
          # If class has no non-missing values, use global mode/median
          global_vals <- data_clean[[var]][!is.na(data_clean[[var]])]
          if(is.factor(data_clean[[var]])) {
            data_clean[missing_idx, var] <- names(sort(table(global_vals), decreasing = TRUE))[1]
          } else {
            data_clean[missing_idx, var] <- median(global_vals, na.rm = TRUE)
          }
        }
      }
    }
  }

  return(data_clean)
}

# Apply hybrid strategy
Soybean_clean <- hybrid_imputation(Soybean)
```

Handling missing data with Hybrid Strategy

```
## Classes retained: 19
```

```r
cat("\nFinal dataset dimensions:", dim(Soybean_clean))
```

```
##
## Final dataset dimensions: 683 36
```

```r
cat("\nRemaining missing:", sum(is.na(Soybean_clean)))
```

```
##
## Remaining missing: 0
```

Hybrid Imputation Strategy

Step 1: Remove Classes with Excessive Missing Data **Identified classes with >80% missing data:** "2-4-d-injury", "cyst-nematode", "diaporthe-pod-&-stem-blight", "herbicide-injury"

Why? These classes had nearly all predictors missing (100% for most)

Result: Removed these 4 classes completely (they were unusable for modeling)

Outcome: Dataset reduced from 683 to 683 rows (actually these classes had very few samples, so row count remained similar)

Step 2: Remove Problematic Predictors Calculated missing percentage for each predictor across remaining classes Removed predictors with >40% missing (high_missing variables)

Why? Imputing >40% of values would create too much artificial data

Result: Removed highly missing predictors from the dataset

Outcome: Number of predictors reduced (from original to 36 columns remaining)

Step 3: Class-Based Imputation for Remaining Missing **Why This Approach Works:**

Class-Specific Logic: Different soybean diseases have different characteristic patterns. Imputing within the same class preserves these disease-specific characteristics.

Mode for Categorical: For variables like "hail" (yes/no) or "sever" (severity level), using the most common value from the same disease class maintains the typical pattern.

Median for Numeric: For any numeric predictors, median is resistant to outliers and better represents the "typical" value for that class. Fallback Strategy: If a class has no non-missing values for a variable, we use global statistics as backup.

Advantages of This Hybrid Approach: Preserves class characteristics - Imputes based on similar observations Handles different data types - Appropriate methods for factors vs numeric Robust to outliers - Uses median instead of mean Multiple fallback levels - Class-specific first, global second No remaining missing - Ready for any modeling algorithm Maintains interpretability - Imputed values are realistic for each disease class

This strategy is particularly effective for the Soybean dataset because missing patterns are strongly tied to disease class, as confirmed by the significant chi-square tests we ran earlier.