Page 3 Practical Task — Agent Ka Working Loop

Source: *AI Coding Agents: Intern se Confident*, Page 3

Date: 20 October 2026

1. Objective

Demonstrate the supervised agent loop and distinguish a proposed action from an executed, observed and verified result.

2. Implemented workflow

Step	What was done
Task	Defined the bounded goal: make task-status matching case-insensitive.
Inspect	Reviewed the small filter function and focused test cases.
Propose	Normalize selected status and task status to lowercase; preserve the All branch.
Policy check	Local fake data only; no API, database, secrets, or external dependency.
Execute / Observe	Ran `node --test` before the fix and saved the actual failing output.
Adjust	Applied the bounded normalization fix in `src/statusFilter.js`.
Verify	Reran `node --test` and saved the actual final output.
Handoff	Recorded scope, change, test command, results, and limitations.

3. Test evidence

Run	Actual result
Before fix — `node --test`	Exit code 1; the case-insensitive Done test failed as expected.
After fix — `node --test`	Exit code 0; all four tests passed.

4. Files included

`README.md`, `AGENT_WORKING_LOOP.md`, `src/statusFilter.js`, `test/statusFilter.test.js`, `package.json`, and the `evidence/` folder containing both actual test outputs and the handoff report.

5. Conclusion

The demonstration follows the loop: propose → execute → observe → adjust → verify → handoff. The initial failure and final passing result are recorded separately so an attempted command is not confused with a verified result.

Scope note: This is a local learning demo using fake data, not a full UI, production integration, or real pull request.