

IoT-Based Home Automation Using Digital Logic

Project Documentation Report

Title:

IoT-Based Home Automation Using Digital Logic

Abstract:

The IoT-Based Home Automation Using Digital Logic project is designed to automate household appliances using sensors, digital logic circuits, and wireless communication technologies. The system uses an ESP32 microcontroller to monitor environmental conditions and control appliances automatically. Sensors such as PIR and LDR detect motion and light intensity, while logic gates process the sensor outputs to make intelligent decisions.

The project supports remote monitoring and control through Wi-Fi or Bluetooth communication. Power optimization techniques such as sleep mode, CMOS logic implementation, and clock gating are incorporated to reduce energy consumption. This project demonstrates the practical integration of Internet of Things (IoT), digital electronics, embedded systems, and VLSI concepts for smart home applications.

Introduction:

Home automation systems are becoming increasingly important in modern smart homes. Traditional electrical systems require manual operation, which may lead to unnecessary power consumption and reduced convenience. IoT technology allows appliances to be monitored and controlled remotely through the internet or wireless communication methods.

This project focuses on implementing a smart home automation system using digital logic circuits and IoT technology. The system automatically controls lights and appliances based on environmental conditions and user commands. The project also emphasizes low-power design techniques commonly used in VLSI systems.

Objectives:

- To automate household appliances using sensors and digital logic.
- To interface sensors and actuators with a microcontroller.
- To provide remote appliance control using Wi-Fi or Bluetooth.
- To implement low-power optimization techniques.
- To demonstrate practical applications of IoT and VLSI concepts.


Components Required

S.No	Component	Quantity	Purpose
1	ESP32 / NodeMCU	1	Main microcontroller with Wi-Fi/Bluetooth
2	PIR Sensor	1	Motion detection
3	LDR Sensor	1	Light intensity sensing
4	Relay Module	1	Appliance switching
5	LED	1	Light indication
6	Buzzer	1	Alert indication
7	Logic Gate ICs	1	Digital logic operations
8	Breadboard	1	Circuit assembly
9	Connecting Wires	Several	Circuit connections
10	Power Supply	1	Powering the system



Software and Tools Used

Software	Purpose
Arduino IDE	Programming ESP32
Wokwi / Tinkercad	Circuit simulation
GitHub	Project hosting
Proteus (Optional)	Advanced simulation

Block Diagram



Block Diagram: Design and Implementation of a Home Automation System Using IOT.



Description of Blocks

1. **Sensors**
PIR and LDR sensors collect environmental data.
2. **Digital Logic Circuit**
Logic gates process sensor outputs using Boolean operations.
3. **ESP32 Microcontroller**
Controls the system and manages wireless communication.
4. **Relay Driver Circuit**
Interfaces high-voltage appliances safely.
5. **Wi-Fi/Bluetooth Module**
Enables remote communication and monitoring.
6. **Appliances**
Lights and devices are controlled automatically.

Circuit Description

The PIR sensor detects human movement and generates a digital HIGH signal. The LDR sensor identifies whether the room is dark or bright. The outputs of both sensors are combined using an AND gate logic condition.

When motion is detected in a dark environment, the ESP32 activates the relay module to switch ON the light automatically. Users can also control appliances remotely using Wi-Fi or Bluetooth communication.

The relay driver isolates the low-voltage control circuit from high-voltage appliances for safe operation.

Boolean Logic Used

Motion and Darkness Detection

The light should turn ON only when:

- Motion is detected
- Room is dark

Boolean equation:

$Y = A \cdot B$

Where:

- (A) = PIR sensor output
- (B) = LDR sensor output
- (Y) = Light output

Truth Table:

PIR (A) LDR (B) Output (Y)

0	0	0
---	---	---

PIR (A) LDR (B) Output (Y)

0	1	0
1	0	0
1	1	1



Working Principle

1. The system continuously monitors the sensors.
2. The PIR sensor detects motion.
3. The LDR sensor detects ambient light conditions.
4. Digital logic circuits process sensor inputs.
5. If motion is detected in darkness, the relay turns ON the light.
6. The ESP32 sends appliance status through Wi-Fi/Bluetooth.
7. Users can remotely control appliances using a mobile device.
8. When no activity is detected, the system enters low-power mode.

Algorithm

1. Start the system.
2. Initialize sensors and communication modules.
3. Read PIR sensor value.
4. Read LDR sensor value.
5. Apply logic conditions.
6. Control relay output.
7. Check remote commands.
8. Update appliance status.
9. Repeat continuously.

Flowchart



SMART HOUSE

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed diam nonummy nibh euismod tincidunt ut laoreet dolore magna aliquam erat volutpat.

Lorem ipsum dolor sit amet
consectetur adipiscing elit, sed
diam nonummy.

SMART HOME



Lorem ipsum dolor sit amet
consectetur adipiscing elit, sed
diam nonummy.

ENERGY MANAGEMENT



Lorem ipsum dolor sit amet
consectetur adipiscing elit, sed
diam nonummy.

SMART WATER SYSTEM




Lorem ipsum dolor sit amet
consectetur adipiscing elit, sed
diam nonummy.

ALARM SYSTEM


Lorem ipsum dolor sit amet
consectetur adipiscing elit, sed
diam nonummy.

APPLIANCES CONTROL



Lorem ipsum dolor sit amet
consectetur adipiscing elit, sed
diam nonummy.

SECURITY SYSTEM



Arduino Code

```
#define PIR 4

#define RELAY 5

#define LDR 34


void setup() {
    pinMode(PIR, INPUT);
    pinMode(RELAY, OUTPUT);

    Serial.begin(9600);
}

void loop() {

    int motion = digitalRead(PIR);
    int light = analogRead(LDR);

    if(motion == HIGH && light < 500) {
        digitalWrite(RELAY, HIGH);
        Serial.println("Light ON");
    }

    else {
        digitalWrite(RELAY, LOW);
        Serial.println("Light OFF");
    }

    delay(1000);
}
```

Power Optimization Techniques

1. Sleep Mode

The ESP32 enters deep sleep mode during inactivity to reduce power consumption.

2. CMOS Logic

CMOS-based logic gates consume low static power and improve efficiency.

3. Clock Gating

Unused modules are disabled temporarily to minimize switching activity.

4. Sensor-Based Automation

Appliances operate only when required, reducing unnecessary power usage.

Power consumption equation:

$$P = \alpha C V^2 f$$

Where:

- (P) = Power
- (C) = Capacitance
- (V) = Supply Voltage
- (f) = Frequency
- (α) = Switching Activity

Advantages

- Reduced power consumption
- Remote appliance control
- Improved convenience
- Increased home security
- Low-cost implementation
- Easy system expansion

Applications

- Smart homes
 - Smart offices
 - Industrial automation
 - Security systems
 - Smart lighting control
-

Result

The IoT-Based Home Automation system was successfully designed and implemented using ESP32, sensors, and digital logic circuits. The system automatically controlled appliances based on environmental conditions and supported wireless remote control. Low-power optimization techniques effectively reduced energy consumption while maintaining reliable operation.

Future Scope

- Integration with voice assistants such as Alexa and Google Assistant
 - Mobile application development
 - Cloud-based monitoring and analytics
 - AI-based automation
 - Smart energy management
 - Facial recognition-based security systems
-

Conclusion

The IoT-Based Home Automation Using Digital Logic project demonstrates an efficient and intelligent approach to smart home automation. By integrating sensors, digital logic circuits, wireless communication, and low-power VLSI techniques, the system provides automation, energy efficiency, and remote accessibility. The project successfully combines embedded systems and IoT technologies to create a modern smart home solution suitable for future expansion and real-world implementation.

References

1. ESP32 Datasheet
2. Arduino IDE Documentation
3. IoT and Embedded Systems Reference Materials
4. Digital Electronics and VLSI Design Textbooks
5. Sensor Datasheets (PIR and LDR)