Gmail mehul chandroliya <mehul.chandroliya@gmail.com>

(no subject)

mehul chandroliya <mehul.chandroliya@gmail.com> Fri 30 Oct at 07:11
To: mehul chandroliya <mehul.chandroliya@gmail.com>

Below is the **comprehensive reference list of Microsoft Dataverse system and platform tables** where granting **Create** and/or **Write** privileges (especially at **Organization** or **Parent: Child Business Unit** scope) creates a high risk of privilege escalation, remote code execution, security bypass, or complete system takeover—effectively making the access equivalent to **System Administrator** or **System Customizer**.

1. Role Assignment & Security Hierarchy (Direct Privilege Escalation)

Writing or creating records in these tables allows a user to elevate their own permissions or assign administrative roles directly to themselves or others.

Table Name	Logical / Schema Name	Risk & Elevation Path
Role	`role`	Controls role definitions and security scopes. Modifying or creating records lets users alter security limits or craft custom roles with unconstrained access.
System User Roles	`systemuserroles`	Intersect table mapping users to security roles. **Creating or modifying a row here allows assigning System Administrator or System Customizer directly to any user account.**
Team Roles	`teamroles`	Intersect table mapping teams to security roles. Writing here allows assigning administrative security roles to a team, elevating all team members.
Privilege	`privilege`	Defines individual security privileges in the system. Direct manipulation alters system-wide permission boundaries.
Role Privileges	`roleprivileges`	Maps privileges to security roles. Modifying this table grants additional permissions to existing custom or baseline roles.
Field Security Profile	`fieldsecurityprofile`	Controls Column-Level Security (CLS). Writing here allows removing restrictions on secured columns (e.g., social security numbers, passwords, financial keys).
System User Field Security Profiles	`systemuserprofiles`	Maps users to column security profiles. Writing here grants access to protected columns.
Business Unit	`businessunit`	Defines the top-level security boundaries and organizational structure. Writing/creating records alters parent-child BU hierarchies and scope inheritance.

2. Business Logic, Plug-ins & Code Execution (System Code Takeover)

Dataverse executes plugins, custom workflows, and API integrations with system-level backend privileges. Writing or creating records in these tables allows arbitrary server-side code execution.

Table Name	Logical / Schema Name	Risk & Elevation Path
Plug-in Assembly	`pluginassembly`	Contains compiled .NET DLL binaries. **Creating/writing allows uploading custom code** that executes on the server under elevated host process context.
Plug-in Type	`plugintype`	Defines classes within compiled plugin assemblies. Writing here registers new logic types for platform execution.
SDK Message	`sdkmessageprocessingstep`	Controls *when* and *on which events* (Create/Update/Delete of any table) plugins fire. Writing

Processing Step		here allows intercepting data across all system operations or altering business logic transactions.
SDK Message Processing Step Image	`sdkmessageprocessingstepimage`	Defines pre- and post-entity images passed to plugins during execution, allowing interception of sensitive record states.
Service Endpoint	`serviceendpoint`	Configures Azure Service Bus, Event Hubs, or Webhooks. Writing here allows exfiltrating Dataverse transaction streams to external endpoints.
Custom API	`customapi`	Defines custom API definitions and request parameters. Creating/writing enables custom unbound or bound platform endpoints.
Custom API Request Parameter / Response Property	`customapirequestparameter`, `customapiresponseproperty`	Alters input validation and parameter mapping for custom API endpoints.

3. Automation, Workflows & Power Automate (Logic Bypass)

Dataverse workflows and classic processes execute under the owner's context or system impersonation.

Table Name	Logical / Schema Name	Risk & Elevation Path
Process / Workflow	`workflow`	Stores Power Automate cloud flows, classic workflows, action processes, and business rules. Creating or modifying records allows executing logic as a System Admin or bypassing validations.
Process Trigger	`processtrigger`	Dictates event conditions that invoke processes. Writing here attaches unauthorized automated logic to critical data events.
Workflow Dependency	`workflowdependency`	Defines dependencies between processes and entities/attributes. Modifying this corrupts or alters execution trees.

4. Metadata, Schema & Solution Architecture (Structural Administrative Control)

These tables store entity-attribute-relationship (EAR) schemas and solution package components.

Table Name	Logical / Schema Name	Risk & Elevation Path
Entity / Table	`entity`	Stores table-level system metadata. Creating or editing metadata modifies data structures, ownership types, and security constraints across the platform.
Attribute / Column	`attribute`	Stores column metadata. Writing allows altering field properties, audit logging toggles, or key boundaries.
Relationship Metadata	`relationship` / `one-to-many-relationship`	Dictates database foreign keys and cascading delete/assign rules across system tables.
Solution	`solution`	Packages customizations, components, and code. **Creating/writing solution records allows deploying unmanaged packages** that overwrite core security configurations or schema settings.
Solution Component	`solutioncomponent`	Intersect table mapping components to solutions. Writing here forces modified components into existing system solutions.
Publisher	`publisher`	Defines solution publishers and prefix controls (`new_`, `cr123_`). Writing allows impersonating official Microsoft or ISV publishers.

5. Security Identities, Users & Application Access

Tables defining non-interactive system users, service principals, and API access.

Table Name	Logical / Schema Name	Risk & Elevation Path
User / System User	`systemuser`	Contains environment user records. Creating or modifying user records (e.g., updating email, user status, or application user IDs) allows user impersonation or account takeover.
Application		Stores Microsoft Entra ID (Azure AD) App Registrations

User / Application ID	`applicationuser`	mapped into Dataverse. Creating/modifying application users allows assigning non-human service principals full administrative roles without MFA.
Connection Reference	`connectionreference`	Links flows and logic apps to embedded authentication credentials. Creating or modifying references allows hijacking existing API connections.
Environment Variable Definition	`environmentvariabledefinition`	Holds configuration keys used by flows and plugins.
Environment Variable Value	`environmentvariablevalue`	Stores runtime environment variable values (e.g., secret endpoints, database connection strings, Azure tenant IDs). Writing here redirects application traffic to malicious endpoints.

6. System Governance, Auditing & Web Application Controls

Table Name	Logical / Schema Name	Risk & Elevation Path
Audit	`audit`	Stores transaction logs. Direct write access allows tempering with or deleting audit trails to cover malicious changes.
Organization	`organization`	Contains tenant/environment global settings (e.g., enabling/disabling auditing, system maintenance modes, security defaults). Modifying this alters global environment behavior.
Web Resource	`webresource`	Stores HTML, JavaScript, CSS, and image files used in forms/apps. **Creating/writing allows injecting XSS scripts** into Model-Driven Apps or Portals that run under the session context of System Administrators.
Site Map	`sitemap`	Defines app navigation structures. Modifying this can expose hidden administrative forms or hide critical security controls.
System Form	`systemform`	Stores form and dashboard layouts. Writing allows injecting malicious JavaScript libraries into main entity forms.

Key Takeaway for Governance & Security Auditing

Standard Dataverse RBAC enforces that **none** of these listed tables should ever have **Organization-level Create or Write** privileges assigned in custom security roles for non-admin users. Granting Create or Write privileges on any table in this list creates a **privilege escalation path** that effectively renders the user a **System Administrator**.