

**ZAP**
by
Checkmarx

ZAP Scanning Report

Sites: https://host.docker.internal:5139 http://host.docker.internal:5139**Generated on Sat, 16 May 2026 18:16:10****ZAP Version: 2.17.0****ZAP by** [Checkmarx](#)

Summary of Alerts

Risk Level	Number of Alerts
High	0
Medium	1
Low	0
Informational	1
False Positives:	0

Insights

Level	Reason	Site	Description	Statistic
Info	Informational		Percentage of network failures	4 %
Info	Informational	http://host.docker.internal:5139	Percentage of responses with status code 4xx	99 %
Info	Informational	http://host.docker.internal:5139	Percentage of endpoints with method GET	100 %
Info	Informational	http://host.docker.internal:5139	Count of total endpoints	3
Info	Informational	https://host.docker.internal:5139	Percentage of endpoints with method GET	100 %
Info	Informational	https://host.docker.internal:5139	Count of total endpoints	1

Summary of Sequences

For each step: result (Pass/Fail) - risk (of highest alert(s) for the step, if any).

Alerts

Name	Risk Level	Number of Instances
HTTP Only Site	Medium	1
Storable and Cacheable Content	Informational	4

Alert Detail

Medium	HTTP Only Site
Description	The site is only served under HTTP and not HTTPS.

URL	http://host.docker.internal:5139/
Node Name	https://host.docker.internal:5139/
Method	GET
Parameter	
Attack	
Evidence	
Other Info	Failed to connect. ZAP attempted to connect via: https://host.docker.internal:5139/
Instances	1
Solution	Configure your web or application server to use SSL (https).
Reference	https://cheatsheetseries.owasp.org/cheatsheets/Transport_Layer_Protection_Cheat_Sheet.html https://letsencrypt.org/
CWE Id	311
WASC Id	4
Plugin Id	10106

Informational**Storable and Cacheable Content**

Description	The response contents are storable by caching components such as proxy servers, and may be retrieved directly from the cache, rather than from the origin server by the caching servers, in response to similar requests from other users. If the response data is sensitive, personal or user-specific, this may result in sensitive information being leaked. In some cases, this may even result in a user gaining complete control of the session of another user, depending on the configuration of the caching components in use in their environment. This is primarily an issue where "shared" caching servers such as "proxy" caches are configured on the local network. This configuration is typically found in corporate or educational environments, for instance.
-------------	--

URL	http://host.docker.internal:5139/
Node Name	http://host.docker.internal:5139
Method	GET
Parameter	
Attack	
Evidence	
Other Info	In the absence of an explicitly specified caching lifetime directive in the response, a liberal lifetime heuristic of 1 year was assumed. This is permitted by rfc7234.

URL	http://host.docker.internal:5139/
Node Name	http://host.docker.internal:5139/
Method	GET
Parameter	
Attack	
Evidence	
Other Info	In the absence of an explicitly specified caching lifetime directive in the response, a liberal lifetime heuristic of 1 year was assumed. This is permitted by rfc7234.

URL	http://host.docker.internal:5139/robots.txt
Node Name	http://host.docker.internal:5139/robots.txt
Method	GET
Parameter	
Attack	

Evidence	
Other Info	In the absence of an explicitly specified caching lifetime directive in the response, a liberal lifetime heuristic of 1 year was assumed. This is permitted by rfc7234.
URL	http://host.docker.internal:5139/sitemap.xml
Node Name	http://host.docker.internal:5139/sitemap.xml
Method	GET
Parameter	
Attack	
Evidence	
Other Info	In the absence of an explicitly specified caching lifetime directive in the response, a liberal lifetime heuristic of 1 year was assumed. This is permitted by rfc7234.
Instances	4 Validate that the response does not contain sensitive, personal or user-specific information. If it does, consider the use of the following HTTP response headers, to limit, or prevent the content being stored and retrieved from the cache by another user: Cache-Control: no-cache, no-store, must-revalidate, private
Solution	Pragma: no-cache Expires: 0 This configuration directs both HTTP 1.0 and HTTP 1.1 compliant caching servers to not store the response, and to not retrieve the response (without validation) from the cache, in response to a similar request. https://datatracker.ietf.org/doc/html/rfc7234 https://datatracker.ietf.org/doc/html/rfc7231 https://www.w3.org/Protocols/rfc2616/rfc2616-sec13.html
Reference	
CWE Id	524
WASC Id	13
Plugin Id	10049

Sequence Details

With the associated active scan results.