

Augmented Reality & Video Service Emerging Technologies


AR Technology

Prof. Jong-Moon Chung

AR Technology

AR Feature Extraction


AR System Process



AR Feature Extraction

❖ AR Feature Extraction Process


- 1. GIG: Grayscale Image Generation
- 2. IIG: Integral Image Generation
- 3. RMG: Response Map Generation



AR Feature Extraction

❖ AR Feature Extraction Process

4. IPD: Interest
Point Detection
5. OA: Orientation
Assignment
6. DE: Descriptor
Extraction



AR Feature Extraction

❖ Feature Extraction Procedures

1. GIG (Grayscale Image Generation)
 - Original image captured by the AR device is changed into a grayscale valued image in order to make it robust to color modifications
2. IIG (Integral Image Generation)
 - Process of building an integral image from the grayscale image
 - This procedure enables fast calculation of summations over image sub-regions

AR Feature Extraction

❖ Feature Extraction Procedures

3. RMG (Response Map Generation)

- In order to detect IPs (Interest Points) using the determinant of the image's Hessian matrix, the RMG process constructs the scale-space of the image

4. IPD (Interest Point Detection)

- Based on the generated scale response maps, the maxima and minima (i.e., extrema) are detected and used as the IPs

AR Feature Extraction

❖ Feature Extraction Procedures

5. OA (Orientation Assignment)

- Each detected IP is assigned a reproducible orientation to provides rotation invariance (i.e., invariance to image rotation)

6. DE (Descriptor Extraction)

- Process of uniquely identifying an IP, such that it is distinguished from other IPs

AR Feature Extraction

❖ Feature Extraction

- Finding the Interest Points from the image/video
- Detecting the Descriptors from Interest Points and compare the descriptors with data in the database



Original Image

Gray Scale

Interest Point

Descriptors

AR Feature Extraction

❖ Feature Extraction

- Qualification for Descriptors
 - Invariability from Noise, Scale, Rotation, etc.
- Kinds of Descriptors
 - Corner
 - Blob
 - Region

AR Feature Extraction

❖ Blob Detection

- LoG (Laplacian of Gaussian)
- Hessian Matrix (H): 2nd order derivative
 - Hessian (determinant of H)
 - Laplacian (trace of H)
- Blob Detection Example



AR Feature Extraction

❖ Blob Detection

- Blob Detection
 - Process of detecting blobs in an image
- Blob
 - Region of an image that has constant (or approximately constant) image properties
→ All the points in a blob are considered to be similar to each other
 - These image properties (i.e., brightness, color, etc.) are used in the comparison process to surrounding regions

AR Feature Extraction

❖ Typical Feature Extraction Techniques

- Haar feature
 - P. Viola, et al., 2001
- SIFT (Scale Invariant Feature Transform)
 - D. G. Lowe, 2004
- HOG (Histogram of Oriented Gradient)
 - N. Dalal, et al., 2005
- SURF (Speeded Up Robust Features)
 - H. Bay, et al., 2006
- ORB (Oriented FAST and Rotated BRIEF)
 - E. Rublee, et al., 2011

AR Technology

References

References

- T. Olsson and M. Salo, "Online User Survey on Current Mobile Augmented Reality Applications," Proc. IEEE International Symposium on Mixed and Augmented Reality, pp. 75-84, Oct. 2011.
- K. Kumar and Y. Lu, "Cloud Computing for Mobile Users: Can Offloading Computation Save Energy?," IEEE Computer, vol. 43, no. 4, pp. 51-56, Apr. 2010.
- B. Girod, V. Chandrasekhar, R. Grzeszczuk, and Y. Reznik, "Mobile Visual Search: Architectures, Technologies, and the Emerging MPEG Standard," IEEE Multimedia, vol. 18, no. 3, pp. 86-94, Mar. 2011.
- D. Lowe, "Distinctive Image Features from Scale-Invariant Keypoints," International Journal of Computer Vision, vol. 60, no. 2, pp. 91-110, Nov. 2004.
- H. Bay, A. Ess, T. Tuytelaars, and L. Van Gool, "Speeded-Up Robust Features (SURF)," Computer Vision and Image Understanding, vol. 110, no. 3, pp 346-359, Jun. 2008.

References

- P. Drews, R. de Bem, and A. de Melo, "Analyzing and Exploring Feature Detectors in Images," Proc. IEEE International Conference on Industrial Informatics, pp. 305-310, Jul. 2011.
- L. Juan and O. Gwun, "A Comparison of SIFT, PCA-SIFT and SURF," International Journal of Image Processing, vol. 3, no. 4, pp. 143-152, Aug. 2009.
- D. Jin, K. Um, and K. Cho, "Development of Real-Time Markerless Augmented Reality System Using Multi-thread Design Patterns," Computer Graphics and Broadcasting Communications in Computer and Information Science, Multimedia, vol. 262, pp. 155-164, Dec. 2011.
- M. Satyanarayanan, "A Brief History of Cloud Offload: A Personal Journey from Odyssey Through Cyber Foraging to Cloudlets," GetMobile, vol. 18, no. 4, pp. 19-23, Oct. 2014.
- Y. Zhang, H. Liu, L. Jiao, and X. Fu, "To offload or not to offload: an efficient code partition algorithm for mobile cloud computing," Proc. IEEE International Conference on Cloud Networking, pp. 80-86, Nov. 2012.

References

- J.-M. Chung, Y.-S. Park, J.-H. Park, and H. Cho, "Adaptive Cloud Offloading of Augmented Reality Applications on Smart Devices for Minimum Energy Consumption," *KSII Trans. Internet Inf. Syst.*, vol. 9, no. 8, pp. 3090-3102, Aug. 2015.
- T. Lindeberg, "A Survey of Recent Advances in Visual Feature Detection," *Neurocomputing*, vol. 149, pp. 736-751, 2015.
- Y. Li, S. Wang, Q. Tian, and X. Ding "Scale-Space Theory: A Basic Tool for Analysing Structures at Different Scales," *Journal of Applied Statistics*, vol. 21, no. 2, pp. 224-270, 1994.
- D. Lowe, "Distinctive Image Features from Scale-Invariant Keypoints," *Int. Journal of Computer Vision*, vol. 60, no. 2, pp. 91-110, Nov. 2004.
- H. Bay, A. Ess, T. Tuytelaars, and L. Van Gool, "Speeded-Up Robust Features (SURF)," *Computer Vision and Image Understanding*, vol. 110, no. 3, pp. 346-359, June 2008.
- E. Rosten and T. Drummond, "Machine Learning for High-speed Corner Detection," in *Proc. of the 9th European Conf. on Computer Vision (ECCV '06)*, Graz, Austria, May 2006, pp. 430-443.
- M. Calonder, V. Lepetit, C. Strecha, and P. Fua, "BRIEF: Binary Robust Independent Elementary Features," in *Proc. European Conf. on Computer Vision (ECCV 2010)*, Heraklion, Greece, Sep. 2010, pp. 778-792.
- E. Rublee, V. Rabaud, K. Konolige, and G. Bradski, "ORB: An Efficient Alternative to SIFT or SURF," in *Proc. 2011 IEEE Int. Conf. on Computer Vision (ICCV)*, Barcelona, Spain, Nov. 2011, pp. 2564-2571.
- S. Leutenegger, M. Chli, and R. Siegwart, "BRISK: Binary Robust Invariant Scalable Keypoints," in *Proc. 2011 IEEE Int. Conf. on Computer Vision (ICCV)*, Barcelona, Spain, Nov. 2011, pp. 2548-2555.
- E. Mair, G. Hager, D. Burschka, M. Suppa, and G. Hirzinger, "Adaptive and Generic Corner Detection Based on the Accelerated Segment Test," in *Proc. European Conference on Computer Vision (ECCV 2010)*, Heraklion, Greece, Sep. 2010, pp. 183-196.
- Yong-Suk Park, "Computation Resource Allocation Through Smart Device Ad-hoc Cloud Establishment in Mobile Environments." Ph.D. Dissertation, Yonsei University, 2018.