
Big Data Spark Streaming




- Spark Streaming Characteristics
 - Extension to the Spark Core API
 - Live data streams can be processed
 - Fault-tolerant and scalable
 - High throughput (near) real-time data processing → 0.5 s or longer
 - Streaming data input from HDFS, Kafka, Flume, TCP sockets, Kinesis, etc.

Spark Streaming

- Spark Streaming Characteristics
 - Stream processing high-level functions
 - · Map, Reduce, Join, Window, etc.
 - Processed Output saved on Filesystems,
 Databases, and Live Dashboards
 - Spark ML (Machine Learning) functions and GraphX graph processing algorithms are fully applicable to streaming data

- ❖ Spark Streaming Characteristics
 - Spark uses (size controllable) micro-batch processing of data for real-time analysis
 - Hadoop uses batch processing of data, which is time consuming to obtain results
 - Spark uses RDD to arrange data and recover from failures



Streaming Receiver Types

- Basic
 - File systems
 - Socket connectors
 - Akka Actors
 - Sources directly available in Streaming Context API

Spark Streaming

Streaming Receiver Types

- Custom
 - Requires implementing an user-defined receiver
- Advanced
 - Requires linking with systems that have extra dependencies
 - · Kafka, Flume, Twitter

Spark Streaming process

- 1. Live input data stream received
- Input data stream is divided into Mini-Batches called a DStream (Discretized Stream), which is saved as a small RDD every mini-batch period
- 3. Spark Stream engine cores process the mini-batches and generate a final output stream of mini-batches

Spark Streaming

DStream

- DStream (Discretized Stream) is a continuous stream of data with high-level abstraction
- DStreams are created from input data stream sources (Kafka, Flume, Kinesis, etc.) or high-level processing operations on other DStreams

DStream

- DStreams are represented as a sequence of small RDDs
- Mini-Batch size is 0.5 s or longer
- RDD is processed through the DAG
- Processing latency (through the DAG)
 has to be smaller than the mini-batch
 period

Spark Streaming

Window Operations

- Window Length
 - Number of blocks (partitions) to conduct a RDD DAG process together



- Sliding Interval
 - Number of blocks (partitions) to slide the Window after a RDD process is conducted


Transformations for Windows

- Key parameters: windowLength, slideInterval
- window()
- countByWindow()
- reduceByWindow()
- reduceByKeyAndWindow()
- countByValueAndWindow()
- etc.

Spark Streaming

Window Operations

If Window Length > Sliding Interval, then
 Overlap Blocks = (Window Length – Sliding Interval)
 will exist for each RDD process



 Overlap Blocks help to analyze correlation (dependency) of sequential blocks of the streamed data

- Spark Streaming Examples
 - IPTV or Web Page Live statistics
 - Channel or Page view of clicks
 - Use Kafka for buffering
 - · Spark Streaming for processing
 - Draw a Heap Map of the current Channel or Page view clicks



Spark Streaming

- Spark Streaming Examples
 - Sales Product Type Monitoring
 - 1. Online Sales
 - Read through Kafka




- 2. Department Store Sales
 - Read through Flume



Join 2 live data streams into Spark Streaming





- ♦ One Stream Input (e.g., from ‰kafka.)
 - One Task slot in the Executor will serve as a Receiver (thread) to receive the live streaming data into a Block (Partition) of the RDD on the node

- ❖ One Stream Input (e.g., from ‰kāfka.)
 - 2. Receiver will also make a copy of this Partition to another node (e.g., replication factor 2)
 - 3. DAG Transformations are executed on the new RDD

Spark Streaming


❖ Another Stream Added (e.g., from



- On a different node, assign one
 Task slot in the Executor to serve as a
 Receiver (thread) to receive the live
 streaming data into a Block (Partition)
 of the RDD on the node
- 2. Receiver will also make a copy of this Partition to another node (e.g., replication factor 2)

- ❖ Another Stream Added (e.g., from

 - 3. DAG Transformations are executed on the new RDD
 - 4. Union can be used to unify the two RDDs into one RDD



Big Data References

References

- Holden Karau, Andy Konwinski, Patrick Wendell, and Matei Zaharia, Learning Spark: Lightning-Fast Big Data Analysis. 1st Edition. O'Reilly, 2015.
- Sameer Farooqui, Databricks, Advanced Apache Spark Training, Devops Advanced Class, Spark Summit East 2015, http://slideshare.net/databricks, www.linkedin.com/in/blueplastic, March 2015.
- Apache Spark documents (all documents and tutorials were used)
 - http://spark.apache.org/docs/latest/rdd-programming-guide.html
 - http://spark.apache.org/docs/latest/rdd-programming-guide.html#working-with-key-value-pairs
 - https://spark.apache.org/docs/2.2.0/rdd-programming-guide.html#rdd-persistence
- Wikipedia, www.wikipedia.org
- Stackoverflow, https://stackoverflow.com/questions
- Bernard Marr, "Spark Or Hadoop -- Which Is The Best Big Data Framework?," Forbes, Tech, June 22, 2015.
- Quick introduction to Apache Spark, https://www.youtube.com/watch?v=TgiBvKcGL24
- Wide vs Narrow Dependencies, https://github.com/rohgar/scala-spark-4/wiki/Wide-vs-Narrow-Dependencies

References

- Partitions and Partitioning, https://jaceklaskowski.gitbooks.io/mastering-apache-spark/spark-rdd-partitions.html
- Neo4j, "From Relational to Neo4j," https://neo4j.com/developer/graph-db-vs-rdbms/ (last accessed Jan. 1, 2018).

Image Sources

- By Robivy64 at English Wikipedia [Public domain], via Wikimedia Commons
- Teravolt at English Wikipedia [CC BY 3.0 (http://creativecommons.org/licenses/by/3.0)], via Wikimedia Commons
- By Konradr (Own work) [GFDL (http://www.gnu.org/copyleft/fdl.html) or CC-BY-SA-3.0 (http://creativecommons.org/licenses/by-sa/3.0/)], via Wikimedia Commons

Course Title

Big Data Emerging Technologies

❖ Modules

- 1. Big Data Rankings & Products
- 2. Big Data & Hadoop
- 3. Spark
- 4. Spark ML & Streaming
- 5. Storm
- 6. IBM SPSS Statistics Project