

## Wi-Fi & Bluetooth

# Wi-Fi DCF & CSMA/CA

### Wi-Fi DCF & CSMA/CA

#### ❖ Wi-Fi Operations

- Wi-Fi standards use the DCF (Distributed Coordination Function) technique that employs CSMA/CA (Carrier-Sense Multiple Access with Collision Avoidance) networking
- Role of DCF & CSMA/CA
  - Used to avoid communication failure due to packet collision
  - Required because the unlicensed ISM band is used

## Wi-Fi DCF & CSMA/CA

### ❖ Wi-Fi Operations

- CSMA/CA
  - Carrier Sense
    - To avoid communication failure (due to packets colliding), each node listens to the shared medium (i.e., 2.4 & 5 GHz wireless channel) to detect whether another node is communicating or not
  - Collision Avoidance
    - If another node's communication is detected, other nodes will not transmit for a specific period of time (NAV period)

## Wi-Fi DCF & CSMA/CA


### ❖ Wi-Fi Operations

- CSMA/CA (DCF)
  - NAV (Network Allocation Vector)
    - Period of time to wait for another node to complete packet communications
  - RTS (Request To Send) / CTS (Clear To Send)
    - RTS/CTS enables the fine-tune of WLAN operations (a solution to the Hidden Node problem)
    - Communication is requested using a RTS frame
    - CTS frame is used to accept the communication request

## Wi-Fi DCF & CSMA/CA

### ❖ Wi-Fi Operations

- IFS (Inter-Frame Space) Priority
  - Control priority using inter-frame space durations



- SIFS (Short IFS): For immediate response action
  - Between RTS, CTS, and Data time duration
- DIFS (DCF IFS): Minimum medium idle time for contention-based services

## Wi-Fi DCF & CSMA/CA

### ❖ Wi-Fi Operations

- IFS (Inter-Frame Space) Priority
  - Stations use SIFS to maintain the highest priority of channel usage during its transmission opportunity (because it is the shortest duration)
  - $DIFS = SIFS + (2 \times \text{Slot time})$


Standard	Slot time ( $\mu s$ )	SIFS ( $\mu s$ )	DIFS ( $\mu s$ )
IEEE 802.11a	9	16	34
IEEE 802.11b	20	10	50
IEEE 802.11g	9 or 20	10	28 or 50
IEEE 802.11n (2.4 GHz)	9 or 20	10	28 or 50

## Wi-Fi DCF & CSMA/CA

### ❖ Wi-Fi

- CSMA/CA & RTS/CTS

$T = 0$




## Wi-Fi DCF & CSMA/CA

### ❖ Wi-Fi

- CSMA/CA & RTS/CTS

$T = \text{DIFS}$




### Wi-Fi DCF & CSMA/CA

❖ Wi-Fi

- CSMA/CA & RTS/CTS

$T = DIFS + T_{RTS}$




### Wi-Fi DCF & CSMA/CA

❖ Wi-Fi

- CSMA/CA & RTS/CTS

$T = DIFS + T_{RTS} + SIFS$




# Wi-Fi DCF & CSMA/CA

## ❖ Wi-Fi

- CSMA/CA & RTS/CTS

$T = DIFS + T_{RTS} + SIFS + T_{CTS}$




# Wi-Fi DCF & CSMA/CA

## ❖ Wi-Fi

- CSMA/CA & RTS/CTS

$T = DIFS + T_{RTS} + SIFS + T_{CTS}$




### Wi-Fi DCF & CSMA/CA

❖ Wi-Fi

- CSMA/CA & RTS/CTS

$T = DIFS + T_{RTS} + SIFS + T_{CTS} + SIFS$




### Wi-Fi DCF & CSMA/CA

❖ Wi-Fi

- CSMA/CA & RTS/CTS

$T = DIFS + T_{RTS} + SIFS + T_{CTS} + SIFS + T_{DATA} + SIFS$




### Wi-Fi DCF & CSMA/CA

❖ Wi-Fi

- CSMA/CA & RTS/CTS

$T = DIFS + T_{RTS} + SIFS + T_{CTS} + SIFS + T_{DATA} + SIFS + T_{ACK} + DIFS$   
 $T' = 0$



### Wi-Fi DCF & CSMA/CA

❖ Wi-Fi

- CSMA/CA & RTS/CTS

$T = 0$






Wi-Fi DCF & CSMA/CA

❖ Wi-Fi

- CSMA/CA & RTS/CTS

$T = \text{DIFS}$




Wi-Fi DCF & CSMA/CA

❖ Wi-Fi

- CSMA/CA & RTS/CTS

$T = \text{DIFS} + T_{\text{RTS}}$




Wi-Fi DCF & CSMA/CA

❖ Wi-Fi

- CSMA/CA & RTS/CTS

$T = DIFS + T_{RTS} + SIFS$




Wi-Fi DCF & CSMA/CA

❖ Wi-Fi

- CSMA/CA & RTS/CTS

$T = DIFS + T_{RTS} + SIFS + T_{CTS}$




### Wi-Fi DCF & CSMA/CA

❖ Wi-Fi

- CSMA/CA & RTS/CTS

$T = DIFS + T_{RTS} + SIFS + T_{CTS} + SIFS$




### Wi-Fi DCF & CSMA/CA

❖ Wi-Fi

- CSMA/CA & RTS/CTS

$T = DIFS + T_{RTS} + SIFS + T_{CTS} + SIFS + T_{DATA} + SIFS$




# Wi-Fi DCF & CSMA/CA

## ❖ Wi-Fi

### ▪ CSMA/CA & RTS/CTS

$T = \text{DIFS} + T_{\text{RTS}} + \text{SIFS} + T_{\text{CTS}} + \text{SIFS} + T_{\text{DATA}} + \text{SIFS} + T_{\text{ACK}} + \text{DIFS}$   
 $T' = 0$



## Wi-Fi & Bluetooth References

## References

- M. Gast, 802.11 wireless networks: the definitive guide. O'Reilly Media, 2005.
- B. P. Crow, I. Widjaja, J. G. Kim, and P.T. Sakai, "IEEE 802.11 Wireless Local Area Networks," IEEE Communication Magazine, vol. 35, no. 9, pp. 116-126, Sep. 1997.
- E. Ferro and F. Potorti, "Bluetooth and Wi-Fi wireless protocols: a survey and a comparison," IEEE Wireless Communications, vol. 12, no. 1, pp. 12-26, Feb. 2005.
- Webopedia, Extended Service Set, [http://www.webopedia.com/TERM/E/Extended\\_Service\\_Set.html](http://www.webopedia.com/TERM/E/Extended_Service_Set.html) [Accessed June 1, 2015]
- Speedguide, Wi-Fi 5 GHz vs 2.4 GHz, <http://www.speedguide.net/faq/is-5ghz-wireless-better-than-24ghz-340> [Accessed June 1, 2015]
- Wi-Fi Alliance, <http://www.wi-fi.org>
- Wikipedia, <http://www.wikipedia.org>
- William Stallings, Data and Computer Communications, 10th Ed. Prentice Hall, 2014.

## References

- "Cisco To Remain A Formidable Player In The Enterprise WLAN Market," Trefis Team Forbes, [Online] Available from: <https://www.forbes.com/sites/greatspeculations/2017/10/02/cisco-to-remain-a-formidable-player-in-the-enterprise-wlan-market/#3abc73ad421a> [Accessed Feb. 24, 2018]
- "Worldwide Enterprise WLAN Market Sees Moderate Growth in the First Quarter of 2017 with Uncertainty in the Year Ahead, According to IDC," IDC, [Online] Available from: <https://www.idc.com/getdoc.jsp?containerId=prUS42757217> [Accessed Feb. 24, 2018]

## References

### Image sources

- Wi-Fi Icon, By Canopus49 (Own work) [CC BY-SA 3.0 (<http://creativecommons.org/licenses/by-sa/3.0/>)], via Wikimedia Commons
- USB, By TEL0000 (Own work) [Public domain], via Wikimedia Commons
- PCI, By Evan-Amos (Own work) [Public domain], via Wikimedia Commons
- Laptop PC Icon, By Everaldo Coelho (YellowIcon) [LGPL (<http://www.gnu.org/licenses/lgpl.html>)], via Wikimedia Commons