


You are reading documentation for the unreleased version of Matplotlib. Try searching for the released version of this page instead?

[Fork me on GitHub](#)

Version 3.3.0rc1.post413+g4b179b92c

[Installation](#) [Documentation](#) [Examples](#) [Tutorials](#) [Contributing](#) [Search](#)[home](#) | [contents](#) » [Creating multiple subplots using plt.subplots](#)[modules](#) | [index](#)

Creating multiple subplots using plt.subplots

`pyplot.subplots` creates a figure and a grid of subplots with a single call, while providing reasonable control over how the individual plots are created. For more advanced use cases you can use `GridSpec` for a more general subplot layout or `Figure.add_subplot` for adding subplots at arbitrary locations within the figure.

```
import matplotlib.pyplot as plt
import numpy as np

# Some example data to display
x = np.linspace(0, 2 * np.pi, 400)
y = np.sin(x ** 2)
```



Table of Contents

Creating multiple subplots using plt.subplots

- [A figure with just one subplot](#)
- [Stacking subplots in one direction](#)
- [Stacking subplots in two directions](#)
- [Sharing axes](#)
- [Polar axes](#)

Related Topics

[Documentation overview](#)

[Show Page Source](#)

A figure with just one subplot


`subplots()` without arguments returns a `Figure` and a single `Axes`.

This is actually the simplest and recommended way of creating a single Figure and Axes.

```
fig, ax = plt.subplots()
ax.plot(x, y)
ax.set_title('A single plot')
```



You are reading documentation for the unreleased version of Matplotlib. Try searching for the released version of this page instead?



Out: Text(0.5, 1.0, 'A single plot')



Stacking subplots in one direction


The first two optional arguments of `pyplot.subplots` define the number of rows and columns of the subplot grid.

When stacking in one direction only, the returned `axs` is a 1D numpy array containing the list of created Axes.

```
fig, axs = plt.subplots(2)
fig.suptitle('Vertically stacked subplots')
axs[0].plot(x, y)
axs[1].plot(x, -y)
```



You are reading documentation for the unreleased version of Matplotlib. Try searching for the released version of this page instead?




Out: [`<matplotlib.lines.Line2D object at 0x7fd64198a760>`]

If you are creating just a few Axes, it's handy to unpack them immediately to dedicated variables for each Axes. That way, we can use `ax1` instead of the more verbose `axs[0]`.

```
fig, (ax1, ax2) = plt.subplots(2)
fig.suptitle('Vertically stacked subplots')
ax1.plot(x, y)
ax2.plot(x, -y)
```

Vertically stacked subplots




Out: [`<matplotlib.lines.Line2D object at 0x7fd63fb68c40>`]

You are reading documentation for the unreleased version of Matplotlib. Try searching for the released version of this page instead?

two columns.

```
fig, (ax1, ax2) = plt.subplots(1, 2)
fig.suptitle('Horizontally stacked subplots')
ax1.plot(x, y)
ax2.plot(x, -y)
```

Horizontally stacked subplots



Out: [

Stacking subplots in two directions

When stacking in two directions, the returned `axs` is a 2D NumPy array.


If you have to set parameters for each subplot it's handy to iterate over all subplots in a 2D grid using `for ax in axs.flat:`.

```
fig, axs = plt.subplots(2, 2)
axs[0, 0].plot(x, y)
axs[0, 0].set_title('Axis [0, 0]')
axs[0, 1].plot(x, y, 'tab:orange')
axs[0, 1].set_title('Axis [0, 1]')
axs[1, 0].plot(x, -y, 'tab:green')
axs[1, 0].set_title('Axis [1, 0]')
axs[1, 1].plot(x, -y, 'tab:red')
axs[1, 1].set_title('Axis [1, 1]')

for ax in axs.flat:
    ax.set(xlabel='x-label', ylabel='y-label')

# Hide x labels and tick labels for top plots and y ticks
```

You are reading documentation for the unreleased version of Matplotlib. Try searching for the released version of this page instead?




You can use tuple-unpacking also in 2D to assign all subplots to dedicated variables:

```
fig, ((ax1, ax2), (ax3, ax4)) = plt.subplots(2, 2)
fig.suptitle('Sharing x per column, y per row')
ax1.plot(x, y)
ax2.plot(x, y**2, 'tab:orange')
ax3.plot(x, -y, 'tab:green')
ax4.plot(x, -y**2, 'tab:red')

for ax in fig.get_axes():
    ax.label_outer()
```

You are reading documentation for the unreleased version of Matplotlib. Try searching for the released version of this page instead?




Sharing axes

By default, each Axes is scaled individually. Thus, if the ranges are different the tick values of the subplots do not align.

```
fig, (ax1, ax2) = plt.subplots(2)
fig.suptitle('Axes values are scaled individually by default')
ax1.plot(x, y)
ax2.plot(x + 1, -y)
```

Axes values are scaled individually by default




Out: [`<matplotlib.lines.Line2D object at 0x7fd640752370>`]

You are reading documentation for the unreleased version of Matplotlib. Try searching for the released version of this page instead?

```
fig.suptitle('Aligning x-axis using sharex')
ax1.plot(x, y)
ax2.plot(x + 1, -y)
```

Aligning x-axis using sharex




Out: [`<matplotlib.lines.Line2D object at 0x7fd640838550>`]

Setting *sharex* or *sharey* to `True` enables global sharing across the whole grid, i.e. also the y-axes of vertically stacked subplots have the same scale when using *sharey*=`True`.

```
fig, axs = plt.subplots(3, sharex=True, sharey=True)
fig.suptitle('Sharing both axes')
axs[0].plot(x, y ** 2)
axs[1].plot(x, 0.3 * y, 'o')
axs[2].plot(x, y, '+')
```

You are reading documentation for the unreleased version of Matplotlib. Try searching for the released version of this page instead?



Out: [`<matplotlib.lines.Line2D object at 0x7fd63fecf580>`]

For subplots that are sharing axes one set of tick labels is enough. Tick labels of inner Axes are automatically removed by `sharex` and `sharey`. Still there remains an unused empty space between the subplots.


To precisely control the positioning of the subplots, one can explicitly create a `GridSpec` with `add_gridspec`, and then call its `subplots` method. For example, we can reduce the height between vertical subplots using `add_gridspec(hspace=0)`.

`label_outer` is a handy method to remove labels and ticks from subplots that are not at the edge of the grid.

```
fig = plt.figure()
gs = fig.add_gridspec(3, hspace=0)
axs = gs.subplots(sharex=True, sharey=True)
fig.suptitle('Sharing both axes')
axs[0].plot(x, y ** 2)
axs[1].plot(x, 0.3 * y, 'o')
axs[2].plot(x, y, '+')

# Hide x labels and tick labels for all but bottom plot.
for ax in axs:
    ax.label_outer()
```


You are reading documentation for the unreleased version of Matplotlib. Try searching for the released version of this page instead?




Apart from True and False, both *sharex* and *sharey* accept the values 'row' and 'col' to share the values only per row or column.

```
fig = plt.figure()
gs = fig.add_gridspec(2, 2, hspace=0, wspace=0)
(ax1, ax2), (ax3, ax4) = gs.subplots(sharex='col', sharey='row')
fig.suptitle('Sharing x per column, y per row')
ax1.plot(x, y)
ax2.plot(x, y**2, 'tab:orange')
ax3.plot(x + 1, -y, 'tab:green')
ax4.plot(x + 2, -y**2, 'tab:red')

for ax in axs.flat:
    ax.label_outer()
```


You are reading documentation for the unreleased version of Matplotlib. Try searching for the released version of this page instead?



If you want a more complex sharing structure, you can first create the grid of axes with no sharing, and then call `axes.Axes.sharex` or `axes.Axes.sharey` to add sharing info a posteriori.

```
fig, axs = plt.subplots(2, 2)
axs[0, 0].plot(x, y)
axs[0, 0].set_title("main")
axs[1, 0].plot(x, y**2)
axs[1, 0].set_title("shares x with main")
axs[1, 0].sharex(axs[0, 0])
axs[0, 1].plot(x + 1, y + 1)
axs[0, 1].set_title("unrelated")
axs[1, 1].plot(x + 2, y + 2)
axs[1, 1].set_title("also unrelated")
fig.tight_layout()
```

You are reading documentation for the unreleased version of Matplotlib. Try searching for the released version of this page instead?




Polar axes

The parameter `subplot_kw` of `pyplot.subplots` controls the subplot properties (see also `Figure.add_subplot`). In particular, this can be used to create a grid of polar Axes.

```
fig, (ax1, ax2) = plt.subplots(1, 2, subplot_kw=dict(proj='polar'))
ax1.plot(x, y)
ax2.plot(x, y ** 2)

plt.show()
```



Total running time of the script: (0 minutes 7.389 seconds)

You are reading documentation for the unreleased version of Matplotlib. Try searching for the released version of this page instead?

Download Jupyter notebook: `subplots_demo.ipynb`

© Copyright 2020 - 2012 John Hunter, Darren Dale, Eric Firing, Michael Droettboom and the Matplotlib development team; 2012 - 2020 The Matplotlib development team.

Last updated on Jun 18, 2020. Created using [Sphinx](#) 3.1.2. Doc version v3.3.0rc1-413-g4b179b92c.