



Watson Studio democratizes machine learning and deep learning to accelerate infusion of AI in your business to drive innovation. Watson Studio provides a suite of tools and a collaborative environment for data scientists, developers and domain experts.

(http://cocl.us/pytorch_link_top)



Softmax Classifier 1D

Table of Contents

In this lab, you will use Softmax to classify three linearly separable classes, the features are in one dimension

- [Make Some Data](#)
- [Build Softmax Classifier](#)
- [Train the Model](#)
- [Analyze Results](#)

Estimated Time Needed: **25 min**

Preparation

We'll need the following libraries:

In [1]:

```
# Import the libraries we need for this lab

import torch.nn as nn
import torch
import matplotlib.pyplot as plt
import numpy as np
from torch.utils.data import Dataset, DataLoader
```

Use the helper function to plot labeled data points:

In [2]:

```
# Create class for plotting

def plot_data(data_set, model = None, n = 1, color = False):
    X = data_set[:,0]
    Y = data_set[:,1]
    plt.plot(X[Y == 0, 0].numpy(), Y[Y == 0].numpy(), 'bo', label = 'y = 0')
    plt.plot(X[Y == 1, 0].numpy(), 0 * Y[Y == 1].numpy(), 'ro', label = 'y = 1')
    plt.plot(X[Y == 2, 0].numpy(), 0 * Y[Y == 2].numpy(), 'go', label = 'y = 2')
    plt.ylim((-0.1, 3))
    plt.legend()
    if model != None:
        w = list(model.parameters())[0][0].detach()
        b = list(model.parameters())[1][0].detach()
        y_label = ['yhat=0', 'yhat=1', 'yhat=2']
        y_color = ['b', 'r', 'g']
        Y = []
        for w, b, y_l, y_c in zip(model.state_dict()['0.weight'], model.state_dict()
                                )['0.bias'], y_label, y_color):
            Y.append((w * X + b).numpy())
            plt.plot(X.numpy(), (w * X + b).numpy(), y_c, label = y_l)
        if color == True:
            x = X.numpy()
            x = x.reshape(-1)
            top = np.ones(x.shape)
            y0 = Y[0].reshape(-1)
            y1 = Y[1].reshape(-1)
            y2 = Y[2].reshape(-1)
            plt.fill_between(x, y0, where = y1 > y1, interpolate = True, color = 'blue')
            plt.fill_between(x, y0, where = y1 > y2, interpolate = True, color = 'blue')
            plt.fill_between(x, y1, where = y1 > y0, interpolate = True, color = 'red')
            plt.fill_between(x, y1, where = ((y1 > y2) * (y1 > y0)),interpolate = True, color = 'red')
            plt.fill_between(x, y2, where = (y2 > y0) * (y0 > 0),interpolate = True, color = 'green')
            plt.fill_between(x, y2, where = (y2 > y1), interpolate = True, color = 'green')
        plt.legend()
        plt.show()
```

Set the random seed:

In [3]:

```
#Set the random seed  
  
torch.manual_seed(0)
```

Out[3]:

```
<torch._C.Generator at 0x7f09f404d090>
```

Make Some Data

Create some linearly separable data with three classes:

In [4]:


```
# Create the data class  
  
class Data(Dataset):  
  
    # Constructor  
    def __init__(self):  
        self.x = torch.arange(-2, 2, 0.1).view(-1, 1)  
        self.y = torch.zeros(self.x.shape[0])  
        self.y[(self.x > -1.0)[: , 0] * (self.x < 1.0)[: , 0]] = 1  
        self.y[(self.x >= 1.0)[: , 0]] = 2  
        self.y = self.y.type(torch.LongTensor)  
        self.len = self.x.shape[0]  
  
    # Getter  
    def __getitem__(self, index):  
        return self.x[index], self.y[index]  
  
    # Get Length  
    def __len__(self):  
        return self.len
```

Create the dataset object:

In [5]:

```
# Create the dataset object and plot the dataset object

data_set = Data()
data_set.x
plot_data(data_set)
```



Build a Softmax Classifier

Build a Softmax classifier by using the Sequential module:

In [6]:

```
# Build Softmax Classifier technically you only need nn.Linear

model = nn.Sequential(nn.Linear(1, 3))
model.state_dict()
```

Out[6]:

```
OrderedDict([('0.weight',
              tensor([[ -0.0075,
                       [ 0.5364,
                       [-0.8230]])),
              ('0.bias', tensor([-0.7359, -0.3852,  0.2682]))])])
```

Train the Model

Create the criterion function, the optimizer and the dataloader

In [7]:

```
# Create criterion function, optimizer, and dataloader



criterion = nn.CrossEntropyLoss()
optimizer = torch.optim.SGD(model.parameters(), lr = 0.01)
trainloader = DataLoader(dataset = data_set, batch_size = 5)
```



Train the model for every 50 epochs plot, the line generated for each class.



In [8]:

```
# Train the model

LOSS = []
def train_model(epochs):
    for epoch in range(epochs):
        if epoch % 50 == 0:
            pass
            plot_data(data_set, model)
        for x, y in trainloader:
            optimizer.zero_grad()
            yhat = model(x)
            loss = criterion(yhat, y)
            LOSS.append(loss)
            loss.backward()
            optimizer.step()
train_model(300)
```







Analyze Results

Find the predicted class on the test data:

In [9]:

```
# Make the prediction
```

```
z = model(data_set.x)
_, yhat = z.max(1)
print("The prediction:", yhat)
```

```
The prediction: tensor([0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 1, 1, 1, 1,
1, 1, 1, 1, 1, 1, 1, 1,
1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2])
```

Calculate the accuracy on the test data:

In [10]:

```
# Print the accuracy
```

```
correct = (data_set.y == yhat).sum().item()
accuracy = correct / len(data_set)
print("The accuracy: ", accuracy)
```

```
The accuracy: 0.975
```

You can also use the softmax function to convert the output to a probability, first, we create a Softmax object:

In [11]:

```
Softmax_fn=nn.Softmax(dim=-1)
```

The result is a tensor `Probability`, where each row corresponds to a different sample, and each column corresponds to that sample belonging to a particular class

In [12]:

```
Probability =Softmax_fn(z)
```

we can obtain the probability of the first sample belonging to the first, second and third class respectively as follows:

In [13]:

```
for i in range(3):
    print("probability of class {} is given by {}".format(i, Probability[0,i]) )
```

```
probability of class 0 is given by 0.9267547726631165
probability of class 1 is given by 0.07310982048511505
probability of class 2 is given by 0.00013548212882597
```

Get IBM Watson Studio free of charge!

Build and train AI & machine learning models, prepare and analyze data – all in a flexible, hybrid cloud environment. Get IBM Watson Studio Lite Plan free of charge.



Learn

Get started or get better with built-in learning.



Create

Use the best of open source tooling with IBM innovation.



Collaborate

Work smarter using community, work faster with your team.

[Sign Up For a Free Trial](#)

(<http://cocl.us/pytorch> link bottom)

About the Authors:

[Joseph Santarcangelo](https://www.linkedin.com/in/joseph-s-50398b136/) (<https://www.linkedin.com/in/joseph-s-50398b136/>) has a PhD in Electrical Engineering, his research focused on using machine learning, signal processing, and computer vision to determine how videos impact human cognition. Joseph has been working for IBM since he completed his PhD.

Other contributors: [Michelle Carey](https://www.linkedin.com/in/michelleccarey/) (<https://www.linkedin.com/in/michelleccarey/>), [Mavis Zhou](https://www.linkedin.com/in/jiahui-mavis-zhou-a4537814a) (www.linkedin.com/in/jiahui-mavis-zhou-a4537814a).

Copyright © 2018 cognitiveclass.ai (cognitiveclass.ai?utm_source=bducopyrightlink&utm_medium=dswb&utm_campaign=bdu). This notebook and its source code are released under the terms of the [MIT License](https://bigdatauniversity.com/mit-license/) (<https://bigdatauniversity.com/mit-license/>).