



Watson Studio democratizes machine learning and deep learning to accelerate infusion of AI in your business to drive innovation. Watson Studio provides a suite of tools and a collaborative environment for data scientists, developers and domain experts.

(<http://cocl.us/pytorch> link top)



## Linear regression: Training and Validation Data

### Table of Contents

In this lab, you will learn to select the best learning rate by using validation data.

- [Make Some Data](#)
- [Create a Linear Regression Object, Data Loader and Criterion Function](#)
- [Different learning rates and Data Structures to Store results for Different Hyperparameters](#)
- [Train different modules for different Hyperparameters](#)
- [View Results](#)

Estimated Time Needed: **30 min**

---

### Preparation

We'll need the following libraries and set the random seed.

In [1]:

```
# Import libraries we need for this lab, and set the random seed

from torch import nn
import torch
import numpy as np
import matplotlib.pyplot as plt
from torch import nn, optim
```

## Make Some Data

First, we'll create some artificial data in a dataset class. The class will include the option to produce training data or validation data. The training data will include outliers.

In [2]:

```
# Create Data class

from torch.utils.data import Dataset, DataLoader

class Data(Dataset):

    # Constructor
    def __init__(self, train = True):
        self.x = torch.arange(-3, 3, 0.1).view(-1, 1)
        self.f = -3 * self.x + 1
        self.y = self.f + 0.1 * torch.randn(self.x.size())
        self.len = self.x.shape[0]

        #outliers
        if train == True:
            self.y[0] = 0
            self.y[50:55] = 20
        else:
            pass

    # Getter
    def __getitem__(self, index):
        return self.x[index], self.y[index]

    # Get Length
    def __len__(self):
        return self.len
```

Create two objects: one that contains training data and a second that contains validation data. Assume that the training data has the outliers.

In [3]:

```
# Create training dataset and validation dataset


train_data = Data()
val_data = Data(train = False)
```

Overlay the training points in red over the function that generated the data. Notice the outliers at  $x=-3$  and around  $x=2$ :

In [4]:

```
# Plot out training points

plt.plot(train_data.x.numpy(), train_data.y.numpy(), 'xr', label="training data ")
plt.plot(train_data.x.numpy(), train_data.f.numpy(), label="true function ")
plt.xlabel('x')
plt.ylabel('y')
plt.legend()
plt.show()
```



## Create a Linear Regression Object, Data Loader, and Criterion Function

In [5]:

```
# Create Linear Regression Class

from torch import nn

class linear_regression(nn.Module):

    # Constructor
    def __init__(self, input_size, output_size):
        super(linear_regression, self).__init__()
        self.linear = nn.Linear(input_size, output_size)

    # Prediction function
    def forward(self, x):
        yhat = self.linear(x)
        return yhat
```

Create the criterion function and a `DataLoader` object:

In [6]:

```
# Create MSELoss function and DataLoader

criterion = nn.MSELoss()
trainloader = DataLoader(dataset = train_data, batch_size = 1)
```

## Different learning rates and Data Structures to Store results for different Hyperparameters

Create a list with different learning rates and a tensor (can be a list) for the training and validating cost/total loss. Include the list `MODELS`, which stores the training model for every value of the learning rate.

In [7]:

```
# Create Learning Rate list, the error lists and the MODELS list

learning_rates=[0.0001, 0.001, 0.01, 0.1]

train_error=torch.zeros(len(learning_rates))
validation_error=torch.zeros(len(learning_rates))

MODELS=[ ]
```

## Train different models for different Hyperparameters

Try different values of learning rates, perform stochastic gradient descent, and save the results on the training data and validation data. Finally, save each model in a list.

In [8]:

```
# Define the train model function and train the model

def train_model_with_lr (iter, lr_list):

    # iterate through different learning rates
    for i, lr in enumerate(lr_list):
        model = linear_regression(1, 1)
        optimizer = optim.SGD(model.parameters(), lr = lr)
        for epoch in range(iter):
            for x, y in trainloader:
                yhat = model(x)
                loss = criterion(yhat, y)
                optimizer.zero_grad()
                loss.backward()
                optimizer.step()

        # train data
        Yhat = model(train_data.x)
        train_loss = criterion(Yhat, train_data.y)
        train_error[i] = train_loss.item()

        # validation data
        Yhat = model(val_data.x)
        val_loss = criterion(Yhat, val_data.y)
        validation_error[i] = val_loss.item()
        MODELS.append(model)

train_model_with_lr(10, learning_rates)
```


## View the Results

Plot the training loss and validation loss for each learning rate:

In [9]:

```
# Plot the training loss and validation loss

plt.semilogx(np.array(learning_rates), train_error.numpy(), label = 'training loss/total Loss')
plt.semilogx(np.array(learning_rates), validation_error.numpy(), label = 'validation cost/total Loss')
plt.ylabel('Cost\ Total Loss')
plt.xlabel('learning rate')
plt.legend()
plt.show()
```




Produce a prediction by using the validation data for each model:

In [10]:

```
# Plot the predictions

i = 0
for model, learning_rate in zip(MODELS, learning_rates):
    yhat = model(val_data.x)
    plt.plot(val_data.x.numpy(), yhat.detach().numpy(), label = 'lr:' + str(learning_rate))
    print('i', yhat.detach().numpy()[0:3])
plt.plot(val_data.x.numpy(), val_data.f.numpy(), 'or', label = 'validation data')
plt.xlabel('x')
plt.ylabel('y')
plt.legend()
plt.show()
```

```
i [[0.07554543]
 [0.0608027 ]
 [0.04605991]]
i [[5.808317 ]
 [5.6901407]
 [5.5719643]]
i [[6.5586753]
 [6.425766 ]
 [6.292856 ]]
i [[14.538845]
 [14.100753]
 [13.66266  ]]
```



## Practice

The object `good_model` is the best performing model. Use the train loader to get the data samples `x` and `y`. Produce an estimate for `yhat` and print it out for every sample in a for a loop. Compare it to the actual prediction `y`.

In [12]:

```
for x, y in trainloader:
    print("yhat= ", good_model(x), "y", y)
```


```
-----
----
NameError                                Traceback (most recent call 1
ast)
<ipython-input-12-1e1e8f2dbb7d> in <module>
      1 for x, y in trainloader:
----> 2     print("yhat= ", good_model(x), "y", y)

NameError: name 'good_model' is not defined
```

Double-click **here** for the solution.


## Get IBM Watson Studio free of charge!

Build and train AI & machine learning models, prepare and analyze data – all in a flexible, hybrid cloud environment. Get IBM Watson Studio Lite Plan free of charge.




**Learn**

Get started or get better with built-in learning.



**Create**

Use the best of open source tooling with IBM innovation.



**Collaborate**

Work smarter using community, work faster with your team.

Sign Up For a Free Trial

([http://cocl.us/pytorch\\_link\\_bottom](http://cocl.us/pytorch_link_bottom))

## About the Authors:

[Joseph Santarcangelo](https://www.linkedin.com/in/joseph-s-50398b136/) (<https://www.linkedin.com/in/joseph-s-50398b136/>) has a PhD in Electrical Engineering, his research focused on using machine learning, signal processing, and computer vision to determine how videos impact human cognition. Joseph has been working for IBM since he completed his PhD.

Other contributors: [Michelle Carey](https://www.linkedin.com/in/michelleccarey/) (<https://www.linkedin.com/in/michelleccarey/>), [Mavis Zhou](https://www.linkedin.com/in/jiahui-mavis-zhou-a4537814a) ([www.linkedin.com/in/jiahui-mavis-zhou-a4537814a](https://www.linkedin.com/in/jiahui-mavis-zhou-a4537814a))



Copyright © 2018 [cognitiveclass.ai](https://cognitiveclass.ai?utm_source=bducopyrightlink&utm_medium=dswb&utm_campaign=bdu) ([cognitiveclass.ai?utm\\_source=bducopyrightlink&utm\\_medium=dswb&utm\\_campaign=bdu](https://cognitiveclass.ai?utm_source=bducopyrightlink&utm_medium=dswb&utm_campaign=bdu)). This notebook and its source code are released under the terms of the [MIT License](https://bigdatauniversity.com/mit-license/) (<https://bigdatauniversity.com/mit-license/>).