



Watson Studio democratizes machine learning and deep learning to accelerate infusion of AI in your business to drive innovation. Watson Studio provides a suite of tools and a collaborative environment for data scientists, developers and domain experts.

(http://cocl.us/pytorch_link_top)



Test Uniform, Default and Xavier Uniform Initialization on MNIST dataset with tanh activation

Table of Contents

In this lab, you will test PyTorch Default Initialization, Xavier Initialization and Uniform Initialization on the MNIST dataset.

- [Neural Network Module and Training Function](#)
- [Make Some Data](#)
- [Define Several Neural Network, Criterion function, Optimizer](#)
- [Test Uniform, Default and Xavier Initialization](#)
- [Analyze Results](#)

Estimated Time Needed: **25 min**

Preparation

We'll need the following libraries:

In [1]:

```
# Import the libraries we need to use in this lab

# Using the following line code to install the torchvision library
# !conda install -y torchvision

import torch
import torch.nn as nn
import torchvision.transforms as transforms
import torchvision.datasets as dsets
import matplotlib.pyplot as plt
import numpy as np

torch.manual_seed(0)
```

Out[1]:

```
<torch._C.Generator at 0x7f56c2b437d0>
```

Neural Network Module and Training Function

Define the neural network module or class with Xavier Initialization

In [2]:

```
# Define the neural network with Xavier initialization

class Net_Xavier(nn.Module):

    # Constructor
    def __init__(self, Layers):
        super(Net_Xavier, self).__init__()
        self.hidden = nn.ModuleList()

        for input_size, output_size in zip(Layers, Layers[1:]):
            linear = nn.Linear(input_size, output_size)
            torch.nn.init.xavier_uniform_(linear.weight)
            self.hidden.append(linear)

    # Prediction
    def forward(self, x):
        L = len(self.hidden)
        for (l, linear_transform) in zip(range(L), self.hidden):
            if l < L - 1:
                x = torch.tanh(linear_transform(x))
            else:
                x = linear_transform(x)
        return x
```

Define the neural network module with Uniform Initialization:

In [3]:

```
# Define the neural network with Uniform initialization

class Net_Uniform(nn.Module):

    # Constructor
    def __init__(self, Layers):
        super(Net_Uniform, self).__init__()
        self.hidden = nn.ModuleList()

        for input_size, output_size in zip(Layers, Layers[1:]):
            linear = nn.Linear(input_size, output_size)
            linear.weight.data.uniform_(0, 1)
            self.hidden.append(linear)

    # Prediction
    def forward(self, x):
        L = len(self.hidden)
        for (l, linear_transform) in zip(range(L), self.hidden):
            if l < L - 1:
                x = torch.tanh(linear_transform(x))
            else:
                x = linear_transform(x)
        return x
```

Define the neural network module with PyTorch Default Initialization

In [4]:

```
# Define the neural network with Default initialization

class Net(nn.Module):

    # Constructor
    def __init__(self, Layers):
        super(Net, self).__init__()
        self.hidden = nn.ModuleList()

        for input_size, output_size in zip(Layers, Layers[1:]):
            linear = nn.Linear(input_size, output_size)
            self.hidden.append(linear)

    # Prediction
    def forward(self, x):
        L = len(self.hidden)
        for (l, linear_transform) in zip(range(L), self.hidden):
            if l < L - 1:
                x = torch.tanh(linear_transform(x))
            else:
                x = linear_transform(x)
        return x
```

Define a function to train the model, in this case the function returns a Python dictionary to store the training loss and accuracy on the validation data

In [5]:

```
# function to Train the model

def train(model, criterion, train_loader, validation_loader, optimizer, epochs = 100):
    i = 0
    loss_accuracy = {'training_loss':[], 'validation_accuracy':[]}

    for epoch in range(epochs):
        for i,(x, y) in enumerate(train_loader):
            optimizer.zero_grad()
            z = model(x.view(-1, 28 * 28))
            loss = criterion(z, y)
            loss.backward()
            optimizer.step()
            loss_accuracy['training_loss'].append(loss.data.item())

        correct = 0
        for x, y in validation_loader:
            yhat = model(x.view(-1, 28 * 28))
            _, label = torch.max(yhat, 1)
            correct += (label==y).sum().item()
        accuracy = 100 * (correct / len(validation_dataset))
        loss_accuracy['validation_accuracy'].append(accuracy)

    return loss_accuracy
```

Make Some Data

Load the training dataset by setting the parameters `train` to `True` and convert it to a tensor by placing a transform object into the argument `transform`

In [6]:

```
# Create the train dataset

train_dataset = datasets.MNIST(root='./data', train=True, download=True, transform=transforms.ToTensor())
```

Load the testing dataset by setting the parameters `train` to `False` and convert it to a tensor by placing a transform object into the argument `transform`

In [7]:

```
# Create the validation dataset

validation_dataset = datasets.MNIST(root='./data', train=False, download=True, transform=transforms.ToTensor())
```

Create the training-data loader and the validation-data loader object

In [8]:

```
# Create Dataloader for both train dataset and validation dataset

train_loader = torch.utils.data.DataLoader(dataset=train_dataset, batch_size=2000, shuffle=True)
validation_loader = torch.utils.data.DataLoader(dataset=validation_dataset, batch_size=5000, shuffle=False)
```

Define Neural Network, Criterion function, Optimizer and Train the Model

Create the criterion function

In [9]:

```
# Define criterion function

criterion = nn.CrossEntropyLoss()
```

Create the model with 100 hidden layers

In [10]:

```
# Set the parameters

input_dim = 28 * 28
output_dim = 10
layers = [input_dim, 100, 10, 100, 10, 100, output_dim]
epochs = 15
```

Test PyTorch Default Initialization, Xavier Initialization, Uniform Initialization

Train the network using PyTorch Default Initialization

In []:

```
# Train the model with default initialization

model = Net(layers)
learning_rate = 0.01
optimizer = torch.optim.SGD(model.parameters(), lr=learning_rate)
training_results = train(model, criterion, train_loader, validation_loader, optimizer, epochs=epochs)
```

Train the network using Xavier Initialization function

In []:

```
# Train the model with Xavier initialization

model_Xavier = Net_Xavier(layers)
optimizer = torch.optim.SGD(model_Xavier.parameters(), lr=learning_rate)
training_results_Xavier = train(model_Xavier, criterion, train_loader, validation_loader, optimizer, epochs=epochs)
```

Train the network using Uniform Initialization

In []:

```
# Train the model with Uniform initialization

model_Uniform = Net_Uniform(layers)
optimizer = torch.optim.SGD(model_Uniform.parameters(), lr=learning_rate)
training_results_Uniform = train(model_Uniform, criterion, train_loader, validation_loader, optimizer, epochs=epochs)
```

Analyse Results

Compare the training loss for each initialization

In []:

```
# Plot the loss

plt.plot(training_results_Xavier['training_loss'], label='Xavier')
plt.plot(training_results['training_loss'], label='Default')
plt.plot(training_results_Uniform['training_loss'], label='Uniform')
plt.ylabel('loss')
plt.xlabel('iteration ')
plt.title('training loss iterations')
plt.legend()
```

compare the validation loss for each model


In []:

```
# Plot the accuracy

plt.plot(training_results_Xavier['validation_accuracy'], label='Xavier')
plt.plot(training_results['validation_accuracy'], label='Default')
plt.plot(training_results_Uniform['validation_accuracy'], label='Uniform')
plt.ylabel('validation accuracy')
plt.xlabel('epochs')
plt.legend()
```

Get IBM Watson Studio free of charge!

Build and train AI & machine learning models, prepare and analyze data – all in a flexible, hybrid cloud environment. Get IBM Watson Studio Lite Plan free of charge.



Learn

Get started or get better with built-in learning.



Create

Use the best of open source tooling with IBM innovation.



Collaborate

Work smarter using community, work faster with your team.

Sign Up For a Free Trial

(http://cocl.us/pytorch_link_bottom)

About the Authors:

[Joseph Santarcangelo](https://www.linkedin.com/in/joseph-s-50398b136/) (<https://www.linkedin.com/in/joseph-s-50398b136/>) has a PhD in Electrical Engineering, his research focused on using machine learning, signal processing, and computer vision to determine how videos impact human cognition. Joseph has been working for IBM since he completed his PhD.

Other contributors: [Michelle Carey](https://www.linkedin.com/in/michelleccarey/) (<https://www.linkedin.com/in/michelleccarey/>), [Mavis Zhou](https://www.linkedin.com/in/jiahui-mavis-zhou-a4537814a) (www.linkedin.com/in/jiahui-mavis-zhou-a4537814a)

Copyright © 2018 cognitiveclass.ai (cognitiveclass.ai?utm_source=bducopyrightlink&utm_medium=dswb&utm_campaign=bdu). This notebook and its source code are released under the terms of the [MIT License](https://bigdatauniversity.com/mit-license/) (<https://bigdatauniversity.com/mit-license/>).