Film Style Parameters and How the Benchmark Uses Them

EN.601.762 Final Project, October 14, 2026

1 Where film style shows up

Bold: used in our benchmark of 4 to 5 s generated clips. Gray: not used.

System	Style dimension	Parameters	Measurement	Use
Mise-en-scène	Setting & costume	Location type; costume style and color	VLM description vs. no-style control	Content drift only
what is filmed	**Color design**	**Dominant color; color scheme; figure vs. background color**	Color statistics after person segmentation	**Yes**
	Lighting	**Key (high / low); quality (hard / soft)**	Luminance histogram; VLM labels, human-calibrated	**Partly**
	Staging	**Number of people; facing (frontal, profile, back); position in frame**	Person and face detection; head pose	**Yes**
Cinematography	**Shot scale**	**Seven levels, BCU to VLS (Salt)**	FilmOps shot-scale classifier	**Yes**
how it is shot	**Camera position**	**Angle (high, eye level, low); Dutch tilt**	FilmOps angle; GeoCalib pitch and roll	**Yes**
	Composition	**Symmetry; rule of thirds; one-point perspective; negative space**	FilmOps composition; symmetry and vanishing point	**Yes**
	Lens	**Focal length (wide, normal, long)**; depth of field	Field-of-view estimation (GeoCalib, Depth Pro)	**Partly**
	Camera movement	**Static, pan, tilt, dolly, truck, crane, arc, zoom, handheld; speed**	CameraBench motion model	**Yes**
	Aspect ratio	1.85:1, 2.39:1, 16:9	Letterbox detection	No (fixed 16:9)
Image rendering	**Color grading**	**Warm / cool; saturation; split toning; white balance shift**	Neutral-region color cast by luminance band	**Yes**
& finishing	**Tonality**	**Mean brightness; contrast; black level; highlight roll-off**	Luminance percentiles	**Yes**
how it looks	**Texture**	**Grain; sharpness; halation; diffusion**	Noise power spectrum; edge sharpness	**Yes**
	Motion rendering	**Frame rate; slow / fast motion; motion blur**	Optical flow and blur length	**Yes**
Editing	Rhythm, transitions, shot patterns	Average shot length; share of dissolves; shot / reverse shot	TransNetV2 shot detection	No (one shot per clip)

2 What the benchmark does with them

Question: when a video model is asked for a director's style, where does it fall short? Every bold parameter goes through the same pipeline.

1. **Reference.** Take shots of the same scene type (e.g., dialogue) from several films by the director; measure each parameter to get the director's **real distribution**.
2. **Generate.** Same content, three prompt conditions: director name only; written style description; no style (control). Several clips per condition.
3. **Measure back.** Apply the same measurements to the generated clips.
4. **Score.** Compute the four scores below.
5. **Human check.** Blind test ("which set looks more like the reference?") to confirm the scores agree with people.

Score	Question	How it is computed	Seen in the pilot
Fidelity	Does the output fall inside the director's real distribution?	Distance between generated and real distributions, per parameter	Veo's "Nolan" has half the real saturation
Content drift	How much does the style request change the content?	Change in setting, costume, people vs. the control, compared with change in shooting parameters	Director names mainly changed people and costumes; shot scale and angle barely moved
Controllability	When a parameter is requested explicitly, is it met, and by how much is it overshot?	Gap between requested and measured value, split into undershoot and overshoot	Requested frontal view stayed at 0%; red / yellow area went from 0 in real films to 0.4
Diversity	Does the model vary within a style, or repeat one template?	Spread of generated clips divided by spread of real clips	Veo's two seeds gave nearly the same frame

Output. A score table per model and parameter, plus a diagnosis of each shortfall: a *knowledge gap* (poor with the name only, better once the style is spelled out) or an *execution gap* (still poor when spelled out).