

```

theory Problem-5
  imports HOL-Analysis.Analysis
begin

```

## 0.1 Problem 5

Real numbers  $M, a_1, a_2, \dots, a_{10}$  are given. Prove that, if  $a_1x_1 + a_2x_2 + \dots + a_{10}x_{10} \leq M$  for all  $x_i$  such that  $|x_i| = 1$ , then

$$\sqrt{a_1^2 + a_2^2 + \dots + a_{10}^2} \leq M.$$

```

lemma sqr-sum-ineq:
  list-all ( $\lambda x. x \geq 0$ ) xs  $\implies$  sum-list (map power2 xs)  $\leq$  (sum-list xs)2
  for xs :: real list
proof (induction xs)
  case Nil
  then show ?case by auto
next
  case (Cons x xs)
  note IH = (list-all ( $\lambda x. x \geq 0$ ) xs  $\implies$  sum-list (map power2 xs)  $\leq$  (sum-list xs)2)
  note nonneg = (list-all ( $\lambda x. x \geq 0$ ) (x # xs))
  then have x  $\geq 0$  and nonneg': list-all ( $\lambda x. x \geq 0$ ) xs by auto
  hence sum-list xs  $\geq 0$  using sum-list-nonneg unfolding list-all-def by auto

  have sum-list (map power2 (x # xs)) = x2 + sum-list (map power2 xs) by auto
  also have ...  $\leq$  x2 + (sum-list xs)2 using IH and nonneg' by auto
  also have ...  $\leq$  x2 + 2*x*(sum-list xs) + (sum-list xs)2
    using (x  $\geq 0$ ) and (sum-list xs  $\geq 0$ ) by auto
  also have ... = (x + sum-list xs)2 by algebra
  also have ... = (sum-list (x # xs))2 by auto
  finally show sum-list (map power2 (x # xs))  $\leq$  (sum-list (x # xs))2.
qed

```

```

definition sgn' :: real  $\Rightarrow$  real where
  sgn' x = (if x  $\geq 0$  then 1 else -1)

```

```

lemma [simp]: x * sgn' x = |x|
  unfolding sgn'-def by auto

```

```

lemma [simp]: |sgn' x| = 1
  unfolding sgn'-def by auto

```

```

theorem problem5:
  fixes M :: real and as :: real list
  assumes *:  $\bigwedge xs. \text{list-all } (\lambda x. |x| = 1) \text{ xs} \implies \text{sum-list (map2 } (*) \text{ as xs)} \leq M$ 
  shows sqrt (sum-list (map power2 as))  $\leq M$ 
proof -
  define xs where xs = map sgn' as
  then have list-all ( $\lambda x. |x| = 1$ ) xs unfolding list-all-def by auto
  with * [of xs] have sum-abs-below-M: sum-list (map abs as)  $\leq M$ 
    unfolding xs-def by (auto simp add: map2-map-map [where f=id, simplified])
  moreover have sum-abs-nonneg: sum-list (map abs as)  $\geq 0$ 
    using sum-list-abs abs-ge-zero order-trans by blast
  ultimately have M  $\geq 0$  by auto

  have [simp]: power2  $\circ$  abs = (power2 :: 'a  $\Rightarrow$  ('a :: linordered-idom))
    by auto
  have list-all ( $\lambda x. x \geq 0$ ) (map abs as) unfolding list-all-def by auto
  from sqr-sum-ineq [OF this]
  have sum-list (map power2 as)  $\leq$  (sum-list (map abs as))2
    by auto
  also have ...  $\leq M^2$  using sum-abs-below-M sum-abs-nonneg by auto

```

```

finally have  $\text{sum-list } (\text{map power2 } as) \leq M^2.$ 
with  $\langle M \geq 0 \rangle$  show  $\text{sqrt } (\text{sum-list } (\text{map power2 } as)) \leq M$ 
  by (metis abs-of-nonneg real-sqrt-abs real-sqrt-le-iff)
qed

end

```