Citations with PDF tooltips

Mikica Kocic

This paper describes package `xcpdftips`
version 1.0 from 2019/03/10

1 Introduction

This package allows one to be able to do `natbib` citations with PDF tooltips.

2 Invoking the Package

The macros in this package are included in the main document with the `\usepackage` command of LaTeX 2_ε,

```
\documentclass[..]{...}
\usepackage{xcpdftips}
```

3 Usage

This package must be used with BibTeX and `natbib`, not with a hand-written `thebibliography` environment. More precisely, there must be a `.bbl` file external to the LaTeX file; whether this is written by hand or by BibTeX is unimportant.

`\xpdfcite` This is a replacement for `natbib`'s `\cite` macro. Usage is the same:

`\xpdfcite{`⟨*key(s)*⟩`}`

Similarly to `\cite`, the command `\xpdfcite` may take one or two optional arguments to add some text before and after the citation.

It is also possible to replace `\cite`:

```
\usepackage{xcpdftips}
\let\cite\xpdfcite \robustify{\cite}
```

The last command `\robustify{\cite}` is needed if you wish to use `\cite`, for instance, in captions.

4 Caveats

The `xcpdftips` package will work with `natbib` with its native `\bibitem` format, and with standard LaTeX. Nothing else can be guaranteed. It will also work with `url` package.

5 Options with `docstrip`

The source `.dtx` file is meant to be processed with `docstrip`, for which a number of options are available:

`package` to produce a `.sty` package file with most comments removed;

`driver` to produce a driver `.drv` file that will print out the documentation under LaTeX 2ε. The documentation cannot be printed under LaTeX 2.09.

The source file `xcpdftips.dtx` is itself a driver file and can be processed directly by LaTeX 2ε.

6 The Coding

This section presents and explains the actual coding of the macros. It is nested between `%<*package>` and `%</package>`, which are indicators to `docstrip` that this coding belongs to the package file.

`\XC@enumeratetips` The macro `\XC@enumeratetips` gets `bibentry` for each key from the list of citations. The output is stored into `\XC@tips`, which can be directly used as a tooltip text in `\pdftooltip`.

```
⟨*package⟩

\ExplSyntaxOn

\NewDocumentCommand{ \XC@enumeratetips }%
{ > { \SplitList , } m }%
{%
  \global\undef\XC@tips%
  \undef\XC@tipsPre%
  \tl_map_inline:nn {#1}%
  {%
    \ifx\XC@tips\undefined%
      \global\def\XC@tips{}%
      \gappto{\XC@tips}{\@nameuse{BR@r@##1\@extra@b@citeb}}%
    \else%
      \def\XC@tipsPre{\textbullet\ \ }
      \gappto{\XC@tips}{,\textCR\textbullet\ \ \@nameuse{BR@r@##1\@extra@b@citeb}}%
    \fi%
  }%
  \ifx\XC@tipsPre\undefined\else%
    \gpreto{\XC@tips}{\XC@tipsPre}%
  \fi%
}

\ExplSyntaxOff

```

`\xcsetauthor` This commands sets the author used for pdf comments (default:).

```

\gdef\XC@opt@author{{}}
```

```
\newcommand{\xcsetauthor}[1]{\gdef\XC@opt@author{#1}}
```

`\xcsetmarkup` This commands sets the markup used for pdf comments (default: Underline).

```
\gdef\XC@opt@markup{Underline}
\newcommand{\xcsetmarkup}[1]{\gdef\XC@opt@markup{#1}}
```

`\xcsetcolor` This commands sets the color used for pdf comments (default: yellow).

```
\gdef\XC@opt@color{1 1 0}
\newcommand{\xcsetcolor}[1]{\gdef\XC@opt@color{#1}}
```

`\XC@opt@opacity` This commands sets the opacity used for pdf comments (default: 0).

```
\gdef\XC@opt@opacity{0}
\newcommand{\xcsetopacity}[1]{\gdef\XC@opt@opacity{#1}}
```

`\XC@citetp` This macro is in fact `\xpdfcite`.
It is a wrapper for `\XC@@citetp` to handle variable number of arguments.

```
\newcommand\XC@citetp{\@ifnextchar[{\XC@@citetp}{\XC@@citetp[]}}
```

`\XC@@citetp` This macro is called from `\xpdfcite`.
It is a wrapper for `\XC@citex` to handle variable number of arguments.

```
\newcommand\XC@@citetp{}

\def\XC@@citetp[#1]{\@ifnextchar[{\XC@citex[#1]}{\XC@citex[][#1]}}
```

`\XC@citex` This is an internal macro that does the job of `\xpdfcite`. It combines `\citep` with `\pdftooltip` and `\pdfmarkupcomment`.

```
\newcommand\XC@citex{}

\def\XC@citex[#1][#2]#3%
  {%{\protect\NoHyper%
    \ifx\tooltip\undefined%
      \XC@enumeratetips{#3}%
      \pdftooltip{\XC@oldcite[#1][#2]{#3}}{\XC@tips}%
      \pdfmarkupcomment[%
        author=\XC@opt@author,%
        markup=\XC@opt@markup,%
        color=\XC@opt@color,%
        opacity=\XC@opt@opacity,%
      ]{\vphantom{.}}{\XC@tips}%
    \else%
```

```
      \let\textCR\par%
      \XC@enumeratetips{#3}%
      \tooltip****{%
        {\protect\NoHyper\XC@oldcite[#1][#2]{#3}\protect\endNoHyper}%
      }{\parbox[t]{0.9\textwidth}{\normalsize\normalfont\XC@tips}}%
    \fi%
  }%\protect\endNoHyper}}

\let\XC@oldcite\citep  % Save \citep (in the case if it becomes redefined)

```

`\xpdfcite` A wrapper for the combined `\pdftooltip` and `\citep`.
It has the same syntax as `\citep`.

```

\let\xpdfcite\XC@citetp
\robustify{\xpdfcite}

\AtBeginDocument{\nobibliography*} % Necessary to get bibentries.

```