

- ▶ Low profile
- ▶ 1.6 x 1.2 mm Footprint
- ▶ Extended Temp Range Option
- ▶ RoHS Compliant
- ▶ MSL: 1
- ▶ Lead Finish: Au

ECX-1247

SMD CRYSTAL

The sub miniature ECX-1247 is a very compact SMD Crystal. The 1.6 x 1.2 x 0.3 mm ceramic package is ideal for today's SMD manufacturing environment.




OPERATING CONDITIONS / ELECTRICAL CHARACTERISTICS

PARAMETERS	CONDITIONS	ECX-1247			UNITS
		MIN	TYP	MAX	
Frequency Range		24.000		80.000	MHz
Frequency Tolerance	at +25°C			± 20 *	ppm
Frequency Stability	-20 to +70°C			± 30 *	ppm
Shunt Capacitance				5	pF
Load Capacitance	Specify in P/N		8		pF
Drive Level				100	µW
Operating Temperature		-20		+70	°C
Storage Temperature		-40		+85	°C
Aging (Per Year)	@ +25°C ±3°C			±5	ppm

EQUIVALENT SERIES RESISTANCE/MODE OF OSCILLATION

FREQUENCY RANGE (MHz)	MODE OF OSC	MAX ESR Ω	FREQUENCY RANGE (MHz)	MODE OF OSC	MAX ESR Ω
24.00 ~ 31.999	Fundamental	150	38.000 ~ 80.000	Fundamental	80
32.000 ~ 37.999	Fundamental	100			

DIMENSIONS (mm)



Pad Connections	
1	In/Out
2	Gnd
3	Out/In
4	Gnd

Figure 1) Top, Side, Bottom, End views and Crystal Connection (Top View)




Figure 2) Suggested Land Pattern

PART NUMBERING GUIDE: Example ECS-260-8-47-TR

ECS - Frequency Abbreviation - Load Capacitance - Package

260 = 26.000 MHz
See P/N Guide

8 = 8 pF
S=Series

47 =
ECX-1247

Custom Options

Tolerance * Stability Temp Range - Packaging

Blank = Std
A = ± 25 ppm
J = ± 20 ppm
R = ± 15 ppm
C = ± 10 ppm

Blank = Std
D = ± 100 ppm
E = ± 50 ppm
G = ± 30 ppm
H = ± 25 ppm
T = ± 20 ppm
W = ± 15 ppm
K = ± 10 ppm

Blank = Std
L = -10 ~ +70°C
M = -20 ~ +70°C
N = -40 ~ +85°C
P = -40 ~ +105°C
S = -40 ~ +125°C
U = -55 ~ +125°C

TR= Tape
& Reel
1K/Reel

*Consult Factory for available stability options over extended temp range.

Rev. 11/11