### **Data Sheet**

# HUBER+SUHNER Excellence in Connectivity Solutions

## Coaxial PCB Connector 83\_CT-0-2-1/-11\_N

#### **Description**

Straight PCB cable terminator

Interface Standards



#### **Technical Data**

**Electrical Data** 

Impedance other  $\Omega$ 

**Mechanical Data** 

Board mounting type through holes Weight 0.0007 kg

**Environmental Data** 

Operating temperature -65 °C to 165 °C 2011/65/EU (RoHS) compliant

#### **Material Data**

Piece Parts	Material	Surface Plating
Centre contact		
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating

#### **Related Documents**

Outline drawingDOU-00012683Catalogue drawingDCA-00012685Assembly instructionDOC-0000192778Mounting holeDOU-00012682

#### **Ordering Information**

Single package 83\_CT-0-2-1/-11\_NE

#### **Remarks**

PCB connector with stand-offs, suitable for cable group U2 (RG\_316\_/U), cable entry: crimped

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.