

COMMON DIMENSIONS							
DIM.	INCHES			ММ			NOTE
	MIN.	N□M.	MAX.	MIN.	N□M.	MAX.	NU E
Α	.050	.055	.059	1.27	1.40	1.50	
В	.015	.017	.019	0.38	0.43	0.49	4
С	.006	.007	.008	0.15	0.18	0.21	
D	.152	.155	.157	3.86	3.94	4.00	3
E1	.143	.148	.153	3.63	3.76	3.89	3
е	.050 BSC			1.27 BSC			
α	0°	_	10°	0°	_	10°	
θ	0°	_	12°	0*	_	12°	

VARIATION A								
DIM.	INCHES			ММ			NOTE	
	MIN.	N□M.	MAX.	MIN.	N□M.	MAX.	NUIL	
E	.163	.169	.175	4.14	4.29	4.45		
L	.025	.032	.039	0.64	0.81	0.99		
PKG. CODE	D6-1							

	VARIATION B								
DIM.	INCHES			ММ			NOTE		
IIM'	MIN.	N□M.	MAX.	MIN.	N□M.	MAX.			
E	.178	.182	.186	4.52	4.62	4.72			
L	.035	.039	.042	0.89	0.99	1.07			
PKG. CODE	D6N-1								

NUTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.
- 2. MATERIAL MUST COMPLY WITH BANNED AND RESTRICTED SUBSTANCES SPEC # 10-0131.
- DIMENSIONS D AND E1 ARE MEASURED AT THE PARTING LINE AND DO NOT INCLUDE FLASH AND PROTRUSIONS; FLASH AND PROTRUSIONS NOT TO EXCEED 0.203mm (.008") PER SIDE ON DIM. D AND 0.279mm (.011") PER SIDE ON DIM. E1.
- EXCLUSIVE OF DAMBAR PROTRUSION AND INTRUSION; DAMBAR PROTRUSION AND INTRUSION NOT TO BE POSITIONED ON FOOT OR LOWER RADIUS OF LEAD.
- ALL DIMENSIONS APPLY TO BOTH LEADED (-) AND PHFREE (+) PKG. CODES.

TITLE:

PACKAGE DUTLINE,

6L TSOC

APPROVAL DOCUMENT CONTROL NO. EDEN CHEN 04/12/11 21-0382

-DRAWING NOT TO SCALE-