

CRUD on Dancer Table

- creation of Ballroom DB and Dancer's table

```
1 /*****
2 * This script creates the database named ballroom
3 *****/
4
5 DROP DATABASE IF EXISTS ballroom;
6 CREATE DATABASE ballroom;
7 USE ballroom;
8
9 CREATE TABLE IF NOT EXISTS Dancers (
10     dancer_id INT AUTO_INCREMENT PRIMARY KEY,
11     first_name VARCHAR(50) NOT NULL,
12     last_name VARCHAR(50) NOT NULL,
13     student_status BOOLEAN NOT NULL
14 );
15
16 INSERT INTO Dancers (first_name, last_name, student_status)
17 VALUES
18 ('Melanie', 'Andrade', 1), ('John', 'Doe', 0), ('Jane', 'Smith', 1);
19
20 SELECT * FROM Dancers;
21
```

Dancers (3r x 4c)

#	dancer_id	first_name	last_name	student_status
1	1	Melanie	Andrade	1
2	2	John	Doe	0
3	3	Jane	Smith	1

- Read

Dancers List

ID	First Name	Last Name	Student	Actions
1	Melanie	Andrade	Yes	Update Delete
2	John	Doe	No	Update Delete
3	Jane	Smith	Yes	Update Delete

[Add New Dancer](#)

- Create

Add Dancer

First Name:

Last Name:

Student: ☒

Dancers List

ID	First Name	Last Name	Student	Actions
1	Melanie	Andrade	Yes	Update Delete
2	John	Doe	No	Update Delete
3	Jane	Smith	Yes	Update Delete
4	Sarah	Yang	Yes	Update Delete

[Add New Dancer](#)

- Update

Edit Dancer

First Name:

Last Name:

Student: ☒

Dancers List

ID	First Name	Last Name	Student	Actions
1	Melanie	Andrade	Yes	Update Delete
2	John	Doe	No	Update Delete
3	Jane	Doe	Yes	Update Delete
4	Sarah	Yang	Yes	Update Delete

[Add New Dancer](#)

- Delete

Dancers List

ID	First Name	Last Name	Student	Actions
1	Melanie	Andrade	Yes	Update Delete
3	Jane	Doe	Yes	Update Delete
4	Sarah	Yang	Yes	Update Delete

[Add New Dancer](#)