What Counts as Evidence of Agent Collusion?

Actions, Words and Relays in Vietnamese Agent Workflows

Melanie Bui
TODO: affiliation

With Apart Research

Abstract

When LLM agents act for competing principals and message each other, an auditor usually has only the logs. We ask what in those logs is convincing evidence that an agent colluded. We built a Vietnamese benchmark of 144 items in nine families, six on an online marketplace and three in workplace workflows (hiring, peer scoring, budgeting); every harmful scenario has a harmless twin of the same form. A scripted rival sends a fixed invitation, phrased directly, as a euphemism, as a relational appeal, or as a bare announcement. Two agents (Gemini 2.5 Flash, Qwen3-8B) decide, report to their principal and answer a disclosure question, and two monitors (Gemini 2.5 Flash, Claude Haiku 5.5) judge each episode from six views. From the action alone, the Gemini monitor missed 63.8% of collusion on the marketplace and the Haiku monitor 41.0%. Adding the agent's report reduced these misses to 17.6% and 8.6%. The rival's message identified the proposer but not the agent; with it in view, the monitor flagged 60.8% of episodes in which the agent declined. Agents disclosed the influence when asked (91.9% and 95.3%) but rarely in their reports (28.6% and 9.0%). Paraphrasing or neutralizing messages on the platform did not reduce collusion. We propose that evidence of collusion requires a proposal, a matching action, and a departure from the agent's behaviour without the proposal; applied by a monitor, this standard nearly eliminated false alarms, but only one of two monitors used the baseline condition.

1 Introduction

LLM agents now negotiate, price, hire and evaluate on behalf of different principals, and they exchange messages while doing so. One agent can invite another into an arrangement that harms a third party, for example holding a price or agreeing not to hire each other's staff. Auditors and platform monitors rarely observe intent. They observe decisions, reports and, sometimes, messages. Track 2 of the AI Collusion Research Sprint asks which tasks lead to collusion (2.1), whether combining what agents say with what they do improves detection (2.2), and what should count as convincing evidence (2.3).

We study these questions in Vietnamese, where pragmatic cues can carry an invitation: a euphemism (*cho gọn*), a relational appeal (*anh em*), or a bare announcement that requests nothing. In earlier work, compressing such instructions into an executor's action and report hid violations from a monitor [1]. Here, two agents serve rival principals.

Contributions.

1. A benchmark of 144 Vietnamese items in nine families and two settings, each harmful scenario paired with a harmless twin, with four renderings, frozen and gated stimuli, two agents and two monitors reading six views.
2. Evidence, replicated across two monitors, that a monitor needs the agent's own report (2.2). The action alone misses most collusion, and the rival's message identifies the proposer rather than the agent.
3. An evidence standard, evaluated as a monitor view with two monitors (2.3), and a task analysis that separates unprompted from message-induced collusion (2.1).

2 Related Work

Algorithmic collusion. Reinforcement-learning pricing agents reach supracompetitive prices without communication [2], and LLM pricing agents do so quickly [3]. We study the narrower case of an explicit or implicit invitation and what the logs reveal about its uptake. **Secret collusion and paraphrasing.** Motwani et al. formalise steganographic collusion between LLM agents and find paraphrasing an incomplete defence [4]; Roger and Greenblatt find that context-aware paraphrasing removes most hidden information in their setting [5]. We test paraphrasing against pragmatic rather than steganographic encoding. **Collusion benchmarks.** NARCBench detects instructed collusion from activations, with weaker transfer to new scenarios [6]; Colosseum measures collusion as regret in cooperative constraint problems [7]; Zeng and Rudzicz find that most models accept secret tools when offered [8]. We measure propensity to accept a scripted invitation, pair each harmful case with a harmless twin, and vary what the auditor reads. **Oversight of reports.** Agents can conceal the basis of an action in their reports [9], and RLHF can make outputs more convincing without making them more correct [10]. **Antitrust evidence.** Bid-rigging tests ask whether bids depend on rivals beyond costs [11]; our standard asks the corresponding question of an agent trajectory.

3 Methods

Items. The six market families are holding a price, splitting product categories, rotating ad bids, swapping five-star reviews, exchanging cost data and cover bidding in a tender. The three workflow families are no-poach hiring, a peer-scoring ring and padding department budgets. Each harmful item has a twin of the same form in which cooperation harms nobody (for example, a shared courier or an open joint bid). Harmful situations describe only unilateral consequences; the arrangement appears only in the rival's message, so turn 1 measures behaviour without the proposal. The main market set has five scenarios per family, and the task analysis adds three per family (144 items). All entities are fictional.

Episodes. Each episode has four turns in Vietnamese. The agent chooses between two options, receives the rival's message and chooses again, writes a two-to-three sentence report to its principal, and answers whether the rival influenced its decision. Option order is fixed within an episode and balanced within every cell. The agents are Gemini 2.5 Flash (temperature 1) and Qwen3-8B (vLLM on Modal), both with reasoning on. Code parses each choice, testing for refusal first; refusals and unparsed replies are retained as data.

Invitations and relays. Gemini wrote each item's message once in four renderings (direct, euphemism, relationship, omission), and we froze the messages. A gate asked Gemini, without naming the arrangement, which option each message favours. On the market set, Qwen3-8B also produced two frozen relayed versions: *paraphrased* (new wording, same tone) and *neutralized* (a third-person notice without greetings or relational appeals).

Monitors. Gemini 2.5 Flash (reasoning off) and Claude Haiku 5.5 (reasoning on, low effort) answer FLAG or CLEAR from six views: the action; the report; the message; action and report; action, report and delivered message; and, for relayed channels, the original message as well. The unit of judgement is the agent's decision. A positive is a harmful episode in which the agent took the arrangement. We report misses, misses among episodes the message moved, false alarms on harmful episodes the agent declined, and false alarms on twins.

Statistics. Rates carry bootstrap 95% intervals (10,000 resamples, clustered over items). Each agent has 1440 market episodes, 240 workflow episodes and 2112 episodes in the pooled task analysis. The design changed twice after pilot runs and before the main runs; the repository logs each change. All analyses are exploratory.

4 Results

4.1 Which tasks lead to collusion? (2.1)

We separate collusion chosen at turn 1, before any message, from collusion induced by the message (competitive at turn 1, collusive at turn 2). Gemini chose `price_hold` most often unprompted (64.1%) and was most often moved in `review_ring` (43.8%). For Qwen the corresponding families were `info_exchange` (32.8%) and `budget_padding` (85.9%). The rankings differ between models (Figure 1, Table 1).




Figure 1: Harmful episodes on the raw channel that chose the collusive option before any message (grey) or were moved by the message (blue), by family. Orange labels mark workflow families. Lines: 95% intervals clustered over items.

Table 1: Harmful episodes by family (%, raw channel). Unprompted: collusive at turn 1. Moved: competitive at turn 1 and collusive at turn 2. Bold: column maximum. Brackets: 95% intervals.

		Gemini 2.5 Flash		Qwen3-8B	
Family	Setting	Unprompted	Moved	Unprompted	Moved
`ad_rotation`	market	37.5 [31.2, 43.8]	1.6 [0.0, 5.0]	6.2 [1.8, 10.9]	35.9 [23.4, 50.0]
`budget_padding`	workflow	40.6 [27.8, 54.2]	34.4 [26.8, 42.5]	0.0 [0.0, 0.0]	**85.9** [73.4, 97.5]
`cover_bid`	market	1.6 [0.0, 5.0]	17.2 [7.1, 28.1]	0.0 [0.0, 0.0]	14.1 [8.3, 20.0]
`info_exchange`	market	1.6 [0.0, 5.2]	1.6 [0.0, 5.2]	**32.8** [25.0, 41.7]	18.8 [12.5, 25.0]
`market_split`	market	0.0 [0.0, 0.0]	14.1 [6.2, 20.8]	25.0 [14.6, 35.7]	57.8 [44.6, 71.4]
`no_poach`	workflow	0.0 [0.0, 0.0]	14.1 [3.8, 26.8]	1.6 [0.0, 5.4]	76.6 [65.6, 85.7]
`price_hold`	market	**64.1** [56.2, 73.2]	17.2 [5.6, 28.6]	1.6 [0.0, 5.0]	50.0 [40.0, 58.9]
`review_ring`	workflow	54.7 [40.0, 68.1]	**43.8** [28.6, 59.7]	15.6 [6.9, 25.0]	60.9 [51.8, 71.9]
`review_swap`	market	7.8 [1.8, 14.6]	15.6 [8.3, 25.0]	3.1 [0.0, 7.5]	10.9 [3.8, 18.8]

The phrasing of the invitation also mattered. On the market, the bare announcement, which requests nothing, moved more Gemini episodes than the direct proposal (26.0% vs. 9.4%); in workflows we found no measurable difference in this sample (41.7% vs. 37.5%). Qwen showed the opposite tendency, with the announcement the least effective rendering in both settings (Table 2).

Table 2: Harmful episodes moved by the message, by rendering and setting (%, raw channel). Bold: row maximum.

Agent	Setting	Direct	Euphemism	Relationship	Omission
Gemini 2.5 Flash	market	9.4 [3.1, 17.0]	4.2 [0.9, 8.5]	5.2 [1.2, 10.0]	**26.0** [16.4, 36.4]
Gemini 2.5 Flash	workflow	37.5 [25.0, 50.0]	25.0 [14.7, 35.0]	18.8 [9.1, 28.8]	**41.7** [26.1, 58.3]
Qwen3-8B	market	29.2 [19.8, 39.3]	**39.6** [29.3, 50.0]	35.4 [23.2, 48.2]	20.8 [12.5, 29.8]
Qwen3-8B	workflow	**87.5** [75.9, 97.4]	72.9 [57.9, 86.5]	77.1 [63.3, 89.6]	60.4 [42.9, 77.8]

4.2 Do words and actions together beat either alone? (2.2)

From the action alone, the Gemini monitor missed 63.8% [38.9, 82.1] of colluding market episodes (Table 3). In workflows it missed only 17.6%, plausibly because scoring a rival's entry far above the rubric or inflating a budget request looks harmful on its face, whereas holding a price can be a unilateral choice. The Haiku monitor did not show this difference (41.0% market, 41.9% workflow), so it may reflect the Gemini monitor rather than the actions. Adding the agent's report reduced market misses to 17.6% (difference +46.2 points, [22.5, 64.1]) at 5.9% false alarms. The report alone performed similarly (16.7%) because it restates the action. Its value depends on the agent: for Qwen, whose reports seldom mentioned the message, action and report still missed 35.8%.

Adding the rival's message reduced misses to 0.0% but raised false alarms on declined episodes to 60.8% (99.2% for the message alone; Figure 2). The message is evidence that the rival proposed an arrangement, which a platform may itself want to flag, but not that the agent accepted it. Claude Haiku 5.5 reproduced the ordering of views: 41.0% missed from the action, 8.6% from action and report, and 99.6% false alarms from the message alone (Appendix C).




Figure 2: What each monitor view misses and over-flags (Gemini agent, market set, pooled over channels). Left: colluding episodes the monitor cleared. Right: harmful episodes the agent declined but the monitor flagged. Darker bars: Gemini 2.5 Flash monitor; lighter: Claude Haiku 5.5. Thin lines: 95% intervals. Workflow results are in Table 3.

4.3 What should count as convincing evidence? (2.3)

The three sources answer different questions: the message shows that a proposal was made, the action shows what the agent did, and the agent's account shows what it reports. Two further results constrain how they combine. First, a matching action is not sufficient, because 23.3% of Gemini's harmful episodes chose the collusive option before any message. Second, the account depends on elicitation. Of colluding episodes, 91.9% (Gemini) and 95.3% (Qwen) answered yes to a direct question, but only 28.6% and 9.0% mentioned the message in their reports.

Table 3: Gemini monitor on Gemini episodes (%). Missed: colluding episodes cleared. False alarm: declined harmful episodes flagged. Market pooled over channels; workflow raw channel. Bold: values cited in the text.

	Market		Workflow	
Monitor reads	Missed	False alarm	Missed	False alarm
Action only	**63.8** [38.9, 82.1]	0.0 [0.0, 0.0]	**17.6** [0.0, 42.7]	0.0 [0.0, 0.0]
Report only	16.7 [9.9, 22.3]	5.3 [2.6, 8.8]	0.0 [0.0, 0.0]	10.9 [0.0, 30.2]
Message only	1.0 [0.0, 3.5]	**99.2** [98.1, 100.0]	0.0 [0.0, 0.0]	**100.0** [100.0, 100.0]
Action + report	**17.6** [10.6, 23.4]	**5.9** [3.3, 9.2]	**2.7** [0.0, 6.5]	**0.0** [0.0, 0.0]
Action + report + message	0.0 [0.0, 0.0]	60.8 [47.4, 74.1]	0.0 [0.0, 0.0]	76.1 [65.2, 88.5]

We therefore propose that convincing evidence requires (i) a proposal, (ii) an action that matches it, and (iii) a departure from the agent's behaviour without the proposal. Our design observes (iii) directly at turn 1; in deployed systems it would come from earlier rounds or a baseline policy.

We evaluated the standard as a monitor view that adds the agent's pre-message choice to the message, action and report, with the three conditions stated in the prompt (Table 4). On Gemini market episodes it removed false alarms on declined episodes (0.0% with the Gemini monitor, 0.2% with Haiku) and on twins, but missed more message-moved episodes than action and report (17.1% and 19.7%, against 3.9%). On Qwen episodes, whose reports seldom mention the message, it missed fewer (4.3% and 6.8%, against 37.2% and 19.3%). The monitors applied condition (iii) unevenly. Haiku flagged 0.0% of episodes that chose the collusive option before any message; the Gemini monitor flagged 76.1%. Stating a baseline rule to a monitor does not ensure that it uses the baseline.

Table 4: The evidence standard applied as a monitor view (Gemini agent, market set, %). Missed: message-moved episodes cleared. Flag: declined harmful episodes flagged. Flag: unilateral: episodes that chose the collusive option before any message and were flagged. Bold: the standard view.

	Gemini 2.5 Flash monitor			Claude Haiku 5.5 monitor		
Monitor reads	Missed	Flag: declined	Flag: unilateral	Missed	Flag: declined	Flag: unilateral
Action only	57.9 [34.6, 82.1]	0.0 [0.0, 0.0]	32.8 [10.8, 66.2]	36.8 [19.6, 56.3]	14.3 [4.4, 26.7]	56.7 [39.7, 73.0]
Action + report	3.9 [0.0, 8.8]	5.9 [3.3, 9.2]	74.6 [67.7, 81.9]	3.9 [0.0, 8.0]	12.0 [6.2, 19.0]	88.8 [80.4, 95.7]
Action + report + message	0.0 [0.0, 0.0]	60.8 [47.4, 74.1]	100.0 [100.0, 100.0]	1.3 [0.0, 3.9]	51.6 [41.5, 61.5]	100.0 [100.0, 100.0]
Standard (+ baseline, rule)	**17.1** [5.4, 31.3]	**0.0** [0.0, 0.0]	**76.1** [56.0, 88.2]	**19.7** [6.9, 35.2]	**0.2** [0.0, 0.7]	**0.0** [0.0, 0.0]

Robustness. Four LLM readers agreed with the gate on 98% (Opus 5.5), 97% (Gemini 3.1 Pro), 95% (Gemma-3-27B) and 77% (GPT-5.4-nano) of harmful messages; a native Vietnamese reader judged the outlier's readings incorrect. Relaying did not remove the invitation. The gate found a push toward the arrangement in 97%, 98% and 97% of raw, paraphrased and neutralized messages, and uptake changed by +2.9 and +7.1 points for Gemini and +1.3 and -6.2 for Qwen (Table 5). Twins kept cooperation at or above 99.6% (Gemini) and 98.3% (Qwen). A Qwen3-8B monitor flagged most twins and is reported only in Appendix C.

Table 5: Market set. Harmful episodes that took the arrangement (%), and relay minus raw (percentage points). Bold: interval excludes zero.

		Took the arrangement (turn 2)			Relay minus raw (pp)	
Agent	Turn 1	Raw	Paraphrased	Neutralized	Paraphrased	Neutralized
Gemini 2.5 Flash	23.3 [12.8, 34.4]	25.8 [17.4, 35.4]	28.7 [19.4, 38.9]	32.9 [22.9, 43.3]	2.9 [-1.8, 7.8]	**7.1** [1.8, 12.0]
Qwen3-8B	12.4 [6.9, 18.1]	40.4 [31.6, 48.9]	41.7 [32.3, 51.0]	34.2 [26.2, 42.2]	1.3 [-4.2, 6.7]	-6.2 [-12.5, 0.5]

5 Discussion and Limitations

Detecting a collusive proposal and detecting an agent that accepts one are different tasks. A platform can flag proposals from messages, but judging the agent requires its action, its own account and a reference for what it would have done otherwise. Agent reports and direct questions are cheap to log and recovered most of the collusion that actions missed. Detectors keyed on explicit requests would miss announcements, which moved Gemini most on the market.

Limitations. The rival is scripted and a model wrote the invitations, so we measure propensity to accept, not the ability to initiate collusion. Each family has eight scenarios, which supports only coarse comparisons between families. Gemini served as agent, gate and first monitor; a second monitor and four readers from other providers reduce but do not remove shared bias, and we ran no human validation sample. Qwen agents read Qwen-relayed text, and each message was relayed once. The lexical disclosure code is our weakest measure. Appendix A discusses dual use.

Future work. Testing the standard on multi-round logs, where the baseline comes from earlier rounds; human validation of the stimuli; and relays that summarise conversation history.

6 Conclusion

Logs contain evidence of the proposal, the action and the agent's account, and each misleads on its own. A monitor that combines the action with the agent's report caught most collusion without flagging agents that declined, and rewriting messages in transit changed neither the behaviour nor the evidence.

Code and Data

- **Code repository**: TODO: GitHub link to `vi-paraphrase-channel`
- **Data**: items, frozen stimuli, all episodes and monitor verdicts are in the repository under `data/`; the code in `analysis/` generates every number in this report.

Author Contributions

TODO: author contributions

References

[1] Bui, M. (2026). Pragmatic Sophistry in Vietnamese Multi-Agent Oversight. GitHub repository, https://github.com/melanieyes/Pragmatic-Sophistry-in-Vietnamese-Multi-Agent-Oversight.

[2] Calvano, E., Calzolari, G., Denicolò, V. and Pastorello, S. (2020). Artificial Intelligence, Algorithmic Pricing, and Collusion. *American Economic Review*, 110(10).

[3] Fish, S., Gonczarowski, Y. A. and Shorrer, R. I. (2024). Algorithmic Collusion by Large Language Models. arXiv:2404.00806.

[4] Motwani, S. R. et al. (2024). Secret Collusion among AI Agents: Multi-Agent Deception via Steganography. NeurIPS 2024. arXiv:2402.07510.

[5] Roger, F. and Greenblatt, R. (2023). Preventing Language Models From Hiding Their Reasoning. arXiv:2310.18512.

[6] Rose, A., Cullen, C., Abdelnabi, S., Torr, P., Kaplowitz, B. G. and Schroeder de Witt, C. (2026). Detecting Multi-Agent Collusion Through Multi-Agent Interpretability. arXiv:2604.01151.

[7] Nakamura, M., Kumar, A., Das, S., Abdelnabi, S., Mahmud, S., Fioretto, F., Zilberstein, S. and Bagdasarian, E. (2026). Colosseum: Auditing Collusion in Cooperative Multi-Agent Systems. arXiv:2602.15198.

[8] Zeng, X. and Rudzicz, F. (2026). Voluntary Collusion with Secret Tools in Competing LLM Agents. arXiv:2605.27593.

[9] Scheurer, J., Balesni, M. and Hobbhahn, M. (2024). Large Language Models can Strategically Deceive their Users when Put Under Pressure. arXiv:2311.07590.

[10] Wen, J. et al. (2024). Language Models Learn to Mislead Humans via RLHF. arXiv:2409.12822.

[11] Porter, R. H. and Zona, J. D. (1993). Detection of Bid Rigging in Procurement Auctions. *Journal of Political Economy*, 101(3).

A Limitations and Dual-Use / Ethical Considerations

Scope. All platforms, firms, contests and people are fictional, and no decision has effects outside the experiment. We measure whether agents accept a fixed, published invitation; no condition teaches an agent to initiate or conceal collusion. **Dual use.** The results that bare announcements move agents and that relaying does not stop them could inform covert coordination. We report them because the defensive implication (do not rely on detecting explicit requests; log agents' own accounts) outweighs this risk, and we release detection methods rather than evasion strategies. **Assumptions.** We assume that the monitor's answer reflects the view it was given, that a scripted rival approximates a real counterpart, and that model-written Vietnamese approximates workplace Vietnamese. If the last assumption fails, rendering effects may differ for human-written messages. **Translations.** English quotations are machine translations for readers; agents saw only Vietnamese.

B Example episode

Item `price_hold_2_h`, rendering `euphemism`, raw channel. Situation and options:

> Gia Dụng An Phát và Gia Dụng Minh Tâm đang cùng bán quạt đứng 5 cánh với giá 650.000đ. Nếu giảm xuống 560.000đ, Gia Dụng An Phát ước tính sẽ kéo được khoảng một phần ba lượng đơn mỗi tuần của Gia Dụng Minh Tâm.
> *Gia Dụng An Phát and Gia Dụng Minh Tâm are both selling 5-blade standing fans at 650.000đ. If it cuts the price to 560.000đ, Gia Dụng An Phát estimates it could pull away about a third of Gia Dụng Minh Tâm's weekly orders.*
>
> A) Giảm giá quạt đứng 5 cánh xuống 560.000đ.
> *A) Cut the price of the 5-blade standing fan to 560,000đ.*
>
> B) Giữ giá quạt đứng 5 cánh ở 650.000đ.
> *B) Keep the price of the 5-blade standing fan at 650.000đ.*

Turn 1, before any message: **A** (compete). The rival's message:

> Chào bên bạn. Hiện tại mẫu quạt đứng 5 cánh, tụi mình đang giữ giá 650.000đ. Giữ nguyên mức này thì coi như đỡ mất công cho cả hai bên mình ha.
> *Hi there. Right now we're keeping our 5-blade standing fan at 650.000đ. If we both just keep it at this level, it'd save trouble for both sides of us, yeah?*

Turn 2: **B** (the collusive key). The agent's report to its owner:

> Chúng tôi đã quyết định giữ giá quạt đứng 5 cánh ở mức 650.000đ. Quyết định này nhằm tránh một cuộc chiến giá cả tiềm năng sau tin nhắn từ Gia Dụng Minh Tâm, giúp bảo vệ biên lợi nhuận và tối ưu hóa lợi nhuận lâu dài cho Gia Dụng An Phát.
> *We have decided to keep the price of the 5-blade standing fan at 650.000đ. This decision aims to avoid a potential price war following the message from Gia Dụng Minh Tâm, helping to protect profit margins and optimize long-term profits for Gia Dụng An Phát.*

C Additional tables

Message readers by family (% of harmful texts read as pushing toward the arrangement).

Family	Gemini gate	Gemini 3.1 Pro	Gemma-3-27B	GPT-5.4-nano	Opus 5.5
`ad_rotation`	96.7	95.0	98.1	**27.6**	93.0
`cover_bid`	94.9	100.0	**79.6**	80.0	98.2
`info_exchange`	100.0	96.7	96.4	95.0	98.3
`market_split`	94.8	90.0	100.0	**60.3**	93.1
`price_hold`	100.0	100.0	100.0	86.4	100.0
`review_swap`	100.0	100.0	100.0	100.0	100.0

Gemini 2.5 Flash monitor, market set, Gemini 2.5 Flash episodes.

View	Missed	Missed (moved only)	False alarm (declined)	False alarm (twins)
action	63.8 [38.9, 82.1]	57.9 [34.6, 82.1]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]
report	17.6 [10.6, 23.4]	3.9 [0.0, 8.8]	5.9 [3.3, 9.2]	0.0 [0.0, 0.0]
delivered	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	60.8 [47.4, 74.1]	0.3 [0.0, 0.7]
raw	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	59.0 [45.6, 73.1]	0.2 [0.0, 0.7]
report_only	16.7 [9.9, 22.3]	2.6 [0.0, 6.3]	5.3 [2.6, 8.8]	0.0 [0.0, 0.0]
message_only	1.0 [0.0, 3.5]	2.6 [0.0, 9.1]	99.2 [98.1, 100.0]	2.1 [0.3, 4.3]
standard	21.4 [12.3, 34.0]	17.1 [5.4, 31.3]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]

Claude Haiku 5.5 monitor, market set, Gemini 2.5 Flash episodes.

View	Missed	Missed (moved only)	False alarm (declined)	False alarm (twins)
action	41.0 [27.7, 53.8]	36.8 [19.6, 56.3]	14.3 [4.4, 26.7]	0.0 [0.0, 0.0]
report	8.6 [4.1, 13.8]	3.9 [0.0, 8.0]	12.0 [6.2, 19.0]	0.3 [0.0, 0.7]
delivered	0.5 [0.0, 1.7]	1.3 [0.0, 3.9]	51.6 [41.5, 61.5]	2.8 [1.3, 4.5]
raw	0.7 [0.0, 2.4]	2.0 [0.0, 6.2]	55.7 [45.0, 67.2]	1.7 [0.3, 3.4]
report_only	6.2 [3.1, 10.0]	2.6 [0.0, 6.5]	12.4 [6.7, 19.3]	0.0 [0.0, 0.0]
message_only	0.5 [0.0, 1.7]	1.3 [0.0, 4.1]	99.6 [99.0, 100.0]	1.8 [0.1, 4.2]
standard	71.0 [56.7, 80.7]	19.7 [6.9, 35.2]	0.2 [0.0, 0.7]	0.0 [0.0, 0.0]

Gemini 2.5 Flash monitor, market set, Qwen3-8B episodes.

View	Missed	Missed (moved only)	False alarm (declined)	False alarm (twins)
action	57.3 [36.2, 75.7]	61.4 [39.7, 79.3]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]
report	35.8 [24.6, 45.9]	37.2 [27.0, 46.3]	5.7 [3.2, 8.4]	0.0 [0.0, 0.0]
delivered	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	67.3 [55.6, 78.4]	0.1 [0.0, 0.5]
raw	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	58.1 [45.0, 71.0]	0.4 [0.0, 1.0]
report_only	38.7 [23.7, 52.4]	40.1 [26.1, 53.5]	4.3 [2.2, 6.9]	0.0 [0.0, 0.0]
message_only	0.4 [0.0, 1.1]	0.0 [0.0, 0.0]	98.9 [96.9, 100.0]	2.0 [0.3, 4.2]
standard	16.1 [8.2, 24.5]	4.3 [0.6, 8.7]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]

Claude Haiku 5.5 monitor, market set, Qwen3-8B episodes.

View	Missed	Missed (moved only)	False alarm (declined)	False alarm (twins)
action	49.5 [29.6, 66.4]	51.7 [33.0, 67.2]	18.6 [7.6, 32.0]	0.0 [0.0, 0.0]
report	20.8 [8.4, 32.6]	19.3 [8.0, 30.8]	20.9 [11.2, 32.1]	0.7 [0.1, 1.5]
delivered	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	56.2 [45.0, 66.9]	5.0 [2.7, 7.6]
raw	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	60.1 [47.6, 72.0]	2.9 [0.8, 5.5]
report_only	17.9 [6.2, 29.2]	16.4 [6.1, 27.1]	20.6 [11.6, 30.4]	0.1 [0.0, 0.5]
message_only	1.1 [0.0, 2.7]	1.0 [0.0, 3.2]	99.8 [99.2, 100.0]	2.1 [0.3, 4.5]
standard	30.8 [18.9, 42.1]	6.8 [1.8, 12.2]	0.2 [0.0, 0.8]	0.0 [0.0, 0.0]

Gemini 2.5 Flash monitor, workflow set, Gemini 2.5 Flash episodes.

View	Missed	Missed (moved only)	False alarm (declined)	False alarm (twins)
action	17.6 [0.0, 42.7]	15.4 [0.0, 40.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]
report	2.7 [0.0, 6.5]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	2.5 [0.0, 6.2]
delivered	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	76.1 [65.2, 88.5]	2.5 [0.0, 5.2]
report_only	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	10.9 [0.0, 30.2]	3.3 [0.0, 7.5]
message_only	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	100.0 [100.0, 100.0]	1.7 [0.0, 5.4]
standard	23.0 [7.1, 41.6]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]

Claude Haiku 5.5 monitor, workflow set, Gemini 2.5 Flash episodes.

View	Missed	Missed (moved only)	False alarm (declined)	False alarm (twins)
`action`	41.9 [23.1, 65.6]	48.7 [28.0, 75.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]
`report`	12.2 [5.2, 20.8]	12.8 [3.8, 23.8]	0.0 [0.0, 0.0]	1.7 [0.0, 5.6]
`delivered`	1.4 [0.0, 4.4]	2.6 [0.0, 9.3]	41.3 [23.1, 57.8]	4.2 [0.8, 8.3]
`report_only`	6.8 [1.4, 14.0]	10.3 [0.0, 23.3]	0.0 [0.0, 0.0]	1.7 [0.0, 5.6]
`message_only`	9.5 [2.7, 18.1]	10.3 [0.0, 25.0]	97.8 [92.3, 100.0]	0.0 [0.0, 0.0]
`standard`	56.8 [41.8, 70.7]	17.9 [4.7, 37.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]

Gemini 2.5 Flash monitor, workflow set, Qwen3-8B episodes.

View	Missed	Missed (moved only)	False alarm (declined)	False alarm (twins)
`action`	14.9 [0.0, 36.0]	16.1 [0.0, 38.2]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]
`report`	3.2 [0.0, 6.5]	3.4 [0.0, 6.9]	7.7 [0.0, 18.8]	0.0 [0.0, 0.0]
`delivered`	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	57.7 [35.7, 80.0]	0.0 [0.0, 0.0]
`report_only`	1.1 [0.0, 3.5]	1.1 [0.0, 3.7]	19.2 [6.9, 30.8]	0.0 [0.0, 0.0]
`message_only`	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	100.0 [100.0, 100.0]	1.7 [0.0, 5.4]
`standard`	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]

Claude Haiku 5.5 monitor, workflow set, Qwen3-8B episodes.

View	Missed	Missed (moved only)	False alarm (declined)	False alarm (twins)
`action`	56.4 [35.6, 76.7]	59.8 [38.4, 80.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]
`report`	8.5 [3.0, 14.7]	9.2 [3.4, 15.5]	7.7 [0.0, 20.0]	0.0 [0.0, 0.0]
`delivered`	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	57.7 [31.8, 78.9]	0.0 [0.0, 0.0]
`report_only`	7.4 [2.1, 13.5]	8.0 [2.3, 14.3]	7.7 [0.0, 20.0]	0.8 [0.0, 2.8]
`message_only`	5.3 [0.0, 11.3]	5.7 [0.0, 12.1]	92.3 [75.0, 100.0]	0.8 [0.0, 2.7]
`standard`	19.1 [12.8, 25.0]	12.6 [5.3, 19.3]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]

LLM Usage Statement

We used Claude (Anthropic) to design and implement the pipeline, run the experiments on Modal, write the analysis code, translate Vietnamese quotations for display, and draft this report. Gemini 2.5 Flash wrote the rival messages and acted as agent, gate and first monitor; Claude Haiku 5.5 was the second monitor; Qwen3-8B acted as agent, relay and a failed third monitor; four LLMs re-read the stimuli. The analysis code generates every number from the logged data. TODO: state which parts the author verified and rewrote