How to Flash and Test
 -Raspberry Pi 2040 Zero

1.) Install Thonny → https://thonny.org/

2.) Download Code → Whammy4_Shutter_Gate.py

3.) Rename to → **main.py**

4.) Start Thonny, open Python File

5.) Tools → Options → Interpreter

6.) →

7.) Connect RP 2040 with PC

8.) Restart Thonny

9.) Test your Functions here

10.) Save as

11.) Flash →

TEST RP ONLY

```python
from machine import Pin, ADC
import time

# ==========================================================
# DEBUG
# ==========================================================
DEBUG = False  # <-- For Tests, set True
DEBUG_A_EVENTS = False # <-- For Tests, set True
DEBUG_A_SCOPE = True # <-- For Tests, set True
SCOPE_EVERY_MS = 5
SCOPE_WIDTH = 80

# ==========================================================
# DEVELOPMENT BYPASS
# ==========================================================
DEV_BYPASS_MOMENTARY = False # <-- For Tests, set True

# ==========================================================
# PC SOUND (Serial Frequency Output)
# ==========================================================
FREQ_SEND_EVERY_MS = 50

# ==========================================================
# BYPASS / GATE LOGIC
# ==========================================================
BYPASS_B_INVERT = True
BBM_DELAY_US = 20

def dbg(msg):
```

Kommandozeile ×

```
█····· ····· █ ···· █ ····· █ ····· █ ····· █ ···· ███ ···· ██ ··· half=30ms
A=0  B=0
··· ██ ···· ··· ██ ···· ██ ···· ██ ···· ██ ···· ██ ····· ·· half=30ms
A=0  B=0
···· ██ ···· ██ ····· ██ ···· ██ ···· ·
[SCOPE STOP]


[SCOPE START]
██ ····· ···· ██ ···· ██ ···· ██ ···· ██ ····· ██ ···· ██ ··· half=30ms
A=0  B=0
··· ██ ···· ██ ···· ██ ···· ██ ···· ██ ···· ██ ····· ·· half=30ms
A=0  B=0
···· ██ ···· ██ ···· ██ ···· ██ ···· ██ ···· ██ half=30ms
A=1  B=1
██ ····· ██ ···· ██ ····· ██ ···· ██ ···· ·
```