

Adversarial Auto-Encoders (AAEs) and Wasserstein Auto-Encoders (WAEs)

Alex Lin Melissa Yu

Harvard University

April 5, 2018

Published as a conference paper at ICLR 2018

WASSERSTEIN AUTO-ENCODERS

Ilya Tolstikhin

MPI for Intelligent Systems
Tübingen, Germany
ilya@tue.mpg.de

Olivier Bousquet

Google Brain
Zürich, Switzerland
obousquet@google.com

Sylvain Gelly

Google Brain
Zürich, Switzerland
sylvaingelly@google.com

Bernhard Schölkopf

MPI for Intelligent Systems
Tübingen, Germany
bs@tue.mpg.de

A Quick Review of VAEs

- Let our data $x_1, \dots, x_n \in \mathcal{X}$ be distributed according to P_X .

A Quick Review of VAEs

- Let our data $x_1, \dots, x_n \in \mathcal{X}$ be distributed according to P_X .
- Goal of generative modeling is to find a model G with $P_G : \mathcal{X} \rightarrow [0, 1]$ that minimizes a specified distance $D(P_X, P_G)$.

A Quick Review of VAEs

- Let our data $x_1, \dots, x_n \in \mathcal{X}$ be distributed according to P_X .
- Goal of generative modeling is to find a model G with $P_G : \mathcal{X} \rightarrow [0, 1]$ that minimizes a specified distance $D(P_X, P_G)$.
- **Variational Auto-Encoders** (VAEs) seek to minimize

$$D_{KL}(P_X, P_G) = \underbrace{-\mathbb{E}_{P_X}[\log P_G(X)]}_{\text{negative log-likelihood}} + \underbrace{\mathbb{E}_{P_X}[\log P_X(X)]}_{\text{entropy of data}}$$

A Quick Review of VAEs

- Let our data $x_1, \dots, x_n \in \mathcal{X}$ be distributed according to P_X .
- Goal of generative modeling is to find a model G with $P_G : \mathcal{X} \rightarrow [0, 1]$ that minimizes a specified distance $D(P_X, P_G)$.
- **Variational Auto-Encoders** (VAEs) seek to minimize

$$D_{KL}(P_X, P_G) = \underbrace{-\mathbb{E}_{P_X}[\log P_G(X)]}_{\text{negative log-likelihood}} + \underbrace{\mathbb{E}_{P_X}[\log P_X(X)]}_{\text{entropy of data}}$$

- The NLL cannot be optimized directly, so VAEs use an **upper bound**.

$$NLL \leq \underbrace{\inf_{Q(Z|X) \in \mathcal{Q}}}_{\text{min over all encoders}} -\mathbb{E}_{P_X} \left[\underbrace{\mathbb{E}_{Q(Z|X)}[\log P_G(X|Z)]}_{\text{reconstruction loss}} - \underbrace{D_{KL}(Q(Z|X), P_Z)}_{\text{regularization loss}} \right]$$

A Quick Review of VAEs

- Let our data $x_1, \dots, x_n \in \mathcal{X}$ be distributed according to P_X .
- Goal of generative modeling is to find a model G with $P_G : \mathcal{X} \rightarrow [0, 1]$ that minimizes a specified distance $D(P_X, P_G)$.
- **Variational Auto-Encoders** (VAEs) seek to minimize

$$D_{KL}(P_X, P_G) = \underbrace{-\mathbb{E}_{P_X}[\log P_G(X)]}_{\text{negative log-likelihood}} + \underbrace{\mathbb{E}_{P_X}[\log P_X(X)]}_{\text{entropy of data}}$$

- The NLL cannot be optimized directly, so VAEs use an **upper bound**.

$$NLL \leq \underbrace{\inf_{Q(Z|X) \in \mathcal{Q}}}_{\text{min over all encoders}} \underbrace{-\mathbb{E}_{P_X}[\mathbb{E}_{Q(Z|X)}[\log P_G(X|Z)]]}_{\text{reconstruction loss}} - \underbrace{D_{KL}(Q(Z|X), P_Z)}_{\text{regularization loss}}$$

- Take-Away: VAEs **minimize an upper bound on KL divergence** between the data and the model.

Using Wasserstein instead of KL

- Alternative way to measure distance between probability distributions

Using Wasserstein instead of KL


- Alternative way to measure distance between probability distributions
- Aka Earth Mover's Distance, Kantorovich-Rubinstein Metric, Optimal Transfer Plan

Using Wasserstein instead of KL

- Alternative way to measure distance between probability distributions
- Aka Earth Mover's Distance, Kantorovich-Rubinstein Metric, Optimal Transfer Plan
- Defined with respect to a cost function $c : \mathcal{X} \times \mathcal{X} \rightarrow \mathbb{R}_+$ as

$$W_c(P_X, P_Y) = \inf_{\Gamma \in \mathcal{P}(X \sim P_X, Y \sim P_Y)} \mathbb{E}_{(X, Y) \sim \Gamma} [c(X, Y)]$$

where $\Gamma(x, y)$ is the "transport plan".



Using Wasserstein instead of KL

- The objective is

$$W_c(P_X, P_Y) = \inf_{\Gamma \in \mathcal{P}(X \sim P_X, Y \sim P_Y)} \mathbb{E}_{(X, Y) \sim \Gamma} [c(X, Y)]$$

Using Wasserstein instead of KL

- The objective is

$$W_c(P_X, P_Y) = \inf_{\Gamma \in \mathcal{P}(X \sim P_X, Y \sim P_Y)} \mathbb{E}_{(X,Y) \sim \Gamma} [c(X, Y)]$$



Using Wasserstein instead of KL

- The objective is

$$W_c(P_X, P_Y) = \inf_{\Gamma \in \mathcal{P}(X \sim P_X, Y \sim P_Y)} \mathbb{E}_{(X,Y) \sim \Gamma} [c(X, Y)]$$



- Γ must be some joint distribution of X, Y because
 - $\int_x \Gamma(x, y) dx = P_X(x) \Rightarrow$ Total earth leaving x = total earth at x
 - $\int_y \Gamma(x, y) dy = P_Y(y) \Rightarrow$ Total earth entering y = total earth at y

- Consider a latent space \mathcal{Z} with prior P_Z . We want to find a model (i.e. decoder) $G : \mathcal{Z} \rightarrow \mathcal{X}$ that minimizes the **Wasserstein distance**

$$W_c(P_X, P_G) = \inf_{\Gamma \in \mathcal{P}(X \sim P_X, Y \sim P_G)} \mathbb{E}_{(X, Y) \sim \Gamma} [c(X, Y)]$$

Wasserstein Auto-Encoder

- Consider a latent space \mathcal{Z} with prior P_Z . We want to find a model (i.e. decoder) $G : \mathcal{Z} \rightarrow \mathcal{X}$ that minimizes the **Wasserstein distance**

$$W_c(P_X, P_G) = \inf_{\Gamma \in \mathcal{P}(X \sim P_X, Y \sim P_G)} \mathbb{E}_{(X, Y) \sim \Gamma} [c(X, Y)]$$

- [Bousquet et al. (2017)]** This is equivalent to minimizing

$$W_c(P_X, P_G) = \underbrace{\inf_{Q : Q_Z = P_Z}}_{\text{min over encoders with marginal } P_Z} \mathbb{E}_{P_X} \underbrace{\mathbb{E}_{Q(Z|X)} [c(X, G(Z))]}_{\text{reconstruction cost}}$$

where $Q_Z = \int Q(Z|X)P_X(X)dX$.

Wasserstein Auto-Encoder

- The **WAE objective** relaxes the constraint $Q_Z = P_Z$ by adding a penalty. It minimizes

$$D_{WAE}(P_X, P_G) = \inf_{Q(Z|X) \in \mathcal{Q}} \mathbb{E}_{P_X} \mathbb{E}_{Q(Z|X)}[c(X, G(Z))] + \lambda \cdot \mathcal{D}_Z(Q_Z, P_Z)$$

where \mathcal{D} is some divergence and λ is some regularization parameter.


Wasserstein Auto-Encoder

- The **WAE objective** relaxes the constraint $Q_Z = P_Z$ by adding a penalty. It minimizes

$$D_{WAE}(P_X, P_G) = \inf_{Q(Z|X) \in \mathcal{Q}} \mathbb{E}_{P_X} \mathbb{E}_{Q(Z|X)} [c(X, G(Z))] + \lambda \cdot \mathcal{D}_Z(Q_Z, P_Z)$$

where \mathcal{D} is some divergence and λ is some regularization parameter.

- Claims to fix **blurriness issue** of VAEs



- The **WAE objective** minimizes

$$D_{WAE}(P_X, P_G) = \inf_{Q(Z|X) \in \mathcal{Q}} \mathbb{E}_{P_X} \mathbb{E}_{Q(Z|X)}[c(X, G(Z))] + \lambda \cdot \mathcal{D}_Z(Q_Z, P_Z)$$

- The **WAE objective** minimizes

$$D_{WAE}(P_X, P_G) = \inf_{Q(Z|X) \in \mathcal{Q}} \mathbb{E}_{P_X} \mathbb{E}_{Q(Z|X)}[c(X, G(Z))] + \lambda \cdot \mathcal{D}_Z(Q_Z, P_Z)$$

- There are two sources of customization.

- The **WAE objective** minimizes

$$D_{WAE}(P_X, P_G) = \inf_{Q(Z|X) \in \mathcal{Q}} \mathbb{E}_{P_X} \mathbb{E}_{Q(Z|X)}[c(X, G(Z))] + \lambda \cdot \mathcal{D}_Z(Q_Z, P_Z)$$

- There are two sources of customization.
 - 1 Choose **divergence** between Q_Z and P_Z .

Wasserstein Auto-Encoder

- The **WAE objective** minimizes

$$D_{WAE}(P_X, P_G) = \inf_{Q(Z|X) \in \mathcal{Q}} \mathbb{E}_{P_X} \mathbb{E}_{Q(Z|X)}[c(X, G(Z))] + \lambda \cdot \mathcal{D}_Z(Q_Z, P_Z)$$

- There are two sources of customization.
 - 1 Choose **divergence** between Q_Z and P_Z .

WAE-GAN	WAE-MMD
$\mathcal{D}_Z = D_{JS}$	$\mathcal{D}_Z = MMD_k$
Introduce adversarial discriminator in \mathcal{Z}	Use unbiased U-statistic estimator

Wasserstein Auto-Encoder

- The **WAE objective** minimizes

$$D_{WAE}(P_X, P_G) = \inf_{Q(Z|X) \in \mathcal{Q}} \mathbb{E}_{P_X} \mathbb{E}_{Q(Z|X)}[c(X, G(Z))] + \lambda \cdot \mathcal{D}_Z(Q_Z, P_Z)$$

- There are two sources of customization.

- 1 Choose **divergence** between Q_Z and P_Z .

WAE-GAN	WAE-MMD
$\mathcal{D}_Z = D_{JS}$	$\mathcal{D}_Z = MMD_k$
Introduce adversarial discriminator in \mathcal{Z}	Use unbiased U-statistic estimator

- 2 Choose **reconstruction cost** function c .

Wasserstein Auto-Encoder

- The **WAE objective** minimizes

$$D_{WAE}(P_X, P_G) = \inf_{Q(Z|X) \in \mathcal{Q}} \mathbb{E}_{P_X} \mathbb{E}_{Q(Z|X)} [c(X, G(Z))] + \lambda \cdot \mathcal{D}_Z(Q_Z, P_Z)$$

- There are two sources of customization.

- 1 Choose **divergence** between Q_Z and P_Z .

WAE-GAN	WAE-MMD
$\mathcal{D}_Z = D_{JS}$	$\mathcal{D}_Z = MMD_k$
Introduce adversarial discriminator in \mathcal{Z}	Use unbiased U-statistic estimator

- 2 Choose **reconstruction cost** function c .
 - If $c(x, x') = \|x - x'\|_2^2$, then WAE-GAN is equivalent to AAE

Wasserstein Auto-Encoder

- The **WAE objective** minimizes

$$D_{WAE}(P_X, P_G) = \inf_{Q(Z|X) \in \mathcal{Q}} \mathbb{E}_{P_X} \mathbb{E}_{Q(Z|X)}[c(X, G(Z))] + \lambda \cdot \mathcal{D}_Z(Q_Z, P_Z)$$

- There are two sources of customization.

- 1 Choose **divergence** between Q_Z and P_Z .

WAE-GAN	WAE-MMD
$\mathcal{D}_Z = D_{JS}$	$\mathcal{D}_Z = MMD_k$
Introduce adversarial discriminator in \mathcal{Z}	Use unbiased U-statistic estimator

- 2 Choose **reconstruction cost** function c .
 - If $c(x, x') = \|x - x'\|_2^2$, then WAE-GAN is equivalent to AAE
 - Theoretical justification of AAE as minimizing 2-Wasserstein distance

- Test VAE, WAE-GAN, WAE-MMD on MNIST and CelebA
- Record Frechet Inception Distance (FID) to assess quality of images

Algorithm	FID
VAE	82
WAE-MMD	55
WAE-GAN	42

Table 1: FID scores for samples on CelebA (smaller is better).

ADVERSARIALLY REGULARIZED AUTOENCODERS

Junbo (Jake) Zhao¹, Yoon Kim², Kelly Zhang¹, Alexander M. Rush², Yann LeCun^{1,3}

¹ Department of Computer Science, New York University

² School of Engineering and Applied Sciences, Harvard University

³ Facebook AI Research

{jakezhao,kz918,yann}@cs.nyu.edu, {yoonkim,srush}@seas.harvard.edu

WASSERSTEIN AUTO-ENCODERS: LATENT DIMENSIONALITY AND RANDOM ENCODERS

Paul Rubenstein*, Bernhard Schölkopf, Ilya Tolstikhin

Empirical Inference

Max Planck Institute for Intelligent Systems, Tübingen

{paul.rubenstein,bs,ilya}@tuebingen.mpg.de

LEARNING DISENTANGLED REPRESENTATIONS WITH WASSERSTEIN AUTO-ENCODERS

Paul Rubenstein*, Bernhard Schölkopf, Ilya Tolstikhin

Empirical Inference

Max Planck Institute for Intelligent Systems, Tübingen

{paul.rubenstein,bs,ilya}@tuebingen.mpg.de

Our Project

- Build on work of Zhao et. al (2018) in applying WAEs to text

Our Project

- Build on work of Zhao et. al (2018) in applying WAEs to text
- Semi-Supervised Learning for transferring between different styles of English

Our Project

- Build on work of Zhao et. al (2018) in applying WAEs to text
- Semi-Supervised Learning for transferring between different styles of English
 - Shakespearean English vs. Modern English

ORIGINAL TEXT	MODERN TEXT
JULIET By and by, I come.— To cease thy strife and leave me to my grief. 155 Tomorrow will I send.	JULIET Alright, I'm coming!—I beg you to stop trying for me and leave me to my sadness. Tomorrow I'll send the messenger.
ROMEO So thrive my soul—	ROMEO My soul depends on it—

Our Project

- Build on work of Zhao et. al (2018) in applying WAEs to text
- Semi-Supervised Learning for transferring between different styles of English
 - Shakespearean English vs. Modern English

ORIGINAL TEXT	MODERN TEXT
JULIET By and by, I come.— To cease thy strife and leave me to my grief. 155 Tomorrow will I send.	JULIET Alright, I'm coming!—I beg you to stop trying for me and leave me to my sadness. Tomorrow I'll send the messenger.
ROMEO So thrive my soul—	ROMEO My soul depends on it—

- Formal English vs. Informal English

Informal: *I'd say it is punk though.*

Formal: *However, I do believe it to be punk.*

Informal: *Gotta see both sides of the story.*

Formal: *You have to consider both sides of the story.*
