# electus versio

## _travelers guide _for timing the void

| 9 | 8× | 7 |
|---|---|---|
| clock ratios | desmodus time | knobs · 2 switches · tap |

[ tap ] press  [ tap ] hold  › then  noon = 12 o'clock  numbers = the numbered panel

clocked stereo atmospheres · delay to reverb · tap tempo · a free firmware for any versio

← back to the versio starsystem

magenta = hold

## 01 what it is

ev_01

| | |
|---|---|
| atmospheres | the clocked sibling of desmodus · delays to reverbs, dirtier and more delay-like |
| the difference | 16 or 20 delays, 8× longer base time than desmodus, so it can follow a clock |
| in 1 · in 2 | stereo in · in 1 alone feeds both sides |
| out 1 · out 2 | stereo out |
| swap in | free on any versio · how to swap · video |

## 02 blend · regen

ev_02 · knobs 1 + 5

| | |
|---|---|
| 1 [ blend ] | dry left · both at noon · only the atmosphere right |
| 5 [ regen ] | feedback · around noon shorter, tamer tails |
| past noon | 100% · endless, evolving tails |
| past 3:00 | input ducks the tails, sidechain style |

## _fig.02 : regen

knob 5




## 10 first flight

ev_10 · a clean start

1. sound into in 1 · out 1 out 2 to your mixer
2. abc lim · xyz c · 1 [ blend ] 3 [ tone ] 4 [ index ] at noon
3. set the space with 6 [ size ] and 7 [ dense ]
4. tap [ tap ] or patch a clock · size now picks the ratio
5. raise 5 [ regen ] · past noon it never stops
6. try dst and shm · [ tap ] 2 s to unclock


## 03 size · dense · tone

ev_03 · knobs 6 · 7 · 3 · fig.01

| | |
|---|---|
| 6 [ size ] | delay time · comb bursts (left) to long lush delays (right) |
| clocked | size becomes a clock ratio · fig.01 |
| 7 [ dense ] | line spacing · left delay-like · right smeared reverb |
| 3 [ tone ] | filter in the tank · left lowpass · noon off · right highpass |

## _fig.01 : size when clocked

nine ratios of the clock · knob 6





## 04 speed · index

ev_04 · knobs 2 + 4

| | |
|---|---|
| 2 [ speed ] | internal lfo rate |
| 4 [ index ] | lfo depth on the lines · noon off · left random · right sine |

## _fig.04 : signal path

from the controls




## 05 switches

ev_05 · abc · xyz

| | |
|---|---|
| abc left | [ lim ] clean · limiting holds the feedback |
| abc mid | [ dst ] clipping instead · dirtier tails |
| abc right | [ shm ] octave-up shimmer fed back in |
| xyz | [ l ] · [ c ] · [ r ] how the delay lines connect · older panels say bnd · lrp · jmp |

## 07 tap · clock

ev_07 · fsu = tap

| | |
|---|---|
| [ tap ] | tap tempo |
| fsu jack | clock in · above 2 V |
| [ tap ] 2 s | back to free-running · size sets the time again |
| patched clock | unpatch it first, then hold tap |
| boot | magenta · yellow · cyan · white = electus is loaded |

## 08 eight patches

ev_08 · from the manual · abc · xyz

| | | |
|---|---|---|
| **room** | size and tone shape the room | lim · c |
| **big hall** | size, tone and index set the colour · vary speed and regen | lim · c |
| **light bright delay** | clock on tap or not · size picks the ratio | lim · c |
| **tape warble delay** | index + speed warble the repeats · tone darkens · regen for grit | dst · l |
| **shimmery** | tone shapes the highs · a little index warbles and diffuses | shm · c |
| **drunken atmosphere** | lots of modulation | dst · c |
| **kick ducker** | a kick in · regen past 3:00 | dst · c |
| **evolving decay** | a repeating sequence · it keeps changing · clock optional | lim · c |

## _fig.06 : what the LEDs say

at boot




## _fig.03 : the panel

numbers match the legend




| | |
|---|---|
| 1 | blend · dry ↔ wet |
| 2 | speed · lfo rate |
| 3 | tone · lp ← · → hp |
| 4 | index · random ← · → sine |
| 5 | regen · endless past noon |
| 6 | size · time · or clock ratio |
| 7 | dense · delay → reverb |
| abc | atmosphere · lim · dst · shm |
| xyz | structure · l · c · r |
| fsu | tap · tap · clock in |
| in | in 1 / 2 · in 1 feeds both if alone |
| out | out 1 / 2 · stereo out |

## 09 specs

ev_09

| | |
|---|---|
| cv in | 0 – 5 V |
| tap gate | above 2 V |
| audio in | clips near 16 V peak to peak |
| size | 10 hp · 1.5 in deep |
| power | version a 70 mA +12 V · 70 mA –12 V · version b 125 mA · 10 mA · no 5 V |