

HARCOURT BUTLER TECHNICAL UNIVERSITY (HBTU), KANPUR

B.Tech 1st Year Engineering Mechanics / Fundamentals

UNIT 2: Fundamental Concepts and Definitions

Complete Academic Notes, Theoretical Formulations, Engineering Mechanics & Design Reference

100% Complete Syllabus

Clean Mathematical Notation

Labeled Technical Diagrams

HBTU Examination Aligned

PRESCRIBED SYLLABUS TOPICS COVERED IN THIS DOCUMENT

- **Mechanical Engineering:** Scope, expanse, and multidisciplinary domains
- **Machines & Mechanisms:** Kinematic links, pairs, kinematic chains, and inversions
- **Classification of Machines:** Energy transformation, motion, automation, and medium
- **Thermodynamic Systems:** Open, closed, isolated, boundaries, and equilibrium
- **Laws of Thermodynamics:** Zeroth, First (SFEE & PMM-1), Second (KP/Clausius), Third
- **Modes of Heat Transfer:** Conduction (Fourier), Convection (Newton), Radiation (Stefan-Boltzmann)
- **Materials Science:** Metals, ceramics, polymers, composites, and selection criteria
- **Manufacturing Processes:** Casting, forming, machining, joining, and hot/cold working

1. Mechanical Engineering: Scope and Expanse

Mechanical Engineering is one of the oldest, broadest, and most versatile branches of engineering. It deals with the fundamental laws of nature—specifically mechanics, thermodynamics, and materials science—to design, analyze, manufacture, and maintain mechanical equipment, energy conversion devices, and complex automated systems.

1.1 Scope of Mechanical Engineering

The traditional scope of mechanical engineering is organized into two primary disciplines:

1. Thermal and Fluid Sciences (Energy Engineering):

- **Thermodynamics and Power Plants:** Generation of electric power through coal-fired thermal power plants (Rankine cycle), gas turbines (Brayton cycle), nuclear reactors, and combined cycle plants.
- **Internal Combustion (IC) Engines:** Spark-ignition (Otto cycle) and compression-ignition (Diesel cycle) engines used in passenger, commercial, and marine transit.
- **Fluid Mechanics and Turbomachinery:** Hydroelectric generation via impulse (Pelton wheel) and reaction (Francis, Kaplan) turbines, industrial pumps, fans, and compressors.
- **Refrigeration and Air Conditioning (HVAC):** Domestic refrigeration (Vapour Compression Refrigeration Systems - VCRS), industrial cold storage, cryogenic gas separation, and climate control in high-rise buildings and aerospace cabins.

2. Solid Mechanics and Machine Design:

- **Mechanics of Solids / Strength of Materials:** Stress-strain analysis, torsion of drive shafts, bending of structural beams, deflection, and stability of columns.
- **Theory of Machines and Kinematics:** Linkage kinematics, transmission gears, cam-follower design, dynamic balancing of reciprocating and rotating engines, and structural vibrations.
- **Machine Design:** Analytical design of fasteners, bolted/welded joints, power screws, roller/journal bearings, helical springs, and pressure vessels complying with safety codes.

1.2 Expanse and Modern Interdisciplinary Frontiers

The expanse of mechanical engineering has expanded rapidly beyond traditional heavy metalworking into high-tech, multi-disciplinary fields:

Emerging Technical Domains

- **Mechatronics and Robotics:** Synergistic integration of mechanical structures with sensors, microcontrollers, and servo-actuators for robotic assembly, surgical robotics, and automated guided vehicles (AGVs).
- **Additive Manufacturing (3D Printing):** Direct laser metal sintering (DMLS) of titanium and Inconel alloys for lightweight aerospace manifolds and personalized medical implants.
- **Renewable Energy Engineering:** Aerodynamic structural optimization of 100-meter composite wind turbine blades, tidal power barrages, and solar thermal collectors.

Societal & Industrial Frontiers

- **Electric Mobility (EV / Hybrid):** Battery Thermal Management Systems (BTMS), lightweight chassis topology optimization, high-torque electric transaxles, and regenerative braking.
- **Bio-Mechanical Engineering:** Prosthetic limbs, artificial heart pumps, vascular stent mechanics, and ergonomic design of assistive devices.
- **Aerospace & Defense Systems:** Hypersonic scramjet propulsion, rocket motor nozzles, satellite deployment hinges, and ballistic impact shielding.

2. Concept of Machines, Mechanisms, and Classification of Machines

Definition of a Machine: A *machine* is an assemblage of resistant bodies (links) configured with definite relative motions, arranged to utilize energy from an external source and transform it into useful mechanical work to perform a specific operation.

Definition of a Mechanism: A *mechanism* is a combination of rigid or resistant bodies constrained and interconnected so that the motion of any one body causes predictable, definite relative motions in all others. Its primary purpose is the **transmission and modification of motion**, whereas a machine transforms **energy into useful work**.

2.1 Comparison: Machine vs. Mechanism

Attribute	Mechanism	Machine
Primary Function	Transmits and modifies relative motion from input to output.	Receives energy and transforms it into useful mechanical work.
Energy Transformation	Does not perform net work transformation; energy transfer is nominal.	Major energy conversion occurs (e.g., thermal/electrical to mechanical).
Forces & Stresses	Transmits minor forces; designed primarily using kinematic geometry.	Withstands heavy operational forces, dynamic stresses, and wear; designed for structural strength.
Standard Examples	Clockwork escapement, pantograph, typewriter linkages, indicator mechanisms.	Internal combustion engine, lathe machine, steam turbine, shaping machine.

2.2 Kinematic Elements and Terminology

- **Kinematic Link (Element):** A resistant body or an assembly of resistant bodies having no relative motion among its parts.
 - *Rigid Link:* Negligible deformation under load (e.g., connecting rod, crank).
 - *Flexible Link:* Deforms in an elastic, controlled manner to transmit tensile pull (e.g., belts, ropes, chains).
 - *Fluid Link:* Transmits power via hydrostatic or hydrodynamic pressure (e.g., hydraulic brake fluid, hydraulic press ram).

- **Kinematic Pair:** Two interconnected links maintained in permanent contact having constrained relative motion.
 - *By Nature of Relative Motion:* Sliding pair (piston inside cylinder), Turning pair (crankshaft in journal bearing), Rolling pair (ball in ball bearing), Screw pair (lead screw and carriage nut), Spherical pair (ball-and-socket suspension joint).
 - *By Nature of Surface Contact:*
 - **Lower Pair:** Surface or area contact between mating bodies (e.g., sliding, turning, and screw pairs). Exhibits higher load capacity and lower contact stress.
 - **Higher Pair:** Point or line contact between mating bodies (e.g., cam and roller follower, meshing spur gear teeth). Subject to higher local contact stresses.
- **Kinematic Chain:** An assembly of kinematic links connected by kinematic pairs such that the relative motion of the links is completely or successfully constrained.

$$L = 2P - 4 \quad \text{and} \quad J = \frac{3}{2}L - 2$$

where L = number of links, P = number of pairs, and J = number of binary joints.

- If $L > 2P - 4$: Structure or locked chain (frame, truss; no relative motion possible).
- If $L = 2P - 4$: Constrained kinematic chain (basis of all mechanisms).
- If $L < 2P - 4$: Unconstrained kinematic chain (indeterminate motion).
- **Inversion of Mechanism:** The technique of obtaining different mechanisms by fixing different links of a kinematic chain one at a time.

Inversions of Slider-Crank Chain:

1. **Link 1 (Cylinder/Frame) Fixed:** Reciprocating IC engine, reciprocating air compressor.
2. **Link 2 (Crank) Fixed:** Whitworth quick-return motion mechanism, Gnome rotary aircraft engine.
3. **Link 3 (Connecting Rod) Fixed:** Crank and slotted-lever quick-return mechanism, oscillating cylinder engine.
4. **Link 4 (Slider/Piston) Fixed:** Hand water pump, Bull engine.



Figure 2.1: Kinematic Inversion 1 of the Slider-Crank Mechanism (Foundation of Internal Combustion Engines)

2.3 Comprehensive Classification of Machines


Classification Basis	Categories	Industrial Examples & Operating Characteristics
1. Energy Transformation	• Prime Movers (Generating): Convert natural energy resources directly into mechanical shaft work. • Driven Machines (Consuming): Absorb mechanical energy to perform useful operations.	• <i>Prime Movers:</i> Steam turbines, hydraulic turbines, IC engines, windmills. • <i>Driven Machines:</i> Centrifugal water pumps, lathes, milling machines, refrigeration compressors.
2. Motion / Kinematics	• Rotary Machines: Continuous 360° rotational motion. • Reciprocating Machines: Periodic back-and-forth linear motion. • Oscillating Machines: Periodic back-and-forth angular motion.	• <i>Rotary:</i> Electric motors, centrifugal fans, turbo-compressors. • <i>Reciprocating:</i> Piston compressors, shaper rams, punch presses. • <i>Oscillating:</i> Industrial vibratory screens, clock pendulums.
3. Level of Automation	• Manual: Hand-powered operation. • Semi-Automatic: Loading/unloading is manual; operational cycle runs automatically. • Fully Automatic / CNC: Closed-loop robotic/computer numerical control.	• <i>Manual:</i> Bench arbor presses, hand shears. • <i>Semi-Automatic:</i> Capstan and turret lathes. • <i>CNC:</i> 5-Axis machining centers, robotic welding workcells.
4. Working Medium	• Thermal Machines: Work via compressible gases or steam. • Hydraulic Machines: Work via pressurized liquids. • Electrical Machines: Work via electromagnetic fields.	• <i>Thermal:</i> Boilers, gas turbine combustors. • <i>Hydraulic:</i> Hydraulic jacks, Pelton wheels, excavators. • <i>Electrical:</i> 3-phase induction motors, synchronous alternators.

3. Thermodynamic Systems, Surroundings, and State Properties

Thermodynamics is the physical science that governs heat, work, energy transformations, and the equilibrium properties of matter.

3.1 System, Surroundings, and Boundaries

- **System:** A specified quantity of matter or a defined region in space selected for thermodynamic investigation.
- **Surroundings:** Everything outside the thermodynamic system boundary.
- **Boundary:** The real or imaginary, fixed or movable envelope separating system from surroundings. Energy (heat, work) and/or mass may traverse this boundary.



3.2 Classification of Thermodynamic Systems

- 1. Open System (Control Volume):** Mass and energy cross the boundary simultaneously.
Examples: Steam boiler, steam turbine, centrifugal compressor, nozzle, open water heater.
- 2. Closed System (Control Mass):** A fixed quantity of matter; mass cannot cross the boundary, but heat and work energy interactions do take place.
Examples: Gas confined in a leak-proof piston-cylinder assembly, closed pressure cooker with weight valve seated, sealed electric storage battery.
- 3. Isolated System:** Neither mass nor energy (heat or work) can cross the boundary. The boundary is completely rigid and adiabatic.
Examples: A rigid vessel with a perfect vacuum jacket (ideal thermos flask), the entire Universe.

3.3 Thermodynamic Properties, State, and Processes

- **Intensive Properties:** Physical properties that are independent of the mass or extent of the system.
Examples: Temperature (T), Pressure (P), Density (ρ), Dynamic Viscosity (μ), Specific Volume (v), Specific Enthalpy (h).
- **Extensive Properties:** Properties whose numerical values depend directly on the mass or physical extent of the system.
Examples: Total Mass (m), Total Volume (V), Total Internal Energy (U), Total Enthalpy (H), Total Entropy (S).
- **Thermodynamic Equilibrium:** A state of rest where no spontaneous macroscopic changes occur. Requires four conditions simultaneously:
 1. *Mechanical Equilibrium:* Absence of unbalanced forces and pressure gradients within the system.
 2. *Thermal Equilibrium:* Completely uniform and constant temperature throughout.
 3. *Chemical Equilibrium:* No chemical reactions or spontaneous mass diffusion between phases.
 4. *Phase Equilibrium:* Mass of each phase remains static over time.
- **Quasi-Static (Reversible) Process:** A process that proceeds infinitesimally slowly such that the system remains in continuous thermodynamic equilibrium at every intermediate state.

4. Laws of Thermodynamics: Core Principles & Mathematical Statements

4.1 The Zeroth Law of Thermodynamics (Concept of Temperature)

Statement: If two thermodynamic bodies A and B are each in thermal equilibrium with a third body C , then bodies A and B are in mutual thermal equilibrium with each other.

Physical Significance: Formulated by Ralph H. Fowler in 1931, the Zeroth Law establishes **Temperature** as an objective thermodynamic scalar property. It provides the foundation for all thermometry: body C functions as the calibrated thermometer, and bodies A and B share identical temperature if they are in thermal equilibrium with C .

4.2 The First Law of Thermodynamics (Conservation of Energy)

Statement: Energy can neither be created nor destroyed; it can only transform from one form to another. For any closed system undergoing a complete thermodynamic cycle, the net cyclic heat added equals the net cyclic work performed.

Cyclic Process Formulation:

$$\oint \delta Q = \oint \delta W \quad \text{or} \quad (\Sigma Q)_{\text{cycle}} = (\Sigma W)_{\text{cycle}}$$

Non-Cyclic Process (Closed System): When a system changes from state 1 to state 2, the difference between heat transferred and work done equals the change in internal energy (ΔU):

$$\delta Q - \delta W = dU \quad \text{implies} \quad Q_{1-2} = \Delta U + W_{1-2} = (U_2 - U_1) + \int_1^2 P dV$$

Perpetual Motion Machine of the First Kind (PMM-1): A hypothetical continuous mechanical engine that produces net work output without consuming equivalent energy input. By the First Law of Thermodynamics, PMM-1 is physically impossible.

Steady Flow Energy Equation (SFEE) for Open Systems

For a control volume operating under steady mass flow conditions with mass flow rate $\dot{m}$:

$$\dot{m} [h_1 + (V_1^2/2) + g z_1] + Q = \dot{m} [h_2 + (V_2^2/2) + g z_2] + W_{cv}$$

Key Engineering Devices Governed by SFEE:

- **Steam / Gas Turbine:** Insulated ($Q \approx 0$), negligible PE change ($\Delta z \approx 0$) $\rightarrow W = \dot{m} (h_1 - h_2)$.
- **Nozzle:** No work ($W = 0$), adiabatic ($Q = 0$) $\rightarrow V_2 = \sqrt{2(h_1 - h_2) + V_1^2}$.
- **Compressor / Pump:** Requires work input $\rightarrow W_{in} = \dot{m} (h_2 - h_1)$.
- **Throttling Valve (Porous Plug):** Adiabatic, rigid, no work $\rightarrow h_1 = h_2$ (Isenthalpic process).

4.3 The Second Law of Thermodynamics (Directional Quality of Energy)

The First Law balances energy quantities but does not dictate whether a transformation is physically possible. The Second Law introduces **Entropy (S)** and establishes the natural direction of heat and work processes.

1. Kelvin-Planck Statement (Heat Engines): It is impossible for any cyclic device to receive heat from a single thermal reservoir and convert that heat entirely into an equivalent amount of useful mechanical work. A heat engine must reject heat to a lower-temperature sink.

$$\text{Thermal Efficiency: } \eta_{th} = W_{net} / Q_H = (Q_H - Q_L) / Q_H = 1 - (Q_L / Q_H) < 100\%$$

2. Clausius Statement (Refrigerators & Heat Pumps): It is impossible to construct a cyclic device whose sole effect is the transfer of heat from a lower-temperature body to a higher-temperature body without external work input.

$$COP_{Ref} = Q_L / W_{in} = Q_L / (Q_H - Q_L) \quad \text{and} \quad COP_{HP} = Q_H / W_{in} = COP_{Ref} + 1$$

Equivalence of Statements: The violation of the Kelvin-Planck statement directly leads to the violation of the Clausius statement, and vice versa. Both are equivalent statements of the Second Law.

Perpetual Motion Machine of the Second Kind (PMM-2): A heat engine operating in a thermodynamic cycle that has 100% thermal efficiency (absorbing heat from a single reservoir and converting all of it to work without rejecting heat to a sink). PMM-2 is physically impossible.

4.4 The Third Law of Thermodynamics (Absolute Entropy Baseline)


Statement (Nernst-Simon Theorem): The entropy of a pure, perfectly crystalline substance approaches zero as the absolute thermodynamic temperature approaches absolute zero ($0 \text{ Kelvin} = -273.15^\circ\text{C}$).

$$\lim_{(T \rightarrow 0 \text{ K})} S = 0$$

Significance: Establishes a true reference zero for absolute entropy calculations and demonstrates that absolute zero temperature cannot be reached in a finite sequence of operations.

5. Introduction to Modes of Heat Transfer & Applications

Heat Transfer investigates the rate of thermal energy transit occurring across space due to a temperature gradient (ΔT). Heat transfer occurs via three distinct physical mechanisms: **Conduction**, **Convection**, and **Radiation**.



5.1 Detailed Mechanism & Governing Equations

Mode	Physical Mechanism	Governing Law & Formula	Parameters & SI Units
Conduction	Energy transfer from high-energy particles to adjacent lower-energy particles via atomic vibrations (phonons) and free electron migration in stationary media.	Fourier's Law: $Q = -k \cdot A \cdot (dT/dx)$ (Minus sign indicates heat flows down the temperature gradient)	k : Thermal conductivity ($W/(m \cdot K)$) A : Heat flow area (m^2) dT/dx : Temp gradient (K/m)
Convection	Energy transfer between a solid surface and an adjacent flowing fluid; combines molecular diffusion with macroscopic bulk fluid transport.	Newton's Law of Cooling: $Q = h \cdot A \cdot (T_s - T_\infty)$	h : Convection coefficient ($W/(m^2 \cdot K)$) T_s : Solid surface temp (K) T_∞ : Surrounding fluid temp (K)
Radiation	Thermal energy emitted by matter at non-zero absolute temperatures via electromagnetic waves (photons). Requires no physical medium (propagates through vacuum).	Stefan-Boltzmann Law: $E_b = \sigma \cdot A \cdot T^4$ $Q_{net} = \epsilon \cdot \sigma \cdot A \cdot (T_1^4 - T_2^4)$	$\sigma = 5.67 \times 10^{-8} W/(m^2 \cdot K^4)$ ϵ : Surface emissivity ($0 \leq \epsilon \leq 1$) T : Absolute temperature (K)

5.2 Major Engineering Applications of Heat Transfer

- **Steam Power Plants:** Heat transfer in boiler furnaces (radiation), superheaters (convection/conduction), and water-cooled surface condensers.
- **Automotive Engines:** Engine coolant radiators, finned air-cooled cylinder heads, intercoolers, and exhaust heat shields.
- **Electronic Thermal Control:** Aluminum pin fins, micro-heat pipes, and liquid cold plates cooling high-power CPU/GPU chips.
- **Aerospace & Cryogenics:** Spacecraft Multi-Layer Insulation (MLI) radiation blankets, atmospheric re-entry thermal protection shields, and vacuum-jacketed cryogenic liquid fuel tanks.

6. Engineering Materials: Classification & Selection in Design

Every mechanical design relies on selecting materials that meet mechanical, thermal, and chemical performance requirements at an economically viable cost.

6.1 Comprehensive Classification of Materials

1. Metallic Materials

- **Ferrous Metals:** Iron-based alloys.
 - *Carbon Steels:* Low carbon (<0.25% C; ductile, sheets, structural beams), Medium carbon (0.25–0.60% C; shafts, gears), High carbon (>0.60% C; springs, cutting dies).
 - *Alloy Steels:* Stainless steel (18% Cr, 8% Ni; high corrosion resistance), High-Speed Steel (HSS: 18% W, 4% Cr, 1% V; retains cutting edge at red heat).
 - *Cast Irons:* High carbon (2.0–4.5% C); Grey cast iron (high compressive strength and vibration damping, machine beds), Nodular/ Ductile iron (engine crankshafts).
- **Non-Ferrous Metals:**
 - *Aluminum & Alloys:* High strength-to-weight ratio (Duralumin in aircraft bodies).
 - *Copper & Alloys:* Brass (Cu-Zn; valves, fittings), Bronze (Cu-Sn; high wear resistance, bush bearings).
 - *Titanium Alloys:* High specific strength and corrosion resistance up to 500°C (aerospace turbines, medical bone plates).

2. Non-Metallic & Advanced Materials

- **Polymers (Plastics & Rubbers):**
 - *Thermoplastics:* Soften reversibly upon heating; recyclable (Polyethylene, Nylon, PTFE/Teflon, Polycarbonate).
 - *Thermosetting Plastics:* Form permanent cross-linked polymer networks; decompose upon heating (Bakelite electrical switchboards, Epoxy resins).
 - *Elastomers:* Large elastic reversible elongation (Natural rubber, Neoprene, Nitrile seals).
- **Ceramics:** Inorganic non-metallic crystalline compounds bound by strong ionic/covalent bonds. High hardness, thermal stability, and wear resistance, but brittle.
Examples: Alumina (Al_2O_3), Silicon Carbide (SiC), Zirconia (ZrO_2). Used in spark plug insulators, abrasive grinding wheels, cutting tool inserts.
- **Composites:** Multiphase materials consisting of reinforcing fibers embedded within a continuous matrix.
Examples: Carbon Fiber Reinforced Polymer (CFRP) in aircraft wings, Glass Fiber Reinforced Polymer (GFRP) in boat hulls and wind blades.

6.2 Key Material Properties Relevant to Mechanical Design

Property Class	Primary Parameters	Design Role & Significance
Mechanical Properties	Yield strength (σ_y), Ultimate tensile strength (σ_u), Ductility (%EL), Hardness (BHN/HRC), Toughness, Endurance limit.	Dictates resistance against yielding under static stress, impact loads without brittle fracture, and cyclic fatigue stress reversals over long service lifespans.
Thermal Properties	Thermal conductivity (k), Thermal expansion coefficient (α), Specific heat capacity (c_p).	Differences in thermal expansion coefficients create severe thermal stresses in engine pistons, turbine blades, and heat exchangers.
Chemical Properties	Corrosion resistance, oxidation resistance, chemical inertness.	Prevents material loss and premature structural failure in marine vessels, chemical process plants, and exhaust ducts.
Manufacturing Properties	Machinability, Weldability, Castability, Malleability, Hardenability.	Determines the ease and cost of fabricating raw materials into final engineered components without defect formation.

6.3 Selection of Materials in Component Design

In modern mechanical engineering design, material selection follows a structured workflow:

- 1. Functional and Operational Requirements:** Type of applied loading (static, dynamic, cyclic, impact), service temperature range, and environmental exposure (corrosive or oxidizing atmospheres).
- 2. Manufacturing Feasibility:** Compatibility with manufacturing methods (casting, forging, sheet stamping, precision CNC machining, or additive manufacturing).
- 3. Weight Optimization and Specific Ratios:** In automotive and aerospace design, materials are compared based on specific strength (σ_y / ρ) and specific stiffness (E / ρ).
- 4. Economic Viability & Availability:** Total lifecycle cost, including raw stock purchase, processing and tooling expense, maintenance frequency, and end-of-life recyclability.

7. Manufacturing Processes & Mechanical Working of Metals

Manufacturing is the industrial transformation of raw materials into finished engineering components through physical, chemical, and mechanical operations.

7.1 Broad Classification of Manufacturing Processes

Process Class	Underlying Operating Mechanism	Techniques & Typical Products
1. Primary Shaping (Casting)	Liquid molten metal is poured into a mold cavity matching the final geometry, allowed to solidify, and removed. Ideal for intricate hollow shapes.	Sand casting, Die casting, Investment (lost-wax) casting, Centrifugal casting. <i>Products:</i> Engine blocks, gearbox housings, pump impellers.
2. Deforming (Forming)	Solid metal is plastically deformed under mechanical forces beyond its yield point without chip removal.	Forging, Rolling, Extrusion, Wire drawing, Sheet metal stamping. <i>Products:</i> Connecting rods, structural I-beams, seamless pipes.
3. Subtractive (Machining)	Excess material is systematically removed in the form of chips using a sharp cutting tool to achieve precise dimensions and fine surface finishes.	Turning (Lathe), Milling, Drilling, Shaping, Grinding. <i>Products:</i> Precision shafts, gear teeth, splines, bearing journals.
4. Joining / Fabricating	Two or more metal or non-metal parts are permanently or semi-permanently bonded together.	Arc welding (TIG, MIG, SMAW), Gas welding, Brazing, Soldering, Riveting, Adhesive bonding. <i>Products:</i> Pressure vessels, bridges, automotive chassis.
5. Advanced / Modern	Material removal or addition utilizing thermal, electrochemical, laser, or additive processes.	Electric Discharge Machining (EDM), Laser Beam Machining (LBM), Ultrasonic Machining (USM), 3D Metal Printing.

7.2 Mechanical Working of Metals (Metal Forming)

Mechanical working involves subjecting metal stocks to severe plastic deformation to alter their external geometry and internal grain microstructure.

Recrystallization Temperature (T_r) — The Critical Boundary

Recrystallization Temperature: The approximate minimum temperature at which distorted, strain-hardened grains in cold-worked metal are completely replaced by a new strain-free, equiaxed grain structure within a specified time (typically 1 hour).

$$T_r \approx (0.3 \text{ to } 0.5) \times T_{\text{melting}} \quad (\text{Kelvin})$$

For pure lead and tin, T_r is below room temperature; for structural steels, $T_r \approx 450^\circ\text{C} - 550^\circ\text{C}$.

7.3 Hot Working vs. Cold Working: Comparative Analysis

Parameter	Hot Working	Cold Working
Working Temperature	Carried out above the recrystallization temperature ($T > T_r$).	Carried out below the recrystallization temperature (usually at ambient room temp, $T < T_r$).
Strain Hardening	No strain hardening occurs because recrystallization relieves internal strain immediately.	Pronounced strain hardening (work hardening) occurs; dislocation density increases substantially.
Deformation Forces	Yield strength drops sharply at high temperatures; lower forces and smaller press capacities are needed.	Metal retains high strength; requires massive deformation pressures and heavier equipment.
Microstructural Changes	Refines coarse dendritic cast grains into fine equiaxed grains; heals internal porosity; produces continuous grain flow lines.	Grains become elongated and distorted in the direction of working; creates severe residual internal stresses.
Surface Finish & Tolerances	Poor surface finish due to rapid surface oxidation and scale formation; loose dimensional tolerances from uneven thermal shrinkage.	Bright, scale-free surface with excellent dimensional tolerances and fine surface finish.
Mechanical Properties	Improves ductility, toughness, and impact resistance; uniform isotropic properties throughout.	Increases tensile strength and hardness; decreases ductility and impact resistance; induces directional anisotropy.

7.4 Principal Bulk Metal Working Operations

- **1. Rolling:** The process of reducing the cross-sectional thickness of a metal ingot or billet by passing it between two opposing cylindrical rolls rotating in opposite directions. Used for structural steel I-beams, railway rails, plates, sheets, and foils.
- **2. Forging:** Plastic deformation of a workpiece into a desired contour by localized compressive impact forces delivered through open or closed dies (hammers or hydraulic presses). Produces components with directional grain-flow strength (e.g., engine connecting rods, aircraft landing gear, forged crankshafts).
- **3. Extrusion:** A metal billet enclosed in a high-pressure container is forced to flow plastically through a restricted die opening to produce continuous lengths of uniform cross-section (e.g., aluminum architectural frames, seamless tubes). Divided into Direct (forward) and Indirect (backward) extrusion.
- **4. Drawing (Wire & Rod Drawing):** The cross-section of a wire, rod, or tube is reduced by pulling (tensile force) the stock through a tapered converging tungsten-carbide die. Conducted cold to yield high tensile strength and smooth finish (e.g., electrical copper cables, guitar strings).

8. High-Yield Examination Summary & Rapid Revision Sheet

Subject Topic	Core Principles & Definitions	Governing Formulae / Mathematical Laws
Kinematics of Machines	- Mechanism transmits/modifies motion. - Machine transforms energy into useful work. - Lower pair (surface contact); Higher pair (point/line).	$L = 2P - 4$ (Kinematic link constraint) $J = (3/2)L - 2$ (Binary joints constraint)
Thermodynamic Systems	- Open: Mass & Energy cross boundary. - Closed: Only Energy crosses; Mass is fixed. - Isolated: Neither Mass nor Energy crosses.	State functions: Exact differentials (dU, dH, dS) Path functions: Inexact differentials ($\delta Q, \delta W$)
First Law of Thermodynamics	Conservation of energy; Cyclic & non-cyclic formulations; PMM-1 is impossible.	Closed system: $\delta Q = dU + \delta W$ SFEE: $h_1 + (V_1^2/2) + gz_1 + q = h_2 + (V_2^2/2) + gz_2 + w$
Second Law of Thermodynamics	Directionality of energy; Heat engine (Kelvin-Planck); Refrigerator/Heat pump (Clausius); PMM-2 impossible.	$\eta_{Carnot} = 1 - (T_L / T_H)$ $COP_{HP} = COP_{Ref} + 1$
Modes of Heat Transfer	- Conduction (Stationary solid/fluid) - Convection (Solid-fluid interface) - Radiation (Electromagnetic photons in vacuum)	Conduction: $Q = -k \cdot A \cdot (dT/dx)$ Convection: $Q = h \cdot A \cdot (T_s - T_\infty)$ Radiation: $Q = \epsilon \cdot \sigma \cdot A \cdot (T_1^4 - T_2^4)$
Mechanical Working	- Hot working ($T > T_p$): Refines grains, no strain hardening. - Cold working ($T < T_p$): Work hardens, high strength, tight tolerance.	Recrystallization Temperature: $T_r \approx (0.3 \text{ to } 0.5) \times T_{melting}$ (Kelvin)

HBTU Semester Examination Strategy: For high-scoring answers in Unit 2, always organize responses with: (1) Formal definition, (2) Labeled schematic diagram, (3) Mathematical governing formula with SI units, (4) Direct engineering application or comparison table.