

Server Network Setup — Quick Guide

No Linux knowledge needed. Two cables, five typed lines, one photo. About 10 minutes.

Router port map (MikroTik RB5009 — ports are numbered on the front)

Port	What plugs in	Network
ether1	Cable from the home router (a LAN port) — this is the internet feed	WAN
ether2	Mini PC (game streaming, in the TV room)	30 gaming
ether3	Backup / storage box	20 servers
ether4	Server's BMC / IPMI management port (small separate port)	10 mgmt
ether5–7	Laptops / any trusted computer (Penn's laptop lives here)	40 trusted
ether8	Server's main 10G network port (temporary — moves to SFP+ later)	trunk
SFP+ cage	Future: server's 10G link via S+RJ10 module (on order)	later

Today you only need the two bold rows: internet feed into **ether1**, server into **ether8**. Everything else can be plugged in any time.

Steps at the server

- 1 Plug in the two cables** — home router → **ether1**; server's 10G port → **ether8**. The server has **two identical 10G ports** — if step 3's first ping fails, move the cable to the other one.
- 2 Log in at the server** — plug a monitor + keyboard into the server. Username `root`, password is the one set during the Proxmox install.
- 3 Type these four lines** (press Enter after each; straight quotes, exact spacing). **Each command is ONE line** — if it wraps on this page, keep typing on the same line:

```
sed -i 's|address .*|address 10.10.10.10/24|; s|gateway .*|gateway 10.10.10.1|' /etc/network/interfaces

sed -i '/bridge-fd/a\ bridge-vlan-aware yes\n bridge-vids 2-4094' /etc/network/interfaces

ifreload -a

ping -c 2 10.10.10.1 && ping -c 2 1.1.1.1
```

You want replies from **both pings**:

- `10.10.10.1` replies = server sees the router. If not → check the ether8 cable / try the other 10G port.
- `1.1.1.1` replies = internet works. If not → check the ether1 cable.

- 4 Type this one line** — it sets up remote access and prints a hardware report:

```
curl -fsSL https://raw.githubusercontent.com/melonmelonz/infra-scripts/main/scripts/host-bootstrap.sh | bash
```

It should end with `BOOTSTRAP DONE`.

5 Take a photo of everything from `=== IP ===` down and send it to Penn. That's it — the rest happens remotely.

If the report's `=== IOMMU ===` section is empty: reboot, press Del to enter BIOS, make sure **SVM** and **IOMMU** are both Enabled (Advanced → CPU / AMD CBS), boot back up, redo step 4.