



Configure

 General

 Triggers

 Pipeline

 Advanced

General

Enabled



Description

MODEL RELEASES : A Proper way of releasing the Models or Releases and stuff. With clean detailed Summary, Fixes and all stuff and things. In this way the communicatrion is clear between teams working and all.



Plain text [Preview](#)

Discard old builds

Strategy

Log Rotation

Days to keep builds

if not empty, build records are only kept up to this number of days

365

Max # of builds to keep

if not empty, only up to this number of build records are kept

50

Advanced 

Do not allow concurrent builds

☐ Abort previous builds

☐ Do not allow the pipeline to resume if the controller restarts

GitHub project

Project url

https://github.com/melonshreyas/gem5_Setup_R.git/

Advanced ▾

 Edited

☐ Permission to Copy Artifact

☐ Pipeline speed/durability override

☐ Preserve stashes from completed builds

This project is parameterized

Choice Parameter



Name

MODEL_UNIT_NAME

Choices

IFU
BPU
IDU
DISPATCH_UNIT
RENAME_UNIT
ISSUE_QUEUE
COMPLETION_UNIT
FXU
ALU
FPU
VSX
CRU
LSU
EA_GENERATION
L1_ICACHE
L1_DCACHE
L2_CACHE
DTLB
PREFETCH_ENGINE
MEMORY_CONTROLLER
COHERENCE_ENGINE
NEST_INTERCONNECT
PCIe_CONTROLLER
CAPI_INTERFACE
NVLINK_INTERFACE
SMT_SCHEDULER

Description

Required POWER9 pipeline/model unit.

Plain text [Preview](#)

String Parameter



Name

BRANCH

Default Value

stable

Description

Required Git branch to clone.

Plain text [Preview](#)

☐ Trim the string

Choice Parameter



Name

COMPILE_TARGET

Choices

opt
debug

Description

gem5 binary to compile.

Plain text [Preview](#)

Choice Parameter



Name

CHIP_NAME

Choices

ALL
CHIP_1
CHIP_2
CHIP_3

Description

Optional chip filter. ALL selects every configured chip.



Plain text [Preview](#)

String Parameter

Name

TESTCASE

Default Value

ALL

Description

Optional comma-separated testcase filter.



Plain text [Preview](#)

☐

Trim the string

String Parameter

Name

CHIP_CONFIGURATION

Default Value

Description

Optional chip_configuration.json path.



Plain text [Preview](#)

☐ Trim the string

Boolean Parameter



Name

DRY_RUN

☐ Set by Default

Description

Print and archive the release plan without executing it.

Plain text [Preview](#)

Boolean Parameter



Name

SEND_EMAIL

☐ Set by Default

Description

Send the unit/version HTML release report by email.

Plain text [Preview](#)

String Parameter



Name

SMTP_SERVER

Default Value

Description

SMTP server hostname.

Plain text [Preview](#)

☐ Trim the string

String Parameter



Name

SENDER_EMAIL

Default Value

Description

Sender email address.

Plain text [Preview](#)

☐ Trim the string

Password Parameter



Name

SENDER_PASSWORD

Default Value

Description

SMTP password or app password.

Plain text [Preview](#)

Multi-line String Parameter



Name

RECIPIENT_EMAILS

Default Value

Description

Comma-separated recipient email addresses.

Plain text [Preview](#)

Multi-line String Parameter



Name

SUMMARY

Default Value

Description

Required release summary.

Plain text [Preview](#)

Multi-line String Parameter



Name

FIXES

Default Value

Description

Required list of fixes and changes.

Plain text [Preview](#)

String Parameter



Name

REPO_URL

Default Value

https://github.com/melonshreyas/gem5_Setup_R.git

Description

Repository to clone for the release.

Plain text [Preview](#)☐ Trim the string[+ Add Parameter](#)☐ Throttle builds

Triggers

Set up automated actions that start your build based on specific events, like code changes or scheduled times.

- ☐ Build after other projects are built
- ☐ Build periodically
- ☐ GitHub hook trigger for GITScm polling
- ☐ Poll SCM
- ☐ Trigger builds remotely (e.g., from scripts)

Pipeline

Define your Pipeline using Groovy directly or pull it from source control.

Definition

Pipeline script

Script

```
1 // Jenkins pipeline for collecting a validate
2
3 pipeline {
4     agent any
5
6     parameters {
7         choice(
8             name: 'MODEL_UNIT_NAME',
9             choices: [
10                 'IFU', 'BPU', 'IDU', 'DISPATC
11                 'COMPLETION_UNIT', 'FXU', 'AL
12                 'EA_GENERATION', 'L1_ICACHE',
```

```
13 'PREFETCH_ENGINE', 'MEMORY_CO  
14 'NEST_INTERCONNECT', 'PCIe_CO  
15 'NVLINK_INTERFACE', 'SMT_SCHE
```

Use Groovy Sandbox

[Pipeline Syntax](#)

Advanced

Advanced ▾