

API for WebSocket: (path: `/room_hub`)

Authentication

You must pass JWT token in `access_token` property in query. Like that:

```
const connection = new signalR.HubConnectionBuilder()
    .withUrl("/room_hub", {
        accessTokenFactory: () => myJwtToken
    })
    .build();
```

Client-to-Server Methods

Clients must call (`invoke`) these methods to perform actions on the server.

EnterRoom()

Called by a client when they successfully connect to the room.

- **Parameters:** None
- **Action:** Broadcasts `EnteredRoom` to all clients in the room.

MakeReady(isReady: boolean)

Called by a client to toggle their ready state in the lobby.

- **Parameters:**
 - `isReady` (boolean): The desired ready state.
- **Action:** Broadcasts `Ready` to all clients in the room.

KickUser(userId: string)

Called to kick a specific user from the room.

- **Parameters:**
 - `userId` (string): The ID of the user to kick.
- **Action:** Broadcasts `KickUser` to all clients in the room.

StartGame()

Called by a client to start the match.

- **Parameters:** none
- **Action:** Broadcasts `StartGame` to all clients in the room.

MakeTurn(message: string)

Called by a player to execute their turn/action.

- **Parameters:** `message` (string)
- **Action:** Broadcasts `TurnMade` to all clients.

MakeVote(userId: string)

Called by a player during the voting phase to cast a vote against someone.

- **Parameters:**
 - `userId` (string): The ID of the player being voted for.
 - **Action:** Broadcasts `VoteChange` to all clients.
-

Server-to-Client Events

Clients must listen (`on`) for these events to update the UI based on server state.

EnteredRoom(string id, string nickname, int order)

Triggered when a player successfully joins the room.

- **Payload:**
 - `id` (string): The unique identifier of the joined user.
 - `nickname` (string): The display name of the joined user.
 - `order` number: The turn of the player(counting from first in the array)

Ready(string id, bool isReady)

Triggered when a player changes their ready state.

- **Payload:**
 - `id` (string): The user ID changing state.
 - `isReady` (boolean): Whether they are ready (`true`) or not (`false`).
-

KickUser(string userId)

Triggered when a user is forcefully removed from the lobby.

- **Payload:**
 - `userId` (string): The ID of the user who was kicked.

StartGame

Triggered when the lobby transitions into the active game phase.

- **Payload:** None

TurnMade(string userId, bool hasMessage, string message, bool hasNextUser, string nextUserId)

Triggered when a user completes their turn.

- **Payload:**
 - `userId` (string): The ID of the user who just took their turn.
 - `hasMessage` (boolean): Indicates if there is an accompanying message.
 - `message` (string): message.
 - `hasNextUser` (boolean): Indicates if the turn passes to another user (`true`) or if a voting phase begins (`false`).
 - `nextUserId` (string): The ID of the next user to play.

VoteChange(string userId1, int newValue1, string userId2, int newValue2)

Triggered when the voting tallies change.

- **Payload:**
 - `userId1` (string): ID of a user.
 - `newValue1` number: The new vote tally for `userId1`.
 - `userId2` (string): ID of another user.
 - `newValue2` number: The new vote tally for `userId2`.

VoteFinish(string userIdToKick, bool wasAmogus)

Triggered when the voting phase concludes.

- **Payload:**

- `userIdToKick` (string): The ID of the player voted out (or null if a tie/skip).
- `wasAmogus` boolean: Indicates whether the ejected player had the impostor/traitor role.