

Project Configuration Report

Tarang_Core_Pipeline

Target Device:

Target Part: EFR32MG26B510F3200IM68

Boards:

- EFR32xG26 Dev Kit Board (BRD2608A Rev A04)

Target SDK

Simplicity SDK Suite v2025.12.3: Connect, Connect, EmberZNet 9.0.2.0, Multiprotocol 1.0.2.0, OpenThread 3.0.2.0 (GitHub-61e43cffb), Platform 5.2.0.0, SDK, Sidewalk 2.8.2, Silicon Labs AI/ML SDK 2.2.2, Silicon Labs Matter 2.8.1-1.5, Wi-Fi SDK 4.0.2-rc.5, Z-Wave SDK 8.0.2.0
SDK Version: 2025.12.3

Project Generators

- VS Code (GCC)

Installed Software Components:

- Application

- Utility

- Assert**

- Configurable: true

- Configs: app_assert_config.h

- Bluetooth

- Application

- GATT Services

- Device Information GATT Service Override**

- Sources: sl_gatt_service_device_information_override.c

- Configurable: false

- Miscellaneous

- Application OS helper**

- Sources: app_micriumos.c, app_bm.c, app_freertos.c

- Configurable: false

- Bluetooth Host (Stack)

- Bluetooth Core**

- Sources: sli_bt_hci_event_table.c, sl_bt_stack_init.c

- Configurable: true

- Configs: sl_bluetooth_config.h

- Static GATT Database and Configuration**

- Configurable: true

- Configs: gatt_configuration.btconf

- Features with Commands and Events

GATT Client

Configurable: false

GATT Server

Configurable: false

Security Manager

Configurable: false

System

Configurable: false

- Bluetooth LE Controller (Link Layer)

- Additional Features

Bluetooth Radio Watchdog

Configurable: false

- Features with Commands and Events

Connection in the Central role

Configurable: false

Connection in the Peripheral role

Configurable: false

Legacy Advertising

Configurable: false

Scanner for legacy advertisements

Configurable: false

- Platform

- Board

- Starter Kit

BRD2608A

Configurable: false

- Device

- EFR32MG26

EFR32MG26B510F3200IM68

Sources: system_efr32mg26.c, startup_efr32mg26.c

Configurable: true

Configs: device.yaml

- Peripheral

- EMLIB

I2C

Sources: em_i2c.c

Configurable: false

IADC

Sources: em_iadc.c

Configurable: false

LETIMER

Sources: em_letimer.c

Configurable: false

- Radio

- RAIL 2.x

RAIL Utility, PTI (RAIL 2.x)

Configurable: false

- Security

- Memory Protection Unit

Simple MPU

Sources: sl_mpu_s3.c, sl_mpu_s2.c

Configurable: false

- Services

- Clock Manager

Clock Manager

Sources: sl_clock_manager_init.c

Configurable: true

Configs: sl_clock_manager_oscillator_config.h, sl_clock_manager_ext_flash_config.h,
sl_clock_manager_tree_config.h

- Device Initialization

Automatic Device Initialization

Configurable: false

- System Setup

System Setup (sl_main)

Configurable: true

Configs: sl_main_start_task_config.h

Pins:

Peripherals:

Peripheral	Software Component	Custom Peripheral Name
ACMP0		
ACMP1		
CMU	Clock Manager	
EUSART0		
EUSART1		
EUSART2		
EUSART3		
GPIO		
I2C0		
I2C1		
I2C2		
I2C3		
IADC0		
KEYSCAN		
LCD		
LETIMER0		
LFXO		
MODEM		
PCNT0		
PRS Channel ASYNCH0		
PRS Channel ASYNCH1		
PRS Channel ASYNCH10		
PRS Channel ASYNCH11		
PRS Channel ASYNCH12		
PRS Channel ASYNCH13		
PRS Channel ASYNCH14		
PRS Channel ASYNCH15		
PRS Channel ASYNCH2		
PRS Channel ASYNCH3		
PRS Channel ASYNCH4		
PRS Channel ASYNCH5		
PRS Channel ASYNCH6		
PRS Channel ASYNCH7		
PRS Channel ASYNCH8		
PRS Channel ASYNCH9		
PRS Channel SYNCH0		
PRS Channel SYNCH1		
PRS Channel SYNCH2		
PRS Channel SYNCH3		
PTI	RAIL Utility, PTI (RAIL 3)	
TIMER0		
TIMER1		
TIMER2		
TIMER3		
TIMER4		

TIMER5		
TIMER6		
TIMER7		
TIMER8		
TIMER9		
USART0		
USART1		
USART2		
VDAC0		
VDAC1		