

Project Configuration Report

Integration

Target Device:

Target Part: EFR32MG26B510F3200IM48

Boards:

- EFR32xG26 Explorer Board (BRD2709A Rev A03)

Target SDK

Simplicity SDK Suite v2025.12.3: Connect, Connect, EmberZNet 9.0.2.0, Multiprotocol 1.0.2.0, OpenThread 3.0.2.0 (GitHub-61e43cffb), Platform 5.2.0.0, SDK, Sidewalk 2.8.2, Silicon Labs AI/ML SDK 2.2.2, Silicon Labs Matter 2.8.1-1.5, Wi-Fi SDK 4.0.2-rc.5, Z-Wave SDK 8.0.2.0
SDK Version: 2025.12.3

Project Generators

- VS Code (GCC)

Installed Software Components:

- Platform

- Board

- Thunderboard

BRD2709A

Configurable: false

- Device

- EFR32MG26

EFR32MG26B510F3200IM48

Sources: system_efr32mg26.c, startup_efr32mg26.c

Configurable: true

Configs: device.yaml

- Driver

DMADRV

Sources: dmadv.c

Configurable: true

Configs: dmadv_config.h

GPIoint

Sources: gpinterrupt.c

Configurable: false

- I2C

I2CSPM

Configurable: true

Configs: sl_i2cspm_mikroe_config.h

- Peripheral

- EMLIB

IADC

Sources: em_iadc.c

Configurable: false

LETIMER

Sources: em_letimer.c

Configurable: false

PRS

Sources: em_prs.c

Configurable: false

- Services

- Clock Manager

Clock Manager

Sources: sl_clock_manager_init.c

Configurable: true

Configs: sl_clock_manager_oscillator_config.h, sl_clock_manager_ext_flash_config.h,
sl_clock_manager_tree_config.h

- Device Initialization

Automatic Device Initialization

Configurable: false

- IO Stream

IO Stream

Sources: sl_iostream.c

Configurable: false

IO Stream - Recommended Stream for debug output

Configurable: false

IO Stream: Recommended Stream for a console

Configurable: false

IO Stream: Retarget STDIO

Sources: sl_iostream_retargt_stdio.c

Configurable: false

IO Stream: STDLIB Configuration

Sources: sl_iostream_stdlib_config.c

Configurable: false

- Memory Manager

Memory Manager

Sources: sl_memory_manager_common.c, sl_memory_manager.c,
sl_memory_manager_dynamic_reservation.c, sl_memory_manager_retarget.c

Configurable: true

Configs: sl_memory_manager_config.h

- Power Manager

Power Manager

Configurable: true

Configs: sl_power_manager_config.h

- System Setup

System Setup (sl_main)

Configurable: true

Configs: sl_main_start_task_config.h

Pins:

Pin #	Pin Name	Function	Custom Pin Name	Software Component
26	AIN0			
25	AIN1			
28	PA00	EUSART0_RTS		IO Stream: EUSART (vcom)
29	PA01			
30	PA02			
31	PA03	GPIO_SWV		SWO Debug
32	PA04			
33	PA05			
34	PA06	EUSART0_CTS		IO Stream: EUSART (vcom)
35	PA07			
21	PB00			
20	PB01			
19	PB02	EUSART0_TX		IO Stream: EUSART (vcom)
18	PB03	EUSART0_RX		IO Stream: EUSART (vcom)
1	PC00			
2	PC01			
3	PC02			
4	PC03			
5	PC04			
6	PC05	I2C1_SCL		I2CSPM (mikroe)
7	PC06			
8	PC07	I2C1_SDA		I2CSPM (mikroe)
9	PC08			
10	PC09			

48	PD00			
47	PD01			
46	PD02			
45	PD03			
44	PD04			
43	PD05			

Peripherals:

Peripheral	Software Component	Custom Peripheral Name
ACMP0		
ACMP1		
CMU	Clock Manager	
EUSART0	IO Stream: EUSART (vcom)	
EUSART1	IO Stream: EUSART (vcom)	
EUSART2	IO Stream: EUSART (vcom)	
EUSART3	IO Stream: EUSART (vcom)	
GPIO	SWO Debug	
I2C0	I2CSPM (mikroe)	
I2C1	I2CSPM (mikroe)	
I2C2	I2CSPM (mikroe)	
I2C3	I2CSPM (mikroe)	
IADC0		
KEYSCAN		
LCD		
LETIMER0		
LFXO		
MODEM		
PCNT0		
PRS Channel ASYNCH0		
PRS Channel ASYNCH1		
PRS Channel ASYNCH10		
PRS Channel ASYNCH11		
PRS Channel ASYNCH12		
PRS Channel ASYNCH13		
PRS Channel ASYNCH14		
PRS Channel ASYNCH15		
PRS Channel ASYNCH2		
PRS Channel ASYNCH3		
PRS Channel ASYNCH4		
PRS Channel ASYNCH5		
PRS Channel ASYNCH6		
PRS Channel ASYNCH7		
PRS Channel ASYNCH8		
PRS Channel ASYNCH9		
PRS Channel SYNCH0		
PRS Channel SYNCH1		
PRS Channel SYNCH2		
PRS Channel SYNCH3		
PTI		

TIMER0		
TIMER1		
TIMER2		
TIMER3		
TIMER4		
TIMER5		
TIMER6		
TIMER7		
TIMER8		
TIMER9		
USART0		
USART1		
USART2		
VDAC0		
VDAC1		