

Project Configuration Report

july6

Target Device:

Target Part: EFR32MG26B510F3200IM48

Boards:

- EFR32xG26 Explorer Board (BRD2709A Rev A03)

Target SDK

Simplicity SDK Suite v2026.6.1: Bluetooth 11.1.1, Bluetooth Mesh SDK 11.0.1, Connect SDK 4.3.1.0, EmberZNet 9.1.1.0, Multiprotocol 1.1.1.0, OpenThread 3.1.1.0 (GitHub-fb274efe6), RAIL SDK 3.1.1.0, Silicon Labs AI/ML SDK 3.0.1, Wi-Fi SDK 4.1.1-rc.2, Z-Wave SDK 8.1.1.0
SDK Version: 2026.6.1

Project Generators

- VS Code (GCC)

Installed Software Components:

- Platform

- Board

- Thunderboard

BRD2709A

Configurable: false

- Device

- EFR32MG26

EFR32MG26B510F3200IM48

Sources: system_efr32mg26.c, startup_efr32mg26.c

Configurable: true

Configs: device.yaml

- Peripheral

- EMLIB

IADC

Sources: em_iadc.c

Configurable: false

LDMA

Sources: em_ldma.c

Configurable: false

LETIMER

Sources: em_letimer.c

Configurable: false

PRS

Sources: em_prs.c

Configurable: false

• Services

- Clock Manager

Clock Manager

Sources: sl_clock_manager_init.c

Configurable: true

Configs: sl_clock_manager_oscillator_config.h, sl_clock_manager_ext_flash_config.h,
sl_clock_manager_tree_config.h

- DMA Manager

DMA Manager: Round-Robin Channel Scheduling

Configurable: true

Configs: sl_dma_manager_round_robin_config.h

- Device Initialization

Automatic Device Initialization

Configurable: false

- IO Stream

IO Stream - Recommended Stream for debug output

Configurable: false

IO Stream: Recommended Stream for a console

Configurable: false

- Power Manager

Power Manager

Configurable: true

Configs: sl_power_manager_config.h

- System Setup

System Setup (sl_main)

Configurable: true

Configs: sl_main_start_task_config.h

Pins:

Peripherals: