

	UGR1124 DECKOVER FLATBED		UPR1124 DECKOVER FLATBED		UGR1526 TANDEM DUALLIES		UPR1628 TRIDEM/TANDEM DUALLIES	
	PERFORMANCE	PREMIUM	PERFORMANCE	PREMIUM	PERFORMANCE	PLATINUM	PERFORMANCE	PLATINUM
RELIABILITY - RATED CAPACITY								
GVWR (lb)	22,000	25,000	22,000	23,000	30,0			000
Rated Payload (lb)	15,300	18,040	15,900	16,600	21,600	21,200	23,550	23,250
Tongue Weight (lb)	5000		3000		6000		4000	
Suspension	Equalized Leaf Spring		Equalized Leaf Spring		Equalized Leaf Spring		Equalized Leaf Spring	
Axle Rating (lb)	3 x 7000	2 x 10,000	3 x 7000	2 x 10,000	2 x 15,	000	3 x 10,000	2 x 15,000
DURABILITY - STRUCTURE								
HSS Mainframe Size (in)	12" l-Beam		12" I-Beam		14" I-Beam		14" I-Beam	
Decking Material	Premium Fir		Premium Fir		Premium Fir		Premium Fir	
Surface Finish	Polyurethane Primer & Paint or Galvanized		Polyurethane Primer & Paint or Galvanized		Polyurethane Primer & Paint		Polyurethane Primer & Paint	
DIMENSIONS								
Total Length (ft)	38	.4	35.	1	48.	8	39	9.6
Fixed Deck Length (ft)	24		24		26		28	
Tail Length (ft)	5		5		5.1		5.1	
Deck Width (in) – inside fender to fender	102		102		102		102	
Deck Height (in)	35.5		35.4		39.5		38.5	
INCLUDED EQUIPMENT								
Pull Type	Gooseneck		Bumper		Gooseneck		Bun	nper
Jackleg Wind Type – top or side	Side		Side		Side		Side	Hydraulic
Jackleg Speeds	Dual		Dual		Dual		Dual	Single
Jackleg Lift Capacity (lb)	2 x 10),000	2 x 10	,000	2 x 10,	000	10,	000
Steel Wheels	Black	Silver	Black	Silver	Blac	:k	Sil	ver
Wheel Size	16" Rim - 6K - 8 Stud - 6.5" Circle	Dual 16" Rim - 8 Stud - 6.5" Circle	16" Rim - 6K - 8 Stud - 6.5" Circle	Dual 16" Rim - 8 Stud - 6.5" Circle	Dual 17.5" Rim - 8 St	ud - 275mm Circle	Dual 16" Rim - 8 Stud - 6.5" Circle	Dual 17.5" Rim - 8 Stud - 275mm Circl
Tire Size	ST235/80	R16 LRE	ST235/80	R16 LRE	ST215/75R	17.5 LRH	ST235/80R16 LRE	ST215/75R17.5 LRH
Premium Radial 10 ply Tires – speed rated to 120 kph	•		•				•	
Premium Radial 16 ply Tires					•			•
- Speed Rated to 120 kph EASY TO OPERATE - SAFETY & CONV	VENIENCE EE ATLIDE	•						
Spring Assist Full Width Beavertail	VENIENCE FEATORE	, ,						
Ramp - 47 x 58" Spring Assist Full Width Beavertail					•		•	
Ramp - 44 x 68" Hydraulic Full Width Beavertail Ramp						•		•
-93 x 67"								
Dual Chains c/w hook latches - 36"			•		•			
Premium Protected Wiring Breakaway Switch – includes LED test			•		•			
lights, battery & charger Integral Footholds								
Tier 1 LED Lighting System								
Forward Self-Adjusting Brakes		•						
EZ-Lube Oil Bath Axle Bearings								
EZ-Lube Grease Axle Bearings			•					
Heavy Duty Toolbox			•		•			
Underbody Toolbox								
110V Shore Charging Plug In						•		
HD Charge Kit						0		•
Wireless Pump Remotes						0		•
Deck Stop								
Front Retractable Step Ladder								
ADDITIONAL FEATURES Tie Down Kit - 4x5000 lb WLL Chains			0		0			
c/w hooks, 4 ratchets								
Mud Flaps)	0		•			
Chain Rack/Tray					0	•		
Spare Tire, Wheel, & Carrier			•		0	•	0	•
ACCESSORIES								
Coupler Lock)	0		0		()
Coupler Lock								
Wheel Locks)	0)	0			