

NEXCORT iQ · CAMPUS · VENUE · TRANSIT

QR Code Installation Guide

Generate, size, print, and place safety-reporting QR codes for Campus, Venue, and Transit. Works on any smartphone camera — no app download for the public.

Legal entity: Apps on Demand LLC · Marketing: www.nexcortiq.us · Ops console: app.rapidcortex.us · (404) 520-1747 · jeff@nexcortiq.us

Each NexCort iQ QR code is tied to one agency and physical location. Scanning opens the tip/report form for that place. Pair with NFC on the same sign for tap users.

WARNING — Always download the QR PNG from the NexCort iQ console. Third-party generators will not track scans or route into your console. PSAP roles do not manage these vertical location codes.

WHO — Create / download / deactivate codes: Campus Admin & Supervisor; Venue Admin, Supervisor & Operator; Transit Admin & Supervisor; RC platform operators (rcadmin / rcitadmin / rcsuperadmin). **PSAP roles are excluded** — dispatcher, supervisor, agencyadmin, and agencyit do not manage campus/venue/transit QR & NFC.

What you need

Item	Details
Console access	Campus / Venue / Transit role that can create codes · app.rapidcortex.us
Printer or sign vendor	Laser preferred in-house; vendor accepts PNG (SVG for large format via support)
Matte stock	Matte label/cardstock or matte laminate — avoid heavy gloss glare

1 — Generate the QR code

- Sign in → Campus / Venue / Transit console → **QR Codes**.
- Create one code per sign: name, zone (building/gate/vehicle/station), report type, vertical.
- Download PNG. Keep the file named by location.
- Do not reuse one QR across multiple physical signs.

TIP — There is no silent "rename in place" for public reporting points in current product guidance: to change the posted name, create a new code, post it, then deactivate the old code.

2 — Size correctly

Viewing distance	Minimum QR size
Up to 1 ft (desk / door plaque)	1.5 in (3.8 cm)
1–3 ft (wall at arm reach)	2 in (5 cm)
3–6 ft (corridor / poster)	3 in (7.5 cm)
6+ ft (lobby / stadium)	5 in (12.5 cm)

Never stretch the PNG. For prints over ~6 in, request a high-DPI PNG or SVG from NexCort support. Keep the white quiet zone (≥4 mm) on all sides.

3 — Print

In-house: Set exact square size in Preview/Word; matte paper; highest quality; no gloss laminate.

Vendor: Black on white only; quiet zone intact; ≥300 DPI at final size; perfect square; matte preferred; place QR in the lower half under instructional text.

4 — Sign copy by vertical

Vertical	Header	Subtext / below QR
NC Campus	See Something? Say Something.	Scan to report to Campus Security. Anonymous option if enabled. "Scan with your phone camera."
NC Venue	Security Concern? Contact Us Now.	Reach Venue Security — no app needed. "Scan with your phone camera."
NC Transit	Safety Issue? Report It Now.	Contact Transit Security — vehicle/station pre-filled. "Scan with your phone camera."
NC Hospital (staff)	Report a Concern	Reach hospital safety staff. Not a public 911 tip line unless SOW says so.

Accessibility: include an SMS alternative on every sign (e.g. "Or text SAFE to [agency number]") for users who cannot scan.

5 — Test before deploying

- Use the native camera app (not a third-party scanner). Hold 12–18 in from the print.
- Confirm the correct vertical + location form opens with no login prompt.
- Confirm scan count increments in the console.
- Retest from the maximum expected reading distance and under real lighting.

6 — Place and mount

- Eye level: about 4.5–5.5 ft from the floor.
- Adequate light; avoid window glare and direct spotlights on the code.
- Keep the code flat; rigid backing; matte protective laminate for durability.
- High-traffic placements: entrances, elevators, stairwells, parking, restroom corridors, gates, vehicles/stations.
- Outdoor: UV-resistant / weatherproof material only.
- Final scan test after mounting.

7 — Troubleshooting

Problem	Solution
Camera does not detect	Light, quiet zone, flat print, no heavy gloss; try 6–12 in.
Wrong form opens	Wrong PNG printed — re-download the correct location code.
Link inactive	Code deactivated — reactivate or create/post a new code.
Scan count not updating	Network at the sign; form may have loaded without tracking.
Older phones fail	Promote SMS alternative on the sign.
Faded / ink bleed	Replace toner; high contrast black-on-white only.

8 — Quick reference card

Pre-install checklist	Rules
■ PNG from NexCort console ■ One code per location ■ Size ≥ min for distance ■ Quiet zone intact · matte ■ Digital + print scan tests ■ Eye level · lighting · no glare ■ Post-mount scan · count OK	✓ Black on white · square · ≥300 DPI ✓ No third-party generators ✓ No stretch / crop / gloss laminate ✓ Test before mounting ✗ PSAP roles managing vertical codes ✗ Reusing one QR on many signs

Need help? jeff@nexcortiq.us · www.nexcortiq.us · Ops: app.rapidcortex.us