

Network Command Log

System: Microsoft Windows [Version 10.0.26200.8246]

```
C:\Users\menak>ping
```

```
Usage: ping [-t] [-a] [-n count] [-l size] [-f] [-i TTL] [-v TOS]
          [-r count] [-s count] [[-j host-list] |
          [-k host-list]]
          [-w timeout] [-R] [-S srcaddr] [-c compartment] [-p]
          [-4] [-6] target_name
```

Options:

-t Ping the specified host until stopped.
To see statistics and continue - type Control-

Break;

To stop - type Control-C.

-a Resolve addresses to hostnames.

-n count Number of echo requests to send.

-l size Send buffer size.

-f Set Don't Fragment flag in packet (IPv4-only).

-i TTL Time To Live.

-v TOS Type Of Service (IPv4-only. This setting has been deprecated and has no effect on the type of service field in the IP

Header).

-r count Record route for count hops (IPv4-only).

-s count Timestamp for count hops (IPv4-only).

-j host-list Loose source route along host-list (IPv4-only).

-k host-list Strict source route along host-list (IPv4-only).

-w timeout Timeout in milliseconds to wait for each reply.

-R Use routing header to test reverse route also (IPv6-only).
Per RFC 5095 the use of this routing header has been deprecated. Some systems may drop echo requests if this header is used.

-S srcaddr Source address to use.

-c compartment Routing compartment identifier.

-p Ping a Hyper-V Network Virtualization provider address.

-4 Force using IPv4.

-6 Force using IPv6.

```
C:\Users\menak>ping google.com
```

Pinging google.com [2404:6800:4002:822::200e] with 32 bytes of data:

Reply from 2404:6800:4002:822::200e: time=94ms

Reply from 2404:6800:4002:822::200e: time=199ms

Reply from 2404:6800:4002:822::200e: time=115ms

Reply from 2404:6800:4002:822::200e: time=125ms

Ping statistics for 2404:6800:4002:822::200e:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 94ms, Maximum = 199ms, Average = 133ms

C:\Users\menak>ipconfig

Windows IP Configuration

Wireless LAN adapter Local Area Connection* 1:

Media State : Media disconnected
Connection-specific DNS Suffix . :

Wireless LAN adapter Local Area Connection* 2:

Media State : Media disconnected
Connection-specific DNS Suffix . :

Wireless LAN adapter Wi-Fi:

Connection-specific DNS Suffix . :
IPv6 Address. : 2409:40f4:410a:
1c7c:dc15:b694:8f84:321e
Temporary IPv6 Address. : 2409:40f4:410a:1c7c:dc3f:
2a4f:bb4d:d03f
Link-local IPv6 Address : fe80::a5ff:bf85:6acb:25be%7
IPv4 Address. : 10.24.17.206
Subnet Mask : 255.255.255.0
Default Gateway : fe80::14e9:16ff:fe2b:326%7
10.24.17.224

Ethernet adapter Bluetooth Network Connection:

Media State : Media disconnected
Connection-specific DNS Suffix . :

C:\Users\menak>tracert

Usage: tracert [-d] [-h maximum_hops] [-j host-list] [-w timeout]
[-R] [-S srcaddr] [-4] [-6] target_name

Options:

-d	Do not resolve addresses to hostnames.
-h maximum_hops	Maximum number of hops to search for target.
-j host-list	Loose source route along host-list (IPv4-only).
-w timeout	Wait timeout milliseconds for each reply.
-R	Trace round-trip path (IPv6-only).
-S srcaddr	Source address to use (IPv6-only).
-4	Force using IPv4.
-6	Force using IPv6.

C:\Users\menak>nslookup google.com

Server: UnKnown
Address: 10.24.17.224

Non-authoritative answer:

Name: google.com
Addresses: 2404:6800:4002:822::200e
142.250.182.142

C:\Users\menak>hostname

MenakaMS

C:\Users\menak>getmac

```
Physical Address      Transport Name
=====
24-B2-B9-1F-4F-D2    Media disconnected
24-B2-B9-1F-4F-D1    \Device\Tcpip_{28C924FA-A2F5-4E55-B9C9-
E9336CFF2E9E}
N/A                  Hardware not present
```

C:\Users\menak>route

Manipulates network routing tables.

ROUTE [-f] [-p] [-4|-6] command [destination]
[MASK netmask] [gateway] [METRIC metric] [IF
interface]

-f Clears the routing tables of all gateway entries.
-p When used with the ADD command, makes a route
persistent across boots.
-4 Force using IPv4.
-6 Force using IPv6.

command PRINT, ADD, DELETE, CHANGE
destination Specifies the host.
MASK Specifies that the next parameter is the 'netmask'
value.
netmask Specifies a subnet mask value. Defaults to
255.255.255.255.
gateway Specifies gateway.
interface The interface number for the specified route.
METRIC Specifies the metric, ie. cost for the destination.

C:\Users\menak>curl https://example.com
(HTML Content from example.com received)

C:\Users\menak>route print

```
=====
=====
IPv4 Route Table
=====
=====
Active Routes:
Network Destination          Netmask                  Gateway                  Interface
Metric
          0.0.0.0            0.0.0.0            10.24.17.224
10.24.17.206            55
          10.24.17.0        255.255.255.0            On-link
10.24.17.206            311
          10.24.17.206    255.255.255.255            On-link
10.24.17.206            311
=====
=====
```