

**Course: Machine Learning Techniques**  
**Week 11: Graded Questions Solutions**

---

1. (1 point) Which of the following is / are true about k-means clustering?

1. k-means is extremely sensitive to cluster center initialisation
2. Bad initialization can lead to poor convergence speed
3. Bad initialization can lead to bad overall clustering

- A. 1 and 2
- B. 1 and 3
- C. 2 and 3
- D. 1,2 and 3

**Answer:** D

**Solution:** Self explanatory.

2. (1 point) What should be the best choice of no. of clusters based on the following graph:




Figure 1: Question no 5

- A. 2
- B. 3
- C. 4

D. 5

**Answer:** D

**Solution:** Since higher the silhouette score better is the clustering.

3. (1 point) Which of the following can act as possible termination conditions in K-Means?

1. Number of iterations.
2. Assignment of observations to clusters does not change between iterations.
3. Centroids do not change between successive iterations.

- A. 1 and 2
- B. 2 and 3
- C. 1 and 3
- D. 1, 2 and 3

**Answer:** D

**Solution:** Self explanatory.

4. (1 point) What is the best choice for number of clusters that can be used for k-means clustering based on the following graph?




Figure 2: Question no 4

- A. 1
- B. 2

- C. 3
- D. 4

**Answer:** D

**Solution:** Look for the elbow like pattern in the chart and identify the elbow point.

5. (1 point) Let there be two features  $x_1$  and  $x_2$  based on which we want to perform k-means clustering. Now consider the following statements
1. If  $x_1$  and  $x_2$  has a correlation of 1, the cluster centroids will be in a straight line
  2. If  $x_1$  and  $x_2$  has a correlation of 0, the cluster centroids will be in a straight line
- A. 1 only
  - B. 2 only
  - C. 1 and 2
  - D. None

**Answer:** A

**Solution:** If the features have correlation of 1, that means the data points form a straight line in 2D plane, hence, the clusters must also be on the same line.

6. (1 point) We want to cluster 9 observations into 3 clusters using K-Means clustering algorithm. After first iteration clusters, C1, C2, C3 has following observations:

C1: (1,1), (1,3), (1,2)

C2: (0,4), (4,0), (5,5)

C3: (2,2), (9,9), (4,4)

What will be the cluster centroids if you want to proceed for second iteration?

- A. C1:(1,1), C2:(4,0), C3:(9,9)
- B. C1:(1,2), C2:(2,2), C3:(7,7)
- C. C1:(1,2), C2:(3,3), C3:(5,5)
- D. C1:(2,1), C2:(4,2), C3:(0,0)

**Answer:** C

**Solution:** Take mean of data points present in each cluster

- Centroid of C1 =  $\left(\frac{1+1+1}{3}, \frac{1+3+2}{3}\right) = (1, 2)$
- Centroid of C2 =  $\left(\frac{0+4+5}{3}, \frac{4+0+5}{3}\right) = (3, 3)$
- Centroid of C3 =  $\left(\frac{2+9+4}{3}, \frac{2+9+4}{3}\right) = (5, 5)$