

CS1010 Laboratory 10

Struct, Wrap-Up

Zhang Puyu

Group BD04

14 November , 2024

Plan of the Day

CS1010
Laboratory 10

Zhang Puyu

Exercise 8
Review

Preamble to
OOP: struct

Anything Else
You Want to
Talk about

1 Exercise 8 Review

2 Preamble to OOP: struct

3 Anything Else You Want to Talk about

Exercise 8

CS1010

Laboratory 10

Zhang Puyu

Exercise 8
Review

Preamble to
OOP: struct

Anything Else
You Want to
Talk about

- This is quite a tedious problem but it is not that difficult.
- We want to retrieve the k nearest training samples given a testing sample.
- This is the same as retrieving the k smallest numbers from a list. Only difference is the way to calculate the near-ness:
 - Let S and T be the sets of '#'s in a testing sample and a training sample.
 - Their “distance” is defined as the number of pixels **in one sample but not the other**.
 - Basically, $|S \cup T| - |S \cap T|$ (in technical terms: symmetric difference).
 - Add-on: in real scientific research, the more standard way to represent the similarity between two images is **intersection over union**.

Preamble to OOP: struct

CS1010
Laboratory 10

Zhang Puyu

Exercise 8
Review

Preamble to
OOP: struct

Anything Else
You Want to
Talk about

So far, we have been representing different objects using **primitive types**: `int`, `float`. (Note that `bool` and `char` are essentially integers.)

In real life, many objects cannot be easily mapped to a single variable.

Example: Personal information consists of

- `name (char *)`
- `age (long)`
- `home address (char *)`
- `birthday (long *)`
- `family members (arrays of the above items)`

Preamble to OOP: struct

CS1010

Laboratory 10

Zhang Puyu

Exercise 8
Review

Preamble to
OOP: struct

Anything Else
You Want to
Talk about

- `name (char *)`
- `age (long)`
- `home address (char *)`
- `birthday (long[3])`
- family members (arrays of the above items)

How to represent a list of persons then?

- `char **name`: an array of names
- `long *age`: an array of ages
- `char **address`: an array of addresses
- `long (*birthday)[3]`: an array of birthdays
- `long **family`: `family[i][j]` is the j -th family member of the i -th person

Preamble to OOP: struct

CS1010

Laboratory 10

Zhang Puyu

Exercise 8
Review

Preamble to
OOP: struct

Anything Else
You Want to
Talk about

- `char **name`: an array of names
- `long *age`: an array of ages
- `char **address`: an array of addresses
- `long (*birthday)[3]`: an array of birthdays
- `long **family`: `family[i][j]` is the j -th family member of the i -th person

This is **verbose** and **unintuitive!**

Suppose we now have a **composite data type**, `person` that captures all the information, then we will only need an array of `person`!

This is the motivation to use a `struct`.

Preamble to OOP: struct

CS1010

Laboratory 10

Zhang Puyu

Exercise 8
Review

Preamble to
OOP: struct

Anything Else
You Want to
Talk about

```
struct person {  
    char *name;  
    long age;  
    char *address;  
    long birthday[3];  
    // Use pointer as we want to access  
    // the actual person instead of a copy  
    person *spouse;  
};  
person *list = read_persons();
```

Now the syntax is much clearer and readable! In fact, we could define another *struct* called **date** to represent the birthday!

In higher-level languages, this evolves into what is known as **Object-Oriented Programming** (taught in detail in CS2030/S and CS2113(T), and somewhat needed for CS2040/S/C).

Moving Forward from CS1010...

CS1010

Laboratory 10

Zhang Puyu

Exercise 8
Review

Preamble to
OOP: struct

Anything Else
You Want to
Talk about

Let's start with an (personal) assertion:

The more you think you know about C, the less you actually know about it...

Things to look forward to after CS1010:

- Learning other programming languages:
 - C++ (officially taught in CS2040C)
 - Java (officially taught in CS2113(T) or CS2030(S))
 - Python? Needed for data analysis and machine learning.
 - JavaScript/TypeScript? You need it for web development.
 - C# ? An ideal choice for solo development (personally highly recommended).
 - Others: Go, Rust, Swift, Scala, etc.
- Learning about other programming paradigms.
- Learning about software engineering principles and design patterns (officially taught in CS2113(T)).
- Doing you own projects!

What to Expect in CS2040C?

CS1010

Laboratory 10

Zhang Puyu

Exercise 8
Review

Preamble to
OOP: struct

Anything Else
You Want to
Talk about

- Fundamentals of C++ and OOP.
- Data structures, their implementations and applications:
 - Arrays and Lists
 - Linked Lists, Stacks and Queues
 - Heaps and Priority Queues
 - Hash Tables
 - Binary Search Trees
 - Graph representations
- Basic-to-intermediate algorithms:
 - Sorting Algorithms
 - Insertion, selection, bubble, counting
 - Merge sort, (randomised) quick sort, heap sort, radix sort
 - Graph traversal
 - Single-source shortest path
 - Minimum spanning tree

Introduction to Different Programming Paradigms

CS1010
Laboratory 10

Zhang Puyu

Exercise 8
Review

Preamble to
OOP: struct

Anything Else
You Want to
Talk about

A “programming paradigm” is a framework for solving computational problems. Suppose we have a problem as follows:

- We are given a list A of integer triplets $A[i] := (a_i, b_i, c_i)$.
- We want to keep only triplets with all-positive entries.
- We want to **group** the triplets based on their first entry.
- We want to find the group where the sum of the second entries over all triplets in the group is the smallest.
- We want to output an integer pair (M, S) , where M is the value of the first entry corresponding to the group, and S is the sum of the third entries over all triplets in the group.

How would a C programmer (that is, you) approach this problem? How would a programmer using a different language reason about the solution differently?

The Procedure-Oriented Way of Thinking

CS1010

Laboratory 10

Zhang Puyu

Exercise 8
Review

Preamble to
OOP: struct

Anything Else
You Want to
Talk about

- Write a function `get_result`
- `get_result` needs to know the first entry of the minimum group.
- Write a function `get_min_group` for that.
- `get_min_group` needs to know the first entry of all groups.
- Write a function `get_groupings` for that.
- Before running `get_groupings`, we need to filter out triplets containing non-positive entries.
- Write a function `filter` for that.

As the task grows in complexity, the number of helper functions increases drastically, which makes our program very hard to maintain.

The Object-Oriented Way of Thinking

CS1010
Laboratory 10

Zhang Puyu

Exercise 8
Review

Preamble to
OOP: struct

Anything Else
You Want to
Talk about

- Suppose we have an object called **List**.
- Let's define a **functionality** exclusive to the list called `keepOnlyPositive`.
- Let's also have another object called **Group** which is essentially a labelled list.
- Now, we define another functionality for our list called `groupByFirst`.
- In our group object, we can define a `SUM` functionality.
- In our list object, let's have a third functionality called `maxBy` which will find the "maximum" according to an attribute (which we will supply as the sum over each group).
- Now we can invoke the functionalities in the correct object and the correct order to get the desired output.

We consider the objects needed to solve a problem, and define the functionalities of each type of objects according to what behaviours or interactions we wish them to support.

The Functional Way of Thinking

CS1010

Laboratory 10

Zhang Puyu

Exercise 8
Review

Preamble to
OOP: struct

Anything Else
You Want to
Talk about

- At a higher level of abstraction, what really happens underneath is just a randomly generated list **undergoing a sequence of transformations**.
- Let's instead forget about the objects and just focus on the transformations.
- Define f_1 as the mapping from a list of triplets to a list of positive triplets.
- Define f_2 as the mapping from a list of triplets to a list of grouped triplets based on their first entry.
- Define f_3 as the mapping from a list of grouped triplets to the group with the minimum sum of the second entries.
- Define f_4 as the mapping from a group of triplets to a list of triplets.
- Define f_5 as the mapping from a list of triplets to the sum of the third entries.
- Define f_6 as the mapping from a group to its label.
- Then, we can find the “minimum group” with $G := L \rightarrow f_1 \rightarrow f_2 \rightarrow f_3$, then $M = f_6(G)$ and $S = G \rightarrow f_4 \rightarrow f_5$.

The functional paradigm views a problem-solving process as a **pipeline** of function applications. By carefully crafting the functions, we can pass in the initial argument into this pipeline and collect the result at the other end.

Other Stuff for Remaining Time

CS1010
Laboratory 10

Zhang Puyu

Exercise 8
Review

Preamble to
OOP: struct

Anything Else
You Want to
Talk about

- Go through PE2
- Clear doubts about any concept taught over the semester
- Suggestions for life as a programmer after CS1010
- Others